

Student Name/ID Number:	Francis Roel L. Abarca bdse-0922-113
Academic Year:	2022 – 2023
Unit Assessor:	Archana Sakpal
Project Title:	Assignment5 – Spring Security, Error Handling, and Logging
Issue Date:	4/18/2023
Submission Date:	4/27/2023
Internal Verifier Name:	Archana Sakpal
Date:	4/26/2023

Learner declaration

I certify that the work submitted for this assignment is my own and research sources are fully acknowledged.

Student signature:



Date: 4/26/2023

This assignment is about implementing Authentication & Authorization solution for Know-Your-Neighbourhood application.

Spring Security

1. Create user, role and user_role tables in the database.
 - a. [Note: The words user & role are reserved in some databases. Use some other name, if so.]

Figure 1: Know Your Neighborhood database, kyn




Figure 2: user Table

Table: user

Columns:

id	bigint AI PK
address	varchar(255)
email	varchar(255)
mobile	varchar(255)
name	varchar(255)
password	varchar(255)
user_name	varchar(255)

Figure 3: role Table

Table: role

Columns:

id	bigint AI PK
description	varchar(255)
name	varchar(255)

Figure 4: user_role Table

Table: user_role	
Columns:	
user_id	bigint PK
role_id	bigint

Figure 5: store Table

Table: store	
Columns:	
id	bigint AI PK
email	varchar(255)
localities	varchar(255)
name	varchar(255)
phone_number	varchar(255)

2. Add entries into user, role(roleid, role name) and user_role tables.
 - a. Add two entries into role table. One role is to view the store info (VIEW_STORE) and the other role is to add/modify store info (ADD_STORE).

Figure 6: role Table

	id	description	name
▶	1	admin	Administrator
	2	User	Users
•	NULL	NULL	NULL

- b. Add two entries into user table. Let one user have play VIEW_STORE role, another user play only both VIEW_STORE & ADD_STORE roles.

Figure 7: user Table

	id	address	email	mobile	name	password	user_name
▶	1	NULL	yeems214@yeems214.xyz	NULL	yeems214	\$2a\$10\$wq956dyHdiqbJYrnLq91bOHtjuXx4ztWQVILLD3FNqycZ7CVzbdAy	yeems214
	2	NULL	cheems214@yeems214.xyz	NULL	cheems	\$2a\$10\$LYnYPxNAbwHNgBCwKz4vKenahjfucI50CudNFsRhJJORzcSEqX7Ce	cheems
•	NULL	NULL	NULL	NULL	NULL	NULL	NULL

Figure 8: user_role Table

	user_id	role_id
▶	1	1
	2	2
•	NULL	NULL


3. Enhance Spring Data JPA enabled version of 'Know-Your-Neighbourhood' application to support authentication and authorization

Figure 9: UserRepository identifies the user by its user_name



```
ava  ⓘ UserRepository.java × ⓘ RoleRepository.java ⓘ SecurityConfig.java ⓘ U
1  package com.yeems214.assignment5.repository;
2
3  import org.springframework.data.jpa.repository.JpaRepository;
4  import org.springframework.stereotype.Repository;
5
6  import com.yeems214.assignment5.entity.User;
7
8  6 usages
9  @Repository
10 public interface UserRepository extends JpaRepository<User, Long>{
11     2 usages
12     User findByUserName(String name);
13 }
14
15
```

Figure 9: RoleRepository



```
ava  ⓘ RoleRepository.java × ⓘ UserRepository.java ⓘ SecurityConfig.java ⓘ U
1  package com.yeems214.assignment5.repository;
2
3  import java.util.Set;
4
5  import org.springframework.data.jpa.repository.JpaRepository;
6  import org.springframework.data.jpa.repository.Query;
7  import org.springframework.data.repository.query.Param;
8  import org.springframework.stereotype.Repository;
9
10 import com.yeems214.assignment5.entity.Role;
11
12 4 usages
13 @Repository
14 public interface RoleRepository extends JpaRepository<Role, Long>{
15     2 usages
16     @Query( "select r from Role r where r.name in :roles" )
17     Set<Role> findBySpecificRoles(@Param("roles") String role);
18 }
19
20
```

Figure 10: StoreRepository finds the store created by email.




```
1 package com.yeems214.assignment5.repository;
2
3 import java.util.List;
4
5 import org.springframework.data.jpa.repository.JpaRepository;
6 import org.springframework.stereotype.Repository;
7
8 import com.yeems214.assignment5.entity.Store;
9
10 @Repository
11 public interface StoreRepository extends JpaRepository<Store, Long> {
12     List<Store> findByEmail(String email);
13 }
14
```

4. Authentication:

- a. Create entities for Role and Store.

Figure 11: Store.java



```
1 package com.yeems214.assignment5.entity;
2
3 import javax.persistence.Column;
4 import javax.persistence.Entity;
5 import javax.persistence.GeneratedValue;
6 import javax.persistence.GenerationType;
7 import javax.persistence.Id;
8
9 @Entity
10 public class Store {
11     @Id // primary key
12     @GeneratedValue(strategy= GenerationType.IDENTITY) // auto increment
13     @Column(name = "id") // column name
14     Long id;
15     String name;
16     String phone_number;
17     String localities;
18     String email;
19 }

```

Figure 12: Role.java


```
Role.java x StoreNotFoundException.java StoreRepository.java RoleRepository.java
1 package com.yeems214.assignment5.entity;
2
3 import javax.persistence.*;
4 import java.util.HashSet;
5 import java.util.Objects;
6 import java.util.Set;
7
8 @Entity
9 public class Role {
10     @Id // primary key
11     @Column(name="id") // column name
12     @GeneratedValue(strategy= GenerationType.IDENTITY) // auto increment
13     private Long id;
14
15     @Column(name="name")
16     private String name;
17
18     @Column(name="description")
19     private String description;
20
21     @ManyToMany(mappedBy = "roles")
22     private Set<User> users = new HashSet<>();
23 }
```

Figure 13: User.java

```
User.java x StoreNotFoundException.java StoreRepository.java RoleRepository.java
1 package com.yeems214.assignment5.entity;
2
3 import java.util.HashSet;
4 import java.util.Objects;
5 import java.util.Set;
6
7 import javax.persistence.*;
8 import javax.persistence.GeneratedValue;
9 import javax.persistence.GenerationType;
10 import javax.persistence.Id;
11 import javax.persistence.JoinColumn;
12 import javax.persistence.JoinTable;
13 import javax.persistence.ManyToMany;
14
15 import javax.persistence.*;
16
17 @Entity
18 public class User {
19     @Id // primary key
20     @GeneratedValue(strategy= GenerationType.IDENTITY) // auto increment
21     private Long id;
22
23     private String name;
24
25     @Column(name="user_name")
26     private String userName;
27
28     private String password;
29
30     @ManyToMany
31     @JoinTable( name="user_role",
32         joinColumns = @JoinColumn(name = "user_id"),
33         inverseJoinColumns = @JoinColumn(name = "role_id"))
34     private Set<Role> roles = new HashSet<>();
35 }
```

- b. Create a login page for the application. User should be forced to login before visiting any of the application page.


Figure 14: login.jsp page



The screenshot shows a web application header with a logo on the left and "REGISTER" and "LOGIN" links on the right. The main content area has a light gray background. In the center, there is a "Sign-in" section with the subtitle "Come and utilize our services!". Below this is a white form box. Inside the form, there are two input fields: "Username:" and "Password:". The "Username:" field contains the placeholder text "Enter username" and has a red border with a red "X" icon on the right. Below it is the text "Please fill out this field.". The "Password:" field contains the placeholder text "Enter password" and has a red border with a red "X" icon on the right. Below it is the text "Please fill out this field.". At the bottom of the form, there is a link "New User? Click here to [Register](#)" and a blue "Sign in" button.

- c. Authenticate user with the credentials entered against the database entries added in the previous step.

Figure 15: login.jsp with credentials



The screenshot shows the same web application header and "Sign-in" section as Figure 14. The "Username:" field now contains the text "yeems214" and has a green border with a green checkmark icon on the right. Below it is the text "Valid.". The "Password:" field now contains three dots "..." and has a green border with a green checkmark icon on the right. Below it is the text "Valid.". The "New User? Click here to [Register](#)" link and the blue "Sign in" button are still present at the bottom of the form.

Figure 16: index.jsp for user




Figure 17: Standard user can only access View Store thus selecting Add your business redirects to an Access Denied page






Figure 18: Access Denied page seen by the standard user



- d. Show a message if user enters invalid user and password. And then allow him to re-enter the credentials.

Figure 19: Login error shown after user enters incorrect credentials



5. Authorization:

- a. Once the user logged in, make sure that only the user with ADD_STORE role can add/modify store data. The user with VIEW_STORE data can only view the stores entered.

Figure 20: StoreController.java authorizing the Administrator role for Add_Store access

```
no usages
52  @PreAuthorize("hasRole('Administrator')")
53  @GetMapping(value = "/addStore")
54  public String addStoreForm(@ModelAttribute("store") Store store) {
55      System.out.println("Add Store Form");
56
57      return "addStore";
58  }
```

Figure 21: StoreController.java authorizing the User role for View_Store while Administrator role for View_Store and Add_Store

```
78 @PreAuthorize("hasAnyRole('Users','Administrator')")
79 @RequestMapping(value = "/viewStore", method = RequestMethod.GET)
80 public ModelAndView viewStore(Model model) {
81     logger.info("before calling Service to fetch all store details");
82     System.out.println("List out all store");
83     List<Store> allStores = s_Service.listAllStore();
84     logger.info("after calling Service to fetch all store details");
85     System.out.println(allStores);
86
87     return new ModelAndView( viewName: "storeList", modelName: "all_Stores", allStores);
88 }
```

Figure 22: SecurityConfig.java authorizing specific URLs based on the available roles.

```
35 @Override
36 protected void configure(HttpSecurity http) throws Exception {
37
38     System.out.println("At Security configure");
39     http
40
41         .formLogin() .formLoginConfigurer<HttpSecurity>
42         .loginPage("/login")
43         .loginProcessingUrl("/login")
44         .failureUrl( authenticationFailureUrl: "/login_error")
45         .permitAll()
46         .defaultSuccessUrl( defaultSuccessUrl: "/login_success", alwaysUse: true)
47         .and() .HttpSecurity
48         .csrf() .CsrfConfigurer<HttpSecurity>
49         .and() .HttpSecurity
50         .authorizeRequests() .ExpressionUrlAuthorizationConfigurer<...>.ExpressionInterceptUrlRegistry
51         .antMatchers( ...antPatterns: "/" ).permitAll()
52         .antMatchers( ...antPatterns: "/css/**" ).permitAll()
53         .antMatchers( ...antPatterns: "/images/**" ).permitAll()
54         .antMatchers( ...antPatterns: "/js/**" ).permitAll()
55         .antMatchers(HttpMethod.GET, ...antPatterns: "/favicon.*" ).permitAll()
56         .antMatchers(HttpMethod.GET, ...antPatterns: "/login" ).permitAll()
57         .antMatchers(HttpMethod.GET, ...antPatterns: "/home" ).hasAnyRole( ...roles: "Users", "Administrator")
58         .antMatchers(HttpMethod.GET, ...antPatterns: "/view_store" ).hasAnyRole( ...roles: "Users", "Administrator")
59         .antMatchers(HttpMethod.GET, ...antPatterns: "/search_store" ).hasAnyRole( ...roles: "Users", "Administrator")
60         .antMatchers(HttpMethod.POST, ...antPatterns: "/saveStore" ).hasRole("Administrator")
61         .antMatchers(HttpMethod.GET, ...antPatterns: "/addStore" ).hasRole("Administrator")
62         .antMatchers(HttpMethod.GET, ...antPatterns: "/update" ).hasRole("Administrator")
63         .antMatchers(HttpMethod.GET, ...antPatterns: "/delete" ).hasRole("Administrator")
64         .and() .HttpSecurity
65         .logout() .LogoutConfigurer<HttpSecurity>
66         .logoutSuccessUrl("/logout")
67         .invalidateHttpSession(true);
68
69     http.exceptionHandling().accessDeniedPage( accessDeniedUrl: "/accessdenied");
70
71 }
72
73
74 }
```

- b. If there are no stores in the system, show appropriate message to the user.

Figure 23: StoreNotFoundException shown when there are no stores available in the store table




Figure 24: StoreNotFoundException shown in console



6. Add CSRF security to the application

Figure 25: login.jsp with the CSRF token added




Figure 26: Security taglib used in header for authorization

```
37 <sec:authorize access="#isAuthenticated()">
38
39
40 <div class="navbar-nav">
41   <a class="nav-item nav-link" href="#home">Home</a>
42
43 </div>
44
45 <a class="nav-item nav-link" href="#addStore">Add Store</a>
46
47 <a class="nav-item nav-link" href="#viewStore">View Store</a>
48
49 <div class="navbar-nav ms-auto">
50
51   <form action="#logout" method="post" style="display: inline-block;">
52     <input type="hidden" name="${_csrf.parameterName}"
53       value="${_csrf.token}" /> <input type="submit" name="Logout"
54       value="Logout" class="btn btn-primary"></input>
55   </form>
56 </div>
57
58 </sec:authorize>
```

Logging

1. Develop 5 unit test cases to validate the role based authorization

Figure 27: LoginControllerTest

```
1 package com.yeems214.assignment5.controller;
2
3 > import ...
4
15
16
17 no usages
18 @RunWith(MockitoJUnitRunner.class)
19 public class LoginControllerTest {
20
21   2 usages
22   @InjectMocks
23   LoginController loginController;
24
25
26   no usages
27   @Mock
28   UserServiceImpl userService; // = new UserServiceImpl();
29
30
31   no usages
32   @Before
33   public void setUp() throws Exception{
34     MockitoAnnotations.initMocks(this);
35   }
36
37
38   no usages
39   @Test
40   public void testLoadLoginPage() {
41     ModelAndView mav = new ModelAndView();
42     String loginViewName = loginController.onLogin();
43     mav.setViewName(loginViewName);
44     Assert.assertEquals("expected: 'login', mav.getViewName()", loginController.onLogin());
45   }
46
47   no usages
48   @Test
49   public void testLoadRegisterPage() {
50     ModelAndView mav = new ModelAndView();
51     User user = new User();
52
53     String RegisterViewName = loginController.showRegistrationForm(user);
54     mav.setViewName(RegisterViewName);
55     Assert.assertEquals("expected: 'Register', mav.getViewName()", RegisterViewName);
56   }
57
58 }
```

Figure 28: Output of LoginControllerTest




Figure 29: StoreServiceTest




Figure 30: Output of StoreServiceTest




Figure 31: UserServiceImplTest





Figure 32: Output of UserServiceImplTest



Logging

1. Implement the rolling file appender and log at the class level

Figure 33: log4j2.xml Source Code





Figure 34: log file directory



Error Handling

1. Create Global Exception Handler that can handle an exception. Add method to handle run away exception. [Run away exception is a RuntimeException that is not handled by any exception handler].

Figure 35: StoreExceptionHandler.java

```
1  package com.yeems214.assignment5.exception;
2
3  import java.time.LocalDateTime;
4
5  import org.springframework.web.bind.annotation.ControllerAdvice;
6  import org.springframework.web.bind.annotation.ExceptionHandler;
7  import org.springframework.web.context.request.WebRequest;
8  import org.springframework.web.servlet.ModelAndView;
9  import org.springframework.web.servlet.mvc.method.annotation.ResponseEntityExceptionHandler;
10
11  no usages
12  @ControllerAdvice
13  public class StoreExceptionHandler extends ResponseEntityExceptionHandler {
14
15      no usages
16      @ExceptionHandler({StoreNotFoundException.class})
17      public ModelAndView handleStoreNotFoundException(StoreNotFoundException ex, WebRequest webRequest) {
18          ExceptionResponse response = new ExceptionResponse();
19          response.setDateTime(LocalDateTime.now());
20          response.setMessage(ex.getMessage());
21          response.setDescription("No Data Found");
22          ModelAndView model = new ModelAndView();
23          model.addObject("message", response.getMessage());
24          model.addObject("description", response.getDescription());
25          model.addObject("dateTime", response.getDateTime());
26          model.setViewName("error");
27          return model;
28      }
29  }
```


Figure 36: *ExceptionResponse.java*

```
2 usages
5 public class ExceptionResponse {
    2 usages
6     private String message;
    2 usages
7     private LocalDateTime dateTime;
    2 usages
8     private String description;
    2 usages
9     private String statusCode;
    1 usage
10    public String getDescription() {
11        return description;
12    }
    1 usage
13    public void setDescription(String description) {
14        this.description = description;
15    }
    1 usage
16    public String getMessage() {
17        return message;
18    }
    1 usage
19    public void setMessage(String message) {
20        this.message = message;
21    }
    1 usage
22    public LocalDateTime getDateTime() {
23        return dateTime;
24    }
    1 usage
25    public void setDateTime(LocalDateTime dateTime) {
26        this.dateTime = dateTime;
27    }
    no usages
28    public String getStatusCode() {
29        return statusCode;
30    }
    no usages
31    public void setStatusCode(String statusCode) {
32        this.statusCode = statusCode;
33    }
34
35 }

assignment5 > exception > © ExceptionResponse > ⓘ getStatusCode
```

2. Create an exception class StoreNotFoundException.

Figure 37: StoreNotFoundException.java

```
1 package com.yeems214.assignment5.exception;
2
3 public class StoreNotFoundException extends RuntimeException {
4     private static final long serialVersionUID = 1L;
5     public StoreNotFoundException(String message) { super(message); }
6 }
7
```

3. Create an end point to search store by email.

Figure 38: StoreRepository.java

```
1 package com.yeems214.assignment5.repository;
2
3 import java.util.List;
4
5 import org.springframework.data.jpa.repository.JpaRepository;
6 import org.springframework.stereotype.Repository;
7
8 import com.yeems214.assignment5.entity.Store;
9
10 @Repository
11 public interface StoreRepository extends JpaRepository<Store, Long> {
12     List<Store> findByEmail(String email);
13 }
14
```

Figure 39: StoreService.java searchStore method

```
48 public List<Store> searchStore(String email) {
49     List<Store> userResponse = storerepository.findByEmail(email);
50     if(userResponse.isEmpty()) {
51         throw new StoreNotFoundException("No store found for " + email + " entered");
52     }
53     return userResponse;
54 }
55 }
56
57
58
59
```

Figure 40: StoreController.java searchStore method

```
108 @GetMapping("search_store")
109 public String searchStore(@RequestParam("keyword") String email, Model model) {
110     logger.info("before calling Service to fetch store details by email");
111     List<Store> search_result = s_Service.searchStore(email);
112     System.out.println(search_result);
113     logger.info("after calling Service to fetch store details by email");
114     model.addAttribute("search_result", search_result);
115     model.addAttribute("searchKey", email);
116
117     return "searchResult";
118 }
119
120 }
```

4. Create exception handler specific to the controller.

Figure 41: StoreExceptionHandler.java

```
1 package com.yeems214.assignment5.exception;
2
3 import java.time.LocalDateTime;
4
5 import org.springframework.web.bind.annotation.ControllerAdvice;
6 import org.springframework.web.bind.annotation.ExceptionHandler;
7 import org.springframework.web.context.request.WebRequest;
8 import org.springframework.web.servlet.ModelAndView;
9 import org.springframework.web.servlet.mvc.method.annotation.ResponseEntityExceptionHandler;
10
11 no usages
12 @ControllerAdvice
13 public class StoreExceptionHandler extends ResponseEntityExceptionHandler {
14
15     no usages
16     @ExceptionHandler({StoreNotFoundException.class})
17     @Override
18     public ModelAndView handleStoreNotFoundException(StoreNotFoundException ex, WebRequest webRequest) {
19         ExceptionResponse response = new ExceptionResponse();
20         response.setDateTime(LocalDateTime.now());
21         response.setMessage(ex.getMessage());
22         response.setDescription("No Data Found");
23         ModelAndView model = new ModelAndView();
24         model.addObject("message", response.getMessage());
25         model.addObject("description", response.getDescription());
26         model.addObject("dateTime", response.getDateTime());
27         model.setViewName("error");
28         return model;
29     }
30 }
```

5. Let the service throw `StoreNotFoundException` if no store is found for given **email**.

Figure 42: StoreService.java searchStore method


```
48     public List<Store> searchStore(String email) {
49
50         List<Store> userResponse = storerepository.findByEmail(email);
51         if(userResponse.isEmpty()) {
52             throw new StoreNotFoundException("No store found for " + email + " entered");
53         }
54
55         return userResponse;
56     }
57
58 }
59 }
```

Figure 43: StoreService.java message passes to StoreNotFoundException.java

```
5     public StoreNotFoundException(String message) {
6         super(message);
7     }
```

7. Let the `StoreNotFoundException` handler route to view stores page and show the error message in view stores page.

Figure 44: storeList.jsp



The screenshot shows a web application titled "Store Manager" with the tagline "Empowering Retail, Managing Success". The navigation bar includes links for HOME, ADD STORE, VIEW STORE, and a Logout button. Below the navigation bar is a search bar with a "search" button. The main content area displays a table with the following data:

Store Name	Phone Number	Localities	Action
Ace Hardware	+19992225555	Laguna, Philippines	Add Update Delete
McDonalds	+19521557281	McKinney, Texas, United States	Add Update Delete
Jollibee	+15552221468	Toronto, Ontario, Canada	Add Update Delete

Figure 45: error.jsp when searching for the email of user with no data



8. Enter the url `http://:/stores?email@test.com`. This should route to view stores page and show the error message.

Figure 46: error.jsp for keyword=email@test.com

