

CMPSCI 187 (Fall 2018) Lab 05: Midterm Review

This lab reviews some topics on the midterm. To work on the assignment:

- Go to **File -> Make a Copy** to make an editable copy of this Google Doc for your account
- Follow the instructions to complete the assignment
- When you are done, go to **File -> Download As -> PDF Document**
- Log in to [Gradescope](#) and submit your PDF

Section A: Multiple Choice

One correct answer per question. **Select your choice by making that option bold**

1. **What's the output of the following code?**

```
int x = 4, y = 5;  
float z = x / y;  
System.out.println(z);
```

- (a) 1.25
- (b) 1.0
- (c) 0.8
- (d) 0.0

2. **If class Triangle implements the Geometry interface, and class RightTriangle extends Triangle, which of the following would not compile?**

- (a) **Geometry g = new Geometry();**
- (b) Geometry g = new Triangle();
- (c) Geometry g = new RightTriangle();
- (d) Triangle t = new RightTriangle();

(End of page 1)

3. Assume that `curr` is a variable that points to a node in the middle of a long linked list. Which of the following inserts a new node `nn` into the linked list after the `curr` node?

(a) `nn.setLink(curr); curr = nn;`
(b) `nn.setLink(curr); curr.setLink(nn);`
(c) `nn.setLink(curr.getLink()); curr = nn;`
(d) `nn.setLink(curr.getLink()); curr.setLink(nn);`

4. Which of these are in increasing order of complexity?

(a) $O(n) < O(\log n) < O(n^2) < O(n^3) < O(2^n)$
(b) $O(n) < O(\log n) < O(2^n) < O(n^2) < O(n^3)$
(c) $O(\log n) < O(n) < O(2^n) < O(n^2) < O(n^3)$
(d) $O(\log n) < O(n) < O(n^2) < O(n^3) < O(2^n)$

5. What is the Big-O cost of the following code (n is a large positive integer)?

```
int count = 0;
for (int i = 1; i < n; i *= 2) {
    for (int k = i; k <= i + 8; k++) {
        count++;
    }
}
```

(a) $O(1)$
(b) $O(\log n)$
(c) $O(n)$
(d) $O(n \log n)$

(End of page 2)

Section B: Arrays

1. Complete the following method which reverses the order of elements stored in an `int` array `a`. For example, if `a[] = {1, 2, 3, 4, 5}`, calling `reverse(a)` will make it become `{5, 4, 3, 2, 1}`. If you declare any new variables, they must be of type `int`. You are **NOT** allowed to create any new method, any new array, or use any object type (such as `Stack` or `ArrayList`). The running time of your method should be no more than $O(n)$.

Remember: during the real midterm, you must write down code correctly without the help of a Java compiler. Therefore when working on these programming questions, **you should treat them as a real exam and should not rely on a Java compiler to tell you if your code is correct or not.**

```
public void reverse(int[] a) {
    int n = a.length;
    for (int i = 0; i < n/2; i++)
    {
        int temp = a[i];
        a[i] = a[n-1-i];
        a[n-1-i] = temp;
    }
}
```

(End of page 3)

2. Complete the method below to perform a circular left-shift of elements stored in a. For example, if $a[] = \{1, 2, 3, 4, 5\}$, calling `circularLeftShift(a, 1)` will circular left-shift the array once, making it $\{2, 3, 4, 5, 1\}$. In other words, the first element is shifted to the last position, and all other elements are shifted to the left by one position. Calling `circularLeftShift(a, k)` (where $k > 0$) is equivalent to repeat `circularLeftShift(a, 1)` k times. If you declare any new variables, they must be of type `int`. You are NOT allowed to create any new method, any new array, or use any object type (such as `Stack` or `ArrayList`). The running time of your method should be no more than $O(k*n)$ (i.e. linear with respect to k times n).

```
public void circularLeftShift(int[] a, int k) {
    int n = a.length;
    k = k % n; // modulo n so that k is always less than n
    if(k <= 0) return;

    int temp = a[0];
    for (int i = 0; i < n-1; i++)
        a[i] = a[i+1];
    a[n-1] = temp;

    circularLeftShift(a, k-1);
}
```

(End of page 4)

Section 3: Linked Lists

```
public class LLStringNode {
    private String data;
    private LLStringNode next;
    public String getData()           { return data; }
    public void setData(String data)  { this.data = data; }
    public LLStringNode getNext()     { return next; }
    public void setNext(LLStringNode next) { this.next = next; }
}
```

Given the above definition of a Linked List node, complete the following LinkedListStrings class. Specifically, complete the add and elementAt methods. Do NOT use iterators. Do NOT create new methods.

```
public class LinkedListStrings {
    private LLStringNode head;

    // Add a new element to the beginning of the linked list. O(1).
    public void add(String element) {
        newNode = new LLStringNode();
        newNode.setData(element);
        newNode.setNext(head);
        head = newNode;
    }
}
```

(End of page 5)

*// Return the k-th element on the List where k is the index
// (the first element has index 0 and so on). If the Linked
// List has less than (k+1) elements, return null. O(n).*

```
public String elementAt(int k) {  
    LLStringNode current = head;  
    for (int count = 0; count < k; count++)  
    {  
        if (current == null) return null;  
        current = current.getNext();  
    }  
    return current.getData();  
}
```

(End of page 6)