MalariaScope

High-Level Design

Kiran Kumar P
DA24B008

1 Purpose

MalariaScope sorts single-cell images from Giemsa-stained thin blood smears into *Parasitized* or *Uninfected*. It is meant as a screening aid for lab technicians: upload a cell image, read the result and its confidence, and confirm or correct it. It supports a trained reader, it does not replace one.

The model is only one part of it. Data and pipeline stages are versioned with DVC, runs and models are tracked in MLflow, a new model has to beat the current one before it is served, and an Airflow DAG retrains on user feedback. Prometheus and Grafana watch the running system. All of it runs on one laptop, no cloud.

2 Architecture

2.1 High-level flow




Figure 1: Data is prepared and versioned, the pipeline trains a model and gates it, the champion is served, and monitoring and user feedback feed the next training run.

2.2 Architecture




Figure 2: The blocks and how they connect. Each block is described in the Architecture document.

The system has four parts.

- **Serving:** Streamlit calls FastAPI, FastAPI calls the MLflow model server. Corrections go to the feedback store.
- **Tracking:** the MLflow server holds runs, artifacts and the model registry. The `@champion` alias decides what is served.
- **ML pipeline:** Airflow runs the DVC stages. DVC versions the data and the models in a local remote.
- **Monitoring:** Prometheus scrapes the backend and the host. Grafana shows the service dashboard and Alertmanager sends alerts to a log. Pipeline runs are watched in Airflow.

2.3 Design paradigm

The pipeline stages are functional: each one is a script that reads declared inputs and writes declared outputs, which is what lets DVC cache and skip them. The services are object-oriented in a small way. `ModelClient` and `FeedbackStore` wrap the model server and the store behind a few methods, and the FastAPI `app`, the model client and the store are created once when `main.py` is imported. The tests swap the model client for a fake with `monkeypatch`.

3 Components

Component	Technology	Responsibility
UI	Streamlit 1.65	Predict page (upload, result, feedback) and Pipeline page (runs, models, links to tools)
API	FastAPI 0.162	Checks uploads, calls the model, applies the tuned threshold, stores feedback, exposes metrics
Model serving	`mlflow models serve`	Serves the `@champion` version over REST and follows the alias
Model	Keras 3 CNN on TensorFlow 2.21	3 convolutional blocks on 64×64 RGB input, 2-way softmax
Data engineering	Ray Data 2.59	Parallel image validation and resizing
Pipeline	DVC 3.67	8 stages with hashed inputs and outputs, data and model versioning, experiments
Orchestration	Airflow 2.10	`training_pipeline` and the 30-minute `feedback_retrain` DAG
Tracking and registry	MLflow 3.17	Runs, metrics, artifacts, model versions, aliases
Monitoring	Prometheus, Alertmanager, node-exporter, Grafana	Metrics from the service and the host; 9 alert rules; 1 dashboard
Packaging	Docker Compose, MLproject	11 pinned services with healthchecks; one entry point per stage

4 Data flow

4.1 Inference

1. The user uploads a PNG or JPEG (at most 5 MB) or picks a sample, then clicks *Analyse*.
2. Streamlit posts the file to the backend at `BACKEND_URL`.
3. The backend checks the file and resizes it with `to_model_input()`. The pipeline uses the same function, so serving can't drift from training.
4. The backend posts the pixels to the model server's `/invocations` and gets p(parasitized) back.
5. It applies the champion's tuned threshold and updates its Prometheus metrics, including the mean image intensity used for drift.
6. The UI shows the label and the confidence, with a warning when confidence is below 70%.
7. The user can confirm or correct the result. The image and the label go to the feedback store.

Measured over 50 calls through the containers: p50 65.6 ms, p95 196.0 ms.

4.2 Training pipeline

ingest → validate → split → preprocess → train → evaluate → promote, with eda alongside.

Stage	What it does	Result on 27,558 images
ingest	TFDS to PNG files plus a manifest	13,779 per class
validate	Ray checks for unreadable, non-RGB, wrong-size and blank images; removes duplicates	None dropped
split	Seeded stratified 80/10/10	22,046 / 2,756 / 2,756
preprocess	Ray resize to 64×64 uint8 `.npz`	About 5,000 images/s
train	Keras CNN with early stopping, logged to MLflow	About 7 minutes on CPU
evaluate	Picks the threshold on val for 97% recall, applies it to test	Test metrics and plots
promote	Registers a challenger, compares it with the champion on the same test split	Moves the alias, or doesn't

4.3 Feedback and retraining loop

1. Every 30 minutes `feedback_retrain` asks the backend how many feedback items are new.

2. With 50 or more, it exports them to `data/feedback`, versions the snapshot with `dvc add` and starts `training_pipeline`.
3. The split stage adds feedback to the train split only. Val and test stay fixed, so challenger and champion are compared on the same images.
4. Feedback whose pixels match a val or test image is dropped, so test data can't leak into training.
5. The promotion gate decides. If the alias moves, the model server switches by itself within about 20 seconds.

This ran for real on 4 Nov: 60 feedback items were added to training and the gate rejected v2 (accuracy 0.9561 vs 0.9626), so v1 kept serving.

5 Design choices

5.1 Loose coupling of UI and backend through configurable REST

Chosen. The UI reaches the backend only through `BACKEND_URL`, and the backend reaches the model only through `MODEL_SERVER_URL`.
Alternative. One app, or a hard-coded address.
Evidence. UI-02 and UI-09 show the UI stays up, with a plain message, when every service is down.

5.2 Ray rather than Spark for preprocessing

Chosen. Ray Data `map_batches` in the validate and preprocess stages.
Alternative. PySpark.
Evidence. With 32 blocks across 16 cores, validate went from 15.4 s to 5.1 s and preprocess from 14.1 s to 5.4 s, with byte-identical output.

5.3 DVC stages run by Airflow, rather than the logic written twice

Chosen. Each Airflow task is `dvc repro <stage>`.
Alternative. Write the steps as Airflow tasks and keep a separate DVC pipeline.
Evidence. A run with no new data finishes in under a minute because DVC skips each stage (2–6 s per task).

5.4 Keras CNN at 64×64

Chosen. A small CNN, lr 1e-3, filters [32, 64, 128], with augmentation.
Alternatives tested. 5 DVC experiments, all scored on the same fixed test split (Table 1).

Experiment	Train time	Acc. at 0.5	Threshold	Tuned acc.	Recall	Missed cells
baseline (chosen)	420 s	0.965	0.242	0.963	0.967	45
lr5e-4	782 s	0.966	0.380	0.963	0.967	46
wider	369 s	0.962	0.119	0.956	0.971	40
img96	856 s	0.963	0.190	0.959	0.971	40
no-augment	295 s	0.957	0.124	0.957	0.972	39

Table 1: The 5 experiments on the test split.

5.5 Backend calls the MLflow model server rather than loading the model

Chosen. REST to `/invocations`.
Alternative. Load the model inside FastAPI.
Evidence. The backend image is 560 MB and the model server image 3.03 GB (TensorFlow). A promotion only touches the model server. The cost is one extra hop, and a short window after a promotion where the backend's cached threshold and the served model can differ (at most `MODEL_INFO_TTL`, 60 s).

5.6 Feedback storage format

Chosen. Image files under `images/<label>/` plus SQLite metadata; a snapshot of new items goes to DVC.
Alternative. SQLite blobs, or a CSV index.
Evidence. The snapshot matches images on a pixel hash, so a match survives re-encoding. This caught the 2 UI samples taken from the test set (`leaked_dropped 2`).

5.7 Promotion rule and rollback

Chosen. Register as `@challenger`, score challenger and champion on the same test split, and promote only if recall ≥ 0.95 and the accuracy gain is ≥ 0.005 (about 14 images). The old champion becomes `@previous_champion` and `rollback.py` swaps them back.
Alternative. Promote on any gain, or on recall alone.
Evidence. The gate rejected v2 although its recall was slightly higher (0.9695 vs 0.9673), because false alarms went from 58 to 79.

5.8 SQLite and files rather than a database server

Chosen. SQLite for feedback, MLflow and Airflow, with Airflow's `SequentialExecutor`.
Alternative. A Postgres service.
Evidence. One machine and one writer per database. The cost is that Airflow runs one task at a time, which is why `feedback_retrain` starts training without waiting for it.

5.9 Threshold tuned for recall

Chosen. The highest threshold on p(parasitized) whose recall on the *val* split is at least 0.97, stored as a tag on the model version.
Alternative. Keep 0.5, or tune on test.
Evidence. On the test split, champion v1 misses 69 infected cells at 0.5 (recall 0.950, 28 false alarms). At 0.2417 it misses 45 (recall 0.967, 58 false alarms). Tuning on test would leak.

6 Non-functional requirements

Requirement	How it is met	Status
Reproducibility	Every MLflow run carries the git commit, the DVC data hash and a `git_dirty` flag. Same commit and data gave identical metrics	Met
Portability	Pinned images, `environment.yml`, `MLproject`, Compose. A fresh clone comes up with 11 healthy services and passes all tests	Met (DVC remote: §7)
Observability	Backend and host metrics; 1 Grafana dashboard; 9 alert rules; pipeline runs in Airflow	Met; MLflow and Streamlit have no metrics of their own
Availability	Healthchecks, ordered start-up, last known model info if the registry is down, clear UI errors	Met for one machine
Rollback	`rollback.py` swaps the aliases; the model server follows within about 20 seconds	Met
Scalability	Ray scales with cores. Serving is one model server	One machine by design
Security	Ports bound to 127.0.0.1, non-root containers, upload type and size checks	Partial: feedback not encrypted, default Grafana and Airflow passwords
Explainability	Confidence score and low-confidence warning	Partial: no Grad-CAM

7 Assumptions and constraints

- CPU only: 16 cores, 14 GB RAM, no GPU.

- No cloud. The DVC remote is a local folder (`~/tmp/dvc_storage`), so `dvc pull` works only where that folder exists. On another machine, copy it and point `.dvc/config` at it, or rerun `dvc repro`, which downloads the data from TFDS.
- Input is a single segmented cell crop. The system doesn't read whole-slide images.
- Data bias: all images come from one hospital (Chittagong Medical College Hospital) with one stain (Giemsa). Results may not carry over to other labs, microscopes or stains.
- The EDA shows parasitized images are darker on average (mean intensity about 115 vs about 125). The model may lean on that, which is one reason mean intensity is watched for drift.

8 Trade-offs and risks

Risk or trade-off	Effect	Mitigation
Parasitized recall is 96.73%, below the 97% target (AC-2)	45 of 1,378 infected cells missed, 4 short of the target	Reported as a failed criterion, not fixed by tuning on test
A low threshold favours recall	Confidence can be under 50% for a "parasitized" result	Shown as it is, with a manual re-check warning
Small feedback batches can make the model worse	v2 lost accuracy	The gate blocks it; val and test stay fixed
Git and DVC follow the latest pipeline run, even when that model is rejected	`results/evaluate.json` can describe a model that isn't serving	The registry alias decides what is served
The drift signal is mean intensity only	It misses changes that keep brightness the same	Simple to explain; a richer signal is future work
Airflow runs one task at a time	A long training run blocks other DAG tasks	Accepted for one machine