

Shenzhen Polcd Technology Co.,Limited	Rev No	Issued Date.	Page
	A	2026-08-21	1/12

Project Size.	2.73 inch		
Model No.	P0273B02-IPS		
Samples No.			
Product type.	320xRGBx320 MCU SPI mode		
Signature by customer:			
Prepared	Checked	Approved	

Shenzhen Polcd Technology Co.,Limited

Email: polcd@polcd.com

Mobile: 86-137 1538 6666

Shenzhen Polcd Technology Co.,Limited	Rev No	Issued Date.	Page
	A	2026-08-21	2/12

1.0 GENERAL DESCRIPTION

Item	Specification	Unit
Screen Size	2.73 inch	Diagonal
Number of Pixel	320RGB(H)x320(V)	Pixels
Display area	48.96(H)x48.96(V)	mm
Pixel pitch	153(H)x153(V)	um
Outline Dimension	53.58x58.75x2.5	mm
Pixel arrangement	RGB Vertical Stripe	— —
Display mode	Normally Black	— —
Viewing Direction(eye)	ALL	— —
Gray inversion direction	--	
Display Color	262K	— —
Luminance(cd/m ²)	460	nit
Contrast Ratio	700:1	— —
Surface treatment	— —	— —
Interface	MCU8/16BIT 3W/4W SPI	
Back-light	LED Side-light type	— —
Drive IC	ST7365	
Operation Temperature	-20~70	°C
Storage Temperature	-30~80	°C
Weight	— —	g

1.1 Features

- MCU8/16BIT 3W/4W SPI interface.

1.2 Applications

- MPOS Device.
- Personal Navigation Device.
- Other devices which require high quality displays.

2.0 INPUT INTERFACE PIN ASSIGNMENT

LCM FPC connector is used for electronics interface

PinNo.	Symbol	Function				
1	XL	Touch the left line				
2	YU	Touch the upper circuit				
3	XR	Touch the right end line				
4	YD	Touch the lower line				
5	GND	Ground				
6	IOVCC	Power Supply. 1.8V				
7	VCC	Power Supply. 2.8V				
8	FMARK	Frame synchronization signal				
9	CS	Chip select input pin (active low)				
10	RS	Display data/command selection pin in parallel				
11	WR/SPI_SCL	Write enable in 8080 MCU parallel interface / SCL pin as Serial Clock				
12	RD	Read enable in 8080 MCU parallel interface.				
13	SPI_SDA	serial data input/output bi-direction pin				
14	SPI_SDO	Serial data output				
15	RESET	External reset input.				
16	GND	Ground				
17-32	DB0-DB15	MCU parallel interface data bus.				
33	LEDA	LED back light(Anode)				
34-36	LEDK	LED back light(Cathode)				
37	GND	Ground				
38	MIPI-DBI Type B					
	IM2	IM1	IM0	Interface	Data Pin in Use	
	39	0	0	0	24-bit bus (DB_EN=1)	DB [23:0]
		0	0	0	18-bit bus (DB_EN=0)	DB [17:0]
		0	0	1	9-bit bus	DB [8:0]
	40	0	1	0	16-bit bus	DB [15:0]
		0	1	1	8-bit bus	DB [7:0]

Shenzhen Polcd Technology Co.,Limited	Rev No	Issued Date.	Page
	A	2026-08-21	4/12

3.0 OPTICAL CHARACTERISTICS

3.1 Optical specification

Item		Symbol	Condition	Min	Type	Max	Unit	Note
White luminance (Center)		Lv	$\Theta=0$ Normal Viewing Angle $I_{BL}=160$	--	460	--	cd/m ²	(4)(5)(7)
Response time		Tr+Tf		--	30	--	ms	(3)
Contrast ratio		CR		--	700	--	--	(2)(4)
Color Chromaticity (CIE1931)	white	Wx		--	0.306	--		(6)
		Wy		--	0.318	--		
Viewing Angle	Hor	Θ_L	$CR \geq 10$	--	80	--		(1)
		Θ_R		--	80	--		
	Ver	Θ_U		--	80	--		
		Θ_D		--	80	--		
Brightness uniformity		Avg	$\Theta=0$	80	90	--	%	(5)
Color Gamut		NTSC	$\Theta=0$	--	70	--	%	(6)
Optima View Direction		ALL						(1)


3.2 Measuring Condition

- Measuring surrounding: dark room
- LED current IL: 120mA
- Ambient temperature: $25 \pm 2^{\circ}\text{C}$
- 15min. warm-up time

3.3 Measuring Equipment

- FPM520 of Westar Display technologies, INC., which utilized SR-3 for Chromaticity and BM-7 for other optical characteristics.
- Measuring spot size: 20 ~ 21 mm

Note (1) Definition of Viewing Angle




Note (2) Definition of Contrast Ratio(CR):


Measured at the center point of panel

$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$

Note (3) Definition of Response Time: Sum of TR and TF



Note (4) Definition of optical measurement setup




Note (5) Definition of brightness uniformity

The luminance uniformity is calculated by using following formula.

$$\Delta B_p = B_p (\text{Min.}) / B_p (\text{Max.}) \times 100 (\%)$$

$B_p (\text{Max.})$ = Maximum brightness in 9 measured spots


$B_p (\text{Min.})$ = Minimum brightness in 9 measured spots .



Note (6) Definition of Color of CIE1931 Coordinate and NTSC Ratio.

Color gamut:

$$S = \frac{\text{Area of RGB triangle}}{\text{Area of NTSC triangle}} \times 100\%$$



Note (7) Measured the luminance of white state at center point.

Shenzhen Polcd Technology Co.,Limited	Rev No	Issued Date.	Page
	A	2026-08-21	7/12

4.0 ELECTRICAL CHARACTERISTICS

4.1 TFT LCD Module

Item	Symbol	Min.	Typ.	Max.	Unit	Remark
Analog supply voltage	VDD	2.4	2.8	3.3	V	
Digital supply voltage	VDDI	1.65	1.8	3.3		
Input signal Voltage	VIH	0.7VDDI	-	VDDI	V	
	VIL	GND	-	0.3VDDI	V	

4.2 Back-Light Unit

The backlight system is an edge-lighting type with 6 LED Dies.

The characteristics of the LED are shown in the following tables.


Item	Symbol	Min	Typ	Max	Unit	Note
LED current	IL	-	90	120	mA	(2)
LED voltage	VL	-	2.8	3.2	V	
Operating LED life time	Hr	-	20000	15000	Hour	(1)(2)

Note (1) LED life time (Hr) can be defined as the time in which it continues to operate under the condition: $T_a=25\pm 3\text{ }^{\circ}\text{C}$, typical IL value indicated in the above table until the brightness becomes less than 50%.

Note (2) The “LED life time” is defined as the module brightness decrease to 50% original brightness at $T_a=25^{\circ}\text{C}$ and $IL=120\text{mA}$.

Shenzhen Polcd Technology Co.,Limited	Rev No	Issued Date.	Page
	A	2026-08-21	8/12

5.0 Reliability conditions

NO	Item	Conditions	Notes								
1	High Temperature Storage	Ta=80℃±2℃, 72hrs									
2	Low Temperature Storage	Ta=-30℃±2℃, 72hrs									
3	High Temperature Operation	Ta=70℃±2℃, 72hrs(Operation state)									
4	Low Temperature Operation	Ta=-20℃±2℃, 72hrs(Operation state)									
5	High Temperature and High Humidity (Storage)	Ta=+60℃, 90%RH, 72hrs									
6	Thermal Cycling Test (non operation)	-20℃(30min) → +70℃(30min), 10cycles									
7	Electro static Discharge	Human Body Mode 100pF±10%/1500Ω±1% Air±8kV / contact±6kV Consecutive 10times/ Each discharge  <table border="1" data-bbox="1027 1128 1233 1240"><thead><tr><th>CLASS</th><th>STRESS LEVELS</th></tr></thead><tbody><tr><td>CLASS I</td><td>0-1999V</td></tr><tr><td>CLASS II</td><td>2000-3999V</td></tr><tr><td>CLASS III</td><td>4000-15999 V</td></tr></tbody></table>	CLASS	STRESS LEVELS	CLASS I	0-1999V	CLASS II	2000-3999V	CLASS III	4000-15999 V	
CLASS	STRESS LEVELS										
CLASS I	0-1999V										
CLASS II	2000-3999V										
CLASS III	4000-15999 V										
8	Vibration test(with carton)	Total fixed amplitude:15mm Vibration Frequency :10~55Hz One cycle 60 seconds to 3 directions of X,Y,Z for Each 15 minutes									
9	Drop (with carton)	Height: 60cm 1 corner, 3 edges, 6 surfaces									

Note: There is no display function NG issue occurred, all the cosmetic specification is judged before the reliability stress.

Shenzhen Polcd Technology Co.,Limited	Rev No	Issued Date.	Page
	A	2026-08-21	10/12

7.0 Items and Criteria:



7.1 Guarantee

APEX warrants the quality of our products for **1 year** (from the date of delivery). If there are functional defects found during the period of warranty, the defective products would be replaced on a one-to-one basis. Apex would not be responsible for any direct /indirect liabilities consequential to any parties.



All the products should be stored or used as specified conditions described in these sheets. If module productions are not stored or used as specified conditions, herein, it will be void the **1 year** warranty(guarantee).

7.2 Visual inspection criterion in cosmetic

(1) Glass defect

Glass defect			
NO	Defect	Criteria	Remark
1	Dimension(Minor)	By engineering diagram	
2	Cracks(Major)	Extensive crack 【Reject】	

(2) LCM appearance defect

NO	Defect	Criteria		Remark
1	Round type(Minor)	Spec	Permissible Qty	1. $\psi = (L+W)/2$, L: Length, W: Width 2. Disregard if out of A.A. 
		$\psi \leq 0.10\text{mm}$	Disregard	
		$0.10\text{mm} < \psi \leq 0.20\text{mm}$	3	
		$0.20\text{mm} < \psi$	0	
2	Line type(Minor)	Spec	Permissible Qty	1. L: Length, W: Width 2. Disregard if out of A.A. 
		$W \leq 0.03\text{mm}$	Disregard	
		$L \leq 3.0\text{mm}$ and $0.03\text{mm} < W \leq 0.05\text{mm}$	2	
		$L \leq 3.0\text{mm}$ and $0.05\text{mm} < W \leq 0.10\text{mm}$	1	
		$W > 0.10\text{mm}$ or $L > 3.0\text{mm}$	0	
3	Polarizer dent(Minor)	Spec.	Permissible Qty	1. $\psi = (L+W)/2$, L: Length, W: Width 2. Disregard if out of A.A.
		$\psi \leq 0.20\text{mm}$	Disregard	
		$0.20\text{mm} < \psi \leq 0.30\text{mm}$	2	
		$0.30\text{mm} < \psi \leq 0.50\text{mm}$	1	

Shenzhen Polcd Technology Co.,Limited	Rev No	Issued Date.	Page
	A	2026-08-21	11/12

(3) FPC

NO	Defect	Criteria	Remark
1	Copper peeling(Minor)	Copper peeling 【Reject】	
2	Golden finger	FPC golden finger broken, dead fold, indentation makes FPC surface broken 【Reject】 Tin plating layer(or gold plating) scratch, but not hurt circuit 【Accept】 Except circuit, other position scratch but not expose metal wire 【Accept】	
3	Pin	FPC PI layer delamination 【Reject】 Material and color are inconsistent with sample, FPC burrs 【Reject】 FPC Pin deformation but not affect function. 【Accept】 FPC Pin area is dirty 【Reject】 Other than FPC Pin area is dirty but not affect function 【Accept】	
4	Golden finger	Golden finger edge has burrs,foreign material 【Reject】 Golden finger oxidation (dark), uneven electroplating, pinhole, foreign material 【Reject】 Golden finger soldering pad crack exceeds 1/3 length of soldering pad, and soldering pad crack exceed 2 Pins 【Reject】 Golden finger tin plating(or gold plating)scratch, but not hurt circuit 【Accept】 Other than golden finger area scratch but not expose metal circuit 【Accept】	
5	FPC Silk printing	Ghosting, incomplete silk printing, wrong printing 【Reject】	
6	FPC Circuit line width	Line width deviation exceed 1/3 line width 【Reject】	

(4) Black tape



NO	Defect	Criteria	Remark
1	Shift(Minor)	IC exposed 【Reject】	
2	No black tape(Minor)	No black tape 【Reject】	

(5) Silicon

NO	Defect	Criteria	Remark
1	Amount of silicon (Minor)	ITO exposed 【Reject】	

Shenzhen Polcd Technology Co.,Limited	Rev No	Issued Date.	Page
	A	2026-08-21	12/12

7.3 Visual inspection criterion in electrical display

NO	Defect	Criteria		Remark
1	No display (Major)	Not allowed		
2	Missing line (Major)	Not allowed		
3	Darker or lighter Line (Major)	Not allowed		
4	Weak line(Major)	By limited sample		
5	Bright / Dark point (Minor)	Spec.	Permissible Qty	1:1sub-pixel: 1R or 1G or1B 2:Point defect area $\geq 1/2$ sub pixel.
		Bright point	1	
		Dark point	2	
6	Round type (Minor)	Spec	Permissible Qty	1. $\varphi=(L+W)/2$, L: Length, W: Width 2. Disregard if out of A.A. 
		$\varphi \leq 0.10\text{mm}$	Disregard	
		$0.10\text{mm} < \varphi \leq 0.20\text{mm}$	3	
		$0.20\text{mm} < \varphi$	0	
7	Line type (Minor)	Spec.	Permissible Qty	1. L: Length, W: Width 2. Disregard if out of A.A. 
		$W \leq 0.03\text{mm}$	Disregard	
		$L \leq 3.0\text{mm}$ and $0.03\text{mm} < W \leq 0.05\text{mm}$	2	
		$L \leq 3.0\text{mm}$ and $0.05\text{mm} < W \leq 0.10\text{mm}$	1	
		$W > 0.10\text{mm}$ or $L > 3.0\text{mm}$	0	
8	Mura (Minor)	By 5% ND filter invisible		