



# SpotNet — Learned iterations for cell detection in image-based immunoassays

Pol del Aguila Pla, Ph.D. Candidate

<https://poldap.github.io>, <https://github.com/poldap>

Division of Information Science and Engineering  
School of Electrical Engineering and Computer Science

Fork this project's repository at <https://github.com/poldap/SpotNet>

April 9, 2019 at



# Acknowledgements



J. Jaldén

V. Saxena

G. Bengtsson

J. Larsson

J. Sörell

E. Ågeby



KUNGL.  
VETENSKAPS-  
AKADEMIEN

THE ROYAL SWEDISH ACADEMY OF SCIENCES

Royal Swedish Academy of Sciences



Knut and Alice Wallenberg foundation



Gålostiftelsen



MabTech AB



Swedish Research Council



KTH Opportunities and EECS school




Plate of Fluorospot wells. Image provided by Mabtech AB, access at [http://bit.ly/Fluoro\\_Plate](http://bit.ly/Fluoro_Plate)




Plate of Fluorospot wells. Image provided by Mabtech AB, access at [http://bit.ly/Fluoro\\_Plate](http://bit.ly/Fluoro_Plate)







Plate of Fluorospot wells. Image provided by Mabtech AB, access at [http://bit.ly/Fluoro\\_Plate](http://bit.ly/Fluoro_Plate)



Fluorospot image, provided by Mabtech AB







The image  $s \in \mathbb{R}_+^{M,N}$  can be expressed as

$$s \approx \sum_{k=1}^K g_k \circledast x_k. \text{ Def. } \mathbf{x} \triangleq \left[ x_k \in \mathbb{R}_+^{M,N} \right]_1^K.$$

$x_k \in \mathbb{R}_+^{M,N}$ , spatial density of new particles at the  $k$ -th time window of an experiment.

Solve the convolutional (group-sparse) coding problem


$$\min_{\mathbf{x}} \left\{ \left\| \sum_{k=1}^K h_k \circledast x_k - s \right\|_2^2 + \lambda \mathcal{R}(\mathbf{x}) \right\}$$

$$\mathbf{x}_k^{(l)} \leftarrow \varphi_\lambda \left[ \mathbf{z}_k^{(l-1)} - \tilde{\mathbf{h}}_k \circledast \left( \sum_{q=1}^K \mathbf{h}_q \circledast \mathbf{z}_q^{(l-1)} - \mathbf{s} \right) \right]$$

with  $\varphi_\lambda(\cdot)$  the operator  $\text{prox}_{\lambda\mathcal{R}}(\cdot)$ , and then


$$\mathbf{z}_k^{(l)} \leftarrow \mathbf{x}_k^{(l)} + \alpha^{(l)} \left( \mathbf{x}_k^{(l)} - \mathbf{x}_k^{(l-1)} \right)$$

Results on real data and a real product




MabTech IRIS™

## Learned iterations for faster inverse problems (SpotNet)




Learned iterations, loop unrolling or learning to learn. Find the optimum faster.

## Learned iterations for faster inverse problems (SpotNet)




# Learned iterations for faster inverse problems (SpotNet)




$$\mathbf{x}_k^{(l)} \leftarrow \varphi_{\lambda} \left[ \mathbf{z}_k^{(l-1)} - \tilde{\mathbf{h}}_k \circledast \left( \sum_{q=1}^K \mathbf{h}_q \circledast \mathbf{z}_q^{(l-1)} - \mathbf{s} \right) \right]$$

# Learned iterations for faster inverse problems (SpotNet)



$$z_k^{(l)} \leftarrow x_k^{(l)} + \alpha^{(l)} \left( x_k^{(l)} - x_k^{(l-1)} \right)$$

## Learned iterations for faster inverse problems (SpotNet)




Based on LISTA from (Gregor and LeCun, 2010). Explored recently by (Giryes, Eldar et al., 2018) and others.

See the details at

<https://github.com/poldap/SpotNet>.

## Results for SpotNet with $L = 3$ and smaller kernels



- ▶ SpotNet vs generic ConvNet trained on  $\text{MSE}\{\hat{\mathbf{x}}\}$ .
- ▶ **Training on 7 synthetic images** with 1250 cells. Testing on 150 images containing 250, 750 or 1250 cells.

## Evaluation on synthetic data

Tolerance of  $\Delta = 3$  pix. Detection metrics

$$\text{pre} = \frac{\text{TP}}{\text{TP} + \text{FP}}, \text{ rec} = \frac{\text{TP}}{\text{TP} + \text{FN}}, \text{ and } \text{F1} = \frac{2 \text{pre} \cdot \text{rec}}{\text{pre} + \text{rec}}.$$

### Example



$\text{x}$ : Real cells

## Evaluation on synthetic data

Tolerance of  $\Delta = 3$  pix. Detection metrics

$$\text{pre} = \frac{\text{TP}}{\text{TP} + \text{FP}}, \text{ rec} = \frac{\text{TP}}{\text{TP} + \text{FN}}, \text{ and } \text{F1} = \frac{2 \text{pre} \cdot \text{rec}}{\text{pre} + \text{rec}}.$$

## Example




$\text{x}$ : Real cells       $\text{+}$ : Detections

## Evaluation on synthetic data

Tolerance of  $\Delta = 3$  pix. Detection metrics

$$\text{pre} = \frac{\text{TP}}{\text{TP} + \text{FP}}, \text{ rec} = \frac{\text{TP}}{\text{TP} + \text{FN}}, \text{ and } \text{F1} = \frac{2 \text{pre} \cdot \text{rec}}{\text{pre} + \text{rec}}.$$


## Example



$$\text{pre} = \text{rec} = \text{F1} = \frac{3}{4}.$$

$\text{x}$ : Real cells       $\text{+}$ : Detections

## Results for SpotNet with $L = 3$ and smaller kernels



- ▶ SpotNet vs generic ConvNet in F1 score.
- ▶ Trained on 7 images with 1250 cells.



# Thank you

Please, feel free to ask questions.

Pol del Aguila Pla, Ph.D. Candidate

Fork this project's repository at <https://github.com/poldap/SpotNet>



April 9, 2019 at