

European Molecular Imaging Meeting | EMIM 2020

24-28 August – virtual edition

Declaration of Financial Interests or Relationships



I have no financial interests or relationships to disclose with regard to the subject matter of this presentation.



Biomedical imaging as an inverse problem

Pol del Aguila Pla, Ph.D.
Center for Biomedical Imaging
Mathematical Imaging Section
Switzerland

Biomedical Imaging Group
EPFL, Lausanne, Switzerland




Slides mostly based on the work of Prof. Michaël Unser and the EPFL's Biomedical Imaging Group, in Lausanne, Switzerland.

EMIM 2020, Educational session on "Image processing & reconstruction"

Virtual conference

Biomedical imaging as an inverse problem



■ 1. Imaging as an inverse problem

- Basic imaging operators \mathbf{H}
- Discretization of the inverse problem $s \mapsto \mathbf{S}$

■ 2. A condensed history of image reconstruction

- Classical image reconstruction (1st gen.)
- Sparsity-based image reconstruction (2nd gen.)
- The learning revolution (3rd gen.)


3

EXAMPLE I

3D widefield microscopy



$s(x_1, x_2, x_3, c)$ (3D + 3 fluorophores)




Download the data from: <http://bigwww.epfl.ch/deconvolution/bio/> (C. Elegans embryo)



EXAMPLE II

ELISpot and FluoroSpot immunoassays



- Vaccine development (very timely)
- $2D \mathbf{y} \rightarrow 3D \mathbf{S}$



[del Aguila Pla, Jaldén, 2018] - IEEE TSP, Parts I and II
Download from: <https://poldap.github.io/#/pubs>


C I B M . C H

© CIBM | Center for Biomedical Imaging

Slide borrows material from: Prof. Joakim Jaldén, and Mabtech AB. 5

EXAMPLE III

Positron emission tomography (PET)



© CIBM | Center for Biomedical Imaging

Slide borrows material from: NiftyPET (github.com/NiftyPET). 6

C I B M . C H

Part 1

Imaging as an inverse problem



Forward imaging model (noise-free)

Unknown molecular/anatomical map: $s(\mathbf{r}), \mathbf{r} = (x, y, z, t) \in \mathbb{R}^d$

defined over a continuum in space-time

$$s \in L_2(\mathbb{R}^d) \quad (\text{space of finite-energy functions})$$

Imaging operator $\mathbf{H} : s \mapsto \mathbf{y} = (y_1, \dots, y_M) = \mathbf{H}\{s\}$

from continuum to discrete (finite dimensional)

$$\mathbf{H} : L_2(\mathbb{R}^d) \rightarrow \mathbb{R}^M$$

Linearity assumption: for all $s_1, s_2 \in L_2(\mathbb{R}^d), \alpha_1, \alpha_2 \in \mathbb{R}$

$$\mathbf{H}\{\alpha_1 s_1 + \alpha_2 s_2\} = \alpha_1 \mathbf{H}\{s_1\} + \alpha_2 \mathbf{H}\{s_2\}$$

$$\Rightarrow [\mathbf{y}]_m = y_m = \langle \eta_m, s \rangle = \int_{\mathbb{R}^d} \eta_m(\mathbf{r}) s(\mathbf{r}) d\mathbf{r}$$

↑ impulse response of the m th detector

(by the Riesz representation theorem)



$\eta_m(\cdot)$: analysis function



Basic operators: Fourier transform

Images are obviously made of sine waves...

$$e^{j\langle \omega_0, x \rangle}$$



EPFL Biomedical Imaging Group

$$\mathcal{F} : L_2(\mathbb{R}^d) \rightarrow L_2(\mathbb{R}^d)$$

$$\hat{s}(\omega) = \mathcal{F}\{s\}(\omega) = \int_{\mathbb{R}^d} s(r) e^{-j\langle \omega, r \rangle} dr$$

Reconstruction formula (inverse Fourier transform)


$$s(r) = \mathcal{F}^{-1}\{s\}(r) = \frac{1}{(2\pi)^d} \int_{\mathbb{R}^d} \hat{s}(\omega) e^{j\langle \omega, r \rangle} d\omega \quad (\text{a.e.})$$

9

Ex.: Magnetic resonance imaging

- Magnetic resonance: $\omega_0 = \gamma B_0$

Frequency encode:



- Linear forward model for MRI

$$r = (x, y, z)$$



$$\hat{s}(\omega_m) = \int_{\mathbb{R}^3} s(r) e^{-j\langle \omega_m, r \rangle} dr \quad (\text{sampling of Fourier transform})$$

Equivalent analysis functions: $\eta_m(r) = e^{j\langle \omega_m, r \rangle}$ (complex sinusoids)

- Extended forward model with coil sensitivity

$$\hat{s}_w(\omega_m) = \int_{\mathbb{R}^3} w(r) s(r) e^{-j\langle \omega_m, r \rangle} dr$$

$$\eta_m(r) = w(r) e^{j\langle \omega_m, r \rangle}$$

10

Basic operators: Multiplication

$$M_w : L_2(\mathbb{R}^d) \rightarrow L_2(\mathbb{R}^d)$$

$$M_w\{s\}(\mathbf{r}) = w(\mathbf{r})s(\mathbf{r})$$

Positive window function (cont. and bounded):

$$w \in \mathbf{C}_b(\mathbb{R}^d), w(\mathbf{r}) \geq 0$$

- Special case: modulation

$$w(\mathbf{r}) = e^{j\langle \omega_0, \mathbf{r} \rangle}$$

$$e^{j\langle \omega_0, \mathbf{r} \rangle} s(\mathbf{r}) \quad \xleftrightarrow{\mathcal{F}} \quad \hat{s}(\boldsymbol{\omega} - \boldsymbol{\omega}_0)$$

Applications:

- MRI with coil sensitivity
- Structured illumination microscopy (SIM)

Convolution

$$C_h : L_2(\mathbb{R}^d) \rightarrow L_2(\mathbb{R}^d)$$

$$C_h\{s\}(\mathbf{r}) = (h * s)(\mathbf{r}) = \int_{\mathbb{R}^d} h(\mathbf{r} - \tilde{\mathbf{r}})s(\tilde{\mathbf{r}})d\tilde{\mathbf{r}}$$

Equivalent analysis functions: $\eta_m(\mathbf{r}) = h(\mathbf{r}_m - \cdot)$

Frequency response: $\hat{h}(\boldsymbol{\omega}) = \mathcal{F}\{h\}(\boldsymbol{\omega})$


- Convolution as a frequency-domain product

$$(h * s)(\mathbf{r}) \quad \xleftrightarrow{\mathcal{F}} \quad \hat{h}(\boldsymbol{\omega})\hat{s}(\boldsymbol{\omega})$$

$$C_h = \mathcal{F}^{-1} \circ M_{\hat{h}} \circ \mathcal{F}$$

11



Ex.: 3D widefield microscopy



(Vonesch, Aguet, Vonesch, Unser, 2006)

■ Diffraction-limited optics

— Convolution / blur



Generate PSFs for a specific microscope with: [bigwww.epfl.ch/algorithms/psfgenerator/](http://www.epfl.ch/algorithms/psfgenerator/)

12



Basic operators: X-ray / Radon transform

Projection geometry: $\mathbf{r} = t\theta + q\theta^\perp$ with $\theta = [\cos \theta, \sin \theta]^T$

- Radon transform (line integrals) $R : \mathcal{S}(\mathbb{R}^2) \rightarrow \mathcal{S}(\mathbb{R} \times S^1)$

$$p_\theta(t) = R\{s\}(t, \theta) = \int_{\mathbb{R}} s(t\theta + q\theta^\perp) dq = \int_{\mathbb{R}^2} s(\mathbf{r}) \delta(t - \langle \mathbf{r}, \theta \rangle) d\mathbf{r}$$

Equivalent analysis functions (generalized): $\eta_m(\mathbf{r}) = \delta(t_m - \langle \mathbf{r}, \theta_m \rangle)$



- Central-slice theorem

$$\hat{p}_\theta(\omega) = (\mathcal{F}_t \circ R)\{s\}(\omega, \theta) = \mathcal{F}_r\{s\}(\omega\theta) = \hat{s}_{\text{pol}}(\omega, \theta)$$

\hat{s}_{pol} : 2D Fourier transform of s in polar coordinates.
 \mathcal{F}_t or \mathcal{F}_r : Fourier transform along t or r (resp.)

13

What we have learned in the perspective of some common biomedical imaging modalities

$$\begin{aligned} [Hs]_m &= y_m = \langle \eta_m, s \rangle \\ &= \int_{\mathbb{R}^d} \eta_m(\mathbf{r}) s(\mathbf{r}) d\mathbf{r} \end{aligned}$$

But how do we represent $s \in L_2(\mathbb{R}^d)$?

Modality	Radiation	Analysis function η_m
2D or 3D tomography	coherent x-ray	$\delta(t_m - \langle \mathbf{r}, \theta_m \rangle)$ θ_m : m th sampled direction
3D deconvolution microscopy	fluorescence	$h(\mathbf{r}_m - \mathbf{r})$ h : PSF of microscope
Structured illumination microscopy (SIM)	fluorescence	$h(\mathbf{r}_m - \mathbf{r}) w_m(\mathbf{r})$ w_m : m th illumination pattern
Positron emission tomography (PET)	gamma rays	$\delta(t_m - \langle \mathbf{r}, \theta_m \rangle)$ (θ_m, t_m) : m th LoR
Magnetic resonance imaging (MRI)	radio frequency	$e^{j\langle \omega_m, \mathbf{r} \rangle}$
Cardiac MRI (parallel, non-uniform)	radio frequency	$w_m(\mathbf{r}) e^{j\langle \omega_m, \mathbf{r} \rangle}$ w_m : sensitivity of the m th coil

Discretization: Finite dimensional formalism

Represent the continuous signal on a finite combination of synthesis functions $\beta_k(\mathbf{r})$


$$s(\mathbf{r}) = \sum_{\mathbf{k} \in \Omega} s[\mathbf{k}] \beta_{\mathbf{k}}(\mathbf{r}) \quad \text{with the signal vector (of coefficients): } \mathbf{s} = [s[\mathbf{k}]]_{\mathbf{k} \in \Omega} \text{ of dimension } K = |\Omega|.$$

- Applying the forward imaging model to such a signal

$$\begin{aligned} y_m &= \int_{\mathbb{R}^d} s(\mathbf{r}) \eta_m(\mathbf{r}) d\mathbf{r} + n[m] = \langle s, \eta_m \rangle + n[m], \quad (m = 1, \dots, M) \\ &= \sum_{\mathbf{k} \in \Omega} \langle \beta_{\mathbf{k}}, \eta_m \rangle s[\mathbf{k}] + n[m] \end{aligned}$$

η_m : analysis function, $\beta_{\mathbf{k}}$: synthesis function

$n[\cdot]$: additive noise



$$\Rightarrow \mathbf{y} = \mathbf{H}\mathbf{s} + \mathbf{n} \quad (M \times K) \text{ system matrix : } \quad [\mathbf{H}]_{m,\mathbf{k}} = \langle \eta_m, \beta_{\mathbf{k}} \rangle = \int_{\mathbb{R}^d} \eta_m(\mathbf{r}) \beta_{\mathbf{k}}(\mathbf{r}) d\mathbf{r}$$

15

Example of basis functions

Shift-invariant representation: $\beta_{\mathbf{k}}(\mathbf{r}) = \beta(\mathbf{r} - \mathbf{k})$


- Pixelated model

$$\beta(x) = \text{rect}(x)$$

- Bilinear model


$$\beta(x) = (\text{rect} * \text{rect})(x) = \text{tri}(x)$$

Separable generator: $\beta(\mathbf{r}) = \prod_{n=1}^d \beta(\mathbf{r}[n])$



- Bandlimited representation

$$\beta(x) = \text{sinc}(x)$$



16

Part 2: A condensed history of image reconstruction

Classical image reconstruction
(1st gen., 20th century)



Sparsity-based image reconstruction
(2nd gen., 21st century)



The learning revolution
(3rd gen.)



See more (2h 30min) at youtu.be/J6_5rPYnr_s

17

Classical image reconstruction
(1st gen., 20th century)



- Easy scenario, well posedness:

$$C_1 \|\mathbf{s}\|_2 \leq \|\mathbf{Hs}\|_2 \leq C_2 \|\mathbf{s}\|_2 \quad \text{for all } \mathbf{s} \in \mathcal{X}$$

$$\Rightarrow \mathbf{s} \approx \mathbf{H}^{-1}\mathbf{y}$$

Backprojection: $\mathbf{s} \approx \mathbf{H}^T\mathbf{y}$

$$\text{Least-squares: } \min_{\tilde{\mathbf{s}} \in \mathbb{R}_+^M} \{ \|\mathbf{y} - \mathbf{H}\tilde{\mathbf{s}}\|^2 \}$$

$$\Rightarrow \mathbf{s} = (\mathbf{H}^T\mathbf{H})^{-1}\mathbf{H}^T\mathbf{y}$$

■ Limitations:



- Amplification of the noise
- Interesting problems are ill-posed
- Computationally expensive matrix inversions

■ Efficient iterative algorithms

$$\min_{\tilde{\mathbf{s}} \in \mathbb{R}_+^K} J(\tilde{\mathbf{s}}, \mathbf{y})$$

$$\|\mathbf{y} - \mathbf{Hs}\|^2 = \mathbf{y}^T\mathbf{y} - 2\mathbf{s}^T\mathbf{H}^T\mathbf{y} + \mathbf{s}^T\mathbf{H}^T\mathbf{Hs}$$

Steepest-descent type: $\mathbf{s}^{(i+1)} \leftarrow \mathbf{s}^{(i)} - \gamma \nabla_{\mathbf{s}}\{J(\mathbf{s}, \mathbf{y})\}(\mathbf{s}^{(i)})$
ex.: projected gradient descent, followed by $\mathbf{s}^{(i+1)} \leftarrow [\mathbf{s}^{(i+1)}]_+$



Andrey N. Tikhonov
(1906-1993)

■ Tikhonov / Wiener theory

$$\min_{\tilde{\mathbf{s}} \in \mathbb{R}_+^K} \underbrace{\|\mathbf{y} - \mathbf{H}\tilde{\mathbf{s}}\|_2^2}_{\text{data consistency}} + \underbrace{\lambda \|\mathbf{L}\tilde{\mathbf{s}}\|_2^2}_{\text{regularization or Gaussian prior}}$$



Norbert Wiener
(1894-1964)

\mathbf{L} to promote smoothness

"Filtered" backprojection

$$\Rightarrow \mathbf{s} = (\mathbf{H}^T\mathbf{H} + \lambda \mathbf{L}^T\mathbf{L})^{-1}\mathbf{H}^T\mathbf{y}$$

■ Limitations:

- Computationally expensive matrix inversions

18

Classical image reconstruction (1st gen., 20th century)



- Easy scenario, well posedness:

$$C_1 \|\mathbf{s}\|_2 \leq \|\mathbf{Hs}\|_2 \leq C_2 \|\mathbf{s}\|_2 \quad \text{for all } \mathbf{s} \in \mathcal{X}$$

$$\Rightarrow \mathbf{s} \approx \mathbf{H}^{-1}\mathbf{y}$$

Backprojection: $\mathbf{s} \approx \mathbf{H}^T\mathbf{y}$

$$\text{Least-squares: } \min_{\tilde{\mathbf{s}} \in \mathbb{R}_+^M} \{\|\mathbf{y} - \mathbf{H}\tilde{\mathbf{s}}\|^2\}$$

$$\Rightarrow \mathbf{s} = (\mathbf{H}^T\mathbf{H})^{-1}\mathbf{H}^T\mathbf{y}$$

- Limitations:

- Amplification of the noise
- Interesting problems are ill-posed
- Computationally expensive matrix inversions

- Efficient iterative algorithms $\min_{\tilde{\mathbf{s}} \in \mathbb{R}_+^K} J(\tilde{\mathbf{s}}, \mathbf{y})$

$$\text{Steepest-descent type: } \mathbf{s}^{(i+1)} \leftarrow \mathbf{s}^{(i)} - \gamma \nabla_{\mathbf{s}}\{J(\mathbf{s}, \mathbf{y})\}(\mathbf{s}^{(i)})$$

ex.: projected gradient descent, followed by $\mathbf{s}^{(i+1)} \leftarrow [\mathbf{s}^{(i+1)}]_+$



Ground truth



Gaussian blur + additive noise



van Cittert animation

$$\|\mathbf{y} - \mathbf{Hs}\|^2 = \mathbf{y}^T\mathbf{y} - 2\mathbf{s}^T\mathbf{H}^T\mathbf{y} + \mathbf{s}^T\mathbf{H}^T\mathbf{Hs}$$

Least squares:

$$\mathbf{s}^{(i+1)} \leftarrow \mathbf{s}^{(i)} + \tilde{\gamma}(\mathbf{s}_0 - (\mathbf{H}^T\mathbf{H})\mathbf{s}^{(i)}) \text{ with } \mathbf{s}_0 = \mathbf{H}^T\mathbf{y}$$

- Tikhonov / Wiener theory

$$\min_{\tilde{\mathbf{s}} \in \mathbb{R}_+^K} \underbrace{\|\mathbf{y} - \mathbf{H}\tilde{\mathbf{s}}\|_2^2}_{\text{data consistency}} + \underbrace{\lambda \|\mathbf{L}\tilde{\mathbf{s}}\|_2^2}_{\text{regularization or Gaussian prior}}$$



Andrey N. Tikhonov
(1906-1993)

Norbert Wiener
(1894-1964)

"Filtered" backprojection

$$\Rightarrow \mathbf{s} = (\mathbf{H}^T\mathbf{H} + \lambda \mathbf{L}^T\mathbf{L})^{-1}\mathbf{H}^T\mathbf{y}$$

- Limitations:

- Computationally expensive matrix inversions

19

Classical image reconstruction (1st gen., 20th century)



- Easy scenario, well posedness:

$$C_1 \|\mathbf{s}\|_2 \leq \|\mathbf{Hs}\|_2 \leq C_2 \|\mathbf{s}\|_2 \quad \text{for all } \mathbf{s} \in \mathcal{X}$$

$$\Rightarrow \mathbf{s} \approx \mathbf{H}^{-1}\mathbf{y}$$

Backprojection: $\mathbf{s} \approx \mathbf{H}^T\mathbf{y}$

$$\text{Least-squares: } \min_{\tilde{\mathbf{s}} \in \mathbb{R}_+^M} \{\|\mathbf{y} - \mathbf{H}\tilde{\mathbf{s}}\|^2\}$$

$$\Rightarrow \mathbf{s} = (\mathbf{H}^T\mathbf{H})^{-1}\mathbf{H}^T\mathbf{y}$$

- Limitations:

- Amplification of the noise
- Interesting problems are ill-posed
- Computationally expensive matrix inversions

- Efficient iterative algorithms $\min_{\tilde{\mathbf{s}} \in \mathbb{R}_+^K} J(\tilde{\mathbf{s}}, \mathbf{y})$

$$\text{Steepest-descent type: } \mathbf{s}^{(i+1)} \leftarrow \mathbf{s}^{(i)} - \gamma \nabla_{\mathbf{s}}\{J(\mathbf{s}, \mathbf{y})\}(\mathbf{s}^{(i)})$$


ex.: projected gradient descent, followed by $\mathbf{s}^{(i+1)} \leftarrow [\mathbf{s}^{(i+1)}]_+$



Ground truth



Gaussian blur + additive noise



Not enough: $\lambda=0.2$



Andrey N. Tikhonov
(1906-1993)

- Tikhonov / Wiener theory

$$\min_{\tilde{\mathbf{s}} \in \mathbb{R}_+^K} \underbrace{\|\mathbf{y} - \mathbf{H}\tilde{\mathbf{s}}\|_2^2}_{\text{data consistency}} + \underbrace{\lambda \|\mathbf{L}\tilde{\mathbf{s}}\|_2^2}_{\text{regularization or Gaussian prior}}$$




Norbert Wiener
(1894-1964)

"Filtered" backprojection

$$\Rightarrow \mathbf{s} = (\mathbf{H}^T\mathbf{H} + \lambda \mathbf{L}^T\mathbf{L})^{-1}\mathbf{H}^T\mathbf{y}$$

- Limitations:

- Computationally expensive matrix inversions



Optimal: $\lambda=2$



Too much: $\lambda=20$

20

Sparsity-based image reconstruction (2nd gen., 21st century)



Non-quadratic regularization

$$\min_{\mathbf{s} \in \mathbb{R}_+^K} \|\mathbf{y} - \mathbf{H}\mathbf{s}\|_2^2 + \lambda \mathcal{R}(\mathbf{s})$$

$$\mathcal{R}(\mathbf{s}) = \|\mathbf{L}\mathbf{s}\|_2^2 \longrightarrow \|\mathbf{L}\mathbf{s}\|_p^p \longrightarrow \mathcal{R}(\mathbf{s}) = \|\mathbf{L}\mathbf{s}\|_1$$

■ Total variation, \mathbf{L} : gradient [Rudin, Osher et al., 1992]

■ Wavelet-domain regularization, $\mathbf{s} = \mathbf{W}\mathbf{x}$, $\mathcal{R}(\mathbf{x}) = \|\mathbf{x}\|_1$ equivalent to $\mathbf{L} = \mathbf{W}^{-1}$

[Figueiredo et al., 2004] [Daubechies et al., 2004]

Formalization: Compressed sensing [Donoho et al., 2005][Candès, Romberg, Tao, 2006]

Sparse representation of signal vector $\mathbf{x} \in \mathbb{R}^N$ with $\|\mathbf{x}\|_0 = S \ll N$

$M \times N$ system matrix: $\mathbf{A} = \mathbf{H}\mathbf{W}$ in the undersampled regime $M \ll N$ and $2S < M$

$$\min_{\mathbf{x}: \|\mathbf{x}\|_0 \leq K} \|\mathbf{y} - \mathbf{Ax}\|_2^2 \Leftrightarrow \min_{\mathbf{x}: \|\mathbf{x}\|_1 \leq C} \|\mathbf{y} - \mathbf{Ax}\|_2^2$$


(nonconvex) (convex)

w. some conditions on \mathbf{A}


A representer-theorem view [Unser, Fageot, Gupta, 2016] - IEEE TIT

$$\min_{\mathbf{x}} \{\|\mathbf{y} - \mathbf{Ax}\|_2^2 + \lambda \|\mathbf{x}\|_2^2\} \Leftrightarrow \min_{\mathbf{x}} \|\mathbf{x}\|_2 \text{ subject to } \|\mathbf{y} - \mathbf{Ax}\|_2^2 \leq \sigma^2$$

$$\min_{\mathbf{x}} \{\|\mathbf{y} - \mathbf{Ax}\|_2^2 + \lambda \|\mathbf{x}\|_1\} \Leftrightarrow \min_{\mathbf{x}} \|\mathbf{x}\|_1 \text{ subject to } \|\mathbf{y} - \mathbf{Ax}\|_2^2 \leq \sigma^2$$



[Guerquin-Kern et al., 2011] - IEEE TMI



23

Sparsity-based image reconstruction (2nd gen., 21st century)



Non-quadratic regularization

$$\min_{\mathbf{s} \in \mathbb{R}_+^K} \|\mathbf{y} - \mathbf{H}\mathbf{s}\|_2^2 + \lambda \mathcal{R}(\mathbf{s})$$

$$\mathcal{R}(\mathbf{s}) = \|\mathbf{L}\mathbf{s}\|_2^2 \longrightarrow \|\mathbf{L}\mathbf{s}\|_p^p \longrightarrow \mathcal{R}(\mathbf{s}) = \|\mathbf{L}\mathbf{s}\|_1$$

■ Total variation, \mathbf{L} : gradient [Rudin, Osher et al., 1992]

■ Wavelet-domain regularization, $\mathbf{s} = \mathbf{W}\mathbf{x}$, $\mathcal{R}(\mathbf{x}) = \|\mathbf{x}\|_1$ equivalent to $\mathbf{L} = \mathbf{W}^{-1}$

[Figueiredo et al., 2004] [Daubechies et al., 2004]

Formalization: Compressed sensing [Donoho et al., 2005][Candès, Romberg, Tao, 2006]

Sparse representation of signal vector $\mathbf{x} \in \mathbb{R}^N$ with $\|\mathbf{x}\|_0 = S \ll N$

$M \times N$ system matrix: $\mathbf{A} = \mathbf{H}\mathbf{W}$ in the undersampled regime $M \ll N$ and $2S < M$

$$\min_{\mathbf{x}: \|\mathbf{x}\|_0 \leq K} \|\mathbf{y} - \mathbf{Ax}\|_2^2 \Leftrightarrow \min_{\mathbf{x}: \|\mathbf{x}\|_1 \leq C} \|\mathbf{y} - \mathbf{Ax}\|_2^2$$

(nonconvex) (convex)


w. some conditions on \mathbf{A}

A representer-theorem view [Unser, Fageot, Gupta, 2016] - IEEE TIT


$$\min_{\mathbf{x}} \{\|\mathbf{y} - \mathbf{Ax}\|_2^2 + \lambda \|\mathbf{x}\|_2^2\} \Leftrightarrow \min_{\mathbf{x}} \|\mathbf{x}\|_2 \text{ subject to } \|\mathbf{y} - \mathbf{Ax}\|_2^2 \leq \sigma^2$$

$$\min_{\mathbf{x}} \{\|\mathbf{y} - \mathbf{Ax}\|_2^2 + \lambda \|\mathbf{x}\|_1\} \Leftrightarrow \min_{\mathbf{x}} \|\mathbf{x}\|_1 \text{ subject to } \|\mathbf{y} - \mathbf{Ax}\|_2^2 \leq \sigma^2$$

Sparsifying transforms \mathbf{W}^{-1}



[Guerquin-Kern et al., 2011] - IEEE TMI




24

Sparsity-based image reconstruction (2nd gen., 21st century)



Non-quadratic regularization



- Total variation, L : gradient [Rudin, Osher et al., 1992]
- Wavelet-domain regularization, $s = \mathbf{W}x$, $R(x) = \|x\|_1$ equivalent to $L = \mathbf{W}^{-1}$
[Figueiredo et al., 2004] [Daubechies et al., 2004]

Formalization: Compressed sensing [Donoho et al., 2005][Candès, Romberg, Tao, 2006]

Sparse representation of signal vector $x \in \mathbb{R}^N$ with $\|x\|_0 = S \ll N$
 $M \times N$ system matrix: $\mathbf{A} = \mathbf{H}\mathbf{W}$ in the undersampled regime $M \ll N$ and $2S < M$

$$\min_{x: \|x\|_0 \leq K} \|y - \mathbf{Ax}\|_2^2 \Leftrightarrow \min_{x: \|x\|_1 \leq C} \|y - \mathbf{Ax}\|_2^2$$

(nonconvex) (convex)

w. some conditions on \mathbf{A}

A representer-theorem view [Unser, Fageot, Gupta, 2016] - IEEE TIT


Representer theorem for constrained ℓ_1 minimization

$$(P1) \quad \mathcal{V} = \arg \min_{x \in \ell_1(\mathbb{Z})} \|x\|_{\ell_1} \text{ s.t. } H\{x\} \in \mathcal{C}$$

is convex, weak*-compact with extreme points of the form

$$x_{\text{sparse}}[\cdot] = \sum_{k=1}^S a_k \delta[\cdot - n_k] \quad \text{with} \quad S = \|x_{\text{sparse}}\|_0 \leq M.$$

Sparsifying transforms \mathbf{W}^{-1}



[Guerquin-Kern et al., 2011] - IEEE TMI

Sparse stochastic processes

Unser and Tafti

An Introduction to
Sparse Stochastic Processes

CAMBRIDGE

There is an operator L that "whitens" the continuous signal, i.e., $w = L\{s\}$

$\Rightarrow \mathbf{u} = \mathbf{L}s$ where \mathbf{L} discretizes L , and $p_U(\mathbf{u})$ is infinitely divisible

$$p_{S|Y}(s|y) \propto \exp\left(-\frac{\|y - Hs\|^2}{2\sigma^2}\right) \prod_{k \in \Omega} p_U([Ls]_k) \quad \|\cdot\|_1 \Leftrightarrow U \text{ is Laplace}$$

25

Sparsity-based image reconstruction (2nd gen., 21st century)



Proximal optimization algorithms: The workhorse of 2nd generation methods

- Ex: Alternating direction method of multipliers (ADMM), [Boyd et al., 2011]

$$\min_{s, u: u=Ls} \frac{1}{2} \|y - Hs\|_2^2 + \lambda R(u) \quad \mathcal{L}_{\mathcal{A}}(s, u, \alpha) = \frac{1}{2} \|y - Hs\|_2^2 + \lambda R(u) + \alpha^T(Ls - u) + \frac{\mu}{2} \|Ls - u\|_2^2$$


Linear inverse problem: $s^{k+1} \leftarrow (\mathbf{H}^T \mathbf{H} + \mu \mathbf{L}^T \mathbf{L})^{-1} (\mathbf{H}^T y + \mathbf{z}^{k+1})$ with $\mathbf{z}^{k+1} \leftarrow \mathbf{L}^T (\mu \mathbf{u}^k - \alpha^k)$

$$\alpha^{k+1} \leftarrow \alpha^k + \mu (\mathbf{L}s^{k+1} - \mathbf{u}^k)$$

Nonlinear denoising: $\mathbf{u}^{k+1} \leftarrow \text{prox}_{\frac{\lambda}{\mu} R}(\mathbf{L}s^{k+1} + \frac{1}{\mu} \alpha^{k+1})$

$$\text{prox}_{\lambda R}(y) = \arg \min_u \frac{1}{2} \|y - u\|_2^2 + \lambda R(u) \quad (\text{often separable})$$

- Example: \mathbf{L} wavelet, $R(u) = \|u\|_1$ (Laplace model) \rightarrow wavelet thresholding denoiser
- Separation in linear step (problem specific) and statistical step (denoiser for prior distribution)



Advantages:

- Higher reconstruction quality [Lustig et al., 2007]
- Low-dose, faster imaging (CS)
- Re-use of fast implementations for 1st gen. methods

Limitations:

- Increased complexity (despite efficient solutions)
- Challenging to implement efficiently



Download from:
github.com/Biomedical-Imaging-Group/GlobalBiomed

See more at bit.ly/GlobalBiomed-example


Explained with all detail at youtu.be/J6_5rPYnr_s?t=6240

26

The learning revolution (3rd gen.)




Overarching topic: How do we leverage what we already know?




CT
data

MAYO CLINIC




27

The learning revolution (3rd gen.)



Overarching topic: How do we leverage what we already know?



Going too far to the right

- Ignoring the physics, learning them instead

[Zhu et al., 2018] - Nature

Guiding principles

- Learn image-to-image maps, either
 - within the image (sparsified or not) domain, or
 - within the measurement domain.
- Need for very large training datasets with gold-standard reconstructions. But exploit the problem structure.
- Data augmentation.


Unrolling as a motivation for deep architectures

[Gregor, LeCun, 2010]

- Use 2nd generation methods as a starting point

- Motivate the architecture using optimization

- Ex:** Unrolled FISTA for inverse diffusion (immunoassays)



The learning revolution (3rd gen.)



Going too far to the right


- Ignoring the physics, learning them instead
[Zhu et al., 2018] - Nature

Guiding principles

- Learn image-to-image maps, either
 1. within the image (sparsified or not) domain, or
 2. within the measurement domain.
- Need for very large training datasets with gold-standard reconstructions. But exploit the problem structure.
- Data augmentation.

Overarching topic: How do we leverage what we already know?

Dimensionality of parameters learnt




2019 Best Paper Award
IEEE Signal Processing Society

Unrolling as a motivation for deep architectures

[Gregor, LeCun, 2010]

- Use 2nd generation methods as a starting point
- Motivate the architecture using optimization

A word of warning: Instability in deep learning



[Antun et al., 2020] On instabilities of deep learning in image reconstruction - Does AI come at a cost?

29

The learning revolution (3rd gen.)



Going too far to the right

- Ignoring the physics, learning them instead
[Zhu et al., 2018] - Nature

Guiding principles

- Learn image-to-image maps, either
 1. within the image (sparsified or not) domain, or
 2. within the measurement domain.
- Need for very large training datasets with gold-standard reconstructions. But exploit the problem structure.
- Data augmentation.

Overarching topic: How do we leverage what we already know?

Dimensionality of parameters learnt




2019 Best Paper Award
IEEE Signal Processing Society

Unrolling as a motivation for deep architectures

[Gregor, LeCun, 2010]

- Use 2nd generation methods as a starting point
- Motivate the architecture using optimization

A word of warning: Instability in deep learning



[Antun et al., 2020] On instabilities of deep learning in image reconstruction - Does AI come at a cost?

30

The learning revolution (3rd gen.)

■ Overarching topic: How do we leverage what we already know?

Dimensionality of parameters learnt			
Parameter tuning	Dictionary learning	Learning non-linear functions	Task-specific learning (CNNs)
<ul style="list-style-type: none"> • Learning λ • Calibrate forward model 	<ul style="list-style-type: none"> • An "optimal" \mathcal{L} [Elad 2006] [Ravishankar 2011] [Mairal 2012] 	<ul style="list-style-type: none"> • An "optimal" \mathcal{R} • CNN parametrization • Backpropagation [Chen, Pock, 2015-2016] [Kamilov 2016] 	<ul style="list-style-type: none"> • Artifact removal for 1st gen. reconstructions • Super-resolution in 3D imaging • Speeding up well-performing 2nd gen. methods • Low-dose / short-scan regime
[Zhu et al., 2018] - Nature	[Elad 2006]	[Chen, Pock, 2015-2016]	[Jin et al., 2016]
[Weigert et al., 2017]	[Ravishankar 2011]	[Kamilov 2016]	[Hammerl et al., 2018]

■ Going too far to the right

- Ignoring the physics, learning them instead

■ Guiding principles

- Learn image-to-image maps, either
 1. within the image (sparsified or not) domain, or
 2. within the measurement domain.
- Need for very large training datasets with gold-standard reconstructions. But exploit the problem structure.
- Data augmentation.

■ Unrolling as a motivation for deep architectures

[Gregor, LeCun, 2010]

- Use 2nd generation methods as a starting point
- Motivate the architecture using optimization

■ A word of warning: Instability in deep learning

Kernel (nullspace) awareness

[Antun et al., 2020] On instabilities of deep learning in image reconstruction - Does AI come at a cost?

2019 Best Paper Award
IEEE Signal Processing Society

31

References

■ Foundations

- M.T. McCann, M. Unser, **Biomedical Image Reconstruction: From the Foundations to Deep Neural Networks**, *Foundations and Trends in Signal Processing*, vol. 13, no. 3, pp. 280-359, December 3, 2019.
- M. Unser and P. Tafti, *An Introduction to Sparse Stochastic Processes*, Cambridge University Press, 2014; preprint, available at <http://www.sparseprocesses.org>.
- M. Unser, J. Fageot, H. Gupta, "Representer Theorems for Sparsity-Promoting ℓ_1 Regularization," *IEEE Trans. Information Theory*, vol. 62, no. 9, pp. 5167-5180, September 2016.
- M. Unser, J. Fageot, J.P. Ward, "Splines Are Universal Solutions of Linear Inverse Problems with Generalized TV Regularization," *SIAM Review*, vol. 59, no. 4, pp. 769-793, December 2017.

■ Algorithms and imaging applications

- E. Soubies, F. Soulez, M.T. McCann, T.-a. Pham, L. Donati, T. Debarre, D. Sage, M. Unser, "Pocket Guide to Solve Inverse Problems with GlobalBiolm," *Inverse Problems*, vol. 35, no. 10, paper no. 104006, pp. 1-20, October 2019.
- E. Bostan, U.S. Kamilov, M. Nilchian, M. Unser, "Sparse Stochastic Processes and Discretization of Linear Inverse Problems," *IEEE Trans. Image Processing*, vol. 22, no. 7, pp. 2699-2710, 2013.
- C. Vonesch, M. Unser, "A Fast Multilevel Algorithm for Wavelet-Regularized Image Restoration," *IEEE Trans. Image Processing*, vol. 18, no. 3, pp. 509-523, 2009.
- M. Guerquin-Kern, M. Häberlin, K.P. Pruessmann, M. Unser, "A Fast Wavelet-Based Reconstruction Method for Magnetic Resonance Imaging," *IEEE Transactions on Medical Imaging*, vol. 30, no. 9, pp. 1649-1660, 2011.
- E. Soubies, M. Unser, "Computational Super-Sectioning for Single-Slice Structured-Illumination Microscopy," *IEEE Trans. Computational Imaging*, vol. 5, no. 2, pp. 24
- M. Nilchian, C. Vonesch, S. Lefkimiatis, P. Modregger, M. Stampanoni, M. Unser, "Constrained Regularized Reconstruction of X-Ray-DPCI Tomograms with Weighted-Norm," *Optics Express*, vol. 21, no. 26, pp. 32340-32348, 2013.

32

References (Cont'd)

- P. del Aguila Pla and J. Jaldén, "Cell detection by functional inverse diffusion and non-negative group sparsity—Part I: Modeling and Inverse Problems", *IEEE Transactions on Signal Processing*, vol. 66, no. 20, pp. 5407–5421, 2018
- P. del Aguila Pla and J. Jaldén, "Cell detection by functional inverse diffusion and non-negative group sparsity—Part II: Proximal optimization and Performance evaluation", *IEEE Transactions on Signal Processing*, vol. 66, no. 20, pp. 5422–5437, 2018

■ Deep neural networks

- K.H. Jin, M.T. McCann, E. Froustey, M. Unser, "Deep Convolutional Neural Network for Inverse Problems in Imaging," *IEEE Trans. Image Processing*, vol. 26, no. 9, pp. 4509-4522, 2017.
- M.T. McCann, K.H. Jin, M. Unser, "Convolutional Neural Networks for Inverse Problems in Imaging—A Review," *IEEE Signal Processing Magazine*, vol. 34, no. 6, pp. 85-95, 2017.
- H. Gupta, K.H. Jin, H.Q. Nguyen, M.T. McCann, M. Unser, "CNN-Based Projected Gradient Descent for Consistent CT Image Reconstruction," *IEEE Trans. Medical Imaging*, vol. 37, no. 6, pp. 1440-1453, 2018.
- M. Unser, "A representer theorem for deep neural networks," *Journal of Machine Learning Research*, vol. 20, no. 110, pp. 1-30, 2019.
- P. del Aguila Pla, V. Saxena, J. Jaldén, "SpotNet - Learned iterations for cell detection in image-based immunoassays," 2019 IEEE 16th International Symposium on Biomedical Imaging (ISBI 2019), Venice, Italy, April 8-11, 2019.

33

Acknowledgments

Many thanks to current and former members of the EPFL's Biomedical Imaging Group



Prof. Michaël Unser

