

Getting Started with Uclid5

Alpha release, version 0.9.5

Pramod Subramanyan and Sanjit A. Seshia
{spramod, ssesia}@eecs.berkeley.edu

June 2018

Contents

1	Syntax	3
2	Uclid5 Semantics	4

1 Syntax

A model consist of a list of modules. Each module consists of a list of declarations followed by an optional control block.

$\langle Model \rangle$	$::= \langle Module \rangle^*$
$\langle Module \rangle$	$::= \text{module } \langle Id \rangle \text{ '}' \langle Decl \rangle^* \langle ControlBlock \rangle? \text{'}'$
$\langle Decl \rangle$	$::= \langle VarDecl \rangle^* \mid \langle NextDecl \rangle$
$\langle VarDecl \rangle$	$::= \text{var } \langle Id \rangle \text{' : ' } \langle Type \rangle \text{' ; '}$
$\langle NextDecl \rangle$	$::= \text{next } \text{'{' } \langle Stmt \rangle^* \text{'}'$
$\langle Stmt \rangle$	$::= \langle Id \rangle \text{' = ' } \langle Expr \rangle \text{' ; '}$
$\langle Expr \rangle$	$::= \langle Id \rangle \mid \langle Expr \rangle \odot_b \langle Expr \rangle \mid \odot_u \langle Expr \rangle$

2 Uclid5 Semantics

Bibliography