

Travlendar+ project Neroni, Pozzi, Vetere

# **Design Document**

Deliverable: DD

**Title:** Design Document

Authors: Cristiano Neroni, Davide Pozzi, Maurizio Vetere

**Version:** 1.0

**Date:** 10-January-2021

**Download page:** https://github.com/pollo-fritto/PozziNeroniVetere

Copyright: Copyright © 2021, Neronil Pozzil Vetere – All rights reserved

# Travlendar+ project by YOUR NAMES

# **Contents**

Table of Contents  List of Figures  List of Tables								
					1	Intr	oduction	5
						1.1	Purpose	5
	1.2	Scope	5					
	1.3	Definitions, Acronyms, Abbreviations	5					
		1.3.1 Definitions	5					
		1.3.2 Acronyms	5					
		1.3.3 Abbreviations	5					
	1.4	Revision history	5					
	1.5	Reference Documents	5					
	1.6	Document Structure	5					
2	Arc	hitectural Design	7					
	2.1	Overview	7					
	2.2	Component view	7					
	2.3	Deployment view	7					
	2.4	Runtime view	7					
	2.5	Component interfaces	7					
	2.6	Selected architectural styles and patterns	7					
	2.7	Other design decisions	7					
3	Use	r Interface Design	8					
	3.1	Overview	8					
		3.1.1 User Interfaces	8					
4	Req	uirements Traceability	13					
5	Implementation, Integration and Test Plan							
	5.1		14					
	5.2	*	14					
	5.3		14					
6	Effo	rt Spent	15					

# **List of Figures**

1	App startup
2	Quick ticket procedure
3	Filters
4	Booking procedure
5	Shop and exit
6	Totem ticket procedure
7	Store manager web app

# **List of Tables**

#### 1 Introduction

### 1.1 Purpose

The purpose of this document is to provide more technical and detailed information about the software discussed in the RASD document. It will represent a strong guide for the programmers that will develop the application considering its different parts: the basic service and the two advanced functions. In this DD we present hardware and software architecture of the system in terms of components and interactions among those components. Furthermore, this document describes a set of design characteristics required for the implementation by introducing constraints and quality attributes. It also gives a detailed presentation of the implementation plan, integration plan and the testing plan. In general, the main different features listed in this document are:

- The high-level architecture of the system
- Main components of the system
- Interfaces provided by the components
- Design patterns adopted

Stakeholders are invited to read this document in order to understand the characteristics of the project being aware of the choices that have been made to offer all the functionalities also satisfying the quality requirements.

### 1.2 Scope

Clup is an application that aims to avoid users from crowding outside supermarkets when doing grocery shopping in pandemic times.

The application can be used both by store customers and store managers. On one hand users can virtually queue by Clup to enter the supermarket and they are provided with real time information about the line, in this way they can arrive at the entrance only when they are allowed to enter. On the other hand the application monitors and stores the information about people fluxes; this data is then provided to store managers who can take actions depending on the situation. The few paragraphs just read represent an overview of the main functionalities offered by the system: more detailed information can be found on the RASD document.

#### 1.3 Definitions, Acronyms, Abbreviations

- 1.3.1 Definitions
- 1.3.2 Acronyms
- 1.3.3 Abbreviations
- 1.4 Revision history
- 1.5 Reference Documents

#### 1.6 Document Structure

- Chapter 1 describes the scope and purpose of the DD, including the structure of the document and the set of definitions, acronyms and abbreviations used.
- Chapter 2 contains the architectural design choice, it includes all the components, the interfaces, the technologies (both hardware and software) used for the development of the application. It also

includes the main functions of the interfaces and the processes in which they are utilised (Runtime view and component interfaces). Finally, there is the explanation of the architectural patterns chosen with the other design decisions.

- Chapter 3 shows how the user interface should be on the mobile and web application.
- Chapter 4 describes the connection between the RASD and the DD, showing the matching between the goals and requirements described previously with the elements which compose the architecture of the application.
- Chapter 5 traces a plan for the development of components to maximize the efficiency of the developer team and the quality controls team. It is divided in two sections: implementation and integration. It also includes the testing strategy.
- Chapter 6 shows the effort spent for each member of the group.
- Chapter 7 includes the reference documents.

### 2 Architectural Design

#### 2.1 Overview

CLup's architecture is layered as follows:

- **Presentation layer** (P) handles the interaction with users. It contains the interfaces able to communicate with them and it is responsible for rendering of the information. Its scope is to make understandable the functions of the application to the customers.
- **Application layer** (A) takes care of the functions to be provided for the users. It also coordinates the work of the application, making logical decisions and moving data between the other two layers.
- **Data access layer** (D) which takes care of the information management, database access control. It also handles data retrieval and passes them to upper level layers.

The architecture style chosen for CLup is the **multi-tier** one. As previously anticipated in the Requirements Analysis and Specifications Document, there will be at least one server for each one of the following interest areas:

- Bookings
- Queues
- Notifications
- Stores
- · Staff members
- Customers

This is mainly done to distribute workload as well as making the overall system more robust. There will be also at least two servers for the two following functionalities:

- Customer related functionalities
- Staff related functionalities

The bookings, queue and notifications databases will be distributed and replicated all over the entire store list. Each store will have its own instance of bookings, queue and notifications database while a central logic server will act as a request redirector towards them whenever needed.

- 2.2 Component view
- 2.3 Deployment view
- 2.4 Runtime view
- 2.5 Component interfaces
- 2.6 Selected architectural styles and patterns
- 2.7 Other design decisions


### 3 User Interface Design

#### 3.1 Overview


CLup is an application aimed at decreasing the probability of contracting COVID-19 (diseases in general) when going shopping to a supermarket. There are two fundamental components: the main one targets customers of supermarkets while the second one is available for store managers.

#### 3.1.1 User Interfaces

**End user functionalities** Regarding the first target - customers - they will be required to register to the service the first time they use it by inserting their full name, email address, ID card, phone number and a password. The customer will also be requested to specify his physical address, or to enable the GPS, in order to allow CLup to find stores nearby; this last information can be changed anytime the user needs. If the customer is not willing to register or share his address, the service will not be available.







(b) Main screen

Figure 1: App startup

Once the setup is done, customers will be able to access the homepage of the application, where they can tap on the "Quick ticket" button that will allow them to see a list of stores inside a specified range from their current location: for each store a distance in kilometers from the user position will be outlined, as well as the number of people inside the store and its maximum capacity; whenever a store is full, the current number of people in line and an *EWT* are displayed.

It is also possible to visualize stores on a map and, by tapping on one of them, to see the same information displayed in the list. Now, if the user chooses to reserve a spot in the line, the application will open a confirm dialog specifying EWT and the expiration of the ticket. If the user refuses nothing happens, if he accepts instead CLup will process the request, show his ticket and the real time evolution of the line; the ticket is also visible from the home screen.

The tickets consist of a QR code and an easy to remember alphanumeric code alternative to enter the store. At the stores entrances there will also be monitors that show the numbers allowed to enter and,





Figure 2: Quick ticket procedure

eventually, delays.

The distance range in which CLup will look for supermarkets is specified by the user through the filter button in the homepage, this button will in fact open the filter screen in which, among other parameters, a sliding bar controls the distance and a drop-down list allows the user to filter the chains of supermarkets. Another important feature is the possibility to book an entrance later in the day or in another day. The



(a) Filters screen

Figure 3: Filters

user can specify from the filters whether he prefers to choose the day or the store first and he can set the time range in which he wants to book. There is a dedicated button in the app's main screen that redirects the user to either the list/map of supermarkets or the calendar, and once the user chooses he will be respectively shown the calendar or the list/map, this time with colours to indicate the average crowdedness of stores/days given the set time range. When the user chooses the day and supermarket combination, a timetable spanning the chosen time range is shown, divided in 15 minutes time slots each one marked to show its availability. The user will be able to check his reservation on the home page exactly like previously for the quick ticket, and near the entrance time he will be provided an actual ticket.





Figure 4: Booking procedure

The access at the supermarket is restricted by turnstiles with QR code readers, a staff member is expected to verify that nobody waits his turn in front of the entrance, jumps the turnstile or does anything irresponsible. During the shopping the user will still be able to view his ticket in order to use it to unlock the turnstile upon exiting the store. Customers who, for any reason, do not use the app will still be able to



Thanks for using CLup


We look forward to seeing you again!

Tap the house to go back to main screen


(b) Exit screen

Figure 5: Shop and exit

queue in CLup supermarkets by obtaining a printed ticket from a physical totem located near such stores; the functioning of the application will be similar to the "Quick ticket" app function with the difference that the user can only obtain a ticket for the current totem's store.



(a) Totem welcome screen



(b) Totem shopping time input

Your ticket is being printed, thank you for choosing CLup

(c) Totem print screen

Figure 6: Totem ticket procedure

**Internal use functionalities** Another component of CLup targets store managers: when the store decides to join the CLup network, ad-hoc credentials to access the web app will be given. Special staff-only functions will then be achieved by the use of a web application, accessible via internal-use terminals.



Figure 7: Store manager web app

# 4 Requirements Traceability

# 5 Implementation, Integration and Test Plan

- **5.1** Implementation
- 5.2 Integration
- 5.3 Test Plan

# 6 Effort Spent