



DKSH Marketing Services Spain, S.A.U. Santaló 152-154 08021 Barcelona, Spain Phone +34 93 240 2222 Fax +34 93 240 2223 www.dksh.com Performance Pigments Sun Chemical Corporation 5020 Spring Grove Avenue Cincinnati, OH 45232-1999 Phone: 513 681-5950

Fax: 513 681-7086 www.sunchemical.com Performance Pigments Sun Chemical Corporation Parc Industrial de la Noire Epine Avenue Fleming 2 1300 Wavre, Belgium

Phone: +32 1023 1500 Fax: +32 1023 1600

## **TECHNICAL DATA SHEET**

PRODUCT CODE:	234-0781	TRADE NAME:	Sunbrite® Red 48:2	
<b>DESCRIPTION:</b> Non-resinated Calcium Permanent Red 2B. Medium shade, easily dispersible, light masstone.				

PRODUCT INFORMATION		
C.I. Name: Pigment Red 48:2		
C.I. Number:	15865:2	
CAS Number:	7023-61-2	

PHYSICAL PROPERTIES		
Form:	Dry Color	
Surface Area (BET):	55 m2/g	
Oil Absorption:	37	
Density:	1.73 g/cc	
	14.44 lbs/gal	
	1.73 kg/liter	

CHEMICAL RESISTANCE		
Acid	4	
Alkali	2	
Lacquer Solvents	4-5	
Ethyl Alcohol	4	
Glycols	3	
Ethyl Acetate	5	
Methyl Ethyl Ketone	5	
Mineral Spirits	5	
Water	5	
Xylene	5	
Paraffin Wax	NT	
(1=Poor; 5=Excellent)		

LIGHTFASTNESS (Blue Wool)			
Masstone	5		
1-10 Tint	5		
1-25 Tint	4		
(1=Poor; 8= Excellent)			

ogenated: Yes
---------------

APPLICATIONS				
COATINGS		PLASTICS		
Automotive	-	Rubber	Α	
Architectural/Deco	-	pPVC	С	
General Industrial	-	LDPE	Α	
Powder	-	PA6	-	
Coil	-	PP	Α	
Solvent	-	HDPE	Α	
Waterborne	-	PS	В	
INKS		PC	-	
Water Based	0	PET	-	
Solvent	0			
UV	0	A = Generally good properties		
Sheet Fed	0	B = Possible heat stability problems/limited suitability		
		C = Possible migration problems		
● - Recommended O - Potential Use		D = Possible migration of carrier resins		
- = Not recommended		- = Not recommended		

HEATFASTNESS				
COATINGS	5:95 Tint DE < 2.0	NT		
INKS	Metal Deco	15 Min @ 150°C 3-4		
		30 Min @ 150°C 2-3		
(1=Poor; 5=Excellent) (NT = Not Tested)				
PLASTICS	LDPE 1:19 DE < 2.0	5 Min @232°C/450°F		
	Warpage 2% in HDPE	NT		
0=Not perceptible 1=Slightly perceptible 3=Not recommended for complicated, thick walled injection molded applications in HDPE NT = Not Tested				

WEATHERFASTNESS (Gray Scale)				
		Masstone	Tint	Metallic
COATINGS	South Florida 5° BB	NT	NT	NT
PLASTICS	DIN EN ISO 4892-2	1	1	
(1=Poor; 5=Excellent) (NT = Not Tested)				

## ISO 9001 Certified

<sup>&</sup>quot;Although the information presented here is believed to be reliable, Sun Chemical Corporation makes no representation or guarantee to its accuracy, completeness or reliability of the information. All recommendations and suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In no event shall Sun Chemical Corporation be liable for damages of any nature arising out of the use or reliance upon the information. Sun Chemical Corporation expressly disclaims that the use of any material referenced herein, either alone or in combination with other materials, shall be free of rightful claim of any third party including a claim of infringement. The observance of all legal regulations and patents is the responsibility of the user."

Revised 01/20/15