

Bookhand CHAKOTEAM!

CHAKOTEAM! — UTFSM

Última actualización: September 27, 2026

Contents

1 Template Base

2 Grafos

2.1	Dijkstra – $O((V + E) \log V)$	1
2.2	Floyd-Warshall – $O(V^3)$	1
2.3	Bellman-Ford – $O(VE)$	2
2.4	Kruskal – $O(E \log E)$	2
2.5	LCA – $O(V \log V)$ build, $O(\log V)$ query	2
2.6	Union-Find / DSU – $O(\alpha(n))$	2
2.7	Dominator Tree – $O((E + V) \log(V))$	3

3 Flujo y Conectividad

3.1	Dinic	3
3.2	2-SAT	4
3.3	Camino-dirigido-euler	4
3.4	Camino-nodirigido-euler	4
3.5	Tarjan	5
3.6	tarjan SCC	5

4 Estructuras de Datos

4.1	Segment Tree – $O(\log n)$	5
4.2	Sparse Table – $O(n \log n)$ build, $O(1)$ query	6
4.3	Segment Tree Lazy – $O(\log n)$	6
4.4	Fenwick Tree – $O(\log n)$	6
4.5	Fenwick Tree 2D – $O(\log n)$	7
4.6	Line container – $O(\log n)$	7
4.7	Sqrt decomp – $O(\sqrt{n})$	7
4.8	Mo – $O(\text{confia})$	8

5 Matemáticas

5.1	Template	8
5.2	BinPow	8
5.3	CatalanNumbers	8
5.4	ConvexHull	8
5.5	Chinese Remainder Theorem	8
5.6	Discrete Log	9
5.7	Discrete Root	9
5.8	Erathostenes Sieve	9
5.9	Factorization using Pollard Rho	9
5.10	Fast Fourier Transform	10
5.11	Gaussian Elimination	10
5.12	GCD	10
5.13	GCD Extended	10
5.14	Geometry Structures	11
5.15	Inclusion Exclusion	11
5.16	Miller Rabin	12
5.17	Mobius	12
5.18	Number Theoric Transform	12
5.19	Primitive Root (Generator of a Prime Group)	13
5.20	Simpson Rule	13
5.21	Tonelli Shanks	13
5.22	Euler Totiente	13

6 Strings 13

6.1	KMP – $O(n + m)$	13
6.2	Z-Function – $O(n + m)$	14
6.3	Trie – $O(s)$ por operación	14
6.4	Rolling Hashing	14
6.5	aho-corasick	14

7 Programación Dinámica 15

7.1	Longest Increasing Subsequence – $O(n \log n)$	15
7.2	LIS of length K – $O(nk \log n)$	15
7.3	LIS elements participate of Optimal solutions – $O(n \log n)$	15
7.4	Knapsack 0/1 – $O(nW)$	16

8 Misceláneos 16

8.1	Búsqueda Binaria – $O(\log n)$	16
-----	--------------------------------	----

1 Template Base

```
1 #pragma GCC optimize("O3", "unroll-loops")
2 #include <bits/stdc++.h>
3 using namespace std;
4 using ll = long long;
5 #define all(v) (v).begin(), (v).end()
6
7 void solve(){
8
9 }
10
11 int main(){
12     ios::sync_with_stdio(false);
13     cin.tie(nullptr);
14     ll t = 1;
15     cin >> t;
16     while(t--){
17         solve();
18     }
19     return 0;
20 }
21
```

template.cpp

2 Grafos

2.1 Dijkstra – $O((V + E) \log V)$

```
1 vector<ll> dist;
2 vector<vector<pair<ll, ll>>> g;
3
4 void dijkstra(){
5     priority_queue<pair<ll, ll>, vector<pair<ll, ll>>,
6         greater<pair<ll, ll>>> pq;
7     pq.push({0, 0});
8     while(pq.size()){
9         ll c, node;
10        auto p = pq.top(); pq.pop();
11        c = p.first, node = p.second;
12        if(dist[node] > c){
13            dist[node] = c;
14            for(auto [c_, v_] : g[node]){
15                if(dist[v_] > c + c_) {
16                    pq.push({c + c_, v_});
17                }
18            }
19        }
20    }
21}
```

dijkstra.cpp

2.2 Floyd-Warshall – $O(V^3)$

```
1 /*
2  *Description: All pairs shortest path,  $O(V^3)$ 
3  *Status: Tested
4  */
5 for (int i = 1; i <= n; i++) {
6     for (int j = 1; j <= n; j++) {
7         if (i == j) distance[i][j] = 0;
```

```

8     else if (adj[i][j]) distance[i][j] = adj[i][j];
9     else distance[i][j] = INF;
10 }
11 }
12 for (int k = 1; k <= n; k++) {
13     for (int i = 1; i <= n; i++) {
14         for (int j = 1; j <= n; j++) {
15             distance[i][j] = min(distance[i][j],
16                 distance[i][k]+distance[k][j]);
17         }
18     }
19 }
20

```

Floyd-Warshall.cpp

2.3 Bellman-Ford – $O(VE)$

```

1  /*
2  *Description:* Calculates shortest paths from $s$ in a
3  *graph that might have negative edge weights.
4  *Status:* Tested on CSES
5  */
6  struct BellmanFord {
7      struct Edge { int from, to; ll weight; };
8      int n, last_updated = -1; const ll INF = 1e18;
9      vector<int> p; vector<ll> dist;
10     BellmanFord(vector<Edge> &G, int s, int _n) {
11         n = _n; dist.assign(n+1, INF);
12         p.assign(n+1, -1); dist[s] = 0;
13         for (int i = 1; i <= n; i++) {
14             last_updated = -1;
15             for (Edge &e : G)
16                 if (dist[e.from] != INF && dist[e.from] + e.weight
17                     < dist[e.to]) {
18                     dist[e.to] = dist[e.from] + e.weight;
19                     p[e.to] = e.from; last_updated = e.to;
20                 }
21         }
22     }
23     bool getCycle(vector<int> &cycle) {
24         if (last_updated == -1) return false;
25         for (int i = 0; i < n-1; i++)
26             last_updated = p[last_updated];
27         for (int x = last_updated; x = p[x];) {
28             cycle.push_back(x);
29             if (x == last_updated and cycle.size() > 1) break;
30         }
31         reverse(cycle.begin(), cycle.end());
32         return true;
33     }
34 };
35

```

Bellman-Ford.cpp

2.4 Kruskal – $O(E \log E)$

```

1  /*
2  *Description:* Minimum spanning tree in  $O(E \log E)$ 
3  *Status:* Tested
4  */
5  struct Edge {
6      int a; int b; ll w;
7      Edge(int a_, int b_, ll w_) : a(a_), b(b_), w(w_) {}
8  };
9  bool c_edge(Edge &a, Edge &b) { return a.w < b.w; }
10 ll Kruskal() {
11     int n = G.size();
12     union_find sets(n);
13     vector<Edge> edges;
14     for (int i = 0; i < n; i++) {
15         for (auto eg : G[i]) {
16             // node i to node eg.first with cost eg.second
17             edges.emplace_back(i, eg.first, eg.second);
18         }
19     }
20     sort(edges.begin(), edges.end(), c_edge);
21     ll min_cost = 0;
22     for (Edge e : edges) {
23         if (sets.sameSet(e.a, e.b) != true) {
24             tree.emplace_back(e.a, e.b, e.w);
25             min_cost += e.w;
26             sets.unionSet(e.a, e.b);
27         }
28     }
29     return min_cost;
30 }
31

```

Kruskal.cpp

2.5 LCA – $O(V \log V)$ build, $O(\log V)$ query

```

1  /*
2  *Description:* Lowest Common Ancestor using binary
3  *lifting.
4  *Preprocessing:  $O(V \log V)$ 
5  *Query:  $O(\log V)$ 
6  *Works on rooted trees and forests represented by
7  *adjacency lists.
8  *Status:* Tested
9  */
10 struct LCA {
11     vector<vector<ll>> T, parent;
12     vector<ll> depth, vis, comp;
13     ll LOGN, V;
14     LCA(vector<vector<ll>> &T) : T(T) {
15         V = (ll)T.size();
16         LOGN = 1;
17         while ((1LL << LOGN) <= max(1LL, V))
18             LOGN++;
19         parent.assign(V, vector<ll>(LOGN, 0));
20         depth.assign(V, 0);
21         vis.assign(V, 0);
22         comp.assign(V, -1);
23         ll id = 0;
24         for (ll u = 0; u < V; u++) {
25             if (!vis[u]) {
26                 dfs(u, u, id++);
27             }
28         }
29     }
30     void dfs(ll u, ll p, ll id) {
31         vis[u] = 1;
32         comp[u] = id;
33         parent[u][0] = p;
34         for (ll j = 1; j < LOGN; j++)
35             parent[u][j] = parent[parent[u][j-1]][j-1];
36     }
37     ll query(ll u, ll v) {
38         if (comp[u] != comp[v])
39             return -1;
40         if (depth[u] < depth[v])
41             swap(u, v);
42         ll k = depth[u] - depth[v];
43         for (ll j = LOGN - 1; j >= 0; j--) {
44             if ((k >> j) & 1)
45                 u = parent[u][j];
46         }
47         if (u == v)
48             return u;
49         for (ll j = LOGN - 1; j >= 0; j--) {
50             if (parent[u][j] != parent[v][j]) {
51                 u = parent[u][j];
52                 v = parent[v][j];
53             }
54         }
55         return parent[u][0];
56     }
57 };
58

```

LCA.cpp

2.6 Union-Find / DSU – $O(\alpha(n))$

```

1  struct union_find {
2      vector<int> e;
3      union_find(int n) { e.assign(n, -1); }
4      int findSet(int x) {
5          return (e[x] < 0
6              ? x : e[x] = findSet(e[x]));
7      }
8      bool sameSet(int x, int y) {
9          return findSet(x) == findSet(y);
10     }
11     int size(int x) { return -e[findSet(x)]; }
12     bool unionSet(int x, int y) {
13         x = findSet(x), y = findSet(y);
14         if (x == y) return 0;
15         if (e[x] > e[y]) swap(x, y);
16         e[x] += e[y], e[y] = x;
17         return 1;
18     }
19 };
20

```

dsu.cpp

2.7 Dominator Tree – $O((|E| + |V|) \log(|V|))$

```

1 struct dominator_tree {
2     ll n,l,s;
3     vector<ll> tin,par,vis_ord, dsu_mn, dsu_par, sdом,
4         dep,rdom,idom;
5     vector<bool> vis;
6     vector<vector<ll>> up;
7     vector<vector<pair<ll,ll>>> up_mn;
8     void dfs(ll u, ll p, vector<vector<ll>> & adj){
9         if (vis[u]) return;
10        vis[u] = 1;
11        dep[u] = dep[p]+1;
12        tin[u] = vis_ord.size();
13        vis_ord.push_back(u);
14        par[u] = p;
15        for (int v : adj[u]) dfs(v,u,adj);
16    }
17    ll find(ll x){
18        if (dsu_par[x] == -1) return x;
19        if (dsu_par[dsu_par[x]] != -1){
20            ll res = find(dsu_par[x]);
21            if (tin[res] < tin[dsu_mn[x]])
22                dsu_mn[x] = res;
23            dsu_par[x] = dsu_par[dsu_par[x]];
24        }
25        assert(dsu_mn[x] != INT32_MAX);
26        return dsu_mn[x];
27    }
28    void get_sdom(vector<vector<ll>> & rev){
29        for (ll i = vis_ord.size()-1; i >= 0; i--){
30            ll c = vis_ord[i];
31            if (c == s) continue;
32            for (ll to : rev[c]){
33                ll res = find(to);
34                if (sdom[c] == -1 || tin[res] < tin[sdom
35                    [c]])
36                    sdom[c] = res;
37            }
38            dsu_par[c] = par[c];
39            dsu_mn[c] = sdom[c];
40            if (sdom[c] == -1) cerr << c << endl;
41        }
42    }
43    void init_up(){
44        for_(i, n){
45            if (!vis[i]) continue;
46            up[i][0] = par[i];
47            up_mn[i][0] = {tin[sdom[i]],i};
48        }
49        for (ll i = 1; i < l; i++) {
50            for_(j, n) {
51                if (!vis[j]) continue;
52                ll h = up[j][i-1];
53                if (h == -1) {
54                    up[j][i] = -1;
55                    up_mn[j][i] = up_mn[j][i-1];
56                } else {
57                    up[j][i] = up[h][i-1];
58                    up_mn[j][i] = min(up_mn[j][i-1], up_mn[h][i
59                        -1]);
60                }
61            }
62        }
63    }
64    ll get_min(ll v, ll u){
65        ll dist = dep[u]-dep[v];
66        pair<ll,ll> ret = up_mn[u][0];
67        ll w = u;
68        for_(i, l)
69            if (dist&(1<<i)){
70                ret = min(ret,up_mn[w][i]);
71                w = up[w][i];
72            }
73        assert(w == v);
74        return ret.second;
75    }
76    void get_idom(){
77        for (ll c : vis_ord){
78            if (c == s) continue;
79            rdom[c] = get_min(sdom[c],c);
80        }
81        for (ll c : vis_ord)
82            if (c != s)
83                idom[c] = ((rdom[c] == c)?sdom[c]:idom[
84                    rdom[c]]);
85    }
86    dominator_tree(vector<vector<ll>> & adj, vector<
87        vector<ll>> & rev, ll _s = 0, ll logn = 20){

```

```

83        n = adj.size(); l = logn; s = _s;
84        tin.resize(n,INT32_MAX);
85        par.resize(n,-1);
86        vis.resize(n,0);
87        dep.resize(n,0);
88        dfs(s,-1,adj);
89        dsu_par.resize(n,-1);
90        dsu_mn.resize(n,INT32_MAX);
91        sdom.resize(n,-1);
92        rdom.resize(n,-1);
93        idom.resize(n,-1);
94        get_sdom(rev);
95        up.assign(n,vector<ll>(logn));
96        up_mn.assign(n,vector<pair<ll,ll>>(logn));
97        init_up();
98        get_idom();
99    }
100 };
101
102 //aux function, cover dom tree
103 void dfs(ll &cnt, ll node, vector<vector<ll>> &adj,
104     vector<ll> &tin, vector<ll> &tout){
105     tin[node] = cnt++;
106     for(ll child : adj[node]) dfs(cnt, child, adj, tin,
107         tout);
108     tout[node] = cnt++;
109 }
110 //verify if u dominates v, for each edge
111 vector<vector<bool>> Verifiy_u_dom_v(ll n, vector<vector<
112     ll>> &adj, vector<vector<ll>> &rev_adj, vector<pair<
113     ll, ll>> &edges){
114     dominator_tree dt(adj, rev_adj);
115     vector<vector<ll>> dom_tree(n);
116     for_(i, n){
117         if(i==0) continue;
118         if(dt.vis[i]) dom_tree[dt.idom[i]].push_back(i);
119     }
120     vector<ll> tin(n, 0), tout(n, 0); ll cnt = 0;
121     dfs(cnt, 0, dom_tree, tin, tout);
122     vector<vector<bool>> dom_matrix(n, vector<bool>(n,
123         false));
124     for_(i, edges.size()){
125         auto &[u,v] = edges[i];
126         if((tin[u]<=tin[v] && tout[v]<=tout[u]))
127             dom_matrix[u][v] = true;
128     }
129     return dom_matrix;
130 }
131

```

dominatorTree.cpp

3 Flujo y Conectividad

3.1 Dinic

```

1 /*
2  *Author:* Pablo Messina
3  *Source:* https://github.com/PabloMessina/Competitive-
4  *Programming-Material
5  *Description:* Flow algorithm with complexity  $O(|E| \cdot |V|^2)$ 
6  *Status:* Not tested
7  */
8 template<class T>
9 struct Dinic {
10     struct Edge { int to, rev; T f, c; bool r; };
11     int n, t_; vector<vector<Edge>> G;
12     vector<int> D, q, W;
13     bool bfs(int s, int t) {
14         W.assign(n, 0); D.assign(n, -1); D[s] = 0;
15         int f = 0, l = 0; q[l++] = s;
16         while (f < l) {
17             int u = q[f++];
18             for (const Edge & e : G[u]) if (D[e.to] == -1 && e.
19                 r && e.c > 0) {
20                 D[e.to] = D[u]+1, q[l++] = e.to;
21             }
22         }
23         return D[t] != -1;
24     }
25     int dfs(int u, T f) {
26         if (u == t_) return f;
27         for (int &i = W[u]; i < (int)G[u].size(); ++i) {
28             Edge &e = G[u][i]; int v = e.to;
29             if (e.c <= e.f || D[v] != D[u] + 1) continue;
30             T df = dfs(v, min(f, e.c - e.f));
31             if (df > 0) { e.f += df, G[v][e.rev].f -= df;
32                 return df; }
33         }
34         return 0;
35     }
36 };

```

```

32 Dinic(int N) : n(N), G(N), D(N), q(N) {}
33 void add_edge(int u, int v, T cap) {
34     G[u].push_back({v, (int)G[v].size(), 0, cap, 0});
35     G[v].push_back({u, (int)G[u].size()-1, 0, 0, 1}); //
36     // Use cap instead of 0 if bidirectional
37 }
38 T max_flow(int s, int t) {
39     t_ = t; T ans = 0;
40     while (bfs(s, t)) while (T dl = dfs(s,
41         numeric_limits<T>::max())) ans += dl;
42     return ans;
43 }
44 };
45 /*
46 Para min cut
47 for(auto [u, v] : edges){
48     if((g.D[u] != -1) != (g.D[v] != -1)){
49         ans.push_back({u,v});
50     }
51 }
52 */

```

dinic.cpp

3.2 2-SAT

```

1 struct TwoSat {
2     int N;
3     vector<vector<int>> gr;
4     vector<int> values;
5     TwoSat(int n = 0) : N(n), gr(2*n) {}
6     int addVar() {
7         gr.emplace_back(); gr.emplace_back();
8         return N++;
9     }
10    void either(int f, int j) {
11        f = max(2*f, -1-2*f);
12        j = max(2*j, -1-2*j);
13        gr[f].push_back(j^1);
14        gr[j].push_back(f^1);
15    }
16    void setValue(int x) { either(x, x); }
17    void atMostOne(const vector<int>& li) {
18        if ((int)li.size() <= 1) return;
19        int cur = ~li[0];
20        for (int i = 2; i < (int)li.size(); i++) {
21            int next = addVar();
22            either(cur, ~li[i]);
23            either(cur, next);
24            either(~li[i], next);
25            cur = ~next;
26        }
27        either(cur, ~li[1]);
28    }
29    vector<int> val, comp, z; int Time = 0;
30    int dfs(int i) {
31        int low = val[i] = ++Time, x; z.push_back(i);
32        for (int e : gr[i]) if (!comp[e])
33            low = min(low, val[e] ? val[e] : dfs(e));
34        if (low == val[i]) do {
35            x = z.back(); z.pop_back();
36            comp[x] = low;
37            if (values[x>>1] == -1)
38                values[x>>1] = x&1;
39        } while (x != i);
40        return val[i] = low;
41    }
42    bool solve() {
43        values.assign(N, -1);
44        val.assign(2*N, 0); comp = val;
45        for (int i = 0; i < 2*N; i++) if (!comp[i]) dfs(i);
46        for (int i = 0; i < N; i++)
47            if (comp[2*i] == comp[2*i+1]) return false;
48        return true;
49    }
50 };

```

2-SAT.cpp

3.3 Camino-dirigido-euler

```

1 /*
2 *Description:* Finds an Eulerian trail/circuit in a
3 directed graph using Hierholzer's algorithm. Handles
4 self-loops and parallel edges.
5 - A trail exists iff all vertices satisfy outdeg = indeg
6 (circuit), or exactly one has outdeg - indeg = 1 (
7 start) and one has indeg - outdeg = 1 (end), and the
8 edge-set is weakly connected.

```

```

4 - 'vertices': vertex sequence of size $m+1$.
5 - 'edges': edge index sequence of size $m$.
6 *Complexity:* $O(V + E)$
7 *Status:* Tested on https://judge.yosupo.jp/problem/
8 eulerian_trail_directed
9 */
10 struct directed_euler_trail {
11     ll n, m = 0;
12     vector<vector<ll>> adj;
13     vector<pair<ll, ll>> E;
14     vector<ll> indeg, outdeg, vertices, edges;
15     directed_euler_trail(ll n) : n(n), adj(n), indeg(n),
16         outdeg(n) {}
17     void add_edge(ll u, ll v) {
18         adj[u].push_back(m);
19         E.push_back({u, v});
20         outdeg[u]++, indeg[v]++, m++;
21     }
22     ll find_start() {
23         ll s = -1, cp = 0, cm = 0;
24         for (ll v = 0; v < n; v++) {
25             ll d = outdeg[v] - indeg[v];
26             if (d == 1) cp++, s = v;
27             else if (d == -1) cm++;
28             else if (d != 0) return -2;
29             if (outdeg[v] > 0 && s < 0) s = v;
30         }
31         if (cp == 0 && cm == 0) return s;
32         return (cp == 1 && cm == 1) ? s : -2;
33     }
34     bool solve() {
35         if (m == 0) { vertices = {0}; return true; }
36         ll s = find_start();
37         if (s == -2) return false;
38         vector<ll> ep(n);
39         edges.resize(m);
40         ll pp = 0, pq = m, v = s;
41         while (pp < pq) {
42             if (ep[v] >= (ll)adj[v].size()) {
43                 if (pp == 0)
44                     return false;
45                 edges[--pq] = edges[--pp];
46                 v = E[edges[pq]].first;
47             } else {
48                 ll e = adj[v][ep[v]++];
49                 edges[pp++] = e;
50                 v = E[e].second;
51             }
52         }
53         vertices = {s};
54         for (ll e : edges) vertices.push_back(E[e].second);
55         return true;
56     }
57 };

```

CaminoDirigidoEuler.cpp

3.4 Camino-nodirigido-euler

```

1 /*
2 *Description:* Finds an Eulerian trail/circuit in an
3 undirected graph using Hierholzer's algorithm.
4 Handles self-loops and parallel edges.
5 - A trail exists iff 0 or 2 vertices have odd degree and
6 the graph is connected.
7 - Uses XOR trick: 'v ^= E[e].first ^ E[e].second' to
8 traverse edges.
9 - 'vertices': vertex sequence of size $m+1$.
10 - 'edges': edge index sequence of size $m$.
11 *Complexity:* $O(V + E)$
12 *Status:* Tested on https://judge.yosupo.jp/problem/
13 eulerian_trail_undirected
14 */
15 struct undirected_euler_trail {
16     ll n, m = 0;
17     vector<vector<ll>> adj;
18     vector<pair<ll, ll>> E;
19     vector<ll> deg, vertices, edges;
20     undirected_euler_trail(ll n) : n(n), adj(n), deg(n) {}
21     void add_edge(ll u, ll v) {
22         adj[u].push_back(m);
23         if (u != v) adj[v].push_back(m);
24         E.push_back({u, v});
25         deg[u]++, deg[v]++, m++;
26     }
27     ll find_start() {
28         ll s = -1, codd = 0;
29         for (ll v = 0; v < n; v++) {
30             if (deg[v]&1) codd++, s = v;
31             else if (deg[v] > 0 && s < 0)

```

```

30     s = v;
31 }
32 return (codd == 0 || codd == 2) ? s : -2;
33 }
34
35 bool solve() {
36     if (m == 0) { vertices = {0}; return true; }
37
38     ll s = find_start();
39     if (s == -2) return false;
40
41     vector<ll> ep(n);
42     edges.resize(m);
43     vector<bool> alive(m, true);
44     ll pp = 0, pq = m, v = s;
45
46     while (pp < pq) {
47         if (ep[v] >= adj[v].size()) {
48             if (pp == 0)
49                 return false;
50             edges[--pq] = edges[--pp];
51             v ^= E[edges[pq]].first ^ E[edges[pq]].second;
52         } else {
53             ll e = adj[v][ep[v]++];
54             if (!alive[e])
55                 continue;
56             alive[e] = false;
57             edges[pp++] = e;
58             v ^= E[e].first ^ E[e].second;
59         }
60     }
61     vertices = {s};
62     for (ll e : edges) {
63         s ^= E[e].first ^ E[e].second;
64         vertices.push_back(s);
65     }
66     return true;
67 }
68 };

```

CaminoNoDirigidoEuler.cpp

3.5 Tarjan

```

1  /*
2  *Description:* Finds bridges, articulation points, and
3  *              biconnected components
4  *in an undirected graph using Tarjan's algorithm.
5  *Complexity:*  $O(V + E)$ 
6  *Status:* Tested on CSES, Codeforces, UVA
7  */
8  struct tarjan {
9      struct edge { int u, v, comp, bridge; };
10     int n, nbc, T;
11     vector<vector<int>> adj;
12     vector<edge> e;
13     vector<int> disc, low, art, st;
14     tarjan(int n) : n(n), nbc(0), T(0), adj(n), disc(n,
15         -1), low(n), art(n, 0) {}
16     int add_edge(int u, int v) {
17         int i = e.size();
18         adj[u].push_back(i);
19         adj[v].push_back(i);
20         e.push_back({u, v, -1, false});
21         return i;
22     }
23     void dfs(int u, int pe) {
24         low[u] = disc[u] = T++;
25         for (int i : adj[u]) {
26             if (i == pe) continue;
27             int v = e[i].u ^ e[i].v ^ u;
28             if (disc[v] < 0) {
29                 st.push_back(i);
30                 dfs(v, i);
31                 if (low[v] > disc[u])
32                     e[i].bridge = true;
33                 if (low[v] >= disc[u]) {
34                     art[u]++;
35                     while (st.back() != i) {
36                         e[st.back()].comp = nbc;
37                         st.pop_back();
38                     }
39                     e[st.back()].comp = nbc;
40                     st.pop_back();
41                     nbc++;
42                 }
43                 low[u] = min(low[u], low[v]);
44             } else if (disc[v] < disc[u]) {
45                 st.push_back(i);
46                 low[u] = min(low[u], disc[v]);
47             }
48         }
49     }
50 };

```

```

48 void solve() {
49     for (int i = 0; i < n; i++)
50         if (disc[i] < 0) dfs(i, -1), art[i]--;
51 }
52 bool is_bridge(int i) { return e[i].bridge; }
53 bool is_art(int v) { return art[v] > 0; }
54 int component(int i) { return e[i].comp; }
55 };

```

tarjan.cpp

3.6 tarjan SCC

```

1  /*
2  *Description:* Finds SCC on a graph
3  *Complexity:*  $O(V+E)$ 
4  *Status:* Tested on CSES
5  */
6  struct tarjan {
7      int n, timer;
8      vector<bool> vis, ist;
9      vector<int> tin, low, st, cmp;
10     vector<vector<int>> scc;
11     void dfs(int u, vector<vector<int>> & adj){
12         vis[u] = ist[u] = 1;
13         st.push_back(u); tin[u] = low[u] = timer++;
14         for (auto v : adj[u]){
15             if (!vis[v]){
16                 dfs(v, adj);
17                 low[u] = min(low[u], low[v]);
18             } else if (ist[v]){
19                 low[u] = min(low[u], tin[v]);
20             }
21         }
22         if (low[u] == tin[u]){
23             scc.emplace_back(); int cur;
24             do {
25                 cur = st.back(); st.pop_back();
26                 ist[cur] = 0; scc.back().push_back(cur);
27                 cmp[cur] = (int)scc.size() - 1;
28             } while (cur != u);
29         }
30     }
31     tarjan(vector<vector<int>> & adj){
32         n = adj.size(); tin.resize(n); timer = 0; cmp.resize(
33             n);
34         low.resize(n); vis.resize(n, 0); ist.resize(n, 0);
35         for (int i = 0; i < n; i++) if (!vis[i]) dfs(i, adj);
36     };

```

TarjanSCC.cpp

4 Estructuras de Datos

4.1 Segment Tree – $O(\log n)$

```

1  /*
2  *Description:* Range queries, build  $O(n)$ , query and
3  *              update  $O(\log n)$ , positions  $[0, n - 1]$ 
4  *Status:* Highly tested
5  */
6  template<class T, T m_(T, T)> struct segment_tree{
7      int n; vector<T> ST;
8      segment_tree(){}
9      segment_tree(vector<T> &a){
10         n = a.size(); ST.resize(n << 1);
11         for (int i=n;i<(n<<1);i++)ST[i]=a[i-n];
12         for (int i=n-1;i>0;i--)ST[i]=m_(ST[i<<1],ST[i<<1|1])
13             ;
14     }
15     void update(int pos, T val){ // replace with val
16         ST[pos += n] = val;
17         for (pos >= 1; pos > 0; pos >= 1)
18             ST[pos] = m_(ST[pos<<1], ST[pos<<1|1]);
19     }
20     T query(int l, int r){ // [l, r]
21         T ansL, ansR; bool hasL = 0, hasR = 0;
22         for (l += n, r += n + 1; l < r; l >= 1, r >= 1) {
23             if (l & 1)
24                 ansL=(hasL?m_(ansL,ST[l++]):ST[l++]),hasL=1;
25             if (r & 1)
26                 ansR=(hasR?m_(ST[--r],ansR):ST[--r]),hasR=1;
27         }
28         if (!hasL) return ansR; if (!hasR) return ansL;
29         return m_(ansL, ansR);
30     };

```

segtree.cpp

4.2 Sparse Table – $O(n \log n)$ build, $O(1)$ query

```

1
2 int min_op(int a, int b) {
3     return min(a, b);
4 }
5
6 template <typename T, T (*m_)(T, T)>
7 struct sparse_table {
8     int n = 0;
9     vector<vector<T>> table;
10
11     sparse_table() {}
12
13     sparse_table(const vector<T>& arr) {
14         n = arr.size();
15         if (n == 0) return;
16
17         int k = log2_floor(n) + 1;
18         table.assign(n, vector<T>(k));
19
20         for (int i = 0; i < n; i++)
21             table[i][0] = arr[i];
22
23         for (int j = 1; j < k; j++) {
24             for (int i = 0; i + (1LL << j) <= n; i++) {
25                 table[i][j] = m_(
26                     table[i][j - 1],
27                     table[i + (1LL << (j - 1))][j - 1]
28                 );
29             }
30         }
31     }
32
33     T query(int l, int r) {
34         assert(0 <= l && l <= r && r < n);
35
36         int k = log2_floor(r - l + 1);
37
38         return m_(
39             table[l][k],
40             table[r - (1LL << k) + 1][k]
41         );
42     }
43
44     int log2_floor(int x) {
45         return x ? 63 - __builtin_clzll(x) : -1;
46     }
47 };
48

```

sparse-table.cpp

4.3 Segment Tree Lazy – $O(\log n)$

```

1 /*
2  *Description: * Seg tree + range updates,
3  *build  $O(n)$ , query/update  $O(\log n)$ 
4  *Status: * Highly tested
5  */
6 using T1 = long long;
7 using T2 = long long;
8
9 T1 merge_op(T1 a, T1 b){ return a + b; }
10
11 void pushUpd_op(T2& parent, T2& child,
12 int l, int r, int cl, int cr){
13     child += parent;
14 }
15
16 void applyUpd_op(T2& lazy, T1& val,
17 int l, int r){
18     val += (r - l + 1) * lazy;
19 }
20
21 template<
22 class T1, class T2,
23 T1 (*merge)(T1, T1),
24 void (*pushUpd)(T2&, T2&, int, int, int, int),
25 void (*applyUpd)(T2&, T1&, int, int)
26 >
27 struct segment_tree_lazy{
28     vector<T1> ST; vector<T2> lazy;
29     vector<bool> upd; int n;
30     void build(int i, int l, int r,
31 vector<T1>&values){

```

```

32     if(l == r){ ST[i] = values[l]; return; }
33     build(i<<1, l, (l+r)>>1, values);
34     build(i<<1|1, (l+r)/2+1, r, values);
35     ST[i] = merge(ST[i<<1], ST[i<<1|1]);
36 }
37 segment_tree_lazy() {}
38 segment_tree_lazy(vector<T1>&values){
39     n = values.size(); ST.resize(n<<2|3);
40     lazy.resize(n<<2|3);
41     upd.resize(n<<2|3, false);
42     build(1, 0, n-1, values);
43 }
44 void push(int i, int l, int r){
45     if(upd[i]){
46         applyUpd(lazy[i], ST[i], l, r);
47         if(l != r){
48             pushUpd(lazy[i], lazy[i<<1],
49 l, r, l, (l+r)/2);
50             pushUpd(lazy[i], lazy[i<<1|1],
51 l, r, (l+r)/2+1, r);
52             upd[i<<1] = 1;
53             upd[i<<1|1] = 1;
54         }
55         upd[i] = false;
56         lazy[i] = T2();
57     }
58 }
59 void update(int i, int l, int r,
60 int a, int b, T2 &u){
61     if(l >= a and r <= b){
62         pushUpd(u, lazy[i], a, b, l, r);
63         upd[i] = true;
64     }
65     push(i, l, r);
66     if(l > b or r < a) return;
67     if(l >= a and r <= b) return;
68     update(i<<1, l, (l+r)>>1, a, b, u);
69     update(i<<1|1, (l+r)/2+1, r, a, b, u);
70     ST[i] = merge(ST[i<<1], ST[i<<1|1]);
71 }
72 void update(int a, int b, T2 u){
73     if(a > b){
74         update(0, b, u);
75         update(a, n-1, u);
76         return;
77     }
78     update(1, 0, n-1, a, b, u);
79 }
80 T1 query(int i, int l, int r,
81 int a, int b){
82     push(i, l, r);
83     if(a <= l and r <= b) return ST[i];
84     int mid = (l+r) >> 1;
85     if(mid < a)
86         return query(i<<1|1, mid+1, r, a, b);
87     if(mid >= b)
88         return query(i<<1, l, mid, a, b);
89     return merge(
90         query(i<<1, l, mid, a, b),
91         query(i<<1|1, mid+1, r, a, b));
92 }
93 T1 query(int a, int b){
94     if(a > b)
95         return merge(query(a, n-1), query(0, b));
96     return query(1, 0, n-1, a, b);
97 }
98 };
99
100 int main(){
101     int n; cin >> n;
102     vector<long long> a(n);
103     for(int i = 0; i < n; i++) cin >> a[i];
104     segment_tree_lazy<long long, long long,
105 merge_op, pushUpd_op, applyUpd_op> st(a);
106     int q; cin >> q;
107     while(q--){
108         int type; cin >> type;
109         if(type == 1){
110             int l, r; long long val;
111             cin >> l >> r >> val;
112             st.update(l, r, val);
113         }
114         else{
115             int l, r; cin >> l >> r;
116             cout << st.query(l, r) << '\n';
117         }
118     }
119 }

```

segment-tree-lazy.cpp

4.4 Fenwick Tree – $O(\log n)$

```

1 struct fenwick_tree {
2     vector<ll> bit; int n;
3     fenwick_tree(int n): n(n) { bit.assign(n, 0); }
4     fenwick_tree(vector<ll> &a): fenwick_tree(a.size()) {
5         for (size_t i = 0; i < a.size(); i++)
6             add(i, a[i]);
7     }
8     ll sum(int r) {
9         ll ret = 0;
10        for (; r >= 0; r = (r & (r + 1)) - 1)
11            ret += bit[r];
12        return ret;
13    }
14    ll sum(int l, int r) {
15        return sum(r) - sum(l - 1);
16    }
17    void add(int idx, ll delta) {
18        for (; idx < n; idx = idx | (idx + 1))
19            bit[idx] += delta;
20    }
21 };
22

```

fenwick_tree.cpp

```

1 // Returns the 0-based index of the k-th remaining
   // element.
2 int fenwick_tree::kth(int k) {
3     int i = -1;
4     int s = 1;
5     while ((s << 1) <= n) s <<= 1;
6     for (; s > 0; s >>= 1) {
7         int j = i + s;
8         if (j < n && bit[j] < k) {
9             i = j;
10            k -= bit[j];
11        }
12    }
13    return i + 1;
14 }
15

```

kth_fenwick.cpp

4.5 Fenwick Tree 2D— $O(\log n)$

```

1 struct fenwick_tree_2d {
2     int N, M;
3     vector<vector<ll>> BIT;
4     fenwick_tree_2d(int N, int M): N(N), M(M) {
5         BIT.assign(N + 1, vector<ll>(M + 1, 0));
6     }
7     void update(int x, int y, ll v) {
8         for (int i = x; i <= N; i += (i & -i))
9             for (int j = y; j <= M; j += (j & -j))
10                BIT[i][j] += v;
11    }
12    ll sum(int x, int y) {
13        ll s = 0;
14        for (int i = x; i > 0; i -= (i & -i))
15            for (int j = y; j > 0; j -= (j & -j))
16                s += BIT[i][j];
17        return s;
18    }
19    ll query(int x1, int y1, int x2, int y2) {
20        return sum(x2, y2) - sum(x2, y1 - 1) - sum(x1 - 1,
21            y2) + sum(x1 - 1, y1 - 1);
22    }
23 };
24
25

```

fenwick_tree_2d.cpp

4.6 Line container — $O(\log n)$

```

1 const ll INF = 1e15;
2 struct Line {
3     mutable ll a, b, c;
4     bool operator<(Line r) const {
5         return a < r.a;
6     }
7     bool operator<(ll x) const {
8         return c < x;
9     }
10 };
11 // dynamically insert 'a*x + b' lines and query for
   // maximum

```

```

12 // at any x all operations have complexity O(log N)
13 struct LineContainer: multiset< Line, less<>> {
14     ll div(ll a, ll b) {
15         return a / b - ((a ^ b) < 0 && a % b);
16     }
17     bool isect(iterator x, iterator y) {
18         if (y == end()) return x -> c = INF, 0;
19         if (x -> a == y -> a) x -> c = x -> b > y -> b ? INF
20             : -INF;
21         else x -> c = div(y -> b - x -> b, x -> a - y -> a);
22         return x -> c >= y -> c;
23     }
24     //az+b
25     void add(ll a, ll b) {
26         // a *= -1, b *= -1 // for min
27         auto z = insert({
28             a,
29             b,
30             0
31         }), y = z++, x = y;
32         while (isect(y, z)) z = erase(z);
33         if (x != begin() && isect(--x, y)) isect(x, y =
34             erase(y));
35         while ((y = x) != begin() && (--x) -> c >= y -> c)
36             isect(x, erase(y));
37     }
38     ll query(ll x) {
39         if (empty()) return -INF; // INF for min
40         auto l = * lower_bound(x);
41         return l.a * x + l.b; // for min
42     }
43 };
44
45 void solve()
46 {
47     ll n; cin>>n;
48     LineContainer lc;
49     for (ll k = 1; k <= n; k++) {
50         ll bi; cin>>bi;
51         lc.add(2*k, -(k*k + bi));
52     }
53     ll q; cin>>q;
54     for (ll k = 0; k < q; k++) {
55         ll t; cin>>t;
56         if (t == 1) {
57             ll x; cin>>x;
58             cout<<-lc.query(x) + x*x<<endl;
59         } else {
60             ll a, b; cin>>a>>b;
61             lc.add(2*a, -(a*a + b));
62         }
63     }
64 }
65

```

line_container.cpp

4.7 Sqrt decomp — $O\sqrt{n}$

```

1 template <class T, T merge(T,T)>
2 struct sqrt_decomp {
3     int n,sq;
4     vector<T> st,bl;
5     sqrt_decomp(vector<T> &a){
6         n = a.size(); st.resize(n);
7         sq = sqrtl(n); bl.resize((n+sq-1)/sq);
8         for (int i = 0; i < n; i++){
9             st[i] = a[i];
10            bl[i/sq] = ((i%sq == 0)?st[i]:merge(bl[i/sq],st[i]
11                ));
12        }
13        void update(int pos, T val) {
14            st[pos] = val;
15            int block = pos/sq, lb = block*sq, rb = min(block*sq
16                +sq-1,n-1);
17            T vl;
18            for (int i = lb; i <= rb; i++)
19                vl = ((i == lb)?st[i]:merge(vl,st[i]));
20            bl[block] = vl;
21        }
22        T query(int l, int r){
23            T res; bool hasR = 0;
24            for (int i = l/sq; i <= r/sq; i++){
25                int lb = i*sq, rb = i*sq+sq-1;
26                if (l <= lb && rb <= r){
27                    res = (hasR?merge(res,bl[i]):bl[i]), hasR = 1;
28                    continue;
29                }
30                for (int j = max(l,lb); j <= min(rb,r); j++)

```

```

30     res = (hasR?merge(res,st[j]):st[j]), hasR = 1;
31 }
32 return res;
33 }
34 };
35

```

sqrt_decomp.cpp

4.8 Mo — $O(\text{confia})$

```

1 struct query {
2     ll l, r, i;
3 };
4 template<class T, typename U, class T2>
5 struct mo_algorithm {
6     vector<U> ans;
7     template<typename... Args>
8     mo_algorithm(vector<T> &v, vector<query> &queries,
9         Args... args) {
10         T2 ds(args...);
11         ll block_sz = sqrtl(v.size());
12         ans.assign(queries.size(), -1);
13         sort(queries.begin(), queries.end(), [&](auto &a,
14             auto &b) {
15             return a.l/block_sz != b.l/block_sz ? a.l/block_sz
16                 < b.l/block_sz : a.r < b.r;
17         });
18         ll l = 0, r = -1;
19         for (query q : queries) {
20             while (l > q.l) ds.add(v[--l]);
21             while (r < q.r) ds.add(v[++r]);
22             while (l < q.l) ds.remove(v[l++]);
23             while (r > q.r) ds.remove(v[r--]);
24             ans[q.i] = ds.answer(q);
25         }
26     };
27 };
28

```

mo.cpp

5 Matemáticas

5.1 Template

```

1 #include<bits/stdc++.h>
2
3 using namespace std;
4
5 #define ll long long
6 #define ld long double
7 #define cd complex<long double>
8 #define ull unsigned long long
9 #define for_(i, n) for(ll i = 0; i < n; ++i)
10 #define INF LLONG_MAX
11 #define NINF LLONG_MIN
12 #define i128 __int128
13 #define u128 __uint128_t
14 const double PI =
15     3.141592653589793238462643383279502884197169399375105;
16
17 const double EPS = 1e-18;
18
19 const ll mod = 1e9 + 7; //switch per case
20

```

template.cpp

5.2 BinPow

```

1 /*
2 Tested : Tested
3 */
4
5 ll binpow(ll a, ll b, ll m){
6     ll ans = 1;
7     while(b > 0){
8         if(b&1) ans = (ans*a)%m;
9         a=(a*a)%m;
10        b>>=1;
11    }
12    return ans;
13 }
14

```

BinPow.cpp

5.3 CatalanNumbers

```

1 //n-catalan number = (2n)!/((n+1)!n!)
2 ll getNCatalanNumber(ll n){
3     double ans = 1;
4     for(ll k = 2; k <= n; k++) ans *= (n+k)/k;
5     return (ll)(ans + 0.001);
6 }
7 //TESTED
8 vector<ll> getCatalanNumbers(ll n){
9     vector<ll> C(n+1, 0);
10    C[0] = C[1] = 1;
11    C[2] = 2;
12    for(ll i = 3; i <= n; ++i){
13        for(ll j = 0; j < i; ++j) C[i] += C[j]*C[i-j-1];
14    }
15    return C;
16 }
17

```

CatalanNumbers.cpp

5.4 ConvexHull

```

1
2 //TESTED
3 //Monotonic Change
4 struct point{
5     double x, y;
6 };
7 ll orientation(const point &a, const point &b, const
8     point &c){
9     double sign = a.x*(b.y - c.y) - b.x*(a.y - c.y) + c.
10        x*(a.y - b.y);
11     if(sign > 0) return 1;
12     else if( sign < 0) return -1;
13     else return 0;
14 }
15 bool cw(const point &a, const point &b, const point &c,
16     const bool &include_colider){
17     ll o = orientation(a, b, c);
18     return (o > 0 || include_colider && 0==0);
19 }
20 bool ccw(const point &a, const point &b, const point &c,
21     const bool &include_colider){
22     ll o = orientation(a, b, c);
23     return (o < 0 || include_colider && 0==0);
24 }
25 void convex_hull(vector<point> &a, bool include_colider)
26 {
27     if(a.size()==1) return;
28     sort(a.begin(), a.end(), [](const point &p1, const
29         point &p2){return (p1.x==p2.x ? p1.y < p2.y : p1.x <
30             p2.x);});
31     point A = a[0], B = a[a.size()-1];
32     vector<point> upper, lower;
33     upper.push_back(A);
34     lower.push_back(A);
35     for(ll i = 1; i < a.size(); ++i){
36         if(i == a.size()-1 || cw(A, a[i], B,
37             include_colider)){
38             while(upper.size() >= 2 && !(cw(upper[upper.
39                 size()-2], upper[upper.size()-1], a[i],
40                 include_colider))) upper.pop_back();
41             upper.push_back(a[i]);
42         }
43         if(i == a.size()-1 || ccw(A, a[i], B,
44             include_colider)){
45             while(lower.size() >= 2 && !(ccw(lower[lower.
46                 size()-2], lower[lower.size()-1], a[i],
47                 include_colider))) lower.pop_back();
48             lower.push_back(a[i]);
49         }
50     }
51     if(include_colider && upper.size() == a.size()){
52         reverse(a.begin(), a.end());
53         return;
54     }
55     a.clear();
56     for(ll i = 0; i < upper.size(); ++i) a.push_back(
57         upper[i]);
58     for(ll i = lower.size()-2; i >= 1; --i) a.push_back(
59         lower[i]);
60 }
61

```

convexhull.cpp

5.5 Chinese Remainder Theorem

```

1 //TESTED (PD: for 2x2 system but should work for any nIn
  )
2 #include "gcdExtended.cpp"
3
4 ll mod_inv(ll a, ll m){
5     ll x, y;
6     ll g = gcdExtended(a, m, x, y);
7     x = (x%m + m)%m;
8     return x;
9 }
10
11 struct Congruence {
12     ll b, n;
13 };
14
15 ll chinese_remainder_theorem(vector<Congruence> const&
  congruences) {
16     ll N = 1;
17     for (auto const& congruence : congruences) N *=
  congruence.n;
18
19     ll x = 0;
20     for (auto const& congruence : congruences) {
21         ll b_i = congruence.b;
22         ll N_i = N / congruence.n;
23         ll invN_i = mod_inv(N_i, congruence.n);
24         i128 aux = (b_i*N_i)%N;
25         aux = (aux*invN_i)%N;
26         x = (ll) (x + aux)%N;
27     }
28     return x;
29 }
30

```

crt.cpp

5.6 Discrete Log

```

1
2 //Tested
3
4 ll discrete_log(ll a, ll b, ll m) {
5     a %= m, b %= m;
6     if (a == 0) return b == 0 ? 1 : -1;
7     ll k = 1, add = 0, g;
8     while ((g = gcd(a, m)) > 1) {
9         if (b == k)
10             return add;
11         if (b % g)
12             return -1;
13         b /= g, m /= g, ++add;
14         k = (k * 1ll * a / g) % m;
15     }
16
17     ll n = sqrt(m) + 1;
18     ll an = 1;
19     for_(i, n) an = (an * 1ll * a) % m;
20
21     unordered_map<ll, ll> f2inv;
22     for (ll q = 0, f2 = b; q <= n; ++q) {
23         f2inv[f2] = q;
24         f2 = (f2 * 1ll * a) % m;
25     }
26
27     for (ll p = 1, f1 = k; p <= n; ++p) {
28         f1 = (f1 * 1ll * an) % m;
29         if (f2inv.count(f1)){
30             ll x = n * p - f2inv[f1] + add;
31             return x;
32         }
33     }
34     return -1;
35 }
36

```

discretelog.cpp

5.7 Discrete Root

```

1
2 //TESTED
3
4 #include "gcd.cpp"
5 #include "bin_pow.cpp"
6 #include "tot_euler.cpp"
7 #include "primitive_root.cpp"
8
9 vector<ll> DiscreteRoot(ll n, ll k, ll a){
10     if(a==0) return {0};
11     ll g = generator_(n);

```

```

12
13     ll sq = (ll)sqrt(n) + 1;
14     vector<pair<ll, ll>> dec(sq);
15     for(ll i = 1; i <= sq; ++i)
16         dec[i-1] = {binpow(g, i * sq * k % (n - 1), n),
17             i};
18     sort(dec.begin(), dec.end());
19     ll h0 = -1;
20     for_(i, sq) {
21         ll my = binpow(g, i * k % (n - 1), n) * a % n;
22         auto it = lower_bound(dec.begin(), dec.end(),
23             make_pair(my, 0));
24         if (it != dec.end() && it->first == my) {
25             h0 = it->second * sq - i;
26             break;
27         }
28     }
29     if(h0 == -1) return {-1};
30
31     ll delta = (n-1)/gcd(k, n-1);
32     vector<ll> x;
33     for (ll h = h0 % delta; h < n-1; h += delta)
34         x.push_back(binpow(g, h, n));
35     sort(x.begin(), x.end());
36     return x;

```

DiscreteRoot.cpp

5.8 Erathostenes Sieve

```

1 //Tested
2
3 vector<bool> erathostenesSieve(ll n){
4     vector<bool> isprime(n+1, true);
5     isprime[0] = isprime[1] = false;
6     for(ll i = 2; i <= n; (i+=2 ? i++ : i+=2)){
7         if(isprime[i]){
8             for(ll j = i*i; j <= n; j+=i) isprime[j] = false;
9         }
10     }
11     return isprime;
12 }
13

```

erathostenes-sieve.cpp

5.9 Factorization using Pollard Rho

```

1
2 mt19937_64 rng(chrono::steady_clock::now().
  time_since_epoch().count());
3
4 //TESTED up to 1e18, run T(n) < 1e8
5
6 ll mult(ll a, ll b, ll m) {
7     return (__int128)a * b % m;
8 }
9
10 ll f(ll x, ll c, ll m) {
11     return (mult(x, x, m) + c) % m;
12 }
13
14 #include "gcd.cpp"
15
16 ll rho(ll n, ll x0=2, ll c=1) {
17     ll x = x0;
18     ll y = x0;
19     ll g = 1;
20     while (g == 1) {
21         x = f(x, c, n);
22         y = f(y, c, n);
23         y = f(y, c, n);
24         g = gcd(abs(x - y), n);
25     }
26     return g;
27 }
28
29 //algorithm for the factorization
30 ll brent(ll n, ll x0=2, ll c=1) {
31     ll x = x0;
32     ll g = 1;
33     ll xs, y;
34
35     ll m = 128;
36     ll l = 1;
37     ll iter = 0;
38     while (g == 1 && iter<1000) {
39         y = x;
40         ll q = 1;

```

```

41     for (ll i = 1; i < l; i++)
42         x = f(x, c, n);
43     ll k = 0;
44     while (k < l && g == 1) {
45         xs = x;
46         for (ll i = 0; i < m && i < l - k; i++) {
47             x = f(x, c, n);
48             q = mult(q, abs(y - x), n);
49         }
50         g = gcd(q, n);
51         k += m;
52     }
53     l *= 2;
54     iter++;
55 }
56 if (g == n) {
57     return n;
58 }
59 return g;
60 }
61
62 #include "miller_rabin.cpp"
63
64 //algorithm to prime factorization
65 void factorize(ll n, map<ll, ll> &factors){
66     if(n==1) return;
67     if(deterministicMillerRabin(n)){
68         factors[n]++;
69         return;
70     }
71     ll d1, d2, iter=0;
72     while(iter<1000){
73         uniform_int_distribution<ll> dist(1, n-1);
74         ll c = dist(rng);
75         ll x0 = dist(rng);
76         d1 = brent(n, x0, c), d2 = n/d1;
77         if(d1>1 && d1<n) break;
78         iter++;
79     }
80     if(d1==1 || d2==1){
81         factors[n]++;
82         return;
83     }
84     factorize(d1, factors);
85     factorize(d2, factors);
86 }
87

```

Factorization-pollard-rho.cpp

5.10 Fast Fourier Transform

```

1  //Tested
2
3  void fft_bottom_up(vector<cd> &c, bool inverse){
4      ll N = 1;
5      while(N < c.size()) N<=1;
6      c.resize(N);
7      if(N<= 1) return;
8      ll cnt = 0;
9      for(ll j = 1; j < N; ++j){
10         ll bit = N >> 1;
11         while(cnt & bit){
12             cnt ^= bit;
13             bit >>= 1;
14         }
15         cnt ^= bit;
16         if(cnt < j) swap(c[cnt], c[j]);
17     }
18
19     //n is the length of the current block of the tree,
20     //thanks to bit reversal is in order, n=2 -> depth= D
21     // -1, n=4 -> depth=D-2, and so on...
22     for(ll n = 2; n <= N; n<=1){
23         double ang = 2*PI/n * (inverse ? -1 : 1);
24         cd wn(cos(ang), sin(ang));
25         //iterate each block(node from the current depth
26     )
27         for(ll currblock = 0; currblock < N; currblock+=
28             n){
29             cd w(1);
30             //iterate the node of the current block,
31             //only recover a half, because butterfly effect(como
32             //se diga la wea).
33             for(ll curr = 0; curr < n/2; ++curr){
34                 cd u = c[currblock + curr], v = c[
35                     currblock + curr + n/2]*w;
36                 c[currblock + curr] = u + v;
37                 c[currblock + curr + n/2] = u - v;
38                 w*=wn;
39             }
40         }
41     }
42 }

```

```

35     if(inverse){
36         for(cd &x : c) x/=N;
37     }
38 }
39
40 vector<cd> conv(vector<cd> &c1, vector<cd> &c2){
41     vector<cd> ans; ll N=1;
42     while(N < (c1.size()+c2.size())) N<=1;
43     c1.resize(N); c2.resize(N);
44     fft_bottom_up(c1, false);
45     fft_bottom_up(c2, false);
46     ans.resize(N);
47     for_(i, N) ans[i] = c1[i]*c2[i];
48     fft_bottom_up(ans, true);
49     return ans;
50 }
51

```

fft.cpp

5.11 Gaussian Elimination

```

1  //Tested
2
3  bool gauss_jordan(vector<vector<ll>> A, vector<ll> &x) {
4      ll n = A.size(), m = A[0].size() - 1;
5
6      vector<ll> where(m, -1);
7      for (ll col = 0, row = 0; col < m && row < n; ++col) {
8          ll pivot = row;
9          for (ll i = row; i < n; ++i){
10             if (abs(A[i][col]) > abs(A[pivot][col])) pivot = i
11             ;
12             if(!A[pivot][col]) continue;
13             for (ll i = col; i <= m; ++i) swap(A[pivot][i], A[
14                 row][i]);
15             where[col] = row;
16
17             for(ll i = 0; i < n; ++i){
18                 ll invm = binpow(A[where[col]][col], MOD - 2, MOD);
19                 if(i != row) {
20                     ll c = (A[i][col] * invm) % MOD;
21                     for (ll j = col; j <= m; ++j) A[i][j] = ((A[i][j
22                         ] - A[where[col]][j] * c) % MOD + MOD) % MOD;
23                 }
24             }
25             ++row;
26         }
27
28         x.assign(m, 0);
29         for (ll i = 0; i < m; ++i){
30             if (where[i] != -1){
31                 ll invm = binpow(A[where[i]][i], MOD - 2, MOD);
32                 x[i] = (A[where[i]][m] * invm) % MOD;
33             }
34         }
35         for(ll i=0; i<n; ++i){
36             ll sum = 0;
37             for(ll j=0; j<m; ++j) sum += (x[j] * A[i][j])%MOD;
38             if(abs(sum - A[i][m]) > 0) return false; //No
39             solution
40         }
41     }
42     return true; //Valid solution, trivial or infinity
43 }
44

```

gaussian-elimination.cpp

5.12 GCD

```

1  //Tested meme
2  ll gcd(ll a, ll b){
3      if(b==0) return a;
4      return gcd(b, a%b);
5  }
6
7  ll gcd(ll a, ll b){
8      while(b) { ll r = a % b; a = b; b = r; }
9      return a;
10 }
11

```

gcd.cpp

5.13 GCD Extended

```

1  //Tested
2
3  ll gcdExtended(ll a, ll b, ll &x, ll &y){

```

```

4   if(b == 0){
5       x = 1;
6       y = 0;
7       return a;
8   }
9   ll x_, y_, gcd = gcdExtended(b, a%b, x_, y_);
10  x = y_;
11  y = x_ - y_*(a/b);
12  return gcd;
13 }
14

```

gcdExtended.cpp

5.14 Geometry Structures

```

1
2 struct p2d {
3     ll x, y;
4     p2d() {}
5     p2d(ll x, ll y): x(x), y(y) {}
6     p2d& operator+=(const p2d &p) {
7         x += p.x;
8         y += p.y;
9         return *this;
10    }
11    p2d& operator-=(const p2d &p) {
12        x -= p.x;
13        y -= p.y;
14        return *this;
15    }
16    p2d& operator*=(ll c) {
17        x *= c;
18        y *= c;
19        return *this;
20    }
21    p2d& operator/=(ll c) {
22        x /= c;
23        y /= c;
24        return *this;
25    }
26    p2d operator+(const p2d &p) const {
27        return p2d(*this) += p;
28    }
29    p2d operator-(const p2d &p) const {
30        return p2d(*this) -= p;
31    }
32    p2d operator*(ll c) const {
33        return p2d(*this) *= c;
34    }
35    p2d operator/(ll c) const {
36        return p2d(*this) /= c;
37    }
38    ll dot(p2d a, p2d b){
39        return a.x*b.x + a.y*b.y;
40    }
41    double norm2(p2d a) {
42        return sqrt(dot(a, a));
43    }
44    double norm2sq(p2d a) {
45        return dot(a, a);
46    }
47    p2d proj(p2d a, p2d b) {
48        return b*(dot(a, b) / norm2sq(b));
49    }
50    double angle(p2d a, p2d b) {
51        return acos(dot(a, b) / norm2(a) / norm2(b));
52    }
53    static ll cross(p2d a, p2d b) {
54        return a.x * b.y - a.y * b.x;
55    }
56    p2d intersect_lines(p2d a1, p2d d1, p2d a2, p2d d2){
57        ll crs = cross(d1, d2);
58        if(crs==0) return p2d(INF, INF);
59        return a1 + d1*(cross(a2 - a1, d2) / crs);
60    }
61 };
62
63 struct p3d {
64     ll x, y, z;
65     p3d() {}
66     p3d(ll x, ll y, ll z): x(x), y(y), z(z) {}
67     p3d& operator+=(const p3d &p) {
68         x += p.x;
69         y += p.y;
70         z += p.z;
71         return *this;
72    }
73    p3d& operator-=(const p3d &p) {
74        x -= p.x;
75        y -= p.y;
76        z -= p.z;
77        return *this;
78    }
79    p3d& operator*=(ll c) {
80        x *= c;
81        y *= c;
82        z *= c;
83        return *this;
84    }
85    p3d& operator/=(ll c) {
86        x /= c;
87        y /= c;
88        z /= c;
89        return *this;
90    }
91    p3d operator+(const p3d &p) const {
92        return p3d(*this) += p;
93    }
94    p3d operator-(const p3d &p) const {
95        return p3d(*this) -= p;
96    }
97    p3d operator*(ll c) const {
98        return p3d(*this) *= c;
99    }
100   p3d operator/(ll c) const {
101       return p3d(*this) /= c;
102   }
103   ll dot(p3d a, p3d b){
104       return a.x*b.x + a.y*b.y + a.z*b.z;
105   }
106   double norm2(p3d a) {
107       return sqrt(dot(a, a));
108   }
109   double norm2sq(p3d a) {
110       return dot(a, a);
111   }
112   p3d proj(p3d a, p3d b) {
113       return b*(dot(a, b) / norm2sq(b));
114   }
115   double angle(p3d a, p3d b) {
116       return acos(dot(a, b) / norm2(a) / norm2(b));
117   }
118   p3d cross(p3d a, p3d b) {
119       return p3d(a.y * b.z - a.z * b.y,
120                 a.z * b.x - a.x * b.z,
121                 a.x * b.y - a.y * b.x);
122   }
123   ll triple(p3d a, p3d b, p3d c) {
124       return dot(a, cross(b, c));
125   }
126
127   p3d intersect_planes(p3d a1, p3d n1, p3d a2, p3d n2,
128                       p3d a3, p3d n3){
129       p3d x(n1.x, n2.x, n3.x);
130       p3d y(n1.y, n2.y, n3.y);
131       p3d z(n1.z, n2.z, n3.z);
132       p3d d(dot(a1, n1), dot(a2, n2), dot(a3, n3));
133       return p3d(triple(d, y, z), triple(x, d, z),
134                 triple(x, y, d)) / triple(n1, n2, n3);
135   }
136 };
137
138 //TESTED
139 //orientation of triangle
140 ll sign(const p2d& a, const p2d& b, const p2d& c){
141     ll val = p2d::cross(b - a, c - a);
142     if (val > 0) return 1;
143     if (val < 0) return -1;
144     return 0;
145 }
146
147 //TESTED
148 bool inter1(ll a, ll b, ll c, ll d) {
149     if (a > b) swap(a, b);
150     if (c > d) swap(c, d);
151     return max(a, c) <= min(b, d);
152 }
153
154 //TESTED
155 bool intersect_segments(const p2d& a, const p2d& b,
156                        const p2d& c, const p2d& d) {
157     if (sign(a, b, c) == 0 && sign(a, b, d) == 0) return
158         inter1(a.x, b.x, c.x, d.x) && inter1(a.y, b.y, c.y,
159         d.y);
160     ll ori1 = sign(a, b, c);
161     ll ori2 = sign(a, b, d);
162     ll ori3 = sign(c, d, a);
163     ll ori4 = sign(c, d, b);
164     return (ori1 != ori2) && (ori3 != ori4);
165 }
166

```

GeometryStructures.cpp

```

78    }
79    p3d& operator*=(ll c) {
80        x *= c;
81        y *= c;
82        z *= c;
83        return *this;
84    }
85    p3d& operator/=(ll c) {
86        x /= c;
87        y /= c;
88        z /= c;
89        return *this;
90    }
91    p3d operator+(const p3d &p) const {
92        return p3d(*this) += p;
93    }
94    p3d operator-(const p3d &p) const {
95        return p3d(*this) -= p;
96    }
97    p3d operator*(ll c) const {
98        return p3d(*this) *= c;
99    }
100   p3d operator/(ll c) const {
101       return p3d(*this) /= c;
102   }
103   ll dot(p3d a, p3d b){
104       return a.x*b.x + a.y*b.y + a.z*b.z;
105   }
106   double norm2(p3d a) {
107       return sqrt(dot(a, a));
108   }
109   double norm2sq(p3d a) {
110       return dot(a, a);
111   }
112   p3d proj(p3d a, p3d b) {
113       return b*(dot(a, b) / norm2sq(b));
114   }
115   double angle(p3d a, p3d b) {
116       return acos(dot(a, b) / norm2(a) / norm2(b));
117   }
118   p3d cross(p3d a, p3d b) {
119       return p3d(a.y * b.z - a.z * b.y,
120                 a.z * b.x - a.x * b.z,
121                 a.x * b.y - a.y * b.x);
122   }
123   ll triple(p3d a, p3d b, p3d c) {
124       return dot(a, cross(b, c));
125   }
126
127   p3d intersect_planes(p3d a1, p3d n1, p3d a2, p3d n2,
128                       p3d a3, p3d n3){
129       p3d x(n1.x, n2.x, n3.x);
130       p3d y(n1.y, n2.y, n3.y);
131       p3d z(n1.z, n2.z, n3.z);
132       p3d d(dot(a1, n1), dot(a2, n2), dot(a3, n3));
133       return p3d(triple(d, y, z), triple(x, d, z),
134                 triple(x, y, d)) / triple(n1, n2, n3);
135   }
136 };
137
138 //TESTED
139 //orientation of triangle
140 ll sign(const p2d& a, const p2d& b, const p2d& c){
141     ll val = p2d::cross(b - a, c - a);
142     if (val > 0) return 1;
143     if (val < 0) return -1;
144     return 0;
145 }
146
147 //TESTED
148 bool inter1(ll a, ll b, ll c, ll d) {
149     if (a > b) swap(a, b);
150     if (c > d) swap(c, d);
151     return max(a, c) <= min(b, d);
152 }
153
154 //TESTED
155 bool intersect_segments(const p2d& a, const p2d& b,
156                        const p2d& c, const p2d& d) {
157     if (sign(a, b, c) == 0 && sign(a, b, d) == 0) return
158         inter1(a.x, b.x, c.x, d.x) && inter1(a.y, b.y, c.y,
159         d.y);
160     ll ori1 = sign(a, b, c);
161     ll ori2 = sign(a, b, d);
162     ll ori3 = sign(c, d, a);
163     ll ori4 = sign(c, d, b);
164     return (ori1 != ori2) && (ori3 != ori4);
165 }
166

```

5.15 Inclusion Exclusion

```

1
2 //Example cardinality of all subsets of size 1

```

```

3 ll cardinalitySubset(ll subset){
4     return 1;
5 }
6
7 //Template
8 ll InclusionExclusion(){
9     //sets
10    ll n = 10; //example
11    ll subsets = (1<n); //total subsets
12    ll ans = 0;
13    //travel on all the subsets, with a particular
    subset
14    for(ll subset = 0; subset < subsets; subset++){
15        //if is odd the subset we sum, otherwise
        subtract, recall, Union of sets = sum sets -
        intersect sets pairs + intersect group of three -
        ...
16        ans += (__builtin_popcount(subset)&1 ?
        cardinalitySubset(subset) : -cardinalitySubset(
        subset));
17    }
18    return ans;
19 }
20

```

InclusionExclusion.cpp

5.16 Miller Rabin

```

1
2 ll binpow(ll a, ll b, ll mod){
3     ll ans = 1;
4     while(b>0){
5         if(b&1) ans = (u128)(ans)*a % mod;
6         a=(u128)a*a % mod;
7         b>>=1;
8     }
9     return ans;
10 }
11
12 bool checkComposite(ll p, ll a, ll s, ll q){
13     ll x = binpow(a, q, p);
14     if(x == 1 || x == p-1) return false;
15     for(ll i = 1; i < s; ++i){
16         x = (u128)x*x % p;
17         if(x == p-1) return false;
18     }
19     return true;
20 }
21
22 bool millerRabin(ll p, ll maxIter=5){
23     if(p<4) return p==2 || p==3;
24     ll s=0, q = p-1;
25     while(!(q&1)){
26         s++;
27         q>>=1;
28     }
29     for(ll i = 0; i < maxIter; ++i){
30         ll a = 2 + rand() % (p-3);
31         if(checkComposite(p, a, s, q)) return false;
32     }
33     return true;
34 }
35
36 bool deterministicMillerRabin(ll p){
37     if(p<4) return p==2 || p==3;
38     ll s=0, q = p-1;
39     while(!(q&1)){
40         s++;
41         q>>=1;
42     }
43     for(ll a : {2,3,5,7,11,13,17,19,23,29,31,37}){
44         if(p==a) return true;
45         if(checkComposite(p, a, s, q)) return false;
46     }
47     return true;
48 }
49

```

miller-rabin.cpp

5.17 Mobius

```

1 //Tested
2
3 vector<ll> mobius(ll n){
4     vector<ll> mob(n+1);
5     mob[1] = 1;
6     vector<bool> isprime(n+1, true);
7     isprime[0]=isprime[1] = false;
8     for(ll i = 2; i < n+1; i++){

```

```

9         if(isprime[i]){
10             for(ll j = i; j < n+1; j+=i){
11                 mob[j] += -1;
12                 isprime[j] = false;
13             }
14             for(ll j = i*i; j < n+1; j += i*i) mob[j] =
15                 0;
16         }
17     }
18     return mob;
19 }

```

mobius.cpp

5.18 Number Theoric Transform

```

1
2 //TESTED
3
4 const ll mod = 998244353, generator = 3, rootn = 3; //
    for N max = 2^23
5 /*more modelus primes of the form p = c*2^m + 1 (
    generators calculated with algorithm in math section
    ) :
6 const ll mod = 7340033, generator = 3, rootn = 3; // for
    N max = 2^20
7 const ll mod = 167772161, generator = 3, rootn = 3; //
    for N max = 2^25
8 const ll mod = 469762049, generator = 3, rootn = 3; //
    for N max = 2^26
9 */
10
11 ll binpow(ll a, ll e){
12     ll ans = 1;
13     while(e > 0){
14         if(e&1) ans = (ans * a)%mod;
15         a = (a*a)%mod;
16         e>>=1;
17     }
18     return ans;
19 }
20
21 ll inv(ll a){return binpow(a, mod-2);}
22
23
24 void ntt(vector<ll> &c, bool invert){
25     ll N = 1;
26     while(N < c.size())N<<=1;
27     c.resize(N);
28     ll cnt = 0;
29     for(ll j = 1; j < N; ++j){
30         ll bit = N>>1;
31         while(bit&cnt){
32             cnt^=bit;
33             bit>>=1;
34         }
35         cnt^=bit;
36         if(cnt < j) swap(c[cnt], c[j]);
37     }
38
39     for(ll n = 2; n <= N; n<<=1){
40         ll wn = binpow(rootn, (mod-1)/n);
41         if(invert) wn = inv(wn);
42         for(ll currblock = 0; currblock < N; currblock+=
43             n){
44             ll w = 1;
45             for(ll i = 0; i < n/2; ++i){
46                 ll u = c[currblock + i]%mod, v = (w*c[
47                     currblock + i + n/2])%mod;
48                 c[currblock + i] = (u + v)%mod;
49                 c[currblock + i + n/2] = ((u - v)%mod +
50                     mod)%mod;
51                 w = (w*wn)%mod;
52             }
53         }
54     }
55     if(invert){
56         for(ll &x : c) x = (x*inv(N))%mod;
57     }
58 }
59
60 vector<ll> conv(vector<ll> c1, vector<ll> c2){
61     ll N=1;
62     while(N <= (c1.size() + c2.size())) N<<=1;
63     c1.resize(N); c2.resize(N);
64     ntt(c1, false);
65     ntt(c2, false);
66     vector<ll> ans(N, 0);
67     for_(i, N) ans[i] = (c1[i] * c2[i])%mod;
68     ntt(ans, true);
69     return ans;
70 }

```

68

ntt.cpp

5.19 Primitive Root (Generator of a Prime Group)

```

1
2 //TESTED
3
4 #include "bin_pow.cpp"
5 #include "tot_euler.cpp"
6
7 ll generator(ll n) {
8     vector<int> facts;
9     ll phi_n = tot_euler(n)[n], m = phi_n;
10    for(ll i=2; i*i<=m; ++i){
11        if(m % i == 0) {
12            facts.push_back(i);
13            while (m % i == 0) m /= i;
14        }
15    }
16    if(m > 1) facts.push_back(m);
17    for (ll g=2; g<=n; ++g) {
18        bool ok = true;
19        for (size_t i=0; i<facts.size() && ok; ++i) ok
20            &= binpow(g, phi_n/facts[i], n) != 1;
21        if (ok) return g;
22    }
23 }
24

```

primitive-root.cpp

5.20 Simpson Rule

```

1 //TESTED
2
3 ld f(ld x) {return x;}
4
5 ld simpson_integration(ld a, ld b, ld d){
6     const ll N = 10000; // number of steps (already
7         multiplied by 2)
8     ld h = (b - a) / N;
9     ld s = f(a) + f(b); // a = x_0 and b = x_{2n}
10    for(ll i = 1; i < N; i++) { // Refer to final Simpson
11        //s formula
12        double xi = a + h * i;
13        s += f(xi) * ((i & 1) ? 4 : 2);
14    }
15    s *= h / 3.0;
16    //1e6 is the decimal precision, if you want 7, the 1
17    //e7 and so on
18    s*=1e6;
19    s=llround(s);
20    s/=1e6;
21    // to print use cout << fixed << setprecision(6) <<
22    //s;
23    return s;
24 }
25

```

SimpsonRule.cpp

5.21 Tonelli Shanks

```

1 // TESTED
2
3 #include "bin_pow.cpp"
4
5 ll TonelliShanks(ll n, ll p) {
6     n %= p; if (n < 0) n += p;
7     if (n == 0) return 0;
8     if (binpow(n, (p-1)/2, p) != 1) return -1; // solution
9         // does not exist
10    if (p % 4 == 3) return binpow(n, (p + 1) / 4, p); //
11        // trivial solution, only one factor 2
12    ll c = p - 1, z = 2;
13    ll s = 0;
14    while(c % 2 == 0) ++s, c /= 2;
15    // find a non-square mod p
16    while(binpow(z, (p-1)/2, p) != p - 1) ++z;
17    ll q = binpow(z, c, p); // generator subgroup, |<q>|
18    // = 2^s
19    ll a = binpow(n, (c+1)/2, p); // candidate root
20    ll t = binpow(n, c, p); // error from equation a^2 =
21    // n*t, if t=1, a is the root
22    ll m = s;
23

```

```

19 while(1){
20     ll i = 0, temp = t;
21     while(i < m && temp != 1){
22         temp = (temp*temp)%p;
23         i++;
24     }
25     if(i==0) return a;
26     ll exponent = 1ll << (m-i-1);
27     ll b = binpow(q, exponent, p);
28     a = (a*b)%p;
29     t = (((t*b)%p)*b)%p;
30     q = (b*b)%p;
31     m=i;
32 }
33 }
34

```

TonelliShanks.cpp

5.22 Euler Totiente

```

1 //Tested
2
3 vector<ll> tot_euler(ll n){
4     vector<ll> tot(n+1, 0);
5     for_(i, n+1) tot[i]=i;
6     for(ll i = 2; i <= n; ++i){
7         if(tot[i] == i){
8             for(ll j = i; j <= n; j+=i) tot[j] -= tot[j]
9                 //i;
10            }
11        }
12    }
13    return tot;
14 }
15

```

tot-euler.cpp

6 Strings

6.1 KMP – $O(n + m)$

```

1 /*
2 *Description:* Pattern matching in  $O(n+m)$ 
3 *Status:* Tested on CSES
4 */
5 template<class T> struct KMP {
6     T pattern; vector<int> lps;
7     KMP(T &pat): pattern(pat) {
8         lps.resize(pat.size(), 0);
9         int len = 0, i = 1;
10        while (i < pattern.size()) {
11            if (pattern[i] == pattern[len])
12                lps[i++] = ++len;
13            else {
14                if (len != 0) len = lps[len-1];
15                else lps[i++] = 0;
16            }
17        }
18    }
19    vector<int> search(T &text) {
20        vector<int> matches;
21        int i = 0, j = 0;
22        while (i < text.size()) {
23            if (pattern[j] == text[i]) {
24                i++, j++;
25                if (j == pattern.size()) {
26                    matches.push_back(i - j);
27                    j = lps[j - 1];
28                }
29            } else {
30                if (j != 0) j = lps[j-1];
31                else i++;
32            }
33        }
34        return matches;
35    }
36 };
37
38 // Prefix function (simple version)
39 template<class T>
40 vector<int> prefix(T &S) {
41     vector<int> P(S.size());
42     P[0] = 0;
43     for(int i = 1; i < S.size(); ++i) {
44         P[i] = P[i - 1];
45         while(P[i] > 0 && S[P[i]] != S[i])
46             P[i] = P[P[i] - 1];
47         if(S[P[i]] == S[i])
48             ++P[i];
49     }
50 }
51

```

```

49     }
50     return P;
51 }
52
53 int main(){
54     string text, pattern;
55     cin >> text >> pattern;
56     KMP<string> kmp(pattern);
57     vector<int> matches = kmp.search(text);
58     cout << matches.size() << '\n';
59     for(int x : matches) cout << x << " ";
60     cout << '\n';
61 }
62

```

KMP.cpp

6.2 Z-Function – $O(n + m)$

```

1  /*
2  *Description:* Z-algorithm, all occurrences
3  in  $O(n+m)$ 
4  *Status:* Tested
5  */
6  struct Z {
7      int n, m;
8      vector<int> z;
9      Z(string s) {
10         n = s.size();
11         z.assign(n, 0);
12         int l = 0, r = 0;
13         for (int i = 1; i < n; i++) {
14             if (i <= r)
15                 z[i] = min(r-i+1, z[i-l]);
16             while (i+z[i] < n
17                 && s[z[i]] == s[i+z[i]])
18                 ++z[i];
19             if (i+z[i]-1 > r)
20                 l = i, r = i+z[i]-1;
21         }
22     }
23     Z(string p, string t) {
24         string s = p + "#" + t;
25         n = p.size();
26         m = t.size();
27         z.assign(n+m+1, 0);
28         int l = 0, r = 0;
29         for (int i = 1; i < n+m+1; i++) {
30             if (i <= r)
31                 z[i] = min(r-i+1, z[i-l]);
32             while (i+z[i] < n+m+1
33                 && s[z[i]] == s[i+z[i]])
34                 ++z[i];
35             if (i+z[i]-1 > r)
36                 l = i, r = i+z[i]-1;
37         }
38     }
39     void p_in_t(vector<int>& ans) {
40         for (int i = n+1; i < n+m+1; i++)
41             if (z[i] == n)
42                 ans.push_back(i-n-1);
43     }
44 };
45
46 int main(){
47     string t, p;
48     cin >> t >> p;
49     Z z(p, t);
50     vector<int> ans;
51     z.p_in_t(ans);
52     cout << ans.size() << '\n';
53     for(int x : ans) cout << x << " ";
54     cout << '\n';
55 }
56

```

z-function.cpp

6.3 Trie – $O(|s|)$ por operación

```

1  /*
2  *Description:* Trie for prefix queries.
3   $O(|s|)$  per operation.
4  *Status:* Tested
5  */
6  struct trie {
7      vector<vector<ll>> tree;
8      vector<ll> counts;
9      trie() {
10         tree.push_back(vector<ll>(26, -1));
11         counts.push_back(0);
12     }
13

```

```

12     };
13     void insert(string &s) {
14         ll i = 0, u = 0;
15         while(i < s.size()){
16             char c = s[i];
17             if (tree[u][c-'a'] == -1){
18                 ll pos = tree.size();
19                 tree.push_back(vector<ll>(26, -1));
20                 counts.push_back(0);
21                 tree[u][c-'a'] = pos;
22             }
23             i++;
24             u = tree[u][c-'a'];
25         }
26         counts[u]++;
27     }
28     ll search(string &s){
29         ll i = 0, u = 0;
30         ll count_ends = 0;
31         while(i < s.size()){
32             char c = s[i];
33             if (tree[u][c-'a'] != -1){
34                 u = tree[u][c-'a'];
35                 i++;
36             }else break;
37         }
38         if(i == s.size())
39             count_ends += counts[u];
40         return count_ends;
41     }
42 };
43
44 int main(){
45     int n; cin >> n;
46     trie t;
47     for(int i = 0; i < n; i++){
48         string s; cin >> s;
49         t.insert(s);
50     }
51     int q; cin >> q;
52     while(q--){
53         string s; cin >> s;
54         cout << t.search(s) << '\n';
55     }
56 }
57

```

trie.cpp

6.4 Rolling Hashing

```

1  template<class T>
2  struct rolling_hashing {
3      int base, mod;
4      vector<long long> p, H;
5      int n;
6      rolling_hashing(const T &s, int b, int m): base(b),
7          mod(m), n(s.size()) {
8          p.assign(n+1, 1);
9          H.assign(n+1, 0);
10         for (int i = 0; i < n; ++i) {
11             H[i+1] = (H[i] * base + s[i]) % mod;
12             p[i+1] = (p[i] * base) % mod;
13         }
14     }
15     int get(int l, int r) {
16         int res = (H[r+1] - H[l]*p[r-l+1]) % mod;
17         if (res < 0) res += mod;
18         return res;
19     }
20 };
21

```

rolling_hashing.cpp

6.5 aho-corasick

```

1  /*
2  *Description:* Aho-Corasick algorithm for multiple
3  pattern matching in text
4  *Status:* Tested
5  */
6  struct AhoCorasick {
7      enum {
8          alpha = 26, first = 'a'
9      }; // change this!
10     struct Node {
11         // (nmatches is optional)
12         int back, next[alpha], start = -1, end = -1,
13             nmatches = 0;
14         Node(int v) {
15

```

```

13     memset(next, v, sizeof(next));
14 }
15 };
16 vector < Node > N;
17 vi backp;
18 void insert(string & s, int j) {
19     assert(!s.empty());
20     int n = 0;
21     for (char c: s) {
22         int & m = N[n].next[c - first];
23         if (m == -1) {
24             n = m = sz(N);
25             N.emplace_back(-1);
26         } else n = m;
27     }
28     if (N[n].end == -1) N[n].start = j;
29     backp.push_back(N[n].end);
30     N[n].end = j;
31     N[n].nmatches++;
32 }
33 AhoCorasick(vector < string > & pat): N(1, -1) {
34     rep(i, 0, sz(pat)) insert(pat[i], i);
35     N[0].back = sz(N);
36     N.emplace_back(0);
37
38     queue < int > q;
39     for (q.push(0); !q.empty(); q.pop()) {
40         int n = q.front(), prev = N[n].back;
41         rep(i, 0, alpha) {
42             int & ed = N[n].next[i], y = N[prev].next[i];
43             if (ed == -1) ed = y;
44             else {
45                 N[ed].back = y;
46                 N[ed].end == -1 ? N[ed].end = N[y].end: backp[
47                     N[ed].start] = N[y].end;
48                 N[ed].nmatches += N[y].nmatches;
49                 q.push(ed);
50             }
51         }
52     }
53     vi find(string word) {
54         int n = 0;
55         vi res; // ll count = 0;
56         for (char c: word) {
57             n = N[n].next[c - first];
58             res.push_back(N[n].end);
59             // count += N[n].nmatches;
60         }
61         return res;
62     }
63     vector < vi > findAll(vector < string > & pat, string
64         word) {
65         vi r = find(word);
66         vector < vi > res(sz(word));
67         rep(i, 0, sz(word)) {
68             int ind = r[i];
69             while (ind != -1) {
70                 res[i - sz(pat[ind]) + 1].push_back(ind);
71                 ind = backp[ind];
72             }
73         }
74         return res;
75     }
76 };

```

aho-corasick.cpp

7 Programación Dinámica

7.1 Longest Increasing Subsequence – $O(n \log n)$

```

1  /*
2  *Description:* LIS in  $O(n \log n)$ ,
3  *allows sequence recovery
4  *Status:* Highly tested
5  */
6  template <class I>
7  vector<int> LIS(const vector<I> &S) {
8      if (S.empty()) return {};
9      vector<int> prev(S.size());
10     vector<pair<I, int>> res;
11     for (int i = 0; i < S.size(); i++) {
12         auto it = lower_bound(res.begin(),
13             res.end(), pair<I, int>{S[i], i});
14         if (it == res.end())
15             res.emplace_back(it, it = res.end() - 1);
16         *it = {S[i], i};
17         prev[i] = (it == res.begin())

```

```

18         ? 0 : (it-1)->second);
19     }
20     int L = res.size(),
21     cur = res.back().second;
22     vector<int> ans(L);
23     while (L--)
24         ans[L] = cur, cur = prev[cur];
25     return ans;
26 }
27
28 int main(){
29     int n; cin >> n;
30     vector<int> a(n);
31     for(int i = 0; i < n; i++) cin >> a[i];
32     vector<int> lis_idx = LIS(a);
33     cout << lis_idx.size() << '\n';
34     for(int i = 0; i < (int)lis_idx.size(); i++)
35         cout << lis_idx[i] << " ";
36     cout << '\n';
37 }
38

```

LIS.cpp

7.2 LIS of length K– $O(nk \log n)$

```

1  //k = searched length, m = compressed size
2  vector<fenwick_tree> bit(k + 1, fenwick_tree(m));
3
4  ll answer = 0;
5  for (ll x : v) {
6      ll value = compress(x); //or already compressed
7      vector<ll> current(k+1);
8      current[i] = 1;
9      for (ll len = 2; len <= k; len++) {
10         current[len] = bit[len-1].sum(value-1);
11     }
12     for (ll len = 1; len <= k; len++) {
13         bit[len].add(value, current[len]);
14     }
15     answer += current[k];
16 }
17
18 cout<<answer<<endl;
19

```

LIS_lenght_k.cpp

7.3 LIS elements participate of Optimal solutions– $O(n \log n)$

```

1  /*
2  L[i]: longest strictly increasing subsequence ending
3  at i
4  R[i]: longest strictly increasing subsequence
5  starting at i
6  Theorem: best sol force through x = best before x+
7  best after x-overlap on x.
8  So if optimal==L[i]+R[i]-1(overlap) -> index i its
9  part of an optimal solution
10 layer: number of LIS-participating elements
11 */
12 fenwick_max<ll> bit(m + 1);
13 fenwick_max<ll> bit2(m + 1);
14
15 vector<ll> L(n), R(n);
16
17 for (ll i = 0; i < n; i++) {
18     L[i] = bit.query(v[i] - 1) + 1;
19     bit.update(v[i], L[i]);
20 }
21
22 for (ll i = n - 1; i >= 0; i--) {
23     R[i] = bit2.query(m - v[i]) + 1;
24     bit2.update(m - v[i] + 1, R[i]);
25 }
26
27 ll k = *max_element(L.begin(), L.end());
28 vector<ll> layer(k + 1, 0);
29
30 for (ll i = 0; i < n; i++) {
31     if (L[i] + R[i] - 1 == k) layer[L[i]]++;
32 }
33

```

LIS_elements_optimal.cpp

7.4 Knapsack 0/1 – $O(nW)$

```
1 void solve(){
2     ll n, w;
3     cin >> n >> w;
4     vector<pair<ll,ll>> v(n);
5     for(auto &[a,b] : v) cin >> a >> b;
6     vector<ll> ans(w+2,0);
7     ll ans_ = 0;
8     for(auto [vi, wi] : v){
9         for(ll j = w; j >= wi; j--){
10             ans[j] = max(ans[j], ans[j-wi]+vi);
11             ans_ = max(ans_, ans[j]);
12         }
13     }
14     cout << ans_ << endl;
15 }
16
```

mochila.cpp

8 Misceláneos

8.1 Búsqueda Binaria – $O(\log n)$

```
1 int bs(vector<ll>& v, int b){
2     int l = 0, r = v.size();
3     while(l < r){
4         int mid = (l + r) / 2;
5         if(v[mid] >= b) r = mid;
6         else l = mid + 1;
7     }
8     return l;
9 }
10
```

binary search.cpp