CHAKOTEAM! BOOKHAND

General
Template 2

Grafos
DominatorTree 2
BellmanFord 2
BinaryLifting 3
Djikstra 3
Floyd-Warshall 3
Kruskal 3
Lca 3

Flujo Y Conectividad
2-sat 3
Camino Dirigido Euler 4
Camino No Dirigido Euler 4
Dinic 4
Tarjan 5
TarjanSCC 5

Estructuras De Datos
Fenwick 5
Fenwick 2D 5
Fenwick Walk 5
Line Container 6
Segment Tree 6
Segment Tree Lazy 6
Segment Tree Misra Gries 6
Segment Tree Walk 7
Sparse Table 7
Sqrt Decomposition 7
Union Find 7

Matematicas
DiscreteRoot 7
InclusionExclusion 7
SimpsonRule 7
TonelliShanks 8
Ztransform 8
Bin Pow 8
CatalanNumbers 8
Convex Hull 8
Crt 9
Discrete Log 9
Erathostenes-sieve 9
Factorization Pollard Rho 9
Fft 9
Gaussian Elimination 10
Gcd 10
GcdExtended 10
Miller Rabin 10
Mobius 10
Ntt 10
Primitive Root 11
Template 11
Tot Euler 11

Strings
Aho-corasick 11
Booth 12
Kmp 12
Manacher 12
RollingHashing 12
Suffix Array 12
Trie 12
Zfunction 13

Programacion Dinamica
Knappsack 13
Lis 13
Lis Length K 13

Offline Algorithms
Cdq 13
Mo 13
Pbs 14
Value Driven 14

Miscelaneo
Busqueda Binaria 14
Random 14
Time 14

General

Template

```cpp
#pragma GCC optimize("O3", "unroll-loops")
#include <bits/stdc++.h>
using namespace std;
using ll = long long;
#define endl '\n'
#define all(v) (v).begin(), (v).end()

void solve(){

}

int main(){
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    ll t = 1; cin >> t;
    while(t--) solve();
}
```

Grafos

DominatorTree

```cpp
/*
  *Description:* Computes the inmediate dominator of every node in a directed graph in O((|E|+|V|)log(|V|)).
  *Status:* Tested on CSES
*/
struct dominator_tree {
    ll n,l,s;
    vector<ll> tin,par,vis_ord, dsu_mn, dsu_par, sdom, dep, rdom,idom;
    vector<bool> vis;
    vector<vector<ll>> up;
    vector<vector<pair<ll,ll>>> up_mn;
    void dfs(ll u, ll p, vector<vector<ll>> & adj){
        if (vis[u]) return;
        vis[u] = 1;
        dep[u] = dep[p]+1;
        tin[u] = vis_ord.size();
        vis_ord.push_back(u);
        par[u] = p;
        for (int v : adj[u]) dfs(v,u,adj);
    }
    ll find(ll x){
        if (dsu_par[x] == -1) return x;
        if (dsu_par[dsu_par[x]] != -1){
            ll res = find(dsu_par[x]);
            if (tin[res] < tin[dsu_mn[x]])
                dsu_mn[x] = res;
            dsu_par[x] = dsu_par[dsu_par[x]];
        }
        assert(dsu_mn[x] != INT32_MAX);
        return dsu_mn[x];
    }
    void get_sdom(vector<vector<ll>> & rev){
        for (ll i = vis_ord.size()-1; i >= 0; i--){
            ll c = vis_ord[i];
            if (c == s) continue;
            for (ll to : rev[c]){
                ll res = find(to);
                if (sdom[c] == -1 || tin[res] < tin[sdom[c]])
                    sdom[c] = res;
            }
            dsu_par[c] = par[c];
            dsu_mn[c] = sdom[c];
            if (sdom[c] == -1) cerr << c << endl;
        }
    }
    void init_up(){
        for_(i, n){
            if (!vis[i]) continue;
            up[i][0] = par[i];
            up_mn[i][0] = {tin[sdom[i]],i};
        }
        for (ll i = 1; i < l; i++) {
            for_(j, n) {
                if (!vis[j]) continue;
                ll h = up[j][i-1];
                if (h == -1) {
                    up[j][i] = -1;
                    up_mn[j][i] = up_mn[j][i-1];
                } else {
                    up[j][i] = up[h][i-1];
                    up_mn[j][i] = min(up_mn[j][i-1], up_mn[h][i-1]);
                }
            }
        }
    }
    ll get_min(ll v, ll u){
        ll dist = dep[u]-dep[v];
```

DominatorTree (cont.)

```cpp
        pair<ll,ll> ret = up_mn[u][0];
        ll w = u;
        for_(i, l)
            if (dist&(1<<i)){
                ret = min(ret,up_mn[w][i]);
                w = up[w][i];
            }
        assert(w == v);
        return ret.second;
    }
    void get_idom(){
        for (ll c : vis_ord){
            if (c == s) continue;
            rdom[c] = get_min(sdom[c],c);
        }
        for (ll c : vis_ord)
            if (c != s)
                idom[c] = ((rdom[c] == c)?sdom[c]:idom[rdom[c]]);
    }
    dominator_tree(vector<vector<ll>> & adj, vector<vector<ll>> & rev, ll _s = 0, ll logn = 20){
        n = adj.size(); l = logn; s = _s;
        tin.resize(n,INT32_MAX);
        par.resize(n,-1);
        vis.resize(n,0);
        dep.resize(n,0);
        dfs(s,-1,adj);
        dsu_par.resize(n,-1);
        dsu_mn.resize(n,INT32_MAX);
        sdom.resize(n,-1);
        rdom.resize(n,-1);
        idom.resize(n,-1);
        get_sdom(rev);
        up.assign(n,vector<ll>(logn));
        up_mn.assign(n,vector<pair<ll,ll>>(logn));
        init_up();
        get_idom();
    }
};

//aux function, cover dom tree
void dfs(ll &cnt, ll node, vector<vector<ll>> &adj, vector<ll> &tin, vector<ll> &tout){
    tin[node] = cnt++;
    for(ll child : adj[node]) dfs(cnt, child, adj, tin, tout);
    tout[node] = cnt++;
}

//verifiy if u dominates v, for each edge, obviusly tle, is to catch de idea, and implement a part of the function
vector<vector<bool>> Verifiy_u_dom_v(ll n, vector<vector<ll>> &adj, vector<vector<ll>> &rev_adj, vector<pair<ll, ll>> &edges){
    dominator_tree dt(adj, rev_adj);
    vector<vector<ll>> dom_tree(n);
    for_(i, n){
        if(i==0) continue;
        if(dt.vis[i]) dom_tree[dt.idom[i]].push_back(i);
    }
    vector<ll> tin(n, 0), tout(n, 0); ll cnt = 0;
    dfs(cnt, 0, dom_tree, tin, tout);
    vector<vector<bool>> dom_matrix(n, vector<bool>(n, false));
    for_(i, edges.size()){
        auto &[u,v] = edges[i];
        if((tin[u]<=tin[v] && tout[v]<=tout[u])) dom_matrix[u][v] = true;
    }
    return dom_matrix;
}
```

BellmanFord

```cpp
struct BellmanFord {
  struct Edge {
    int from, to, weight;
  };
  int n, last_updated = -1;
  const ll INF = 1e18;
  vector<int> p, dist;
  BellmanFord(vector<Edge>& G, int s, int nn) {
    n = nn;
    dist.assign(n + 2, INF);
    p.assign(n + 2, -1);
    dist[s] = 0;
    for (int i = 1; i <= n; i++) {
      last_updated = -1;
      for (Edge& e : G)
        if (dist[e.from] + e.weight < dist[e.to]) {
          dist[e.to] = dist[e.from] + e.weight;
          p[e.to] = e.from;
          last_updated = e.to;
        }
```

BellmanFord (cont.)

```
    }
  }
  bool getCycle(vector<int>& cycle) {
    if (last_updated == -1) return false;
    for (int i = 0; i < n - 1; i++) last_updated = p[last_u
pdated];
    for (int x = last_updated;; x = p[x]) {
      cycle.push_back(x);
      if (x == last_updated and cycle.size() > 1) break;
    }
    reverse(cycle.begin(), cycle.end());
    return true;
  }
};
```

BinaryLifting

```
void BinaryLifting(ll node) {
  stack<pair<ll, ll>> st;
  st.push({node, -1});
  while (st.size()) {
    auto [n, p] = st.top();
    st.pop();
    for (auto v : tree[n]) {
      if (p == v) continue;
      st.push({v, n});
      bl[v][0] = n;
      for (ll j = 1; j < 33; j++) {
        if (bl[v][j - 1] != -1) {
          bl[v][j] = bl[bl[v][j - 1]][j - 1];
        } else {
          bl[v][j] = -1;
        }
      }
    }
  }
}
```

Djikstra

```
vector<ll> dist;
vector < vector<pair<ll, ll>> g;

void djikstra() {
  priority_queue<pair<ll, ll>, vector<pair<ll, ll>>, greate
r<pair<ll, ll>>> pq;
  pq.push({0, 0});  // nodo_inicio, distancia
  while (pq.size()) {
    auto [c, node] = pq.top();
    pq.pop();
    if (dist[node] <= c) continue;
    dist[node] = c;
    for (auto [c_, v_] : g[node]) {
      if (dist[v_] > c + c_) pq.push({c + c_, v_});
    }
  }
}
```

Floyd-Warshall

```
for (int i = 1; i <= n; i++) {
  for (int j = 1; j <= n; j++) {
    if (i == j)
      distance[i][j] = 0;
    else if (adj[i][j])
      distance[i][j] = adj[i][j];
    else
      distance[i][j] = INF;
  }
}
for (int k = 1; k <= n; k++) {
  for (int i = 1; i <= n; i++) {
    for (int j = 1; j <= n; j++) {
      distance[i][j] = min(distance[i][j], distance[i][k] +
 distance[k][i]);
    }
  }
}
```

Kruskal

```
struct Edge {
  int a;
  int b;
  ll w;
  Edge(int a_, int b_, ll w_) : a(a_), b(b_), w(w_) {}
};
bool c_edge(Edge& a, Edge& b) { return a.w < b.w; }
ll Kruskal() {
  int n = G.size();
  union_find sets(n);
  vector<Edge> edges;
  for (int i = 0; i < n; i++) {
    for (auto eg : G[i]) {
```

Kruskal (cont.)

```
      // node i to node eg.first with cost eg.second
      edges.emplace_back(i, eg.first, eg.second);
    }
  }
  sort(edges.begin(), edges.end(), c_edge);
  ll min_cost = 0;
  for (Edge e : edges) {
    if (sets.sameSet(e.a, e.b) != true) {
      tree.emplace_back(e.a, e.b, e.w);
      min_cost += e.w;
      sets.unionSet(e.a, e.b);
    }
  }
  return min_cost;
}
```

Lca

```
struct LCA {
  vector<vector<ll>> T, parent;
  vector<ll> depth, vis, comp;
  ll LOGN, V;
  LCA(vector<vector<ll>>& T) : T(T) {
    V = (ll)T.size();
    LOGN = 1;
    while ((1LL << LOGN) <= max(1LL, V)) LOGN++;
    parent.assign(V, vector<ll>(LOGN, 0));
    depth.assign(V, 0);
    vis.assign(V, 0);
    comp.assign(V, -1);
    ll id = 0;
    for (ll u = 0; u < V; u++) {
      if (!vis[u]) {
        dfs(u, u, id++);
      }
    }
  }

  void dfs(ll u, ll p, ll id) {
    vis[u] = 1;
    comp[u] = id;
    parent[u][0] = p;
    for (ll j = 1; j < LOGN; j++)
      parent[u][j] = parent[parent[u][j - 1]][j - 1];

    for (ll v : T[u]) {
      if (!vis[v]) {
        depth[v] = depth[u] + 1;
        dfs(v, u, id);
      }
    }
  }
  ll query(ll u, ll v) {
    if (comp[u] != comp[v]) return -1;
    if (depth[u] < depth[v]) swap(u, v);
    ll k = depth[u] - depth[v];
    for (ll j = LOGN - 1; j >= 0; j--) {
      if ((k >> j) & 1) u = parent[u][j];
    }
    if (u == v) return u;
    for (ll j = LOGN - 1; j >= 0; j--) {
      if (parent[u][j] != parent[v][j]) {
        u = parent[u][j];
        v = parent[v][j];
      }
    }
    return parent[u][0];
  }
};
```

Flujo Y Conectividad

2-sat

```
struct TwoSat {
  int N;
  vector<vector<int>> gr;
  vector<int> values;
  TwoSat(int n = 0) : N(n), gr(2 * n) {}
  int addVar() {
    gr.emplace_back();
    gr.emplace_back();
    return N++;
  }
  void either(int f, int j) {
    f = max(2 * f, -1 - 2 * f);
    j = max(2 * j, -1 - 2 * j);
    gr[f].push_back(j ^ 1);
    gr[j].push_back(f ^ 1);
  }
  void setValue(int x) { either(x, x); }
  void atMostOne(const vector<int>& li) {
    if ((int)li.size() <= 1) return;
    int cur = ~li[0];
```

2-sat (cont.)

```
    for (int i = 2; i < (int)li.size(); i++) {
      int next = addVar();
      either(cur, ~li[i]);
      either(cur, next);
      either(~li[i], next);
      cur = ~next;
    }
    either(cur, ~li[1]);
  }
  vector<int> val, comp, z;
  int Time = 0;
  int dfs(int i) {
    int low = val[i] = ++Time, x;
    z.push_back(i);
    for (int e : gr[i])
      if (!comp[e]) low = min(low, val[e] ? val[e] : dfs(e)
);
    if (low == val[i]) do {
        x = z.back();
        z.pop_back();
        comp[x] = low;
        if (values[x >> 1] == -1) values[x >> 1] = x & 1;
      } while (x != i);
    return val[i] = low;
  }
  bool solve() {
    values.assign(N, -1);
    val.assign(2 * N, 0);
    comp = val;
    for (int i = 0; i < 2 * N; i++)
      if (!comp[i]) dfs(i);
    for (int i = 0; i < N; i++)
      if (comp[2 * i] == comp[2 * i + 1]) return false;
    return true;
  }
};
```

Camino Dirigido Euler

```
struct directed_euler_trail {
  ll n, m = 0;
  vector<vector<ll>> adj;
  vector<pair<ll, ll>> E;
  vector<ll> indeg, outdeg, vertices, edges;
  directed_euler_trail(ll n) : n(n), adj(n), indeg(n), outd
eg(n) {}
  void add_edge(ll u, ll v) {
    adj[u].push_back(m);
    E.push_back({u, v});
    outdeg[u]++, indeg[v]++, m++;
  }
  ll find_start() {
    ll s = -1, cp = 0, cm = 0;
    for (ll v = 0; v < n; v++) {
      ll d = outdeg[v] - indeg[v];
      if (d == 1)
        cp++, s = v;
      else if (d == -1)
        cm++;
      else if (d != 0)
        return -2;
      if (outdeg[v] > 0 && s < 0) s = v;
    }
    if (cp == 0 && cm == 0) return s;
    return (cp == 1 && cm == 1) ? s : -2;
  }
  bool solve() {
    if (m == 0) {
      vertices = {0};
      return true;
    }
    ll s = find_start();
    if (s == -2) return false;
    vector<ll> ep(n);
    edges.resize(m);
    ll pp = 0, pq = m, v = s;
    while (pp < pq) {
      if (ep[v] >= (ll)adj[v].size()) {
        if (pp == 0) return false;
        edges[--pq] = edges[--pp];
        v = E[edges[pq]].first;
      } else {
        ll e = adj[v][ep[v]++];
        edges[pp++] = e;
        v = E[e].second;
      }
    }
    vertices = {s};
    for (ll e : edges) vertices.push_back(E[e].second);
    return true;
  }
};
```

Camino No Dirigido Euler

```
struct undirected_euler_trail {
  ll n, m = 0;
  vector<vector<ll>> adj;
  vector<pair<ll, ll>> E;
  vector<ll> deg, vertices, edges;

  undirected_euler_trail(ll n) : n(n), adj(n), deg(n) {}

  void add_edge(ll u, ll v) {
    adj[u].push_back(m);
    if (u != v) adj[v].push_back(m);
    E.push_back({u, v});
    deg[u]++, deg[v]++, m++;
  }

  ll find_start() {
    ll s = -1, codd = 0;
    for (ll v = 0; v < n; v++) {
      if (deg[v] & 1)
        codd++, s = v;
      else if (deg[v] > 0 && s < 0)
        s = v;
    }
    return (codd == 0 || codd == 2) ? s : -2;
  }

  bool solve() {
    if (m == 0) {
      vertices = {0};
      return true;
    }

    ll s = find_start();
    if (s == -2) return false;

    vector<ll> ep(n);
    edges.resize(m);
    vector<bool> alive(m, true);
    ll pp = 0, pq = m, v = s;

    while (pp < pq) {
      if (ep[v] >= adj[v].size()) {
        if (pp == 0) return false;
        edges[--pq] = edges[--pp];
        v ^= E[edges[pq]].first ^ E[edges[pq]].second;
      } else {
        ll e = adj[v][ep[v]++];
        if (!alive[e]) continue;
        alive[e] = false;
        edges[pp++] = e;
        v ^= E[e].first ^ E[e].second;
      }
    }
    vertices = {s};
    for (ll e : edges) {
      s ^= E[e].first ^ E[e].second;
      vertices.push_back(s);
    }
    return true;
  }
};
```

Dinic

```
template <class T>
struct Dinic {
  struct Edge {
    int to, rev;
    T f, c;
    bool r;
  };
  int n, t_;
  vector<vector<Edge>> G;
  vector<pair<ll, ll>> min_cut;
  vector<int> D, q, W;
  bool bfs(int s, int t) {
    W.assign(n, 0);
    D.assign(n, -1);
    D[s] = 0;
    int f = 0, l = 0;
    q[l++] = s;
    while (f < l) {
      int u = q[f++];
      for (const Edge& e : G[u])
        if (D[e.to] == -1 && e.f < e.c) D[e.to] = D[u] + 1,
 q[l++] = e.to;
    }
    return D[t] != -1;
  }
  int dfs(int u, T f) {
    if (u == t_) return f;
    for (int& i = W[u]; i < (int)G[u].size(); ++i) {
      Edge& e = G[u][i];
      int v = e.to;
      if (e.c <= e.f || D[v] != D[u] + 1) continue;
```

Dinic (cont.)

```
      T df = dfs(v, min(f, e.c - e.f));
      if (df > 0) {
        e.f += df, G[v][e.rev].f -= df;
        return df;
      }
    }
    return 0;
  }
  Dinic(int N) : n(N), G(N), D(N), q(N) {}
  void add_edge(int u, int v, T cap) {
    G[u].push_back({v, (int)G[v].size(), 0, cap, 0});
    G[v].push_back({u, (int)G[u].size() - 1, 0, 0, 1});  // Use cap instead of 0 if bidirectional
  }
  T max_flow(int s, int t) {
    t_ = t;
    T ans = 0;
    while (bfs(s, t))
      while (T dl = dfs(s, numeric_limits<T>::max())) ans += dl;
    return ans;
  }
  void solve_min_cut(vector<pair<ll, ll>>& edges) {
    for (auto [u, v] : edges) {
      if ((D[u] != -1) != (D[v] != -1)) {
        min_cut.emplace_back(u, v);
      }
    }
  }
};
```

Tarjan

```
struct tarjan {
  struct edge {
    int u, v, comp, bridge;
  };
  int n, nbc, T;
  vector<vector<int>> adj;
  vector<edge> e;
  vector<int> disc, low, art, st;
  tarjan(int n) : n(n), nbc(0), T(0), adj(n), disc(n, -1), low(n), art(n, 0) {}
  int add_edge(int u, int v) {
    int i = e.size();
    adj[u].push_back(i);
    adj[v].push_back(i);
    e.push_back({u, v, -1, false});
    return i;
  }
  void dfs(int u, int pe) {
    low[u] = disc[u] = T++;
    for (int i : adj[u]) {
      if (i == pe) continue;
      int v = e[i].u ^ e[i].v ^ u;
      if (disc[v] < 0) {
        st.push_back(i);
        dfs(v, i);
        if (low[v] > disc[u]) e[i].bridge = true;
        if (low[v] >= disc[u]) {
          art[u]++;
          while (st.back() != i) {
            e[st.back()].comp = nbc;
            st.pop_back();
          }
          e[st.back()].comp = nbc;
          st.pop_back();
          nbc++;
        }
        low[u] = min(low[u], low[v]);
      } else if (disc[v] < disc[u]) {
        st.push_back(i);
        low[u] = min(low[u], disc[v]);
      }
    }
  }
  void solve() {
    for (int i = 0; i < n; i++)
      if (disc[i] < 0) dfs(i, -1), art[i]--;
  }
  bool is_bridge(int i) { return e[i].bridge; }
  bool is_art(int v) { return art[v] > 0; }
  int component(int i) { return e[i].comp; }
};
```

TarjanSCC

```
struct tarjan {
  int n, timer;
  vector<bool> vis, ist;
  vector<int> tin, low, st, cmp;
  vector<vector<int>> scc;
  void dfs(int u, vector<vector<int>>& adj) {
    vis[u] = ist[u] = 1;
    st.push_back(u);
    tin[u] = low[u] = timer++;
    for (auto v : adj[u]) {
      if (!vis[v]) {
        dfs(v, adj);
        low[u] = min(low[u], low[v]);
      } else if (ist[v]) {
        low[u] = min(low[u], tin[v]);
      }
    }
    if (low[u] == tin[u]) {
      scc.emplace_back();
      int cur;
      do {
        cur = st.back();
        st.pop_back();
        ist[cur] = 0;
        scc.back().push_back(cur);
        cmp[cur] = (int)scc.size() - 1;
      } while (cur != u);
    }
  }
  tarjan(vector<vector<int>>& adj) {
    n = adj.size();
    tin.resize(n);
    timer = 0;
    cmp.resize(n);
    low.resize(n);
    vis.resize(n, 0);
    ist.resize(n, 0);
    for (int i = 0; i < n; i++)
      if (!vis[i]) dfs(i, adj);
  }
};
```

Estructuras De Datos

Fenwick

```
struct fenwick_tree {
  vector<ll> bit;
  int n;
  fenwick_tree(int n) : n(n) { bit.assign(n, 0); }
  fenwick_tree(vector<ll>& a) : fenwick_tree(a.size()) {
    for (size_t i = 0; i < a.size(); i++) {
      bit[i] += a[i];
      if ((i | (i + 1)) < a.size()) bit[i | (i + 1)] += bit[i];
    }
  }
  ll sum(int r) {
    ll ret = 0;
    for (; r >= 0; r = (r & (r + 1)) - 1) ret += bit[r];
    return ret;
  }
  ll sum(int l, int r) { return sum(r) - sum(l - 1); }
  void add(int idx, ll delta) {
    for (; idx < n; idx = idx | (idx + 1)) bit[idx] += delta;
  }
};
```

Fenwick 2D

```
struct fenwick_tree_2d {
  int N, M;
  vector<vector<ll>> BIT;
  fenwick_tree_2d(int N, int M) : N(N), M(M) {
    BIT.assign(N + 1, vector<ll>(M + 1, 0));
  }
  void update(int x, int y, ll v) {
    for (int i = x; i <= N; i += (i & -i))
      for (int j = y; j <= M; j += (j & -j)) BIT[i][j] += v;
  }
  ll sum(int x, int y) {
    ll s = 0;
    for (int i = x; i > 0; i -= (i & -i))
      for (int j = y; j > 0; j -= (j & -j)) s += BIT[i][j];
    return s;
  }
  ll query(int x1, int y1, int x2, int y2) {
    return sum(x2, y2) - sum(x2, y1 - 1) - sum(x1 - 1, y2) +
           sum(x1 - 1, y1 - 1);
  }
};
```

Fenwick Walk

```
struct fenwick_tree_with_walk : fenwick_tree {
  ll walk(ll k) {
    if (k <= 0 || k > sum(n - 1)) return n;
    ll i = -1, s = 1;
```

Fenwick Walk (cont.)

```
    while ((s << 1) < n) s <<= 1;
    while (s > 0) {
      ll m = i + s;
      if (m < n && bit[m] < k) {
        i = m;
        k -= bit[m];
      }
      s >>= 1;
    }
    return i + 1;
  }
};
```

Line Container

```
const ll INF = 1e15;
struct Line {
  mutable ll a, b, c;
  bool operator<(Line r) const {
    return a < r.a;
  }
  bool operator<(ll x) const {
    return c < x;
  }
};
// dynamically insert `a*x + b` lines and query for maximum
// at any x all operations have complexity O(log N)
struct LineContainer: multiset < Line, less < >> {
  ll div(ll a, ll b) {
    return a / b - ((a ^ b) < 0 && a % b);
  }
  bool isect(iterator x, iterator y) {
    if (y == end()) return x -> c = INF, 0;
    if (x -> a == y -> a) x -> c = x -> b > y -> b ? INF : -INF;
    else x -> c = div(y -> b - x -> b, x -> a - y -> a);
    return x -> c >= y -> c;
  }

  void add(ll a, ll b) {
    // a *= -1, b *= -1 // for min
    auto z = insert({
      a,
      b,
      0
    }), y = z++, x = y;
    while (isect(y, z)) z = erase(z);
    if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
    while ((y = x) != begin() && (--x) -> c >= y -> c) isect(x, erase(y));
  }

  ll query(ll x) {
    if (empty()) return -INF; // INF for min
    auto l = * lower_bound(x);
    return l.a * x + l.b;
    // return -l.a * x - l.b; // for min
  }
};
```

Segment Tree

```
template<class T, T m_(T, T)> struct segment_tree{
  int n; vector<T> ST;
  segment_tree(){}
  segment_tree(vector<T> &a){
    n = a.size(); ST.resize(n << 1);
    for (int i=n;i<(n<<1);i++)ST[i]=a[i-n];
    for (int i=n-1;i>0;i--)ST[i]=m_(ST[i<<1],ST[i<<1|1]);
  }
  void update(int pos, T val){ // replace with val
    ST[pos += n] = val;
    for (pos >>= 1; pos > 0; pos >>= 1)
      ST[pos] = m_(ST[pos<<1], ST[pos<<1|1]);
  }
  T query(int l, int r){ // [l, r]
    T ansL, ansR; bool hasL = 0, hasR = 0;
    for (l += n, r += n + 1; l < r; l >>= 1, r >>= 1) {
      if (l & 1)
        ansL=(hasL?m_(ansL,ST[l++]):ST[l++]),hasL=1;
      if (r & 1)
        ansR=(hasR?m_(ST[--r],ansR):ST[--r]),hasR=1;
    }
    if (!hasL) return ansR; if (!hasR) return ansL;
    return m_(ansL, ansR);
  }
};
```

Segment Tree Lazy

```
template<
  class T1, // answer value stored on nodes
  class T2, // lazy update value stored on nodes
```

Segment Tree Lazy (cont.)

```
  T1 merge(T1, T1),
  void pushUpd(T2& /*parent*/, T2& /*child*/, int, int, int, int), // push update value from a node to another. parent -> child
  void applyUpd(T2&, T1&, int, int)           // apply the update value of a node to its answer value. upd -> ans
>
struct segment_tree_lazy{
  vector<T1> ST; vector<T2> lazy; vector<bool> upd;
  int n;
  void build(int i, int l, int r, vector<T1>&values){
    if (l == r){
      ST[i] = values[l];
      return;
    }
    build(i << 1, l, (l + r) >> 1, values);
    build(i << 1 | 1, (l + r) / 2 + 1, r, values);
    ST[i] = merge(ST[i << 1], ST[i << 1 | 1]);
  }
  segment_tree_lazy() {}
  segment_tree_lazy(vector<T1>&values){
    n = values.size(); ST.resize(n << 2 | 3);
    lazy.resize(n << 2 | 3); upd.resize(n << 2 | 3, false);
    build(1, 0, n - 1, values);
  }
  void push(int i, int l, int r){
    if (upd[i]){
      applyUpd(lazy[i], ST[i], l, r);
      if (l != r){
        pushUpd(lazy[i], lazy[i << 1], l, r, l, (l + r) / 2);
        pushUpd(lazy[i], lazy[i << 1 | 1], l, r, (l + r) / 2 + 1, r);
        upd[i << 1] = 1;
        upd[i << 1 | 1] = 1;
      }
      upd[i] = false;
      lazy[i] = T2();
    }
  }
  void update(int i, int l, int r, int a, int b, T2 &u){
    if (l >= a and r <= b){
      pushUpd(u, lazy[i], a, b, l, r);
      upd[i] = true;
    }
    push(i, l, r);
    if (l > b or r < a) return;
    if (l >= a and r <= b) return;
    update(i << 1, l, (l + r) >> 1, a, b, u);
    update(i << 1 | 1, (l + r) / 2 + 1, r, a, b, u);
    ST[i] = merge(ST[i << 1], ST[i << 1 | 1]);
  }
  void update(int a, int b, T2 u){
    if (a > b){
      update(0, b, u);
      update(a, n - 1, u);
      return ;
    }
    update(1, 0, n - 1, a, b, u);
  }
  T1 query(int i, int l, int r, int a, int b){
    push(i, l, r);
    if (a <= l and r <= b)
      return ST[i];
    int mid = (l + r) >> 1;
    if (mid < a)
      return query(i << 1 | 1, mid + 1, r, a, b);
    if (mid >= b)
      return query(i << 1, l, mid, a, b);
    return merge(query(i << 1, l, mid, a, b), query(i << 1 | 1, mid + 1, r, a, b));
  }
  T1 query(int a, int b){
    if (a > b) return merge(query(a, n - 1), query(0, b));
    return query(1, 0, n - 1, a, b);
  }
};
```

Segment Tree Misra Gries

```
template<ll K>
vector<pair<ll, ll>> misra_merge(vector<pair<ll, ll>> a, vector<pair<ll, ll>> b) {
  for (auto [x, c]: b) {
    auto it = find_if(a.begin(), a.end(), [&](auto i){return i.first == x;});
    if (it != a.end()) it->second += c;
    else a.emplace_back(x, c);
  }
  while (a.size() >= K) {
    ll mini = LLONG_MAX;
    for (auto [x, c]: a) mini = min(mini, c);
    vector<pair<ll, ll>> tmp;
    for (auto [x, c]: a) {
      c -= mini;
```

Segment Tree Misra Gries (cont.)

```
      if (c > 0) tmp.emplace_back(x, c);
    }
    a = tmp;
  }
  return a;
}
template<ll K>
struct segment_tree_misra_gries : segment_tree<vector<pair<ll, ll>>, misra_merge<K>> {
  using base = segment_tree<vector<pair<ll, ll>>, misra_merge<K>>;
  using base::base;
};
```

Segment Tree Walk

```
template<class T, T m_(T, T)> struct segment_tree_with_walk : segment_tree<T,m_> {
  int walk(int l, T k) {
    vector<int> L, R;
    int r = this->n - 1;
    for (l += this->n, r += this->n + 1; l < r; l >>= 1, r >>= 1) {
      if (l & 1) L.push_back(l++);
      if (r & 1) R.push_back(--r);
    }
    reverse(R.begin(), R.end());
    L.insert(L.end(), R.begin(), R.end());
    for (int v : L) {
      if (this->ST[v] >= k) {
        while (v < this->n) v = (this->ST[v << 1] >= k) ? (v << 1) : (v << 1 | 1);
        return v - this->n;
      }
    }
    return -1;
  }
};
```

Sparse Table

```
template <typename T, T m_(T, T)>
struct sparse_table {
  int n;
  vector<vector<T>> table;
  sparse_table() {}
  sparse_table(vector<T> &arr) {
    n = arr.size();
    int k = log2_floor(n) + 1;
    table.assign(n, vector<T>(k));
    for (int i = 0; i < n; i++)
      table[i][0] = arr[i];
    for (int j = 1; j < k; j++)
      for (int i = 0; i + (1 << j) <= n; i++)
        table[i][j] = m_(table[i][j-1], table[i+(1<<(j-1))][j-1]);
  }
  T query(int l, int r) {
    int k = log2_floor(r - l + 1);
    return m_(table[l][k], table[r-(1 << k)+1][k]);
  }
  int log2_floor(int n) { return n ? __builtin_clzll(1) - __builtin_clzll(n) : -1; }
};
```

Sqrt Decomposition

```
template <class T, T merge(T,T)>
struct sqrt_decomp {
  int n,sq;
  vector<T> st,bl;
  sqrt_decomp(vector<T> & a){
    n = a.size(); st.resize(n);
    sq = sqrtl(n); bl.resize((n+sq-1)/sq);
    for (int i = 0; i < n; i++){
      st[i] = a[i];
      bl[i/sq] = ((i%sq == 0)?st[i]:merge(bl[i/sq],st[i]));
    }
  }
  void update(int pos, T val) {
    st[pos] = val;
    int block = pos/sq, lb = block*sq, rb = min(block*sq+sq-1,n-1);
    T vl;
    for (int i = lb; i <= rb; i++)
      vl = ((i == lb)?st[i]:merge(vl,st[i]));
    bl[block] = vl;
  }
  T query(int l, int r){
    T res; bool hasR = 0;
    for (int i = l/sq; i <= r/sq; i++){
      int lb = i*sq, rb = i*sq+sq-1;
      if (l <= lb && rb <= r){
        res = (hasR?merge(res,bl[i]):bl[i]), hasR = 1;
        continue;
      }
      for (int j = max(l,lb); j <= min(rb,r); j++)
        res = (hasR?merge(res,st[j]):st[j]), hasR = 1;
    }
    return res;
  }
};
```

Sqrt Decomposition (cont.)

Union Find

```
struct union_find {
  vector<int> e;
  union_find(int n) { e.assign(n, -1); }
  int findSet(int x) { return (e[x] < 0 ? x : e[x] = findSet(e[x])); }
  bool sameSet(int x, int y) { return findSet(x) == findSet(y); }
  int size(int x) { return -e[findSet(x)]; }
  bool unionSet(int x, int y) {
    x = findSet(x), y = findSet(y);
    if (x == y) return 0;
    if (e[x] > e[y]) swap(x, y);
    e[x] += e[y], e[y] = x;
    return 1;
  }
};
```

Matematicas

DiscreteRoot

```
// TESTED
#include "bin_pow.cpp"
#include "gcd.cpp"
#include "primitive_root.cpp"
#include "tot_euler.cpp"
vector<ll> DiscreteRoot(ll n, ll k, ll a) {
  if (a == 0) return {0};
  ll g = generator_(n);
  ll sq = (ll)sqrt(n) + 1;
  vector<pair<ll, ll>> dec(sq);
  for (ll i = 1; i <= sq; ++i)
    dec[i - 1] = {binpow(g, i * sq * k % (n - 1), n), i};
  sort(dec.begin(), dec.end());
  ll h0 = -1;
  for_(i, sq) {
    ll my = binpow(g, i * k % (n - 1), n) * a % n;
    auto it = lower_bound(dec.begin(), dec.end(), make_pair(my, 0));
    if (it != dec.end() && it->first == my) {
      h0 = it->second * sq - i;
      break;
    }
  }
  if (h0 == -1) return {-1};
  ll delta = (n - 1) / gcd(k, n - 1);
  vector<ll> x;
  for (ll h = h0 % delta; h < n - 1; h += delta) x.push_back(binpow(g, h, n));
  sort(x.begin(), x.end());
  return x;
}
```

InclusionExclusion

```
// Example cardinality of all subsets of size 1
ll cardinalitySubset(ll subset) { return 1; }
// Template
ll InclusionExclusion() {
  // sets
  ll n = 10;              // example
  ll subsets = (1 << n);  // total subsets
  ll ans = 0;
  // travel on all the subsets, with a particular subset
  for (ll subset = 0; subset < subsets; subset++) {
    // if is odd the subset we sum, otherwise substract, recall, Union of sets =
    // sum sets - intersect sets pairs + intersect group of three - ...
    ans += (__builtin_popcount(subset) & 1 ? cardinalitySubset(subset)
                                           : -cardinalitySubset(subset));
  }
  return ans;
}
```

SimpsonRule

```
// TESTED
ld f(ld x) { return x; }
ld simpson_integration(ld a, ld b, ld d) {
  const ll N = 10000;  // number of steps (already multipli
```

SimpsonRule (cont.)

```
ed by 2)
  ld h = (b - a) / N;
  ld s = f(a) + f(b);            // a = x_0 and b = x_2n
  for (ll i = 1; i < N; i++) {  // Refer to final Simpson's formula
    double xi = a + h * i;
    s += f(xi) * ((i & 1) ? 4 : 2);
  }
  s *= h / 3.0;
  // 1e6 is the decimal precision, if you want 7, the 1e7 and so on
  s *= 1e6;
  s = llround(s);
  s /= 1e6;
  // to print use cout << fixed << setprecision(6) << s;
  return s;
}
```

TonelliShanks

```
// TESTED
#include "bin_pow.cpp"
ll TonelliShanks(ll n, ll p) {
  n %= p;
  if (n < 0) n += p;
  if (n == 0) return 0;
  if (binpow(n, (p - 1) / 2, p) != 1) return -1;  // solution does not exist
  if (p % 4 == 3)
    return binpow(n, (p + 1) / 4, p);  // trivial solution, only one factor 2
  ll c = p - 1, z = 2;
  ll s = 0;
  while (c % 2 == 0) ++s, c /= 2;
  // find a non-square mod p
  while (binpow(z, (p - 1) / 2, p) != p - 1) ++z;
  ll q = binpow(z, c, p);            // generator subgroup, |<q>| = 2^s
  ll a = binpow(n, (c + 1) / 2, p);  // candidate root
  ll t =
      binpow(n, c, p);  // error from equation a^2 = n*t, if t=1, a is the root
  ll m = s;
  while (1) {
    ll i = 0, temp = t;
    while (i < m && temp != 1) {
      temp = (temp * temp) % p;
      i++;
    }
    if (i == 0) return a;
    ll exponent = 1ll << (m - i - 1);
    ll b = binpow(q, exponent, p);
    a = (a * b) % p;
    t = (((t * b) % p) * b) % p;
    q = (b * b) % p;
    m = i;
  }
}
```

Ztransform

```
// TESTED for gcd
// only if it is neccesary, but Z transform work on any module, and without
ll mod = 998244353;
void Z(vector<ll>& C, ll N, bool g) {
  if (g) {
    for (ll d = 1; d <= N; d++) {
      for (ll m = 2 * d; m <= N; m += d) C[d] = (C[d] + C[m]) % mod;
    }
  } else {
    for (ll d = N; d > 0; d--) {
      for (ll m = 2 * d; m <= N; m += d) C[m] = (C[d] + C[m]) % mod;
    }
  }
}
void Zinv(vector<ll>& C, ll N, bool g) {
  if (g) {
    for (ll d = N; d > 0; d--) {
      for (ll m = 2 * d; m <= N; m += d)
        C[d] = (mod + (C[d] - C[m]) % mod) % mod;
    }
  } else {
    for (ll d = 1; d <= N; d++) {
      for (ll m = 2 * d; m <= N; m += d)
        C[m] = (mod + (C[m] - C[d]) % mod) % mod;
    }
  }
}
vector<ll> conv(vector<ll> A, vector<ll> B, bool g) {
  ll N = A.size() - 1ll;
  Z(A, N, g);
  Z(B, N, g);
  vector<ll> C(N + 1ll);
  for (ll i = 1; i <= N; i++) C[i] = (A[i] * B[i]) % mod;
  Zinv(C, N, g);
  return C;
}
```

Ztransform (cont.)

```
  Z(B, N, g);
  vector<ll> C(N + 1ll);
  for (ll i = 1; i <= N; i++) C[i] = (A[i] * B[i]) % mod;
  Zinv(C, N, g);
  return C;
}
```

Bin Pow

```
ll binpow(ll a, ll b, ll m) {
  ll ans = 1;
  while (b > 0) {
    if (b & 1) ans = (ans * a) % m;
    a = (a * a) % m;
    b >>= 1;
  }
  return ans;
}
```

CatalanNumbers

```
// n-catalan number = (2n)!/((n+1)!n!)
ll getNCatalanNumber(ll n) {
  double ans = 1;
  for (ll k = 2; k <= n; k++) ans *= (n + k) / k;
  return (ll)(ans + 0.001);
}
// TESTED
vector<ll> getCatalanNumbers(ll n) {
  vector<ll> C(n + 1, 0);
  C[0] = C[1] = 1;
  C[2] = 2;
  for (ll i = 3; i <= n; ++i) {
    for (ll j = 0; j < i; ++j) C[i] += C[j] * C[i - j - 1];
  }
  return C;
}
```

Convex Hull

```
// TESTED
// Monotic Change
struct point {
  double x, y;
};
ll orientation(const point& a, const point& b, const point& c) {
  double sign = a.x * (b.y - c.y) - b.x * (a.y - c.y) + c.x * (a.y - b.y);
  if (sign > 0)
    return 1;
  else if (sign < 0)
    return -1;
  else
    return 0;
}
bool cw(const point& a, const point& b, const point& c,
        const bool& include_colider) {
  ll o = orientation(a, b, c);
  return (o > 0 || include_colider && 0 == 0);
}
bool ccw(const point& a, const point& b, const point& c,
         const bool& include_colider) {
  ll o = orientation(a, b, c);
  return (o < 0 || include_colider && o == 0);
}
void convex_hull(vector<point>& a, bool include_colider) {
  if (a.size() == 1) return;
  sort(a.begin(), a.end(), [](const point& p1, const point& p2) {
    return (p1.x == p2.x ? p1.y < p2.y : p1.x < p2.x);
  });
  point A = a[0], B = a[a.size() - 1];
  vector<point> upper, lower;
  upper.push_back(A);
  lower.push_back(A);
  for (ll i = 1; i < a.size(); ++i) {
    if (i == a.size() - 1 || cw(A, a[i], B, include_colider)) {
      while (upper.size() >= 2 &&
             !(cw(upper[upper.size() - 2], upper[upper.size() - 1], a[i],
                  include_colider)))
        upper.pop_back();
      upper.push_back(a[i]);
    }
    if (i == a.size() - 1 || ccw(A, a[i], B, include_colider)) {
      while (lower.size() >= 2 &&
             !(ccw(lower[lower.size() - 2], lower[lower.size() - 1], a[i],
                   include_colider)))
        lower.pop_back();
      lower.push_back(a[i]);
```

Convex Hull (cont.)

```
    }
  }
  if (include_colider && upper.size() == a.size()) {
    reverse(a.begin(), a.end());
    return;
  }
  a.clear();
  for (ll i = 0; i < upper.size(); ++i) a.push_back(upper[i]);
  for (ll i = lower.size() - 2; i >= 1; --i) a.push_back(lower[i]);
}
```

Crt

```
// TESTED (PD: for 2x2 system but should work for any nXn)
#include "gcdExtended.cpp"
ll mod_inv(ll a, ll m) {
  ll x, y;
  ll g = gcdExtended(a, m, x, y);
  x = (x % m + m) % m;
  return x;
}
struct Congruence {
  ll b, n;
};
ll chinese_remainder_theorem(vector<Congruence> const& congruences) {
  ll N = 1;
  for (auto const& congruence : congruences) N *= congruence.n;
  ll x = 0;
  for (auto const& congruence : congruences) {
    ll b_i = congruence.b;
    ll N_i = N / congruence.n;
    ll invN_i = mod_inv(N_i, congruence.n);
    i128 aux = (b_i * N_i) % N;
    aux = (aux * invN_i) % N;
    x = (ll)(x + aux) % N;
  }
  return x;
}
```

Discrete Log

```
// Tested
ll discrete_log(ll a, ll b, ll m) {
  a %= m, b %= m;
  if (a == 0) return b == 0 ? 1 : -1;
  ll k = 1, add = 0, g;
  while ((g = gcd(a, m)) > 1) {
    if (b == k) return add;
    if (b % g) return -1;
    b /= g, m /= g, ++add;
    k = (k * 1ll * a / g) % m;
  }
  ll n = sqrt(m) + 1;
  ll an = 1;
  for_(i, n) an = (an * 1ll * a) % m;
  unordered_map<ll, ll> f2inv;
  for (ll q = 0, f2 = b; q <= n; ++q) {
    f2inv[f2] = q;
    f2 = (f2 * 1ll * a) % m;
  }
  for (ll p = 1, f1 = k; p <= n; ++p) {
    f1 = (f1 * 1ll * an) % m;
    if (f2inv.count(f1)) {
      ll x = n * p - f2inv[f1] + add;
      return x;
    }
  }
  return -1;
}
```

Erathostenes-sieve

```
// Tested
vector<bool> erathostenesSieve(ll n) {
  vector<bool> isprime(n + 1, true);
  vector<ll> primes;
  isprime[0] = isprime[1] = false;
  for (ll i = 2; i <= n; (i == 2 ? i++ : i += 2)) {
    if (isprime[i]) {
      for (ll j = i * i; j <= n; j += i) isprime[j] = false;
      primes.push_back(i);
    }
  }
  return isprime;
}
```

Factorization Pollard Rho

```
// TESTED up to 1e18, run T(n) < 1e8
ll mult(ll a, ll b, ll m) { return (__int128)a * b % m; }
ll f(ll x, ll c, ll m) { return (mult(x, x, m) + c) % m; }
#include "gcd.cpp"
ll rho(ll n, ll x0 = 2, ll c = 1) {
  ll x = x0;
  ll y = x0;
  ll g = 1;
  while (g == 1) {
    x = f(x, c, n);
    y = f(y, c, n);
    y = f(y, c, n);
    g = gcd(abs(x - y), n);
  }
  return g;
}
// algorithm for the factorization
ll brent(ll n, ll x0 = 2, ll c = 1) {
  ll x = x0;
  ll g = 1;
  ll xs, y;
  ll m = 128;
  ll l = 1;
  ll iter = 0;
  while (g == 1 && iter < 1000) {
    y = x;
    ll q = 1;
    for (ll i = 1; i < l; i++) x = f(x, c, n);
    ll k = 0;
    while (k < l && g == 1) {
      xs = x;
      for (ll i = 0; i < m && i < l - k; i++) {
        x = f(x, c, n);
        q = mult(q, abs(y - x), n);
      }
      g = gcd(q, n);
      k += m;
    }
    l *= 2;
    iter++;
  }
  if (g == n) {
    return n;
  }
  return g;
}
#include "miller_rabin.cpp"
// algorithm to prime factorization
void factorize(ll n, map<ll, ll>& factors) {
  if (n == 1) return;
  if (deterministicMillerRabin(n)) {
    factors[n]++;
    return;
  }
  ll d1, d2, iter = 0;
  while (iter < 1000) {
    uniform_int_distribution<ll> dist(1, n - 1);
    ll c = dist(rng);
    ll x0 = dist(rng);
    d1 = brent(n, x0, c), d2 = n / d1;
    if (d1 > 1 && d1 < n) break;
    iter++;
  }
  if (d1 == 1 || d2 == 1) {
    factors[n]++;
    return;
  }
  factorize(d1, factors);
  factorize(d2, factors);
}
```

Fft

```
// Tested
void fft_bottom_up(vector<cd>& c, bool inverse) {
  ll N = 1;
  while (N < c.size()) N <<= 1;
  c.resize(N);
  if (N <= 1) return;
  ll cnt = 0;
  for (ll j = 1; j < N; ++j) {
    ll bit = N >> 1;
    while (cnt & bit) {
      cnt ^= bit;
      bit >>= 1;
    }
    cnt ^= bit;
    if (cnt < j) swap(c[cnt], c[j]);
  }
  // n is the length of the current block of the tree, thanks to bit reversal is
  // in order, n=2 -> depth= D-1, n=4 -> depth=D-2, and so on...
  for (ll n = 2; n <= N; n <<= 1) {
    double ang = 2 * PI / n * (inverse ? -1 : 1);
```

Fft (cont.)

```
    cd wn(cos(ang), sin(ang));
    // iterate each block(node from the current depth)
    for (ll currblock = 0; currblock < N; currblock += n) {
      cd w(1);
      // iterate the node of the current block, only recove
r a half, because
      // butterfly effect(como se diga la wea).
      for (ll curr = 0; curr < n / 2; ++curr) {
        cd u = c[currblock + curr], v = c[currblock + curr
+ n / 2] * w;
        c[currblock + curr] = u + v;
        c[currblock + curr + n / 2] = u - v;
        w *= wn;
      }
    }
  }
  if (inverse) {
    for (cd& x : c) x /= N;
  }
}
vector<cd> conv(vector<cd> c1, vector<cd> c2) {
  vector<cd> ans;
  ll N = 1;
  while (N < (c1.size() + c2.size() - 1ll)) N <<= 1;
  c1.resize(N);
  c2.resize(N);
  fft_bottom_up(c1, false);
  fft_bottom_up(c2, false);
  ans.resize(N);
  for_(i, N) ans[i] = c1[i] * c2[i];
  fft_bottom_up(ans, true);
  return ans;
}
```

Gaussian Elimination

```
// Tested
bool gauss_jordan(vector<vector<ll>> A, vector<ll>& x) {
  ll n = A.size(), m = A[0].size() - 1;
  vector<ll> where(m, -1);
  for (ll col = 0, row = 0; col < m && row < n; ++col) {
    ll pivot = row;
    for (ll i = row; i < n; ++i) {
      if (abs(A[i][col]) > abs(A[pivot][col])) pivot = i;
    }
    if (!A[pivot][col]) continue;
    for (ll i = col; i <= m; ++i) swap(A[pivot][i], A[row][
i]);
    where[col] = row;
    for (ll i = 0; i < n; ++i) {
      ll invm = binpow(A[row][col], MOD - 2, MOD);
      if (i != row) {
        ll c = (A[i][col] * invm) % MOD;
        for (ll j = col; j <= m; ++j)
          A[i][j] = ((A[i][j] - A[row][j] * c) % MOD + MOD)
 % MOD;
      }
    }
    ++row;
  }
  x.assign(m, 0);
  for (ll i = 0; i < m; ++i) {
    if (where[i] != -1) {
      ll invm = binpow(A[where[i]][i], MOD - 2, MOD);
      x[i] = (A[where[i]][m] * invm) % MOD;
    }
  }
  for (ll i = 0; i < n; ++i) {
    ll sum = 0;
    for (ll j = 0; j < m; ++j) sum += (x[j] * A[i][j]) % MO
D;
    if (abs(sum - A[i][m]) > 0) return false;  // No soluti
on
  }
  return true;  // Valid solution, trivial or infinity
```

Gcd

```
// Tested
ll gcd(ll a, ll b) {
  if (b == 0) return a;
  return gcd(b, a % b);
}
ll gcd(ll a, ll b) {
  while (b) {
    ll r = a % b;
    a = b;
    b = r;
  }
  return a;
}
```

GcdExtended

```
// Tested
ll gcdExtended(ll a, ll b, ll& x, ll& y) {
  if (b == 0) {
    x = 1;
    y = 0;
    return a;
  }
  ll x_, y_, gcd = gcdExtended(b, a % b, x_, y_);
  x = y_;
  y = x_ - y_ * (a / b);
  return gcd;
}
```

Miller Rabin

```
// Tested
ll binpow(ll a, ll b, ll mod) {
  ll ans = 1;
  while (b > 0) {
    if (b & 1) ans = (u128)(ans)*a % mod;
    a = (u128)a * a % mod;
    b >>= 1;
  }
  return ans;
}
bool checkComposite(ll p, ll a, ll s, ll q) {
  ll x = binpow(a, q, p);
  if (x == 1 || x == p - 1) return false;
  for (ll i = 1; i < s; ++i) {
    x = (u128)x * x % p;
    if (x == p - 1) return false;
  }
  return true;
}
bool millerRabin(ll p, ll maxIter = 5) {
  if (p < 4) return p == 2 || p == 3;
  ll s = 0, q = p - 1;
  while (!(q & 1)) {
    s++;
    q >>= 1;
  }
  for (ll i = 0; i < maxIter; ++i) {
    ll a = 2 + rand() % (p - 3);
    if (checkComposite(p, a, s, q)) return false;
  }
  return true;
}
bool deterministicMillerRabin(ll p) {
  if (p < 4) return p == 2 || p == 3;
  ll s = 0, q = p - 1;
  while (!(q & 1)) {
    s++;
    q >>= 1;
  }
  for (ll a : {2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37})
 {
    if (p == a) return true;
    if (checkComposite(p, a, s, q)) return false;
  }
  return true;
}
```

Mobius

```
// Tested
vector<ll> mobius(ll n) {
  vector<ll> mob(n + 1, 1);
  mob[1] = 1;
  vector<bool> isprime(n + 1, true);
  isprime[0] = isprime[1] = false;
  for (ll i = 2; i < n + 1; i++) {
    if (isprime[i]) {
      for (ll j = i; j < n + 1; j += i) {
        mob[j] *= -1;
        isprime[j] = false;
      }
      for (ll j = i * i; j < n + 1; j += i * i) mob[j] = 0;
    }
  }
  return mob;
}
```

Ntt

```
// TESTED
const ll mod = 998244353, generator = 3, rootn = 3; // for
N max = 2^23
/*more modelus primes of the form p = c*2^m + 1 (generators
 calculated with algorithm in math section):
const ll mod = 7340033, generator = 3, rootn = 3; // for N
max = 2^20
const ll mod = 167772161, generator = 3, rootn = 3; // for
N max = 2^25
const ll mod = 469762049, generator = 3, rootn = 3; // for
```

Ntt (cont.)

```
N max = 2^26
*/
#include "bin_pow.cpp"
ll inv(ll a) { return binpow(a, mod - 2); }
void ntt(vector<ll>& c, bool invert) {
  ll N = 1;
  while (N < c.size()) N <<= 1;
  c.resize(N);
  ll cnt = 0;
  for (ll j = 1; j < N; ++j) {
    ll bit = N >> 1;
    while (bit & cnt) {
      cnt ^= bit;
      bit >>= 1;
    }
    cnt ^= bit;
    if (cnt < j) swap(c[cnt], c[j]);
  }
  for (ll n = 2; n <= N; n <<= 1) {
    ll wn = binpow(rootn, (mod - 1) / n);
    if (invert) wn = inv(wn);
    for (ll currblock = 0; currblock < N; currblock += n) {
      ll w = 1;
      for (ll i = 0; i < n / 2; ++i) {
        ll u = c[currblock + i] % mod, v = (w * c[currblock
 + i + n / 2]) % mod;
        c[currblock + i] = (u + v) % mod;
        c[currblock + i + n / 2] = ((u - v) % mod + mod) %
mod;
        w = (w * wn) % mod;
      }
    }
  }
  if (invert) {
    for (ll& x : c) x = (x * inv(N)) % mod;
  }
}
vector<ll> conv(vector<ll> c1, vector<ll> c2) {
  ll N = 1;
  while (N <= (c1.size() + c2.size() - 1ll)) N <<= 1;
  c1.resize(N);
  c2.resize(N);
  ntt(c1, false);
  ntt(c2, false);
  vector<ll> ans(N, 0);
  for_(i, N) ans[i] = (c1[i] * c2[i]) % mod;
  ntt(ans, true);
  return ans;
}
```

Primitive Root

```
// TESTED
#include "bin_pow.cpp"
#include "tot_euler.cpp"
ll generator_(ll n) {
  vector<int> facts;
  ll phi_n = tot_euler(n), m = phi_n;
  for (ll i = 2; i * i <= m; ++i) {
    if (m % i == 0) {
      facts.push_back(i);
      while (m % i == 0) m /= i;
    }
  }
  if (m > 1) facts.push_back(m);
  for (ll g = 2; g <= n; ++g) {
    bool ok = true;
    for (size_t i = 0; i < facts.size() && ok; ++i)
      ok &= binpow(g, phi_n / facts[i], n) != 1;
    if (ok) return g;
  }
  return -1;
}
```

Template

```
#include <bits/stdc++.h>
using namespace std;
#define ll long long
#define ld long double
#define for_(i, n) for (ll i = 0; i < n; ++i)
#define ull unsigned long long
#define INF LLONG_MAX
#define NINF LLONG_MIN
#define i128 __int128
#define u128 __uint128_t
#define cd complex<ld>
const double PI = 3.14159265358979323846264338327950288419
169399375105;
const double EPS = 1e-18;
```

Tot Euler

```
// Tested
// sieve
vector<ll> tot_euler(ll n) {
  vector<ll> tot(n + 1, 0);
  for_(i, n + 1) tot[i] = i;
  for (ll i = 2; i <= n; ++i) {
    if (tot[i] == i) {
      for (ll j = i; j <= n; j += i) tot[j] -= tot[j] / i;
    }
  }
  return tot;
}
// for a simply n
ll tot_euler(ll n) {
  ll n_ = n, tot = n;
  for (ll i = 2; i * i <= n; i++) {
    if (n_ % i == 0) {
      tot -= tot / i;
      while (n_ % i == 0) n_ /= i;
    }
  }
  if (n_ > 1) tot -= tot / n_;
  return tot;
}
```

Strings

Aho-corasick

```
#define sz(x) ((int)(x).size())
#define rep(i, a, b) for (int i = (a); i < (b); ++i)
typedef vector<int> vi;
struct AhoCorasick {
  enum { alpha = 26, first = 'a' };  // change this!
  struct Node {
    // (nmatches is optional)
    int back, next[alpha], start = -1, end = -1, nmatches =
 0;
    Node(int v) { memset(next, v, sizeof(next)); }
  };
  vector<Node> N;
  vi backp;
  void insert(string& s, int j) {
    assert(!s.empty());
    int n = 0;
    for (char c : s) {
      int& m = N[n].next[c - first];
      if (m == -1) {
        n = m = sz(N);
        N.emplace_back(-1);
      } else
        n = m;
    }
    if (N[n].end == -1) N[n].start = j;
    backp.push_back(N[n].end);
    N[n].end = j;
    N[n].nmatches++;
  }
  AhoCorasick(vector<string>& pat) : N(1, -1) {
    rep(i, 0, sz(pat)) insert(pat[i], i);
    N[0].back = sz(N);
    N.emplace_back(0);

    queue<int> q;
    for (q.push(0); !q.empty(); q.pop()) {
      int n = q.front(), prev = N[n].back;
      rep(i, 0, alpha) {
        int &ed = N[n].next[i], y = N[prev].next[i];
        if (ed == -1)
          ed = y;
        else {
          N[ed].back = y;
          if (N[ed].end == -1) {
            N[ed].end = N[y].end;
          } else {
            backp[N[ed].start] = N[y].end;
          }
          N[ed].nmatches += N[y].nmatches;
          q.push(ed);
        }
      }
    }
  }
  vi find(string word) {
    int n = 0;
    vi res;  // ll count = 0;
    for (char c : word) {
      n = N[n].next[c - first];
      res.push_back(N[n].end);
      // count += N[n].nmatches;
    }
    return res;
  }
  vector<vi> findAll(vector<string>& pat, string word) {
```

Aho-corasick (cont.)

```
    vi r = find(word);
    vector<vi> res(sz(word));
    rep(i, 0, sz(word)) {
      int ind = r[i];
      while (ind != -1) {
        res[i - sz(pat[ind]) + 1].push_back(ind);
        ind = backp[ind];
      }
    }
    return res;
  }
};
```

Booth

```
int Booth(string s) {
  s += s;
  vector<int> t(s.size(), -1);
  int ans = 0;
  int n = s.size();
  for (int i = 1; i < n; i++) {
    char c = s[i];
    int j = t[i - ans - 1];
    while (j != -1 && c != s[ans + j + 1]) {
      if (c < s[ans + j + 1]) {
        ans = i - j - 1;
      }
      j = t[j];
    }
    if (c != s[ans + 1 + j]) {
      if (c < s[ans]) {
        ans = i;
      }
      t[i - ans] = -1;
    } else {
      t[i - ans] = j + 1;
    }
  }
  return ans;
}
```

Kmp

```
struct KMP {
  vector<int> lps;
  string s;
  KMP(string s) : s(s) {
    int n = s.size();
    lps.assign(n, 0);
    int len = 0, i = 1;
    while (i < n) {
      if (s[i] == s[len]) {
        lps[i++] = ++len;
      } else {
        if (len != 0)
          len = lps[len - 1];
        else
          lps[i++] = 0;
      }
    }
  }
};
```

Manacher

```
vector<int> manacher_odd(string s) {
  int n = s.size();
  s = "$" + s + "^";
  vector<int> p(n + 2);
  int l = 0, r = 1;
  for (int i = 1; i <= n; i++) {
    if (i <= r) {
      p[i] = min(r - i, p[l + (r - i)]);
    }
    while (s[i - p[i]] == s[i + p[i]]) {
      p[i]++;
    }
    if (i + p[i] > r) {
      l = i - p[i], r = i + p[i];
    }
  }
  return vector<int>(begin(p) + 1, end(p) - 1);
}

vector<int> manacher(string s) {
  string t;
  for (auto c : s) {
    t += string("#") + c;
  }
  auto res = manacher_odd(t + "#");
  /*
  int ans_largo = v[i]-1;
  if(i%2 == 0){
      int indice = i/2;
      int l = indice - (ans_largo/2);
      int r = indice + (ans_largo/2);
  } else {
      int indice = (i+1)/2;
      int l = indice - (ans_largo/2);
      int r = indice + (ans_largo/2)-1;
  }
  palindromo -> s[l , r] <-- r incluido
  */
  return vector<int>(begin(res) + 1, end(res) - 1);
}
```

Manacher (cont.)

RollingHashing

```
template <class T>
struct rolling_hashing {
  int base, mod;
  vector<long long> p, H;
  int n;
  rolling_hashing(const T& s, int b, int m) : base(b), mod(m), n(s.size()) {
    p.assign(n + 1, 1);
    H.assign(n + 1, 0);
    for (int i = 0; i < n; ++i) {
      H[i + 1] = (H[i] * base + s[i]) % mod;
      p[i + 1] = (p[i] * base) % mod;
    }
  }
  int get(int l, int r) {
    int res = (H[r + 1] - H[l] * p[r - l + 1]) % mod;
    if (res < 0) res += mod;
    return res;
  }
};
```

Suffix Array

```
struct SA {
  int n;
  vector<int> C, R, R_, sa, sa_, lcp;
  inline int gr(int i) { return i < n ? R[i] : 0; }
  void csort(int maxv, int k) {
    C.assign(maxv + 1, 0);
    for (int i = 0; i < n; i++) C[gr(i + k)]++;
    for (int i = 1; i < maxv + 1; i++) C[i] += C[i - 1];
    for (int i = n - 1; i >= 0; i--) sa_[--C[gr(sa[i] + k)]] = sa[i];
    sa.swap(sa_);
  }
  void getSA(vector<int>& s) {
    R = R_ = sa = sa_ = vector<int>(n);
    for (ll i = 0; i < n; i++) sa[i] = i;
    sort(sa.begin(), sa.end(), [&s](int i, int j) { return s[i] < s[j]; });
    int r = R[sa[0]] = 1;
    for (ll i = 1; i < n; i++) R[sa[i]] = (s[sa[i]] != s[sa[i - 1]]) ? ++r : r;
    for (int h = 1; h < n && r < n; h <<= 1) {
      csort(r, h);
      csort(r, 0);
      r = R_[sa[0]] = 1;
      for (int i = 1; i < n; i++) {
        if (R[sa[i]] != R[sa[i - 1]] || gr(sa[i] + h) != gr(sa[i - 1] + h)) r++;
        R_[sa[i]] = r;
      }
      R.swap(R_);
    }
  }
  void getLCP(vector<int>& s) {
    lcp.assign(n, 0);
    int k = 0;
    for (ll i = 0; i < n; i++) {
      int r = R[i] - 1;
      if (r == n - 1) {
        k = 0;
        continue;
      }
      int j = sa[r + 1];
      while (i + k < n && j + k < n && s[i + k] == s[j + k]) k++;
      lcp[r] = k;
      if (k) k--;
    }
  }
  SA(vector<int>& s) {
    n = s.size();
    getSA(s);
    getLCP(s);
  }
};
```

Trie

```
struct trie {
  vector<vector<ll>> tree;
  vector<ll> counts;
  trie() {
    tree.push_back(vector<ll>(26, -1));
    counts.push_back(0);
  };
  void insert(string& s) {
    ll i = 0, u = 0;
    while (i < s.size()) {
      char c = s[i];
      if (tree[u][c - 'a'] == -1) {
        ll pos = tree.size();
        tree.push_back(vector<ll>(26, -1));
        counts.push_back(0);
        tree[u][c - 'a'] = pos;
      }
      i++;
      u = tree[u][c - 'a'];
    }
    counts[u]++;  // count final character
  }
  ll search(string& s) {
    ll i = 0, u = 0;
    ll count_ends = 0;
    while (i < s.size()) {
      char c = s[i];
      if (tree[u][c - 'a'] != -1) {
        // If you need to know how many trailing characters
 it goes through,
        // uncomment. count_ends += counts[u];
        u = tree[u][c - 'a'];
        i++;
      } else
        break;
    }
    if (i == s.size()) count_ends += counts[u];
    return count_ends;
  }
};
```

Zfunction

```
struct Z {
  string s;
  vector<int> z;
  ll n;
  Z(string s) : s(s) {
    n = s.size();
    z.assign(n, 0);
    int l = 0, r = 0;
    for (int i = 1; i < n; i++) {
      if (i < r) {
        z[i] = min(r - i, z[i - l]);
      }
      while (i + z[i] < n && s[z[i]] == s[i + z[i]]) {
        z[i]++;
      }
      if (i + z[i] > r) {
        l = i;
        r = i + z[i];
      }
    }
  }
};
```

Programacion Dinamica

Knappsack

```
void solve() {
  ll n, w;
  cin >> n >> w;
  vector<pair<ll, ll>> v(n);
  for (auto& [a, b] : v) cin >> a >> b;
  vector<ll> ans(w + 2, 0);
  ll ans_ = 0;
  for (auto [vi, wi] : v) {
    for (ll j = w; j >= wi; j--) {
      ans[j] = max(ans[j], ans[j - wi] + vi);
      ans_ = max(ans_, ans[j]);
    }
  }
  cout << ans_ << endl;
}
```

Lis

```
template <class I>
vector<int> LIS(const vector<I>& S) {
  if (S.empty()) return {};
  vector<int> prev(S.size());
  vector<pair<I, int>> res;
  for (int i = 0; i < S.size(); i++) {
    auto it = lower_bound(res.begin(), res.end(), pair<I, i
nt>{S[i], i});
    if (it == res.end()) res.emplace_back(), it = res.end()
 - 1;
    *it = {S[i], i};
    prev[i] = (it == res.begin() ? 0 : (it - 1)->second);
  }
  int L = res.size(), cur = res.back().second;
  vector<int> ans(L);
  while (L--) ans[L] = cur, cur = prev[cur];
  /* Recover the sequence
  for (int i = 0; i+1 < ans.size(); i++)
    ans[i] = S[ans[i]];
  */
  return ans;
}
```

Lis (cont.)

```
    auto it = lower_bound(res.begin(), res.end(), pair<I, i
nt>{S[i], i});
    if (it == res.end()) res.emplace_back(), it = res.end()
 - 1;
    *it = {S[i], i};
    prev[i] = (it == res.begin() ? 0 : (it - 1)->second);
  }
  int L = res.size(), cur = res.back().second;
  vector<int> ans(L);
  while (L--) ans[L] = cur, cur = prev[cur];
  /* Recover the sequence
  for (int i = 0; i+1 < ans.size(); i++)
    ans[i] = S[ans[i]];
  */
  return ans;
}
```

Lis Length K

```
vector<fenwick_tree> bit(k + 1, fenwick_tree(m));

ll answer = 0;
for (ll x : v) {
  ll value = compress(x);  // or already compressed
  vector<ll> current(k + 1);
  current[1] = 1;
  for (ll len = 2; len <= k; len++) {
    current[len] = bit[len - 1].sum(value - 1);
  }
  for (ll len = 1; len <= k; len++) {
    bit[len].add(value, current[len]);
  }
  answer += current[k];
}
cout << answer << endl;
```

Offline Algorithms

Cdq

```
void cdq(ll l, ll r, vector<pt> &v)
{
    if (r - l <= 1) return;
    ll m = (l+r)/2;
    cdq(l, m, v);
    cdq(m, r, v);
    vector<pt> tmp;
    ll a = l, b = m;
    while (a < m && b < r) {
        if (v[a].y < v[b].y) {
            st.add(v[a].z, 1);
            tmp.push_back(v[a++]);
        } else {
            ans[v[b].id] += st.sum(v[b].z-1);
            tmp.push_back(v[b++]);
        }
    }
    ll record = a;
    while (a < m) tmp.push_back(v[a++]);
    while (b < r) {
        ans[v[b].id] += st.sum(v[b].z-1);
        tmp.push_back(v[b++]);
    }
    for (ll i = l; i < record; i++) st.add(v[i].z, -1);
    for (ll i = l; i < r; i++) v[i] = tmp[i-l];
}
/*
sort(v, v + n, [](const pt &a, const pt &b) {
    if (a.x != b.x) return a.x < b.x;
    if (a.y != b.y) return a.y > b.y; // Opposite of merge
condition!
    return a.z > b.z;
});
*/
```

Mo

```
struct query {
  ll l, r, i;
};
template<class T, typename U, class T2>
struct mo_algorithm {
  vector<U> ans;
  template<typename... Args>
  mo_algorithm(vector<T> &v, vector<query> &queries, Args..
. args) {
    T2 ds(args...);
    ll block_sz = sqrtl(v.size());
    ans.assign(queries.size(), -1);
    sort(queries.begin(), queries.end(), [&](auto &a, auto
&b) {
      return a.l/block_sz != b.l/block_sz ? a.l/block_sz <
b.l/block_sz : a.r < b.r;
    });
```

Mo (cont.)

```
    ll l = 0, r = -1;
    for (query q : queries) {
      while (l > q.l) ds.add(v[--l]);
      while (r < q.r) ds.add(v[++r]);
      while (l < q.l) ds.remove(v[l++]);
      while (r > q.r) ds.remove(v[r--]);
      ans[q.i] = ds.answer(q);
    }
  }
};
```

Pbs

```
vector<ll>l(q, 0), r(q, m+1);
while(1) {
    vector<vector<ll>> bucket(m+1);
    bool flag = 0;
    for (ll i = 0; i < q; i++) {
        if (r[i] - l[i] <= 1) continue;
        flag = 1;
        bucket[(l[i]+r[i])>>1] = i;
    }
    if (!flag) break;
    //RESET DATA STRUCTURE

    //SWEEP THROUGH POSIBLE ANSWERS POSITIONS
    for (ll i = 1; i<=m; i++) {
        update(i);

        for (auto j: bucket[i]) {
            if (foo(j)) r[j] = i;
            else l[j] = i;
        }
    }
}
```

Value Driven

```
struct event {
    ll l, r, x; //For update value, for query threshold
    ll id, q;   //query type 0 update
};
vector<ll> ans;
void value_driven(ll l, ll r, vector<event>& v)
{
    if (v.empty()) return;
    if (r - l <= 1) {
        //COUNTING -> return;
        for (auto &i: v) {
            if (i.q == 1) ans[i.id] = l;
        }
        return;
    }
    ll m = (l+r)>>1;
    vector<event> vl, vr;
    for (auto &i: v) {
        if (i.q == 0) {
            if (i.x >= m) {
                //UPDATE
                //st.add(i.l, 1);
                vr.push_back(i);
            } else {
                vl.push_back(i);
            }
        } else {
            //ll cnt = query;
            //ll cnt = st.sum(i.l, i.r);
            if (cnt >= i.x) {
                vr.push_back(i);
            } else {
                //COUNTING -> ans[i.id] += cnt; push_back(i);

                event ni = i;
                ni.x-=cnt;
                vl.push_back(ni);
            }
        }
    }
    //ROLLBACK
    //for (auto &i: v) {
    //    if (i.q == 0 && i.x >= m) {
    //        st.add(i.l, -1);
    //    }
    //}
    value_driven(l, m, vl);
    value_driven(m, r, vr);
}
```

Miscelaneo

Busqueda Binaria

```
int bs(vector<ll>& v, int b) {
  int l = 0, r = v.size();
```

Busqueda Binaria (cont.)

```
  while (l < r) {
    int mid = (l + r) / 2;
    if (v[mid] >= b)
      r = mid;
    else
      l = mid + 1;
  }
  return l;
}
```

Random

```
mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());
mt19937_64 rng64(chrono::steady_clock::now().time_since_epoch().count());

// Número aleatorio entero [a, b]
int random(int a, int b) {
    return uniform_int_distribution<int>(a, b)(rng);
}
// Número aleatorio long long [a, b]
ll random(ll a, ll b) {
    return uniform_int_distribution<ll>(a, b)(rng64);
}
// shuffle a un vector v
shuffle(v.begin(), v.end(), rng);

```

Time

```
using Clock = chrono::steady_clock;
using TimePoint = Clock::time_point;
// Obtener instante actual
TimePoint getTime() { return Clock::now(); }

// Diferencia en segundos
double elapsedSeconds(TimePoint start) {
  return chrono::duration<double>(Clock::now() - start).count();
}

// Diferencia en milisegundos
ll elapsedMilliseconds(TimePoint start) {
  return chrono::duration_cast<chrono::milliseconds>(Clock::now() - start)
      .count();
}

// Diferencia en microsegundos
ll elapsedMicroseconds(TimePoint start) {
  return chrono::duration_cast<chrono::microseconds>(Clock::now() - start)
      .count();
}

// Diferencia en nanosegundos
ll elapsedNanoseconds(TimePoint start) {
  return chrono::duration_cast<chrono::nanoseconds>(Clock::now() - start)
      s.count();
}

// Dormir durante cierta cantidad de tiempo
void sleepSeconds(int s) { this_thread::sleep_for(chrono::seconds(s)); }

void sleepMilliseconds(int ms) {
  this_thread::sleep_for(chrono::milliseconds(ms));
}
```