Bookhand CHAKOTEAM!

CHAKOTEAM! — UTFSM

Última actualización: October 20, 2026

Contents

1 Template Base **1**

2 Grafos **1**
- 2.1 Dijkstra – $O((V+E)\log V)$ . . . 1
- 2.2 Floyd-Warshall – $O(V^3)$ . . . 2
- 2.3 Bellman-Ford – $O(VE)$ . . . 2
- 2.4 Kruskal – $O(E \log E)$ . . . 2
- 2.5 LCA – $O(V \log V)$ build, $O(\log V)$ query . . . 2
- 2.6 Union-Find / DSU – $O(\alpha(n))$ . . . 2
- 2.7 Dominator Tree – $O((|E|+|V|)\log(|V|))$ . . . 3

3 Flujo y Conectividad **3**
- 3.1 Dinic . . . 3
- 3.2 2-SAT . . . 4
- 3.3 Camino-dirigido-euler . . . 4
- 3.4 Camino-nodirigido-euler . . . 4
- 3.5 Tarjan . . . 5
- 3.6 tarjan SCC . . . 5

4 Estructuras de Datos **5**
- 4.1 Segment Tree – $O(\log n)$ . . . 5
- 4.2 Sparse Table – $O(n \log n)$ build, $O(1)$ query . . . 6
- 4.3 Segment Tree Lazy – $O(\log n)$ . . . 6
- 4.4 Fenwick Tree – $O(\log n)$ . . . 7
- 4.5 Fenwick Tree 2D– $O(\log n)$ . . . 7
- 4.6 Line container – $O(\log n)$ . . . 7
- 4.7 Sqrt decomp — $O\sqrt{n}$ . . . 7
- 4.8 Mo — $O(confia)$ . . . 8

5 Matemáticas **8**
- 5.1 Template . . . 8
- 5.2 BinPow . . . 8
- 5.3 CatalanNumbers . . . 8
- 5.4 ConvexHull . . . 8
- 5.5 Chinese Remainder Theorem . . . 9
- 5.6 Discrete Log . . . 9
- 5.7 Discrete Root . . . 9
- 5.8 Erathostenes Sieve . . . 9
- 5.9 Factorization using Pollard Rho . . . 9
- 5.10 Fast Fourier Transform . . . 10
- 5.11 Gaussian Elimination . . . 10
- 5.12 GCD . . . 10
- 5.13 GCD Extended . . . 11
- 5.14 Inclusion Exclusion . . . 11
- 5.15 Miller Rabin . . . 11
- 5.16 Mobius . . . 11
- 5.17 Number Theoric Transform . . . 11
- 5.18 Primitive Root (Generator of a Prime Group) . . . 12
- 5.19 Simpson Rule . . . 12
- 5.20 Tonelli Shanks . . . 12
- 5.21 Euler Totiente . . . 12

6 Strings **12**
- 6.1 KMP – $O(n+m)$ . . . 12
- 6.2 Z-Function – $O(n+m)$ . . . 13
- 6.3 Trie – $O(|s|)$ por operación . . . 13
- 6.4 Rolling Hashing . . . 13
- 6.5 aho-corasick . . . 14

7 Programación Dinámica **14**
- 7.1 Longest Increasing Subsequence – $O(n \log n)$ . . . 14
- 7.2 LIS of length K– $O(nk \log n)$ . . . 14
- 7.3 LIS elements participate of Optimal solutions– $O(n \log n)$ . . . 14
- 7.4 Knapsack $0/1$ – $O(nW)$ . . . 15

8 Misceláneos **15**
- 8.1 Búsqueda Binaria – $O(\log n)$ . . . 15

9 Formulary **15**
- 9.1 Bits . . . 15
- 9.2 Number theory . . . 15

1 Template Base

```cpp
#pragma GCC optimize("O3", "unroll-loops")
#include <bits/stdc++.h>
using namespace std;
using ll = long long;
#define all(v) (v).begin(), (v).end()

void solve(){

}

int main(){
  ios::sync_with_stdio(false);
  cin.tie(nullptr);
  ll t = 1;
  cin >> t;
  while(t--){
    solve();
  }
  return 0;
}

```

template.cpp

2 Grafos

2.1 Dijkstra – $O((V+E)\log V)$

```cpp
vector<ll> dist;
vector<vector<pair<ll,ll>>> g;

void djikstra(){
  priority_queue<pair<ll,ll>, vector<pair<ll,ll>> ,
     greater<pair<ll,ll>> > pq;
  pq.push({0,0});
  while(pq.size()){
    ll c, node;
    auto p = pq.top(); pq.pop();
    c = p.first, node = p.second;
    if(dist[node] > c){
      dist[node] = c;
      for(auto [c_, v_] : g[node]){
        if(dist[v_] > c + c_ ) {
          pq.push({c+c_, v_});
        }
      }
    }
  }
}
```

dijkstra.cpp

2.2 Floyd-Warshall – $O(V^3)$

```cpp
/*
*Description:* All pairs shortest path, O(V^3)
*Status:* Tested
*/
for (int i = 1; i <= n; i++) {
  for (int j = 1; j <= n; j++) {
    if (i == j) distance[i][j] = 0;
    else if (adj[i][j]) distance[i][j] = adj[i][j];
    else distance[i][j] = INF;
  }
}
for (int k = 1; k <= n; k++) {
  for (int i = 1; i <= n; i++) {
    for (int j = 1; j <= n; j++) {
      distance[i][j] = min(distance[i][j],
      distance[i][k]+distance[k][j]);
    }
  }
}

```

Floyd-Warshall.cpp

2.3 Bellman-Ford – $O(VE)$

```cpp
/*
*Description:* Calculates shortest paths from $s$ in a
     graph that might have negative edge weights.
*Status:* Tested on CSES
*/
struct BellmanFord {
  struct Edge { int from, to; ll weight; };
  int n, last_updated = -1; const ll INF = 1e18;
  vector<int> p; vector<ll> dist;
  BellmanFord(vector<Edge> &G, int s, int _n) {
    n = _n; dist.assign(n+1,INF);
    p.assign(n+1,-1); dist[s] = 0;
    for (int i = 1; i <= n; i++) {
      last_updated = -1;
      for (Edge &e : G)
      if (dist[e.from] != INF && dist[e.from] + e.weight
      < dist[e.to]) {
        dist[e.to] = dist[e.from] + e.weight;
        p[e.to] = e.from; last_updated = e.to;
      }
    }
  }
  bool getCycle(vector<int> &cycle) {
    if (last_updated == -1) return false;
    for (int i = 0; i < n-1; i++)
    last_updated = p[last_updated];
    for (int x = last_updated ;; x=p[x]) {
      cycle.push_back(x);
      if (x == last_updated and cycle.size() > 1) break;
    }
    reverse(cycle.begin(), cycle.end());
    return true;
  }
};

```

Bellman-Ford.cpp

2.4 Kruskal – $O(E \log E)$

```cpp
/*
*Description:* Minimum spanning tree in $O(E log E)$
*Status:* Tested
*/
struct Edge {
  int a; int b; ll w;
  Edge(int a_, int b_, ll w_) : a(a_), b(b_), w(w_) {}
};
bool c_edge(Edge &a, Edge &b) { return a.w < b.w; }
ll Kruskal() {
  int n = G.size();
  union_find sets(n);
  vector<Edge> edges;
  for(int i = 0; i < n; i++) {
    for(auto eg : G[i]) {
      // node i to node eg.first with cost eg.second
      edges.emplace_back(i, eg.first, eg.second);
    }
  }
  sort(edges.begin(), edges.end(), c_edge);
  ll min_cost = 0;
  for(Edge e : edges) {
    if(sets.sameSet(e.a, e.b) != true) {
      tree.emplace_back(e.a, e.b, e.w);
      min_cost += e.w;
      sets.unionSet(e.a, e.b);
    }
  }
  return min_cost;
}

```

Kruskal.cpp

2.5 LCA – $O(V \log V)$ build, $O(\log V)$ query

```cpp
/*
*Description:* Lowest Common Ancestor using binary
     lifting.
*Preprocessing: O(V log V)
*Query: O(log V)
*Works on rooted trees and forests represented by
     adjacency lists.
*Status:* Tested
*/
struct LCA {
  vector<vector<ll>> T, parent;
  vector<ll> depth, vis, comp;
  ll LOGN, V;
  LCA(vector<vector<ll>> &T) : T(T) {
    V = (ll)T.size();
    LOGN = 1;
    while ((1LL << LOGN) <= max(1LL, V))
    LOGN++;
    parent.assign(V, vector<ll>(LOGN, 0));
    depth.assign(V, 0);
    vis.assign(V, 0);
    comp.assign(V, -1);
    ll id = 0;
    for (ll u = 0; u < V; u++) {
      if (!vis[u]) {
        dfs(u, u, id++);
      }
    }
  }

  void dfs(ll u, ll p, ll id) {
    vis[u] = 1;
    comp[u] = id;
    parent[u][0] = p;
    for (ll j = 1; j < LOGN; j++)
    parent[u][j] = parent[parent[u][j - 1]][j - 1];

    for (ll v : T[u]) {
      if (!vis[v]) {
        depth[v] = depth[u] + 1;
        dfs(v, u, id);
      }
    }
  }
  ll query(ll u, ll v) {
    if (comp[u] != comp[v])
    return -1;
    if (depth[u] < depth[v])
    swap(u, v);
    ll k = depth[u] - depth[v];
    for (ll j = LOGN - 1; j >= 0; j--) {
      if ((k >> j) & 1)
      u = parent[u][j];
    }
    if (u == v)
    return u;
    for (ll j = LOGN - 1; j >= 0; j--) {
      if (parent[u][j] != parent[v][j]) {
        u = parent[u][j];
        v = parent[v][j];
      }
    }
    return parent[u][0];
  }
};

```

LCA.cpp

2.6 Union-Find / DSU – $O(\alpha(n))$

```cpp
struct union_find {
  vector<int> e;
  union_find(int n) { e.assign(n, -1); }
  int findSet(int x) {
    return (e[x] < 0
    ? x : e[x] = findSet(e[x]));
  }
  bool sameSet(int x, int y) {
```

```
    return findSet(x) == findSet(y);
  }
  int size(int x) { return -e[findSet(x)]; }
  bool unionSet(int x, int y) {
    x = findSet(x), y = findSet(y);
    if (x == y) return 0;
    if (e[x] > e[y]) swap(x, y);
    e[x] += e[y], e[y] = x;
    return 1;
  }
};
```

dsu.cpp

2.7 Dominator Tree – $O((|E| + |V|)\log(|V|))$

```
struct dominator_tree {
    ll n,l,s;
    vector<ll> tin,par,vis_ord, dsu_mn, dsu_par, sdom,
     dep,rdom,idom;
    vector<bool> vis;
    vector<vector<ll>> up;
    vector<vector<pair<ll,ll>>> up_mn;
    void dfs(ll u, ll p, vector<vector<ll>> & adj){
        if (vis[u]) return;
        vis[u] = 1;
        dep[u] = dep[p]+1;
        tin[u] = vis_ord.size();
        vis_ord.push_back(u);
        par[u] = p;
        for (int v : adj[u]) dfs(v,u,adj);
    }
    ll find(ll x){
        if (dsu_par[x] == -1) return x;
        if (dsu_par[dsu_par[x]] != -1){
            ll res = find(dsu_par[x]);
            if (tin[res] < tin[dsu_mn[x]])
        dsu_mn[x] = res;
      dsu_par[x] = dsu_par[dsu_par[x]];
        }
        assert(dsu_mn[x] != INT32_MAX);
        return dsu_mn[x];
    }
    void get_sdom(vector<vector<ll>> & rev){
        for (ll i = vis_ord.size()-1; i >= 0; i--){
            ll c = vis_ord[i];
            if (c == s) continue;
            for (ll to : rev[c]){
                ll res = find(to);
                if (sdom[c] == -1 || tin[res] < tin[sdom
     [c]])
                    sdom[c] = res;
            }
            dsu_par[c] = par[c];
            dsu_mn[c] = sdom[c];
            if (sdom[c] == -1) cerr << c << endl;
        }
    }
    void init_up(){
        for_(i, n){
            if (!vis[i]) continue;
            up[i][0] = par[i];
            up_mn[i][0] = {tin[sdom[i]],i};
        }
        for (ll i = 1; i < l; i++) {
      for_(j, n) {
                if (!vis[j]) continue;
        ll h = up[j][i-1];
        if (h == -1) {
          up[j][i] = -1;
          up_mn[j][i] = up_mn[j][i-1];
        } else {
          up[j][i] = up[h][i-1];
          up_mn[j][i] = min(up_mn[j][i-1], up_mn[h][i
     -1]);
        }
      }
    }
    }
    ll get_min(ll v, ll u){
        ll dist = dep[u]-dep[v];
        pair<ll,ll> ret = up_mn[u][0];
        ll w = u;
        for_(i, l)
            if (dist&(1<<i)){
                ret = min(ret,up_mn[w][i]);
                w = up[w][i];
            }
        assert(w == v);
        return ret.second;
    }
    void get_idom(){
        for (ll c : vis_ord){
            if (c == s) continue;
            rdom[c] = get_min(sdom[c],c);
        }
        for (ll c : vis_ord)
            if (c != s)
                idom[c] = ((rdom[c] == c)?sdom[c]:idom[
     rdom[c]]);
    }
    dominator_tree(vector<vector<ll>> & adj, vector<
     vector<ll>> & rev, ll _s = 0, ll logn = 20){
        n = adj.size(); l = logn; s = _s;
        tin.resize(n,INT32_MAX);
        par.resize(n,-1);
        vis.resize(n,0);
        dep.resize(n,0);
        dfs(s,-1,adj);
        dsu_par.resize(n,-1);
        dsu_mn.resize(n,INT32_MAX);
        sdom.resize(n,-1);
        rdom.resize(n,-1);
        idom.resize(n,-1);
        get_sdom(rev);
        up.assign(n,vector<ll>(logn));
        up_mn.assign(n,vector<pair<ll,ll>>(logn));
        init_up();
        get_idom();
    }
};

//aux function, cover dom tree
void dfs(ll &cnt, ll node, vector<vector<ll>> &adj,
     vector<ll> &tin, vector<ll> &tout){
    tin[node] = cnt++;
    for(ll child : adj[node]) dfs(cnt, child, adj, tin,
     tout);
    tout[node] = cnt++;
}

//verifiy if u dominates v, for each edge
vector<vector<bool>> Verifiy_u_dom_v(ll n, vector<vector
     <ll>> &adj, vector<vector<ll>> &rev_adj, vector<pair
     <ll, ll>> &edges){
    dominator_tree dt(adj, rev_adj);
    vector<vector<ll>> dom_tree(n);
    for_(i, n){
        if(i==0) continue;
        if(dt.vis[i]) dom_tree[dt.idom[i]].push_back(i);
    }
    vector<ll> tin(n, 0), tout(n, 0); ll cnt = 0;
    dfs(cnt, 0, dom_tree, tin, tout);
    vector<vector<bool>> dom_matrix(n, vector<bool>(n,
     false));
    for_(i, edges.size()){
        auto &[u,v] = edges[i];
        if((tin[u]<=tin[v] && tout[v]<=tout[u]))
     dom_matrix[u][v] = true;
    }
    return dom_matrix;
}

```

dominatorTree.cpp

3 Flujo y Conectividad

3.1 Dinic

```
/*
*Author:* Pablo Messina
*Source:* https://github.com/PabloMessina/Competitive-
     Programming-Material
*Description:* Flow algorithm with complexity  $0 (|E|
     dot |V|^2)$
*Status:* Not tested
*/
template<class T>
struct Dinic {
  struct Edge { int to, rev; T f, c; bool r; };
  int n, t_; vector<vector<Edge>> G;
  vector<int> D, q, W;
  bool bfs(int s, int t) {
    W.assign(n, 0); D.assign(n, -1); D[s] = 0;
    int f = 0, l = 0; q[l++] = s;
    while (f < l) {
      int u = q[f++];
      for (const Edge &e : G[u]) if (D[e.to] == -1 && e.
     f < e.c)
        D[e.to] = D[u]+1, q[l++] = e.to;
    }
    return D[t] != -1;
  }
```

```
  int dfs(int u, T f) {
    if (u == t_) return f;
    for (int &i = W[u]; i < (int)G[u].size(); ++i) {
      Edge &e = G[u][i]; int v = e.to;
      if (e.c <= e.f || D[v] != D[u] + 1) continue;
      T df = dfs(v,min(f,e.c-e.f));
      if (df > 0) { e.f += df, G[v][e.rev].f -= df;
     return df; }
    }
    return 0;
  }
  Dinic(int N) : n(N), G(N), D(N), q(N) {}
  void add_edge(int u, int v, T cap) {
    G[u].push_back({v, (int)G[v].size(), 0, cap,0});
    G[v].push_back({u, (int)G[u].size()-1, 0, 0,1}); //
     Use cap instead of 0 if bidirectional
  }
  T max_flow(int s, int t) {
    t_ = t; T ans = 0;
    while (bfs(s, t)) while (T dl = dfs(s,
     numeric_limits<T>::max())) ans += dl;
    return ans;
  }
};


/*
Para min cut
for(auto [u, v] : edges){
  if((g.D[u] != -1) != (g.D[v] != -1)){
    ans.push_back({u,v});
  }
}
*/
```

dinic.cpp

3.2 2-SAT

```
struct TwoSat {
  int N;
  vector<vector<int>> gr;
  vector<int> values;
  TwoSat(int n = 0) : N(n), gr(2*n) {}
  int addVar() {
    gr.emplace_back(); gr.emplace_back();
    return N++;
  }
  void either(int f, int j) {
    f = max(2*f, -1-2*f);
    j = max(2*j, -1-2*j);
    gr[f].push_back(j^1);
    gr[j].push_back(f^1);
  }
  void setValue(int x) { either(x, x); }
  void atMostOne(const vector<int>& li) {
    if ((int)li.size() <= 1) return;
    int cur = ~li[0];
    for (int i = 2; i < (int)li.size(); i++) {
      int next = addVar();
      either(cur, ~li[i]);
      either(cur, next);
      either(~li[i], next);
      cur = ~next;
    }
    either(cur, ~li[1]);
  }
  vector<int> val, comp, z; int Time = 0;
  int dfs(int i) {
    int low = val[i] = ++Time, x; z.push_back(i);
    for (int e : gr[i]) if (!comp[e])
    low = min(low, val[e] ? val[e] : dfs(e));
    if (low == val[i]) do {
      x = z.back(); z.pop_back();
      comp[x] = low;
      if (values[x>>1] == -1)
      values[x>>1] = x&1;
    } while (x != i);
    return val[i] = low;
  }
  bool solve() {
    values.assign(N, -1);
    val.assign(2*N, 0); comp = val;
    for (int i = 0; i < 2*N; i++) if (!comp[i]) dfs(i);
    for (int i = 0; i < N; i++)
    if (comp[2*i] == comp[2*i+1]) return false;
    return true;
  }
};
```

2-SAT.cpp

3.3 Camino-dirigido-euler

```
/*
*Description:* Finds an Eulerian trail/circuit in a
     directed graph using Hierholzer's algorithm. Handles
      self-loops and parallel edges.
- A trail exists iff all vertices satisfy outdeg = indeg
     (circuit), or exactly one has outdeg - indeg = 1 (
     start) and one has indeg - outdeg = 1 (end), and the
      edge-set is weakly connected.
- `vertices`: vertex sequence of size $m+1$.
- `edges`: edge index sequence of size $m$.
*Complexity:* $O(V + E)$
*Status:* Tested on https://judge.yosupo.jp/problem/
     eulerian_trail_directed
*/
struct directed_euler_trail {
  ll n, m = 0;
  vector<vector<ll>> adj;
  vector<pair<ll, ll>> E;
  vector<ll> indeg, outdeg, vertices, edges;
  directed_euler_trail(ll n) : n(n), adj(n), indeg(n),
     outdeg(n) {}
  void add_edge(ll u, ll v) {
    adj[u].push_back(m);
    E.push_back({u, v});
    outdeg[u]++, indeg[v]++, m++;
  }
  ll find_start() {
    ll s = -1, cp = 0, cm = 0;
    for (ll v = 0; v < n; v++) {
      ll d = outdeg[v] - indeg[v];
      if (d == 1) cp++, s = v;
      else if (d == -1) cm++;
      else if (d != 0) return -2;
      if (outdeg[v] > 0 && s < 0) s = v;
    }
    if (cp == 0 && cm == 0) return s;
    return (cp == 1 && cm == 1) ? s : -2;
  }
  bool solve() {
    if (m == 0) { vertices = {0}; return true; }
    ll s = find_start();
    if (s == -2) return false;
    vector<ll> ep(n);
    edges.resize(m);
    ll pp = 0, pq = m, v = s;
    while (pp < pq) {
      if (ep[v] >= (ll)adj[v].size()) {
        if (pp == 0)
        return false;
        edges[--pq] = edges[--pp];
        v = E[edges[pq]].first;
      } else {
        ll e = adj[v][ep[v]++];
        edges[pp++] = e;
        v = E[e].second;
      }
    }
    vertices = {s};
    for (ll e : edges) vertices.push_back(E[e].second);
    return true;
  }
};
```

CaminoDirigidoEuler.cpp

3.4 Camino-nodirigido-euler

```
/*
*Description:* Finds an Eulerian trail/circuit in an
     undirected graph using Hierholzer's algorithm.
     Handles self-loops and parallel edges.
- A trail exists iff 0 or 2 vertices have odd degree and
     the graph is connected.
- Uses XOR trick: `v ^= E[e].first ^ E[e].second` to
     traverse edges.
- `vertices`: vertex sequence of size $m+1$.
- `edges`: edge index sequence of size $m$.
*Complexity:* $O(V + E)$
*Status:* Tested on https://judge.yosupo.jp/problem/
     eulerian_trail_undirected
*/
struct undirected_euler_trail {
  ll n, m = 0;
  vector<vector<ll>> adj;
  vector<pair<ll, ll>> E;
  vector<ll> deg, vertices, edges;

  undirected_euler_trail(ll n) : n(n), adj(n), deg(n) {}

  void add_edge(ll u, ll v) {
    adj[u].push_back(m);
```

```
    if (u != v) adj[v].push_back(m);
    E.push_back({u, v});
    deg[u]++, deg[v]++, m++;
  }

  ll find_start() {
    ll s = -1, codd = 0;
    for (ll v = 0; v < n; v++) {
      if (deg[v]&1) codd++, s = v;
      else if (deg[v] > 0 && s < 0)
      s = v;
    }
    return (codd == 0 || codd == 2) ? s : -2;
  }

  bool solve() {
    if (m == 0) { vertices = {0}; return true; }

    ll s = find_start();
    if (s == -2) return false;

    vector<ll> ep(n);
    edges.resize(m);
    vector<bool> alive(m, true);
    ll pp = 0, pq = m, v = s;

    while (pp < pq) {
      if (ep[v] >= adj[v].size()) {
        if (pp == 0)
        return false;
        edges[--pq] = edges[--pp];
        v ^= E[edges[pq]].first ^ E[edges[pq]].second;
      } else {
        ll e = adj[v][ep[v]++];
        if (!alive[e])
        continue;
        alive[e] = false;
        edges[pp++] = e;
        v ^= E[e].first ^ E[e].second;
      }
    }
    vertices = {s};
    for (ll e : edges) {
      s ^= E[e].first ^ E[e].second;
      vertices.push_back(s);
    }
    return true;
  }
};
```

CaminoNoDirigidoEuler.cpp

3.5 Tarjan

```
/*
*Description:* Finds bridges, articulation points, and
    biconnected components
in an undirected graph using Tarjan's algorithm.
*Complexity:* $O(V + E)$
*Status:* Tested on CSES, Codeforces, UVA
*/
struct tarjan {
  struct edge { int u, v, comp, bridge; };
  int n, nbc, T;
  vector<vector<int>> adj;
  vector<edge> e;
  vector<int> disc, low, art, st;
  tarjan(int n) : n(n), nbc(0), T(0), adj(n), disc(n,
    -1), low(n), art(n, 0) {}
  int add_edge(int u, int v) {
    int i = e.size();
    adj[u].push_back(i);
    adj[v].push_back(i);
    e.push_back({u, v, -1, false});
    return i;
  }
  void dfs(int u, int pe) {
    low[u] = disc[u] = T++;
    for (int i : adj[u]) {
      if (i == pe) continue;
      int v = e[i].u ^ e[i].v ^ u;
      if (disc[v] < 0) {
        st.push_back(i);
        dfs(v, i);
        if (low[v] > disc[u])
        e[i].bridge = true;
        if (low[v] >= disc[u]) {
          art[u]++;
          while (st.back() != i) {
            e[st.back()].comp = nbc;
            st.pop_back();
          }
          e[st.back()].comp = nbc;
          st.pop_back();
          nbc++;
        }
        low[u] = min(low[u], low[v]);
      } else if (disc[v] < disc[u]) {
        st.push_back(i);
        low[u] = min(low[u], disc[v]);
      }
    }
  }
  void solve() {
    for (int i = 0; i < n; i++)
    if (disc[i] < 0) dfs(i, -1), art[i]--;
  }
  bool is_bridge(int i) { return e[i].bridge; }
  bool is_art(int v) { return art[v] > 0; }
  int component(int i) { return e[i].comp; }
};
```

tarjan.cpp

3.6 tarjan SCC

```
/*
*Description:* Finds SCC on a graph
*Complexity:* $O(V+E)$
*Status:* Tested on CSES
*/
struct tarjan {
  int n,timer;
  vector<bool> vis,ist;
  vector<int> tin,low,st,cmp;
  vector<vector<int>> scc;
  void dfs(int u, vector<vector<int>> & adj){
    vis[u] = ist[u] = 1;
    st.push_back(u); tin[u] = low[u] = timer++;
    for (auto v : adj[u]){
      if (!vis[v]){
        dfs(v,adj);
        low[u] = min(low[u],low[v]);
      } else if (ist[v]){
        low[u] = min(low[u],tin[v]);
      }
    }
    if (low[u] == tin[u]){
      scc.emplace_back(); int cur;
      do {
        cur = st.back(); st.pop_back();
        ist[cur] = 0; scc.back().push_back(cur);
        cmp[cur] = (int)scc.size()-1;
      } while (cur != u);
    }
  }
  tarjan(vector<vector<int>> & adj){
    n = adj.size(); tin.resize(n); timer = 0; cmp.resize
     (n);
    low.resize(n); vis.resize(n,0); ist.resize(n,0);
    for (int i = 0; i < n; i++) if (!vis[i]) dfs(i,adj);
  }
};
```

TarjanSCC.cpp

4 Estructuras de Datos

4.1 Segment Tree – $O(\log n)$

```
/*
*Description:* Range queries, build $O(n)$, query and
     update $O(log n)$, positions [0, n - 1]
*Status:* Highly tested
*/
template<class T, T m_(T, T)> struct segment_tree{
  int n; vector<T> ST;
  segment_tree(){}
  segment_tree(vector<T> &a){
    n = a.size(); ST.resize(n << 1);
    for (int i=n;i<(n<<1);i++)ST[i]=a[i-n];
    for (int i=n-1;i>0;i--)ST[i]=m_(ST[i<<1],ST[i<<1|1])
     ;
  }
  void update(int pos, T val){ // replace with val
    ST[pos += n] = val;
    for (pos >>= 1; pos > 0; pos >>= 1)
    ST[pos] = m_(ST[pos<<1], ST[pos<<1|1]);
  }
  T query(int l, int r){ // [l, r]
    T ansL, ansR; bool hasL = 0, hasR = 0;
    for (l += n, r += n + 1; l < r; l >>= 1, r >>= 1) {
      if (l & 1)
```

```
      ansL=(hasL?m_(ansL,ST[l++]):ST[l++]),hasL=1;
      if (r & 1)
      ansR=(hasR?m_(ST[--r],ansR):ST[--r]),hasR=1;
    }
    if (!hasL) return ansR; if (!hasR) return ansL;
    return m_(ansL, ansR);
  }
};

```

segtree.cpp

4.2 Sparse Table – $O(n \log n)$ build, $O(1)$ query

```

int min_op(int a, int b) {
  return min(a, b);
}

template <typename T, T (*m_)(T, T)>
struct sparse_table {
  int n = 0;
  vector<vector<T>> table;

  sparse_table() {}

  sparse_table(const vector<T>& arr) {
    n = arr.size();
    if (n == 0) return;

    int k = log2_floor(n) + 1;
    table.assign(n, vector<T>(k));

    for (int i = 0; i < n; i++)
    table[i][0] = arr[i];

    for (int j = 1; j < k; j++) {
      for (int i = 0; i + (1LL << j) <= n; i++) {
        table[i][j] = m_(
        table[i][j - 1],
        table[i + (1LL << (j - 1))][j - 1]
        );
      }
    }
  }

  T query(int l, int r) {
    assert(0 <= l && l <= r && r < n);

    int k = log2_floor(r - l + 1);

    return m_(
    table[l][k],
    table[r - (1LL << k) + 1][k]
    );
  }

  int log2_floor(int x) {
    return x ? 63 - __builtin_clzll(x) : -1;
  }
};

```

sparse-table.cpp

4.3 Segment Tree Lazy – $O(\log n)$

```
/*
*Description:* Seg tree + range updates,
build O(n), query/update O(log n)
*Status:* Highly tested
*/
using T1 = long long;
using T2 = long long;

T1 merge_op(T1 a, T1 b){ return a + b; }

void pushUpd_op(T2& parent, T2& child,
int l, int r, int cl, int cr){
  child += parent;
}

void applyUpd_op(T2& lazy, T1& val,
int l, int r){
  val += (r - l + 1) * lazy;
}

template<
class T1, class T2,
T1 (*merge)(T1, T1),
void (*pushUpd)(T2&,T2&,int,int,int,int),
void (*applyUpd)(T2&, T1&, int, int)
>
struct segment_tree_lazy{
  vector<T1> ST; vector<T2> lazy;
  vector<bool> upd; int n;
  void build(int i, int l, int r,
  vector<T1>&values){
    if(l == r){ ST[i] = values[l]; return; }
    build(i<<1, l, (l+r)>>1, values);
    build(i<<1|1, (l+r)/2+1, r, values);
    ST[i] = merge(ST[i<<1], ST[i<<1|1]);
  }
  segment_tree_lazy() {}
  segment_tree_lazy(vector<T1>&values){
    n = values.size(); ST.resize(n<<2|3);
    lazy.resize(n<<2|3);
    upd.resize(n<<2|3, false);
    build(1, 0, n-1, values);
  }
  void push(int i, int l, int r){
    if(upd[i]){
      applyUpd(lazy[i], ST[i], l, r);
      if(l != r){
        pushUpd(lazy[i], lazy[i<<1],
        l, r, l, (l+r)/2);
        pushUpd(lazy[i], lazy[i<<1|1],
        l, r, (l+r)/2+1, r);
        upd[i<<1] = 1;
        upd[i<<1|1] = 1;
      }
      upd[i] = false;
      lazy[i] = T2();
    }
  }
  void update(int i, int l, int r,
  int a, int b, T2 &u){
    if(l >= a and r <= b){
      pushUpd(u, lazy[i], a, b, l, r);
      upd[i] = true;
    }
    push(i, l, r);
    if(l > b or r < a) return;
    if(l >= a and r <= b) return;
    update(i<<1, l, (l+r)>>1, a, b, u);
    update(i<<1|1, (l+r)/2+1, r, a, b, u);
    ST[i] = merge(ST[i<<1], ST[i<<1|1]);
  }
  void update(int a, int b, T2 u){
    if(a > b){
      update(0, b, u);
      update(a, n-1, u);
      return;
    }
    update(1, 0, n-1, a, b, u);
  }
  T1 query(int i, int l, int r,
  int a, int b){
    push(i, l, r);
    if(a <= l and r <= b) return ST[i];
    int mid = (l+r) >> 1;
    if(mid < a)
    return query(i<<1|1, mid+1, r, a, b);
    if(mid >= b)
    return query(i<<1, l, mid, a, b);
    return merge(
    query(i<<1, l, mid, a, b),
    query(i<<1|1, mid+1, r, a, b));
  }
  T1 query(int a, int b){
    if(a > b)
    return merge(query(a,n-1), query(0,b));
    return query(1, 0, n-1, a, b);
  }
};

int main(){
  int n; cin >> n;
  vector<long long> a(n);
  for(int i = 0; i < n; i++) cin >> a[i];
  segment_tree_lazy<long long, long long,
  merge_op, pushUpd_op, applyUpd_op> st(a);
  int q; cin >> q;
  while(q--){
    int type; cin >> type;
    if(type == 1){
      int l, r; long long val;
      cin >> l >> r >> val;
      st.update(l, r, val);
    }else{
      int l, r; cin >> l >> r;
      cout << st.query(l, r) << '\n';
    }
```

```
  }
}

```

segment-tree-lazy.cpp

4.4 Fenwick Tree – $O(\log n)$

```
struct fenwick_tree {
  vector<ll> bit; int n;
  fenwick_tree(int n): n(n) { bit.assign(n, 0); }
  fenwick_tree(vector<ll> &a): fenwick_tree(a.size()) {
    for (size_t i = 0; i < a.size(); i++) {
      bit[i]+=a[i];
      if ((i|(i + 1)) < a.size()) bit[i|(i + 1)]+=bit[i
    ];
    }
  }
  ll sum(int r) {
    ll ret = 0;
    for (; r >= 0; r = (r & (r + 1)) - 1)
      ret += bit[r];
    return ret;
  }
  ll sum(int l, int r) {
    return sum(r) - sum(l - 1);
  }
  void add(int idx, ll delta) {
    for (; idx < n; idx = idx | (idx + 1))
      bit[idx] += delta;
  }
};

```

fenwick_tree.cpp

```
// Returns the 0-based index of the k-th remaining
    element.
int fenwick_tree::kth(int k) {
    int i = -1;
    int s = 1;
    while ((s << 1) <= n) s <<= 1;
    for (; s > 0; s >>= 1) {
        int j = i + s;
        if (j < n && bit[j] < k) {
            i = j;
            k -= bit[j];
        }
    }
    return i + 1;
}

```

kth_fenwick.cpp

4.5 Fenwick Tree 2D– $O(\log n)$

```

struct fenwick_tree_2d {
  int N, M;
  vector<vector<ll>> BIT;
  fenwick_tree_2d(int N, int M): N(N), M(M) {
    BIT.assign(N + 1, vector<ll>(M + 1, 0));
  }
  void update(int x, int y, ll v) {
    for (int i = x; i <= N; i += (i & -i))
      for (int j = y; j <= M; j += (j & -j))
        BIT[i][j] += v;
  }
  ll sum(int x, int y) {
    ll s = 0;
    for (int i = x; i > 0; i -= (i & -i))
      for (int j = y; j > 0; j -= (j & -j))
        s += BIT[i][j];
    return s;
  }
  ll query(int x1, int y1, int x2, int y2) {
    return sum(x2, y2) - sum(x2, y1 - 1) - sum(x1 - 1,
    y2) + sum(x1 - 1, y1 - 1);
  }
};


```

fenwick_tree_2d.cpp

4.6 Line container – $O(\log n)$

```
const ll INF = 1e15;
struct Line {
  mutable ll a, b, c;
  bool operator<(Line r) const {
    return a < r.a;
  }
  bool operator<(ll x) const {
    return c < x;
  }
};
// dynamically insert `a*x + b` lines and query for
    maximum
// at any x all operations have complexity O(log N)
struct LineContainer: multiset < Line, less < >> {
  ll div(ll a, ll b) {
    return a / b - ((a ^ b) < 0 && a % b);
  }
  bool isect(iterator x, iterator y) {
    if (y == end()) return x -> c = INF, 0;
    if (x -> a == y -> a) x -> c = x -> b > y -> b ? INF
      : -INF;
    else x -> c = div(y -> b - x -> b, x -> a - y -> a);
    return x -> c >= y -> c;
  }

  //ax+b
  void add(ll a, ll b) {
    // a *= -1, b *= -1 // for min
    auto z = insert({
      a,
      b,
      0
    }), y = z++, x = y;
    while (isect(y, z)) z = erase(z);
    if (x != begin() && isect(--x, y)) isect(x, y =
    erase(y));
    while ((y = x) != begin() && (--x) -> c >= y -> c)
    isect(x, erase(y));
  }

  ll query(ll x) {
    if (empty()) return -INF; // INF for min
    auto l = * lower_bound(x);
    return l.a * x + l.b;
    // return -l.a * x - l.b; // for min
  }
};

void solve()
{
  ll n; cin>>n;
  LineContainer lc;
  for (ll k = 1; k <= n; k++) {
    ll bi; cin>>bi;
    lc.add(2*k, -(k*k + bi));
  }
  ll q; cin>>q;
  for (ll k = 0; k < q; k++) {
    ll t; cin>>t;
    if (t == 1) {
      ll x; cin>>x;
      cout<<-lc.query(x) + x*x<<endl;
    } else {
      ll a, b; cin>>a>>b;
      lc.add(2*a, -(a*a + b));
    }
  }
}

```

line_container.cpp

4.7 Sqrt decomp — $O\sqrt{n}$

```
template <class T, T merge(T,T)>
struct sqrt_decomp {
  int n,sq;
  vector<T> st,bl;
  sqrt_decomp(vector<T> & a){
    n = a.size(); st.resize(n);
    sq = sqrtl(n); bl.resize((n+sq-1)/sq);
    for (int i = 0; i < n; i++){
      st[i] = a[i];
      bl[i/sq] = ((i%sq == 0)?st[i]:merge(bl[i/sq],st[i
    ]));
    }
  }
  void update(int pos, T val) {
    st[pos] = val;
    int block = pos/sq, lb = block*sq, rb = min(block*sq
    +sq-1,n-1);
```

```
    T vl;
    for (int i = lb; i <= rb; i++)
      vl = ((i == lb)?st[i]:merge(vl,st[i]));
    bl[block] = vl;
  }
  T query(int l, int r){
    T res; bool hasR = 0;
    for (int i = l/sq; i <= r/sq; i++){
      int lb = i*sq, rb = i*sq+sq-1;
      if (l <= lb && rb <= r){
        res = (hasR?merge(res,bl[i]):bl[i]), hasR = 1;
        continue;
      }
      for (int j = max(l,lb); j <= min(rb,r); j++)
        res = (hasR?merge(res,st[j]):st[j]), hasR = 1;
    }
    return res;
  }
};

```

sqrt_decomp.cpp

4.8 Mo — $O(confia)$

```
struct query {
  ll l, r, i;
};
template<class T, typename U, class T2>
struct mo_algorithm {
  vector<U> ans;
  template<typename... Args>
  mo_algorithm(vector<T> &v, vector<query> &queries,
     Args... args) {
    T2 ds(args...);
    ll block_sz = sqrtl(v.size());
    ans.assign(queries.size(), -1);
    sort(queries.begin(), queries.end(), [&](auto &a,
     auto &b) {
      return a.l/block_sz != b.l/block_sz ? a.l/block_sz
      < b.l/block_sz : a.r < b.r;
    });
    ll l = 0, r = -1;
    for (query q : queries) {
      while (l > q.l) ds.add(v[--l]);
      while (r < q.r) ds.add(v[++r]);
      while (l < q.l) ds.remove(v[l++]);
      while (r > q.r) ds.remove(v[r--]);
      ans[q.i] = ds.answer(q);
    }
  }
};

```

mo.cpp

5 Matemáticas

5.1 Template

```
#include<bits/stdc++.h>

using namespace std;

#define ll long long
#define ld long double
#define cd complex<long double>
#define ull unsigned long long
#define for_(i, n) for(ll i = 0; i < n; ++i)
#define INF LLONG_MAX
#define NINF LLONG_MIN
#define i128 __int128
#define u128 __uint128_t
const double PI =
     3.14159265358979323846264338327950288419716939937510582;

const double EPS = 1e-18;


const ll mod = 1e9 + 7; //switch per case

```

template.cpp

5.2 BinPow

```
/*
Tested : Tested
*/

ll binpow(ll a, ll b, ll m){
    ll ans = 1;
    while(b > 0){
        if(b&1) ans = (ans*a)%m;
        a=(a*a)%m;
        b>>=1;
    }
    return ans;
}

```

BinPow.cpp

5.3 CatalanNumbers

```
//n-catalan number = (2n)!/((n+1)!n!)
ll getNCatalanNumber(ll n){
    double ans = 1;
    for(ll k = 2; k <= n; k++) ans *= (n+k)/k;
    return (ll)(ans + 0.001);
}
//TESTED
vector<ll> getCatalanNumbers(ll n){
    vector<ll> C(n+1, 0);
    C[0] = C[1] = 1;
    C[2] = 2;
    for(ll i = 3; i <= n; ++i){
        for(ll j = 0; j < i; ++j) C[i] += C[j]*C[i-j-1];
    }
    return C;
}

```

CatalanNumbers.cpp

5.4 ConvexHull

```

//TESTED
//Monotic Change
struct point{
    double x,  y;
};
ll orientation(const point &a, const point &b,const
     point &c){
    double sign = a.x*(b.y - c.y) - b.x*(a.y - c.y) + c.
     x*(a.y -b.y);
    if(sign > 0) return 1;
    else if( sign < 0) return -1;
    else return 0;
}
bool cw(const point &a, const point &b,const point &c,
     const bool &include_colider){
    ll o = orientation(a, b, c);
    return (o > 0 || include_colider && 0==0);
}

bool ccw(const point &a, const point &b,const point &c,
     const bool &include_colider){
    ll o = orientation(a, b, c);
    return (o < 0 || include_colider && o==0);
}

void convex_hull(vector<point> &a, bool include_colider)
     {
    if(a.size()==1) return;
    sort(a.begin(), a.end(), [](const point &p1, const
     point &p2){return (p1.x==p2.x ? p1.y < p2.y : p1.x <
      p2.x);});
    point A = a[0], B = a[a.size()-1];
    vector<point> upper, lower;
    upper.push_back(A);
    lower.push_back(A);
    for(ll i = 1; i < a.size(); ++i){
        if(i == a.size()-1 || cw(A, a[i], B,
     include_colider)){
            while(upper.size() >= 2 && !(cw(upper[upper.
     size()-2], upper[upper.size()-1], a[i],
     include_colider))) upper.pop_back();
            upper.push_back(a[i]);
        }
        if(i == a.size()-1 || ccw(A, a[i], B,
     include_colider)){
            while(lower.size() >= 2 && !(ccw(lower[lower
     .size()-2], lower[lower.size()-1], a[i],
     include_colider))) lower.pop_back();
            lower.push_back(a[i]);
        }
    }

```

```
    if(include_colider && upper.size() == a.size()){
        reverse(a.begin(), a.end());
        return;
    }
    a.clear();
    for(ll i = 0; i < upper.size(); ++i) a.push_back(upper[i]);
    for(ll i = lower.size()-2; i >= 1; --i) a.push_back(lower[i]);
}

```

convexhull.cpp

5.5 Chinese Remainder Theorem

```
//TESTED (PD: for 2x2 system but should work for any nXn)
#include"gcdExtended.cpp"

ll mod_inv(ll a, ll m){
    ll x, y;
    ll g = gcdExtended(a, m, x, y);
    x = (x%m + m)%m;
    return x;
}

struct Congruence {
    ll b, n;
};

ll chinese_remainder_theorem(vector<Congruence> const& congruences) {
    ll N = 1;
    for (auto const& congruence : congruences) N *= congruence.n;

    ll x = 0;
    for (auto const& congruence : congruences) {
        ll b_i = congruence.b;
        ll N_i = N / congruence.n;
        ll invN_i = mod_inv(N_i, congruence.n);
        i128 aux = (b_i*N_i)%N;
        aux = (aux*invN_i)%N;
        x = (ll) (x + aux)%N;
    }
    return x;
}

```

crt.cpp

5.6 Discrete Log

```

//Tested

ll discrete_log(ll a, ll b, ll m) {
    a %= m, b %= m;
    if (a == 0) return b == 0 ? 1 : -1;
    ll k = 1, add = 0, g;
    while ((g = gcd(a, m)) > 1) {
        if (b == k)
            return add;
        if (b % g)
            return -1;
        b /= g, m /= g, ++add;
        k = (k * 1ll * a / g) % m;
    }

    ll n = sqrt(m) + 1;
    ll an = 1;
    for_(i, n) an = (an * 1ll * a) % m;

    unordered_map<ll, ll> f2inv;
    for (ll q = 0, f2 = b; q <= n; ++q) {
        f2inv[f2] = q;
        f2 = (f2 * 1ll * a) % m;
    }

    for (ll p = 1, f1 = k; p <= n; ++p) {
        f1 = (f1 * 1ll * an) % m;
        if (f2inv.count(f1)){
            ll x = n * p - f2inv[f1] + add;
            return x;
        }
    }
    return -1;
}

```

discretelog.cpp

5.7 Discrete Root

```

//TESTED

#include"gcd.cpp"
#include"bin_pow.cpp"
#include"tot_euler.cpp"
#include"primitive_root.cpp"

vector<ll> DiscreteRoot(ll n,ll k,ll a){
    if(a==0) return {0};
    ll g = generator_(n);

    ll sq = (ll)sqrt(n) + 1;
    vector<pair<ll, ll>> dec(sq);
    for(ll i = 1; i <= sq; ++i)
        dec[i-1] = {binpow(g, i * sq * k % (n - 1), n), i};
    sort(dec.begin(), dec.end());
    ll h0 = -1;
    for_(i, sq) {
        ll my = binpow(g, i * k % (n - 1), n) * a % n;
        auto it = lower_bound(dec.begin(), dec.end(), make_pair(my, 0));
        if (it != dec.end() && it->first == my) {
            h0 = it->second * sq - i;
            break;
        }
    }
    if(h0 == -1) return {-1};

    ll delta = (n-1)/gcd(k, n-1);
    vector<ll> x;
    for (ll h = h0 % delta; h < n-1; h += delta)
        x.push_back(binpow(g, h, n));
    sort(x.begin(), x.end());
    return x;
}

```

DiscreteRoot.cpp

5.8 Erathostenes Sieve

```
//Tested

vector<bool> erathostenesSieve(ll n){
  vector<bool> isprime(n+1, true);
  isprime[0] = isprime[1] = false;
  for(ll i = 2; i <= n; (i==2 ? i++ : i+=2)){
    if(isprime[i]){
      for(ll j = i*i; j <= n; j+=i) isprime[j] = false;
    }
  }
  return isprime;
}

```

erathostenes-sieve.cpp

5.9 Factorization using Pollard Rho

```

mt19937_64 rng(chrono::steady_clock::now().time_since_epoch().count());

//TESTED up to 1e18, run T(n) < 1e8

ll mult(ll a, ll b, ll m) {
    return (__int128)a * b % m;
}

ll f(ll x, ll c, ll m) {
    return (mult(x, x, m) + c) % m;
}

#include"gcd.cpp"

ll rho(ll n, ll x0=2, ll c=1) {
    ll x = x0;
    ll y = x0;
    ll g = 1;
    while (g == 1) {
        x = f(x, c, n);
        y = f(y, c, n);
        y = f(y, c, n);
        g = gcd(abs(x - y), n);
    }
    return g;
}
```

```cpp

//algorithm for the factorization
ll brent(ll n, ll x0=2, ll c=1) {
    ll x = x0;
    ll g = 1;
    ll xs, y;

    ll m = 128;
    ll l = 1;
    ll iter = 0;
    while (g == 1 && iter<1000) {
        y = x;
        ll q = 1;
        for (ll i = 1; i < l; i++)
            x = f(x, c, n);
        ll k = 0;
        while (k < l && g == 1) {
            xs = x;
            for (ll i = 0; i < m && i < l - k; i++) {
                x = f(x, c, n);
                q = mult(q, abs(y - x), n);
            }
            g = gcd(q, n);
            k += m;
        }
        l *= 2;
        iter++;
    }
    if (g == n) {
        return n;
    }
    return g;
}

#include"miller_rabin.cpp"

//algorithm to prime factorization
void factorize(ll n, map<ll, ll> &factors){
    if(n==1) return;
    if(deterministicMillerRabin(n)){
        factors[n]++;
        return;
    }
    ll d1, d2, iter=0;
    while(iter<1000){
        uniform_int_distribution<ll> dist(1, n-1);
        ll c = dist(rng);
        ll x0 = dist(rng);
        d1 = brent(n, x0, c), d2 = n/d1;
        if(d1>1 && d1<n) break;
        iter++;
    }
    if(d1==1 || d2==1){
        factors[n]++;
        return;
    }
    factorize(d1, factors);
    factorize(d2, factors);
}

```

Factorization-pollard-rho.cpp

5.10 Fast Fourier Transform

```cpp
//Tested

void fft_bottom_up(vector<cd> &c, bool inverse){
    ll N = 1;
    while(N < c.size()) N<<=1;
    c.resize(N);
    if(N<= 1) return;
    ll cnt = 0;
    for(ll j = 1; j < N; ++j){
        ll bit = N >> 1;
        while(cnt & bit){
            cnt^=bit;
            bit>>=1;
        }
        cnt^=bit;
        if(cnt < j) swap(c[cnt], c[j]);
    }

    //n is the length of the current block of the tree, thanks to bit reversal is in order, n=2 -> depth= D-1, n=4 -> depth=D-2, and so on...
    for(ll n = 2; n <= N; n<<=1){
        double ang = 2*PI/n * (inverse ? -1 : 1);
        cd wn(cos(ang), sin(ang));
        //iterate each block(node from the current depth)
        for(ll currblock = 0; currblock < N; currblock+=n){
            cd w(1);
            //iterate the node of the current block, only recover a half, because butterfly effect(como se diga la wea).
            for(ll curr = 0; curr < n/2; ++curr){
                cd u = c[currblock + curr], v = c[currblock + curr + n/2]*w;
                c[currblock + curr] = u + v;
                c[currblock + curr + n/2] = u - v;
                w*=wn;
            }
        }
    }
    if(inverse){
        for(cd &x : c) x/=N;
    }
}

vector<cd> conv(vector<cd> &c1, vector<cd> &c2){
    vector<cd> ans; ll N=1;
    while(N < (c1.size()+c2.size())) N<<=1;
    c1.resize(N); c2.resize(N);
    fft_bottom_up(c1, false);
    fft_bottom_up(c2, false);
    ans.resize(N);
    for_(i, N) ans[i] = c1[i]*c2[i];
    fft_bottom_up(ans, true);
    return ans;
}

```

fft.cpp

5.11 Gaussian Elimination

```cpp
//Tested

bool gauss_jordan(vector<vector<ll>> A, vector<ll> &x) {
  ll n = A.size(), m = A[0].size() - 1;

  vector<ll> where(m, -1);
  for (ll col = 0, row = 0; col < m && row < n; ++col) {
    ll pivot = row;
    for (ll i = row; i < n; ++i){
      if (abs(A[i][col]) > abs(A[pivot][col])) pivot = i;
    }
    if(!A[pivot][col]) continue;
    for (ll i = col; i <= m; ++i) swap(A[pivot][i], A[row][i]);
    where[col] = row;

    for(ll i = 0; i < n; ++i){
      ll invm = binpow(A[row][col], MOD - 2, MOD);
      if(i != row) {
        ll c = (A[i][col] * invm) % MOD;
        for (ll j = col; j <= m; ++j) A[i][j] = ((A[i][j] - A[row][j] * c) % MOD + MOD) % MOD;
      }
    }
    ++row;
  }

  x.assign(m, 0);
  for (ll i = 0; i < m; ++i){
    if (where[i] != -1){
      ll invm = binpow(A[where[i]][i], MOD - 2, MOD);
      x[i] = (A[where[i]][m] * invm) % MOD;
    }
  }
  for(ll i=0; i<n; ++i){
    ll sum = 0;
    for(ll j=0; j<m; ++j) sum += (x[j] * A[i][j])%MOD;
    if(abs(sum - A[i][m]) > 0) return false; //No solution
  }
  return true;//Valid solution, trivial or infinity


```

gaussian-elimination.cpp

5.12 GCD

```cpp
//Tested meme
ll gcd(ll a, ll b){
    if(b==0) return a;
    return gcd(b, a%b);
}

ll gcd(ll a, ll b){
```

```
    while(b) { ll r = a % b; a = b; b = r; }
    return a;
}

```

gcd.cpp

5.13 GCD Extended

```
//Tested

ll gcdExtended(ll a, ll b, ll &x, ll &y){
    if(b == 0){
        x = 1;
        y = 0;
        return a;
    }
    ll x_, y_, gcd = gcdExtended(b, a%b, x_, y_);
    x = y_;
    y = x_ - y_*(a/b);
    return gcd;
}

```

gcdExtended.cpp

5.14 Inclusion Exclusion

```

//Example cardinality of all subsets of size 1
ll cardinalitySubset(ll subset){
    return 1;
}

//Template
ll InclusionExclusion(){
    //sets
    ll n = 10;//example
    ll subsets = (1<<n);//total subsets
    ll ans = 0;
    //travel on all the subsets, with a particular
     subset
    for(ll subset = 0; subset < subsets; subset++){
        //if is odd the subset we sum, otherwise
     substract, recall, Union of sets = sum sets -
     intersect sets pairs + intersect group of three -
     ...
        ans += (__builtin_popcount(subset)&1 ?
     cardinalitySubset(subset) : -cardinalitySubset(
     subset));
    }
    return ans;
}

```

InclusionExclusion.cpp

5.15 Miller Rabin

```

ll binpow(ll a, ll b, ll mod){
  ll ans = 1;
  while(b>0){
    if(b&1) ans = (u128)(ans)*a % mod;
    a=(u128)a*a % mod;
    b>>=1;
  }
  return ans;
}

bool checkComposite(ll p, ll a, ll s, ll q){
  ll x = binpow(a, q, p);
  if(x == 1 || x == p-1) return false;
  for(ll i = 1; i < s; ++i){
    x = (u128)x*x % p;
    if(x == p-1) return false;
  }
  return true;
}

bool millerRabin(ll p, ll maxIter=5){
  if(p<4) return p==2 || p==3;
  ll s=0,q = p-1;
  while(!(q&1)){
    s++;
    q>>=1;
  }
  for(ll i = 0; i < maxIter; ++i){
    ll a = 2 + rand() % (p-3);
    if(checkComposite(p, a, s, q)) return false;
  }
  return true;
}

bool deterministicMillerRabin(ll p){
  if(p<4) return p==2 || p==3;
  ll s=0,q = p-1;
  while(!(q&1)){
    s++;
    q>>=1;
  }
  for(ll a : {2,3,5,7,11,13,17,19,23,29,31,37}){
    if(p==a) return true;
    if(checkComposite(p, a, s, q)) return false;
  }
  return true;
}

```

miller-rabin.cpp

5.16 Mobius

```
//Tested

vector<ll> mobius(ll n){
    vector<ll> mob(n+1, 1);
    mob[1] = 1;
    vector<bool> isprime(n+1, true);
    isprime[0]=isprime[1] = false;
    for(ll i = 2; i < n+1; i++){
        if(isprime[i]){
            for(ll j = i; j < n+1; j+=i){
                mob[j] *= -1;
                isprime[j] = false;
            }
            for(ll j = i*i; j < n+1; j += i*i) mob[j] =
     0;
        }
    }
    return mob;
}

```

mobius.cpp

5.17 Number Theoric Transform

```

//TESTED

const ll mod = 998244353, generator = 3, rootn = 3; //
     for N max = 2^23
/*more modelus primes of the form p = c*2^m + 1 (
     generators calculated with algorithm in math section
     ):
const ll mod = 7340033, generator = 3, rootn = 3; // for
      N max = 2^20
const ll mod = 167772161, generator = 3, rootn = 3; //
     for N max = 2^25
const ll mod = 469762049, generator = 3, rootn = 3; //
     for N max = 2^26
*/

ll binpow(ll a, ll e){
    ll ans = 1;
    while(e > 0){
        if(e&1) ans = (ans * a)%mod;
        a = (a*a)%mod;
        e>>=1;
    }
    return ans;
}

ll inv(ll a){return binpow(a, mod-2);}


void ntt(vector<ll> &c, bool invert){
    ll N = 1;
    while(N < c.size())N<<=1;
    c.resize(N);
    ll cnt = 0;
    for(ll j = 1; j < N; ++j){
        ll bit = N>>1;
        while(bit&cnt){
            cnt^=bit;
            bit>>=1;
        }
        cnt^=bit;
        if(cnt < j) swap(c[cnt], c[j]);
    }
```

```
38
39      for(ll n = 2; n <= N; n<<=1){
40          ll wn = binpow(rootn, (mod-1)/n);
41          if(invert) wn = inv(wn);
42          for(ll currblock = 0; currblock < N; currblock+=
        n){
43              ll w = 1;
44              for(ll i = 0; i < n/2; ++i){
45                  ll u = c[currblock + i]%mod, v = (w*c[
        currblock + i + n/2])%mod;
46                  c[currblock + i] = (u + v)%mod;
47                  c[currblock + i + n/2] = ((u - v)%mod +
        mod)%mod;
48                  w = (w*wn)%mod;
49              }
50          }
51      }
52      if(invert){
53          for(ll &x : c) x = (x*inv(N))%mod;
54      }
55  }
56
57  vector<ll> conv(vector<ll> c1, vector<ll> c2){
58      ll N=1;
59      while(N <= (c1.size() + c2.size())) N<<=1;
60      c1.resize(N); c2.resize(N);
61      ntt(c1, false);
62      ntt(c2, false);
63      vector<ll> ans(N, 0);
64      for_(i, N) ans[i] = (c1[i] * c2[i])%mod;
65      ntt(ans, true);
66      return ans;
67  }
68
```

ntt.cpp

5.18 Primitive Root (Generator of a Prime Group)

```
1
2   //TESTED
3
4   #include"bin_pow.cpp"
5   #include"tot_euler.cpp"
6
7   ll generator_(ll n) {
8       vector<int> facts;
9       ll phi_n = tot_euler(n)[n], m = phi_n;
10      for(ll i=2; i*i<=m; ++i){
11          if(m % i == 0) {
12              facts.push_back(i);
13              while (m % i == 0) m/= i;
14          }
15      }
16      if(m > 1) facts.push_back(m);
17      for (ll g=2; g<=n; ++g) {
18          bool ok = true;
19          for (size_t i=0; i<facts.size() && ok; ++i) ok
        &= binpow(g, phi_n/facts[i], n) != 1;
20          if (ok)  return g;
21      }
22      return -1;
23  }
24
```

primitive-root.cpp

5.19 Simpson Rule

```
1   //TESTED
2
3   ld f(ld x) {return x;}
4
5   ld simpson_integration(ld a, ld b, ld d){
6       const ll N = 10000; // number of steps (already
        multiplied by 2)
7       ld h = (b - a) / N;
8       ld s = f(a) + f(b); // a = x_0 and b = x_2n
9       for(ll i= 1; i < N; i++) { // Refer to final Simpson
        's formula
10          double xi = a + h * i;
11          s += f(xi) * ((i & 1) ? 4 : 2);
12      }
13      s *= h / 3.0;
14      //1e6 is the decimal precision, if you want 7, the 1
        e7 and so on
15      s*=1e6;
16      s=llround(s);
17      s/=1e6;
18      // to print use cout << fixed << setprecision(6) <<
        s;
19      return s;
20  }
21
```

SimpsonRule.cpp

5.20 Tonelli Shanks

```
1   // TESTED
2
3   #include"bin_pow.cpp"
4
5   ll TonelliShanks(ll n, ll p) {
6       n %= p; if (n < 0) n += p;
7       if (n == 0) return 0;
8       if (binpow(n,(p-1)/2,p) != 1) return -1; // solution
          does not exist
9       if (p % 4 == 3) return binpow(n, (p + 1) / 4, p); //
          trivial solution, only one factor 2
10      ll c = p - 1, z = 2;
11      ll s = 0;
12      while(c % 2 == 0) ++s, c /= 2;
13      // find a non-square mod p
14      while(binpow(z,(p-1)/2, p) != p - 1) ++z;
15      ll q = binpow(z, c, p); // generator subgroup, |<q>|
          = 2^s
16      ll a = binpow(n, (c+1)/2, p); // candidate root
17      ll t = binpow(n, c, p); // error from equation a^2 =
          n*t, if t=1, a is the root
18      ll m = s;
19      while(1){
20          ll i = 0, temp = t;
21          while(i < m && temp != 1){
22              temp = (temp*temp)%p;
23              i++;
24          }
25          if(i==0) return a;
26          ll exponent = 1ll << (m-i-1);
27          ll b = binpow(q, exponent, p);
28          a = (a*b)%p;
29          t = (((t*b)%p)*b)%p;
30          q = (b*b)%p;
31          m=i;
32      }
33  }
34
```

TonelliShanks.cpp

5.21 Euler Totiente

```
1   //Tested
2
3   vector<ll> tot_euler(ll n){
4       vector<ll> tot(n+1, 0);
5       for_(i, n+1) tot[i]=i;
6       for(ll i = 2; i <= n; ++i){
7           if(tot[i] == i){
8               for(ll j = i; j <= n; j+=i) tot[j] -= tot[j
        ]/i;
9           }
10      }
11      return tot;
12  }
13
```

tot-euler.cpp

6 Strings

6.1 KMP – $O(n+m)$

```
1   /*
2   *Description:* Pattern matching in O(n+m)
3   *Status:* Tested on CSES
4   */
5   template<class T> struct KMP {
6     T pattern; vector<int> lps;
7     KMP(T &pat): pattern(pat) {
8       lps.resize(pat.size(), 0);
9       int len = 0, i = 1;
10      while (i < pattern.size()) {
11        if (pattern[i] == pattern[len])
12        lps[i++] = ++len;
13        else {
14          if (len != 0) len = lps[len-1];
```

```
        else lps[i++] = 0;
      }
    }
  }
  vector<int> search(T &text) {
    vector<int> matches;
    int i = 0, j = 0;
    while (i < text.size()) {
      if (pattern[j] == text[i]) {
        i++, j++;
        if (j == pattern.size()) {
          matches.push_back(i - j);
          j = lps[j - 1];
        }
      } else {
        if (j != 0) j = lps[j-1];
        else i++;
      }
    }
    return matches;
  }
};

// Prefix function (simple version)
template<class T>
vector<int> prefix(T &S) {
  vector<int> P(S.size());
  P[0] = 0;
  for(int i = 1; i < S.size(); ++i) {
    P[i] = P[i - 1];
    while(P[i] > 0 && S[P[i]] != S[i])
    P[i] = P[P[i] - 1];
    if(S[P[i]] == S[i])
    ++P[i];
  }
  return P;
}

int main(){
  string text, pattern;
  cin >> text >> pattern;
  KMP<string> kmp(pattern);
  vector<int> matches = kmp.search(text);
  cout << matches.size() << '\n';
  for(int x : matches) cout << x << " ";
  cout << '\n';
}

```

KMP.cpp

6.2 Z-Function – $O(n+m)$

```
/*
*Description:* Z-algorithm, all occurrences
in O(n+m)
*Status:* Tested
*/
struct Z {
  int n, m;
  vector<int> z;
  Z(string s) {
    n = s.size();
    z.assign(n, 0);
    int l = 0, r = 0;
    for (int i = 1; i < n; i++) {
      if (i <= r)
      z[i] = min(r-i+1, z[i-l]);
      while (i+z[i] < n
      && s[z[i]] == s[i+z[i]])
      ++z[i];
      if (i+z[i]-1 > r)
      l = i, r = i+z[i]-1;
    }
  }
  Z(string p, string t) {
    string s = p + "#" + t;
    n = p.size();
    m = t.size();
    z.assign(n+m+1, 0);
    int l = 0, r = 0;
    for (int i = 1; i < n+m+1; i++) {
      if (i <= r)
      z[i] = min(r-i+1, z[i-l]);
      while (i+z[i] < n+m+1
      && s[z[i]] == s[i+z[i]])
      ++z[i];
      if (i+z[i]-1 > r)
      l = i, r = i+z[i]-1;
    }
  }
  void p_in_t(vector<int>& ans) {
    for (int i = n+1; i < n+m+1; i++)
    if (z[i] == n)
    ans.push_back(i-n-1);
  }
};

int main(){
  string t, p;
  cin >> t >> p;
  Z z(p, t);
  vector<int> ans;
  z.p_in_t(ans);
  cout << ans.size() << '\n';
  for(int x : ans) cout << x << " ";
  cout << '\n';
}

```

z-function.cpp

6.3 Trie – $O(|s|)$ por operación

```
/*
*Description:* Trie for prefix queries.
O(|s|) per operation.
*Status:* Tested
*/
struct trie {
  vector<vector<ll>> tree;
  vector<ll> counts;
  trie() {
    tree.push_back(vector<ll>(26, -1));
    counts.push_back(0);
  };
  void insert(string &s) {
    ll i = 0, u = 0;
    while(i < s.size()){
      char c = s[i];
      if (tree[u][c-'a'] == -1){
        ll pos = tree.size();
        tree.push_back(vector<ll>(26, -1));
        counts.push_back(0);
        tree[u][c-'a'] = pos;
      }
      i++;
      u = tree[u][c-'a'];
    }
    counts[u]++;
  }
  ll search(string &s){
    ll i = 0, u = 0;
    ll count_ends = 0;
    while(i < s.size()){
      char c = s[i];
      if (tree[u][c-'a'] != -1){
        u = tree[u][c-'a'];
        i++;
      }else break;
    }
    if(i == s.size())
    count_ends += counts[u];
    return count_ends;
  }
};

int main(){
  int n; cin >> n;
  trie t;
  for(int i = 0; i < n; i++){
    string s; cin >> s;
    t.insert(s);
  }
  int q; cin >> q;
  while(q--){
    string s; cin >> s;
    cout << t.search(s) << '\n';
  }
}

```

trie.cpp

6.4 Rolling Hashing

```
template<class T>
struct rolling_hashing {
  int base, mod;
  vector<long long> p, H;
  int n;
  rolling_hashing(const T &s, int b, int m): base(b),
    mod(m), n(s.size()) {
    p.assign(n+1, 1);
```

```
    H.assign(n+1, 0);
    for (int i = 0; i < n; ++i) {
      H[i+1] = (H[i] * base + s[i]) % mod;
      p[i+1] = (p[i] * base) % mod;
    }
  }
  int get(int l, int r) {
    int res = (H[r+1] - H[l]*p[r-l+1]) % mod;
    if (res < 0) res += mod;
    return res;
  }
};

```

rolling_hashing.cpp

6.5 aho-corasick

```
/*
*Description:* Aho-Corasick algorithm for multiple
     pattern matching in text
*Status:* Tested
*/
struct AhoCorasick {
  enum {
    alpha = 26, first = 'a'
  }; // change this!
  struct Node {
    // (nmatches is optional)
    int back, next[alpha], start = -1, end = -1,
     nmatches = 0;
    Node(int v) {
      memset(next, v, sizeof(next));
    }
  };
  vector < Node > N;
  vi backp;
  void insert(string & s, int j) {
    assert(!s.empty());
    int n = 0;
    for (char c: s) {
      int & m = N[n].next[c - first];
      if (m == -1) {
        n = m = sz(N);
        N.emplace_back(-1);
      } else n = m;
    }
    if (N[n].end == -1) N[n].start = j;
    backp.push_back(N[n].end);
    N[n].end = j;
    N[n].nmatches++;
  }
  AhoCorasick(vector < string > & pat): N(1, -1) {
    rep(i, 0, sz(pat)) insert(pat[i], i);
    N[0].back = sz(N);
    N.emplace_back(0);

    queue < int > q;
    for (q.push(0); !q.empty(); q.pop()) {
      int n = q.front(), prev = N[n].back;
      rep(i, 0, alpha) {
        int & ed = N[n].next[i], y = N[prev].next[i];
        if (ed == -1) ed = y;
        else {
          N[ed].back = y;
          N[ed].end == -1 ? N[ed].end = N[y].end: backp[
     N[ed].start] = N[y].end;
          N[ed].nmatches += N[y].nmatches;
          q.push(ed);
        }
      }
    }
  }
  vi find(string word) {
    int n = 0;
    vi res; // ll count = 0;
    for (char c: word) {
      n = N[n].next[c - first];
      res.push_back(N[n].end);
      // count += N[n].nmatches;
    }
    return res;
  }
  vector < vi > findAll(vector < string > & pat, string
     word) {
    vi r = find(word);
    vector < vi > res(sz(word));
    rep(i, 0, sz(word)) {
      int ind = r[i];
      while (ind != -1) {
        res[i - sz(pat[ind]) + 1].push_back(ind);
        ind = backp[ind];
      }
    }
    return res;
  }
};

```

aho-corasick.cpp

7 Programación Dinámica

7.1 Longest Increasing Subsequence – $O(n \log n)$

```
    /*
    *Description:* LIS in O(n log n),
    allows sequence recovery
    *Status:* Highly tested
    */
    template <class I>
    vector<int> LIS(const vector<I> &S) {
      if (S.empty()) return {};
      vector<int> prev(S.size());
      vector<pair<I, int>> res;
      for (int i = 0; i < S.size(); i++) {
        auto it = lower_bound(res.begin(),
        res.end(), pair<I,int>{S[i], i});
        if (it == res.end())
        res.emplace_back(), it = res.end()-1;
        *it = {S[i], i};
        prev[i] = (it == res.begin()
        ? 0 : (it-1)->second);
      }
      int L = res.size(),
      cur = res.back().second;
      vector<int> ans(L);
      while (L--)
      ans[L] = cur, cur = prev[cur];
      return ans;
    }

    int main(){
      int n; cin >> n;
      vector<int> a(n);
      for(int i = 0; i < n; i++) cin >> a[i];
      vector<int> lis_idx = LIS(a);
      cout << lis_idx.size() << '\n';
      for(int i = 0; i < (int)lis_idx.size(); i++)
      cout << lis_idx[i] << " ";
      cout << '\n';
    }

```

LIS.cpp

7.2 LIS of length K– $O(nk \log n)$

```
    //k = searched length, m = compressed size
    vector<fenwick_tree> bit(k + 1, fenwick_tree(m));

    ll answer = 0;
    for (ll x : v) {
        ll value = compress(x); //or already compressed
        vector<ll> current(k+1);
        current[1] = 1;
        for (ll len = 2; len <= k; len++) {
            current[len] = bit[len-1].sum(value-1);
        }
        for (ll len = 1; len <= k; len++) {
            bit[len].add(value, current[len]);
        }
        answer += current[k];
    }

    cout<<answer<<endl;

```

LIS_lenght_k.cpp

7.3 LIS elements participate of Optimal solutions– $O(n \log n)$

```
    /*
    L[i]: longest strictly increasing subsequence ending
      at i
    R[i]: longest strictly increasing subsequence
     starting at i
```

```
    Theroem: best sol force through x = best before x+
     best after x-overlap on x.
    So if optimal==L[i]+R[i]-1(overlap) -> index i its
     part of an optimal solution
    layer: number of LIS-participating elements
    */
    fenwick_max<ll> bit(m + 1);
    fenwick_max<ll> bit2(m + 1);

    vector<ll> L(n), R(n);

    for (ll i = 0; i < n; i++) {
        L[i] = bit.query(v[i] - 1) + 1;
        bit.update(v[i], L[i]);
    }

    for (ll i = n - 1; i >= 0; i--) {
        R[i] = bit2.query(m - v[i]) + 1;
        bit2.update(m - v[i] + 1, R[i]);
    }

    ll k = *max_element(L.begin(), L.end());

    vector<ll> layer(k + 1, 0);

    for (ll i = 0; i < n; i++) {
        if (L[i] + R[i] - 1 == k) layer[L[i]]++;
    }
```

LIS_elements_optimal.cpp

7.4 Knapsack 0/1 – $O(nW)$

```
    void solve(){
      ll n, w;
      cin >> n >> w;
      vector<pair<ll,ll>> v(n);
      for(auto &[a,b] : v) cin >> a >> b;
      vector<ll> ans(w+2,0);
      ll ans_ = 0;
      for(auto [vi, wi] : v){
        for(ll j = w; j >= wi; j--){
          ans[j] = max(ans[j], ans[j-wi]+vi);
          ans_ = max(ans_, ans[j]);
        }
      }
      cout << ans_ << endl;
    }
```

mochila.cpp

8 Misceláneos

8.1 Búsqueda Binaria – $O(\log n)$

```
    int bs(vector<ll>& v, int b){
      int l = 0, r = v.size();
      while(l < r){
        int mid = (l + r) / 2;
        if(v[mid] >= b) r = mid;
        else l = mid + 1;
      }
      return l;
    }
```

binary search.cpp

9 Formulary

9.1 Bits

LSB & Isolation

Isolate LSB: `x & -x` = `x & (~x + 1)`
Remove LSB: `x & (x - 1)`
XOR: `(x + y) - 2*(x and y)`
Full Mask (k bits): `(1 << k) - 1`

Subset Logics

Subset Check: `(A & B) == A`
Iterate Submasks: `for (s=m; s>0; s=(s-1)&m)`
Mask Complement: `~x & mask`

Advanced Bit Arithmetic

Fast Average: `(x & y) + ((x ^y) >> 1)`
Fast Modulo 2^k: `x & ((1 << k) - 1)`
Parity: `__builtin_popcount(x) & 1`

Iota & Sequences

std iota: `std::iota(begin, end, val)` → $val, val+1, \ldots$
Binary → Gray Code: `i ^(i >> 1)`

Gosper's Hack (Next k-bit integer)

Gosper's Hack is used to find the next lexicographical integer with the same number of set bits.
If you have a number x with k bits set, Gosper's Hack gives you the smallest number greater than x that also has exactly k bits set. **Formula:**

```
int c = x & -x, r = x + c;
x = (((r ^x) >> 2) / c) | r;
```

Iterates only through numbers with exactly k bits set.

Bit-Reversal

Mapping: $i \to$ reverse bits of i over W bits
Formula:
$rev(x) = \sum_{i=0}^{W-1}((x \gg i)\&1) \ll (W-1-i)$
Algorithm:

```
int rev = 0;
for(int i=0; i<W; i++) rev = (rev << 1) | ((x
>> i) & 1);
```

GCC Built-ins

`__builtin_popcount(x)` → Counts set bits (1s)
`__builtin_clz(x)` → Leading zeros (Finds $\lfloor \log_2(x) \rfloor$)
`__builtin_ctz(x)` → Trailing zeros (Finds index of LSB)
`__builtin_ffs(x)` → Index of first set bit (1-indexed)

9.2 Number theory

Advanced Modular Arithmetic

Modular Inverse (Prime M): $a^{-1} \equiv a^{M-2} \pmod{M}$
Modular Inverse (General): Solve $ax + My = 1$ via Ext. Euclidean
Modular Division: $(a/b) \pmod{M} = (a \cdot b^{-1}) \pmod{M}$
Euler's Theorem: $a^{\phi(M)} \equiv 1 \pmod{M}$
Fermat's Little Theorem: $a^{M-1} \equiv 1 \pmod{M}$ (for prime M)
Chinese Remainder Theorem (CRT): Solve $x \equiv r_i \pmod{m_i}$