

Project 3: Reinforcement Learning

Table of Contents

- [Introduction](#)
 - [Welcome](#)
 - [Q1: Q-Learning](#)
 - [Q2: Epsilon Greedy](#)
 - [Q3: Bridge Crossing Revisited](#)
 - [Q4: Q-Learning and Pacman](#)
-



Pacman seeks reward.
Should he eat or should he run?
When in doubt, Q-learn.

Introduction

In this project, you will implement Q-learning. You will test your agents first on Gridworld (from class), then apply them to a simulated robot controller (Crawler) and Pacman.

As in previous projects, this project includes an autograder for you to grade your solutions on your machine. This can be run on all questions with the command:

```
python autograder.py
```

It can be run for one particular question, such as q2, by:

```
python autograder.py -q q2
```

It can be run for one particular test by commands of the form:

```
python autograder.py -t test_cases/q2/1-bridge-grid
```

The code for this project is available at the Campus Virtual and contains the following files:

Files you'll edit:

[qlearningAgents.py](#)

Q-learning agents for Gridworld, Crawler and Pacman.

[analysis.py](#)

A file to put your answers to questions given in the project.

Files you should read but NOT edit:

| | |
|--|---|
| <u>mdp.py</u> | Defines methods on general MDPs. |
| <u>learningAgents.py</u> | Defines the base class of <code>QLearningAgent</code> , which your agent will extend. |
| <u>util.py</u> | Utilities, including <code>util.Counter</code> , which is particularly useful for Q-learners. |
| <u>gridworld.py</u> | The Gridworld implementation. |

Files you can ignore:

| | |
|--|---|
| <u>valueIterationAgents.py</u> | A value iteration agent for solving known MDPs. |
| <u>environment.py</u> | Abstract class for general reinforcement learning environments. Used by <u>gridworld.py</u> . |
| <u>graphicsGridworldDisplay.py</u> | Gridworld graphical display. |
| <u>graphicsUtils.py</u> | Graphics utilities. |
| <u>featureExtractors.py</u> | Classes for extracting features on (state,action) pairs. Used for approximate Q-learning agents. |
| <u>textGridworldDisplay.py</u> | Plug-in for the Gridworld text interface. |
| <u>crawler.py</u> | The crawler code and test harness. You will run this but not edit it. |
| <u>graphicsCrawlerDisplay.py</u> | GUI for the crawler robot. |
| <u>autograder.py</u> | Project autograder |
| <u>testParser.py</u> | Parses autograder test and solution files |
| <u>testClasses.py</u> | General autograding test classes |
| test_cases/ | Directory containing the test cases for each question |
| <u>reinforcementTestClasses.py</u> | Project 3 specific autograding test classes |

Files to Edit and Submit: You will fill in portions of [qlearningAgents.py](#), and [analysis.py](#) during the assignment. You should submit these files with your code and comments. Please *do not* change the other files in this distribution or submit any of our original files other than these files.

Evaluation: Your code will be autograded for technical correctness. Please *do not* change the names of any provided functions or classes within the code, or you will wreak havoc on the autograder. However, the correctness of your implementation -- not the autograder's judgements -- will be the final judge of your score. If necessary, we will review and grade assignments individually to ensure that you receive due credit for your work.

Getting Help: You are not alone! If you find yourself stuck on something, contact the course

staff for help. We want these projects to be rewarding and instructional, not frustrating and demoralizing. But, we don't know when or how to help unless you ask.

Gridworld

To get started, run Gridworld in manual control mode, which uses the arrow keys:

```
python gridworld.py -m
```

You will see the two-exit layout from class. The blue dot is the agent. Note that when you press *up*, the agent only actually moves north 80% of the time. Such is the life of a Gridworld agent!

You can control many aspects of the simulation. A full list of options is available by running:

```
python gridworld.py -h
```

The default agent moves randomly

```
python gridworld.py -g MazeGrid
```

You should see the random agent bounce around the grid until it happens upon an exit. Not the finest hour for an AI agent.

Note: The Gridworld MDP is such that you first must enter a pre-terminal state (the double boxes shown in the GUI) and then take the special 'exit' action before the episode actually ends (in the true terminal state called `TERMINAL_STATE`, which is not shown in the GUI). If you run an episode manually, your total return may be less than you expected, due to the discount rate (`-d` to change; 0.9 by default).

Look at the console output that accompanies the graphical output (or use `-t` for all text). You will be told about each transition the agent experiences (to turn this off, use `-q`).

As in Pacman, positions are represented by (x, y) Cartesian coordinates and any arrays are indexed by `[x][y]`, with 'north' being the direction of increasing y , etc. By default, most transitions will receive a reward of zero, though you can change this with the living reward option (`-r`).

Question 1 (5 points): Q-Learning

You will now write a Q-learning agent, which learns by trial and error from interactions with the environment through its `update(state, action, nextState, reward)` method. A stub of a Q-learner is specified in `QLearningAgent` in `qlearningAgents.py`, and you can select it with the option `-a q`. For this question, you must implement the `update`, `computeValueFromQValues`, `getQValue`, and `computeActionFromQValues` methods.

Note: For `computeActionFromQValues`, you should break ties randomly for better behavior. The `random.choice()` function will help. In a particular state, actions that your agent *hasn't* seen before still have a Q-value, specifically a Q-value of zero, and if all of the actions that your agent *has* seen before have a negative Q-value, an unseen action may be optimal.


Important: Make sure that in your `computeValueFromQValues` and `computeActionFromQValues` functions, you only access Q values by calling `getQValue`.

With the Q-learning update in place, you can watch your Q-learner learn under manual control,

using the keyboard:

```
python gridworld.py -a q -k 5 -m
```

Notice that `-k` will control the number of episodes your agent gets to learn. Watch how the agent learns about the state it was just in, not the one it moves to, and "leaves learning in its wake." Hint: to help with debugging, you can turn off noise by using the `--noise 0.0` parameter (though this obviously makes Q-learning less interesting). If you manually steer Pacman north and then east along the optimal path for four episodes, you should see the following Q-values:



Grading: We will run your Q-learning agent and check that it learns the same Q-values and policy as our reference implementation when each is presented with the same set of examples. To grade your implementation, run the autograder:

```
python autograder.py -q q1
```

Question 2 (3 points): Epsilon Greedy

Complete your Q-learning agent by implementing epsilon-greedy action selection in `getAction`, meaning it chooses random actions an epsilon fraction of the time, and follows its current best Q-values otherwise. Note that choosing a random action may result in choosing the best action - that is, you should not choose a random sub-optimal action, but rather *any* random legal action.

```
python gridworld.py -a q -k 100
```

Your final Q-values should resemble those of your value iteration agent, especially along well-traveled paths. However, your average returns will be lower than the Q-values predict because of the random actions and the initial learning phase.

You can choose an element from a list uniformly at random by calling the `random.choice` function. You can simulate a binary variable with probability `p` of success by using `util.flipCoin(p)`, which returns `True` with probability `p` and `False` with probability `1-p`.

To test your implementation, run the autograder:

```
python autograder.py -q q2
```

With no additional code, you should now be able to run a Q-learning crawler robot:

```
python crawler.py
```

If this doesn't work, you've probably written some code too specific to the GridWorld problem and you should make it more general to all MDPs.

This will invoke the crawling robot from class using your Q-learner. Play around with the various learning parameters to see how they affect the agent's policies and actions. Note that the step delay is a parameter of the simulation, whereas the learning rate and epsilon are parameters of your learning algorithm, and the discount factor is a property of the environment.

Question 3 (1 point): Bridge Crossing Analysis

BridgeGrid is a grid world map with the a low-reward terminal state and a high-reward terminal state separated by a narrow "bridge", on either side of which is a chasm of high negative reward. The agent starts near the low-reward state. You can inspect and manually play with the map to get a better idea:

```
python gridworld.py -g BridgeGrid -m
```

Train a completely random Q-learner with the default learning rate on the noiseless BridgeGrid for 50 episodes and observe whether it crosses the bridge.

```
python gridworld.py -a q -k 50 -n 0 -g BridgeGrid -e 1
```

Now try the same experiment with an epsilon of 0. Is there an epsilon and a learning rate for which it is highly likely (greater than 99%) that the optimal policy will be learned after 50 iterations? `question3()` in `analysis.py` should return EITHER a 2-item tuple of (`epsilon`, `learning rate`) OR the string 'NOT POSSIBLE' if there is none. Epsilon is controlled by `-e`, learning rate by `-l`.

Note: Your response should be not depend on the exact tie-breaking mechanism used to choose actions. This means your answer should be correct even if for instance we rotated the entire bridge grid world 90 degrees.

To grade your answer, run the autograder:

```
python autograder.py -q q3
```

Question 4 (1 point): Q-Learning and Pacman

Time to play some Pacman! Pacman will play games in two phases. In the first phase, *training*, Pacman will begin to learn about the values of positions and actions. Because it takes a very long time to learn accurate Q-values even for tiny grids, Pacman's training games run in quiet mode by default, with no GUI (or console) display. Once Pacman's training is complete, he will enter *testing* mode. When testing, Pacman's `self.epsilon` and `self.alpha` will be set to 0.0, effectively stopping Q-learning and disabling exploration, in order to allow Pacman to exploit his learned policy. Test games are shown in the GUI by default. Without any code changes you should be able to run Q-learning Pacman for very tiny grids as follows:

```
python pacman.py -p PacmanQAgent -x 2000 -n 2010 -l smallGrid
```

Note that `PacmanQAgent` is already defined for you in terms of the `QLearningAgent` you've already written. `PacmanQAgent` is only different in that it has default learning parameters that are more effective for the Pacman problem (`epsilon=0.05`, `alpha=0.2`, `gamma=0.8`). You will receive full credit for this question if the command above works without exceptions and your agent wins at least 80% of the time. The autograder will run 100 test games after the 2000

training games.

Hint: If your `QLearningAgent` works for `gridworld.py` and `crawler.py` but does not seem to be learning a good policy for Pacman on `smallGrid`, it may be because your `getAction` and/or `computeActionFromQValues` methods do not in some cases properly consider unseen actions. In particular, because unseen actions have by definition a Q-value of zero, if all of the actions that *have* been seen have negative Q-values, an unseen action may be optimal. Beware of the `argmax` function from `util.Counter`!

Note: To grade your answer, run:

```
python autograder.py -q q4
```

Note: If you want to experiment with learning parameters, you can use the option `-a`, for example `-a epsilon=0.1,alpha=0.3,gamma=0.7`. These values will then be accessible as `self.epsilon`, `self.gamma` and `self.alpha` inside the agent.

Note: While a total of 2010 games will be played, the first 2000 games will not be displayed because of the option `-x 2000`, which designates the first 2000 games for training (no output). Thus, you will only see Pacman play the last 10 of these games. The number of training games is also passed to your agent as the option `numTraining`.

Note: If you want to watch 10 training games to see what's going on, use the command:

```
python pacman.py -p PacmanQAgent -n 10 -l smallGrid -a numTraining=10
```

During training, you will see output every 100 games with statistics about how Pacman is faring. Epsilon is positive during training, so Pacman will play poorly even after having learned a good policy: this is because he occasionally makes a random exploratory move into a ghost. As a benchmark, it should take between 1,000 and 1400 games before Pacman's rewards for a 100 episode segment becomes positive, reflecting that he's started winning more than losing. By the end of training, it should remain positive and be fairly high (between 100 and 350).

Make sure you understand what is happening here: the MDP state is the *exact* board configuration facing Pacman, with the now complex transitions describing an entire ply of change to that state. The intermediate game configurations in which Pacman has moved but the ghosts have not replied are *not* MDP states, but are bundled in to the transitions.

Once Pacman is done training, he should win very reliably in test games (at least 90% of the time), since now he is exploiting his learned policy.

However, you will find that training the same agent on the seemingly simple `mediumGrid` does not work well. In our implementation, Pacman's average training rewards remain negative throughout training. At test time, he plays badly, probably losing all of his test games. Training will also take a long time, despite its ineffectiveness.

Pacman fails to win on larger layouts because each board configuration is a separate state with separate Q-values. He has no way to generalize that running into a ghost is bad for all positions. Obviously, this approach will not scale.

Submission

You're not done yet! Follow your instructor's guidelines to receive credit on your project!