

Chap 5.1

```
1 md"# Chap 5.1"
```

```
1 versioninfo()
```

```
Julia Version 1.11.0
Commit 501a4f25c2b (2024-10-07 11:40 UTC)
Build Info:
  Official https://julialang.org/ release
Platform Info:
  OS: Linux (x86_64-linux-gnu)
  CPU: 32 × Intel(R) Xeon(R) CPU E5-2630 v3 @ 2.40GHz
  WORD_SIZE: 64
  LLVM: libLLVM-16.0.6 (ORCJIT, haswell)
Threads: 16 default, 0 interactive, 8 GC (on 32 virtual cores)
Environment:
  JULIA_PKG_SERVER = https://mirrors.tuna.tsinghua.edu.cn/julia
  JULIA_REVISE_WORKER_ONLY = 1
```

```
1 html""
2 <style>
3     main {
4         margin: 0 auto;
5         max-width: max(1800px, 75%);
6         padding-left: max(5px, 1%);
7         padding-right: max(350px, 10%);
8     }
9 </style>
10 ""
```

Table of Contents

Chap 5.1

Set defaults for plot and logging.

5.1 Spurious association.

Code 5.1

Code 5.2

Code 5.3

Code 5.4

Code 5.5

Code 5.6

Code 5.7

Code 5.8

Code 5.9

Code 5.10

Code 5.11

Code 5.12

Code 5.13

Code 5.14

Code 5.15

Code 5.18

Code 5.19

Code 5.20 - 5.22

Code 5.23

Code 5.25

Code 5.26

```
1 begin
2     using Pkg, DrWatson
3     using PlutoUI
4     TableOfContents()
5 end
```

Note

Dagitty.jl needs to be replaced by CausalInference.jl. Dagitty is not part of SR2TuringPluto.jl.

```
1 md"
2
3 !!! note
4
5 Dagitty.jl needs to be replaced by CausalInference.jl. Dagitty is not part of
  SR2TuringPluto.jl."
```

```
1 #Pkg.activate(expanduser("~/julia/dev/SR2TuringPluto"))
```

```
1 begin
2     using Distributions
3     using Optim
4     using StatsPlots
5     using StatsBase
6     using LaTeXStrings
7     using CSV
8     using DataFrames
9     using LinearAlgebra
10    using Logging
11    using Random
12    using Turing
13    using Dagitty
14    using StatisticalRethinking
15    using StatisticalRethinkingPlots
16 end
```

Error requiring `Turing` from `StatisticalRethinking`
exception:

Error message from Main

LoadError: UndefVarError: `TuringOptimExt` not defined in
`StatisticalRethinking`

Suggestion: check for spelling errors or missing imports.

Hint: a global variable of this name also exists in TuringOptimExt.

in expression starting at
/y/home/huangyu/.julia/packages/StatisticalRethinking/Bzph1/src/require
/turing/turing_optim_sample.jl:3

in expression starting at
/y/home/huangyu/.julia/packages/StatisticalRethinking/Bzph1/src/require
/turing/turing.jl:7

Stack trace

Here is what happened, the most recent locations are first:

- 1. include(mod::Module, _path::String)
from `julia` → `Base.jl:557` [docs](#)
- 2. include(x::String)
from `StatisticalRethinking` → `StatisticalRethinking.jl:1` [docs](#)
- 3. from `turing.jl:7`
- 4. include(mod::Module, _path::String)
from `julia` → `Base.jl:557` [docs](#)
- 5. include(x::String)
from `StatisticalRethinking` → `StatisticalRethinking.jl:1` [docs](#)
- 6. from `Requires.jl:40`
- 7. eval

Set defaults for plot and logging.

```
1 begin
2     Plots.default(label=false)
3     #Logging.disable_logging(Logging.Warn);
4 end;
```

5.1 Spurious association.

Code 5.1

[-0.60629, -0.686699, -0.204241, -1.41039, 0.599857, -0.284651, 1.24313, 0.439037, 2.9317

```
1 begin
2   d = CSV.read(sr_datadir("WaffleDivorce.csv"), DataFrame)
3   d[:,D] = standardize(ZScoreTransform, d.Divorce)
4   d[:,M] = standardize(ZScoreTransform, d.Marriage)
5   d[:,A] = standardize(ZScoreTransform, d.MedianAgeMarriage);
6 end
```

Code 5.2

1.2436303013880823

```
1 std(d.MedianAgeMarriage)
```

Code 5.3

m5_1 (generic function with 2 methods)

```
1 @model function m5_1(A, D)
2   σ ~ Exponential(1)
3   a ~ Normal(0, 0.2)
4   bA ~ Normal(0, 0.5)
5   μ = @. a + bA * A
6   D ~ MvNormal(μ, σ)
7 end
```

	variable	mean	min	median	max	nmissing	eltype
1	:a	-0.00665887	-0.550246	-0.00575653	0.58982	0	Float64
2	:bA	0.00168184	-1.71989	0.00890987	1.40209	0	Float64
3	:σ	1.06709	0.000728128	0.732709	6.1367	0	Float64

```
1 begin
2   @time m5_1t = sample(m5_1(d.A, d.D), NUTS(), 1000)
3   m5_1_df = DataFrame(m5_1t)
4   @time prior = sample(m5_1([0], [0]), Prior(), 1000)
5   prior_df = DataFrame(prior)
6   describe(prior_df)
7 end
```

Sampling 100%

Found initial step size
ϵ: 0.05


Sampling 100%

0.421065 seconds (1.45 M allocations: 120.137 MiB, 7.21% gc time)
0.209363 seconds (590.67 k allocations: 26.836 MiB) ?

Code 5.4

```
1 let
2   # calculate μ for every prior sample on age=-2 and age=2
3
4   bounds = [-2, 2]
5   μ = StatisticalRethinking.link(prior_df, [:a, :bA], bounds)
6   μ = hcat(μ...);
7
8   p = plot(xlab="Median age marriage (std)", ylab="Divorce rate (std)")
9   for μp ∈ first(eachrow(μ), 50)
10    plot!(bounds, μp; c=:black, alpha=0.3)
11  end
12 end
```

Code 5.5



```
1 let
2   A_seq = range(-3, 3.2; length=30)
3
4   μ = StatisticalRethinking.link(m5_1_df, [:a, :bA], A_seq)
5   μ = hcat(μ...)
6   μ_mean = mean.(eachcol(μ))
7   μ_PI = PI.(eachcol(μ))
8   μ_PI = vcat(μ_PI'...)
9
10  @df d scatter(:A, :D; xlabel="Median age marriage (std)",
11               ylabel="Divorce rate (std)")
12  plot!(A_seq, [μ_mean μ_mean]; c=:black, fillrange=μ_PI, fillalpha=0.2)
13 end
```

Code 5.6

m5_2 (generic function with 2 methods)


```
1 @model function m5_2(M, D)
2   σ ~ Exponential(1)
3   a ~ Normal(0, 0.2)
4   bM ~ Normal(0, 0.5)
5   μ = @. a + bM * M
6   D ~ MvNormal(μ, σ)
7 end
```

	variable	mean	min	median	max	nmissing	eltype
1	:a	0.00353923	-0.397905	0.00728162	0.414083	0	Float64
2	:bM	0.349397	-0.147691	0.354223	0.692693	0	Float64
3	:σ	0.948557	0.701307	0.943838	1.2883	0	Float64

```
1 begin
2   m5_2t = sample(m5_2(d.M, d.D), NUTS(), 1000)
3   m5_2_df = DataFrame(m5_2t)
4   describe(m5_2_df)
5 end
```


Sampling

Found initial step size
ε: 0.4



```
1 let
2   M_seq = range(-1.74, 2.8; length=30)
3
4   μ = StatisticalRethinking.link(m5_2_df, [:a, :bM], M_seq)
5   μ = hcat(μ...)
6   μ_mean = mean.(eachcol(μ))
7   μ_PI = PI.(eachcol(μ))
8   μ_PI = vcat(μ_PI'...)
9
10  @df d scatter(:M, :D; xlabel="Marriage rate (std)", ylabel="Divorce rate (std)")
11  plot!(M_seq, [μ_mean μ_mean]; c=:black, fillrange=μ_PI, fillalpha=0.2)
12 end
```

Code 5.7



```
1 let
2   g = Dagitty.DAG(:A => :M, :A => :D, :M => :D)
3   drawdag(g, [0, 1, 2], [0, 1, 0])
4 end
```

Code 5.8

```
[ConditionalIndependence(:D, :M, [:A])]

1 let
2   g = Dagitty.DAG(:A => :M, :A => :D)
3   implied_conditional_independencies(g)
4 end
```

Code 5.9

```
[]

1 let
2   g = Dagitty.DAG(:A => :M, :A => :D, :M => :D)
3   implied_conditional_independencies(g)
4 end
```

Code 5.10

m5_3 (generic function with 2 methods)

```
1 @model function m5_3(A, M, D)
2   σ ~ Exponential(1)
3   a ~ Normal(0, 0.2)
4   bA ~ Normal(0, 0.5)
5   bM ~ Normal(0, 0.5)
6   μ = @. a + bA * A + bM * M
7   D ~ MvNormal(μ, σ)
8 end
```


	variable	mean	min	median	max	nmissing	eltype
1	:a	-0.00320073	-0.3646	-0.00389141	0.293064	0	Float64
2	:bA	-0.602126	-1.0686	-0.606997	0.010838	0	Float64
3	:bM	-0.0536286	-0.67119	-0.0565273	0.481899	0	Float64
4	:σ	0.830328	0.615499	0.820962	1.26056	0	Float64

```
1 begin
2   m5_3t = sample(m5_3(d.A, d.M, d.D), NUTS(), 1000)
3   m5_3_df = DataFrame(m5_3t)
4   describe(m5_3_df)
5 end
```

Sampling


Found initial step size
ε: 0.05

Code 5.11



```
1 coeftab_plot(m5_1_df, m5_2_df, m5_3_df; pars=(:bA, :bM),
2   names=["m5.1", "m5.2", "m5.3"])
```

Code 5.12



```
1 let
2   N = 50
3   age = rand(Normal(), N)
4   mar = rand.(Normal.(-age))
5   div = rand.(Normal.(age));
6
7   s1 = DataFrame(sample(m5_1(age, div), NUTS(), 1000))
8   s2 = DataFrame(sample(m5_2(mar, div), NUTS(), 1000))
9   s3 = DataFrame(sample(m5_3(age, mar, div), NUTS(), 1000));
10  coeftab_plot(s1, s2, s3; pars=(:bA, :bM), names=["s1", "s2", "s3"])
11 end
```

Sampling


Found initial step size
ε: 0.4

Sampling

Found initial step size
ε: 0.4

Sampling

Found initial step size
ε: 0.4



```
1 let
2   N = 50
3   age = rand(Normal(), N)
4   mar = rand.(Normal.(-age))
5   div = rand.(Normal.(age .+ mar));
6
7   s1 = DataFrame(sample(m5_1(age, div), NUTS(), 1000))
8   s2 = DataFrame(sample(m5_2(mar, div), NUTS(), 1000))
9   s3 = DataFrame(sample(m5_3(age, mar, div), NUTS(), 1000));
10  coeftab_plot(s1, s2, s3; pars=(:bA, :bM), names=["s1", "s2", "s3"])
11 end
```

Sampling

Found initial step size
ϵ: 0.4

Sampling

Found initial step size
ϵ: 0.4

Sampling

Found initial step size
ϵ: 0.025

Code 5.13

m5_4 (generic function with 2 methods)

```
1 @model function m5_4(A, M)
2   σ ~ Exponential(1)
3   a ~ Normal(0, 0.2)
4   bAM ~ Normal(0, 0.5)
5   μ = @. a + bAM * A
6   M ~ MvNormal(μ, σ)
7 end
```



	a	bAM	σ
1	-0.163794	-0.69913	0.680176
2	-0.0146904	-0.738857	0.716546
3	-0.0146904	-0.738857	0.716546
4	0.100295	-0.696143	0.727446
5	-0.0477447	-0.741093	0.76938
6	0.0909004	-0.770785	0.702593
7	0.106044	-0.813987	0.637198
8	-0.10963	-0.585643	0.712284
9	0.0655574	-0.837556	0.683335
10	0.155692	-0.773712	0.780996
more			
1000	-0.0142223	-0.884129	0.774043

```
1 begin
2   m5_4t = sample(m5_4(d.A, d.M), NUTS(), 1000)
3   m5_4_df = DataFrame(m5_4t);
4 end
```

Sampling


Found initial step size
ε: 0.2

Code 5.14



```
1 let
2   mu = StatisticalRethinking.link(m5_4_df, [:a, :bAM], d.A);
3   mu = hcat(mu...)
4   mu_mean = mean.(eachcol(mu))
5   mu_resid = mu_mean .- d.M;
6
7   # +
8   # Side-note: how to plot the residuals
9   # getting yerr - list of 2-tuples with distance to the regression line
10  yerr = collect(zip(-clamp.(mu_resid, -Inf, -0.0), clamp.(mu_resid, 0, Inf)));
11
12  plot(d.A, mu_mean; xlabel="Age at marriage (std)", ylabel="Marriage rate (std)")
13  scatter!(d.A, d.M)
14  scatter!(d.A, d.M; yerr=yerr, markersize=0)
15 end
```

Code 5.15



```
1 let
2
3   # explicit link form before I improved it
4
5   mu = [
6       @. r.a + r.bA * d.A + r.bM * d.M
7       for r in eachrow(m5_3_df)
8   ]
9
10  mu = vcat(mu'...)
11  mu_mean = mean.(eachcol(mu))
12  mu_PI = PI.(eachcol(mu))
13  mu_PI = vcat(mu_PI'...);
14
15  D_sim = [
16      rand(MvNormal((@. r.a + r.bA * d.A + r.bM * d.M), r.σ))
17      for r in eachrow(m5_3_df)
18  ]
19  D_sim = vcat(D_sim'...);
20  D_PI = PI.(eachcol(D_sim))
21  D_PI = vcat(D_PI'...);
22  # -
23
24  # Code 5.16
25
26  yerr = mu_PI[:,2] .- mu_mean
27  scatter(d.D, mu_mean; xlabel="Observed divorce", ylabel="Predicted divorce",
28          yerr=yerr)
29  plot!(x->x; style=:dash)
30
31  # Code 5.17
32
33  loc_flags = d.Loc .∈ ("ID", "UT", "RI", "ME");
34  loc_idxes = findall(loc_flags);
35  anns = [
36      (d.D[idx] - 0.1, mu_mean[idx], (d.Loc[idx], 8))
37      for idx in loc_idxes
38  ]
39  annotate!(anns)
40 end
```

Code 5.18

	variable	mean	min	median	max	nmissing	eltype
1	:y	0.15905	-3.48325	0.0670999	3.66854	0	Float64
2	:x_real	0.0826649	-2.13272	-0.0501045	2.71956	0	Float64
3	:x_spur	-0.0222719	-3.59033	-0.140535	3.03337	0	Float64

```
1 let
2   N = 100
3   x_real = rand(Normal(), N)
4   x_spur = rand.(Normal.(x_real))
5   y = rand.(Normal.(x_real))
6   df = DataFrame(:y => y, :x_real => x_real, :x_spur => x_spur)
7   describe(df)
8 end
```

Code 5.19

m5_3A (generic function with 2 methods)

```
1 @model function m5_3A(A, M, D)
2   # A → D ← M
3   σ ~ Exponential(1)
4   a ~ Normal(0, 0.2)
5   bA ~ Normal(0, 0.5)
6   bM ~ Normal(0, 0.5)
7   μ = @. a + bA * A + bM * M
8   D ~ MvNormal(μ, σ)
9   # A → M
10  σ_M ~ Exponential(1)
11  aM ~ Normal(0, 0.2)
12  bAM ~ Normal(0, 0.5)
13  μ_M = @. aM + bAM * A
14  M ~ MvNormal(μ_M, σ_M)
15 end
```


	variable	mean	min	median	max	nmissing	eltype
1	:a	0.00248769	-0.28923	0.00456427	0.348169	0	Float64
2	:aM	0.000473606	-0.305489	0.000514117	0.292643	0	Float64
3	:bA	-0.612116	-1.06976	-0.612527	-0.0825706	0	Float64
4	:bAM	-0.692251	-0.991939	-0.689197	-0.396236	0	Float64
5	:bM	-0.0656085	-0.592612	-0.0655231	0.480857	0	Float64
6	:σ	0.823608	0.602889	0.81688	1.13432	0	Float64
7	:σ_M	0.712641	0.509175	0.705253	1.12785	0	Float64

```
1 begin
2   d1 = CSV.read(sr_datadir("WaffleDivorce.csv"), DataFrame)
3   d2 = DataFrame(
4     :D => standardize(ZScoreTransform, d1.Divorce),
5     :M => standardize(ZScoreTransform, d1.Marriage),
6     :A => standardize(ZScoreTransform, d1.MedianAgeMarriage),
7   );
8
9   m5_3At = sample(m5_3A(d2.A, d2.M, d2.D), NUTS(), 1000)
10  m5_3A_df = DataFrame(m5_3At)
11  describe(m5_3A_df)
12 end
```


Sampling

Found initial step size
ε: 0.2

Code 5.20 - 5.22




```
1 let
2   A_seq = range(-2, 2; length=30);
3   global s_M, s_D = [], []
4
5   for r ∈ eachrow(m5_3A_df)
6       M = rand(MvNormal((@. r.aM + r.bAM * A_seq), r.σ_M))
7       D = rand(MvNormal((@. r.a + r.bA * A_seq + r.bM * M), r.σ))
8       push!(s_M, M)
9       push!(s_D, D)
10  end
11
12  s_M = vcat(s_M'...)
13  s_D = vcat(s_D'...);
14  μ_D = mean.(eachcol(s_D))
15  PI_D = vcat(PI.(eachcol(s_D))'...)
16
17  plot(
18      A_seq, [μ_D, μ_D];
19      fillrange=PI_D, fillalpha=0.2, color=:black,
20      xlabel="manupulated A", ylabel="counterfactual D",
21      title="Total counterfactual effect of A on D"
22  )
23 end
```



```
1 let
2   μ_M = mean.(eachcol(s_M))
3   PI_M = vcat(PI.(eachcol(s_M))'...)
4
5   plot(
6       A_seq, [μ_M, μ_M];
7       fillrange=PI_M, fillalpha=0.2, color=:black,
8       xlabel="manupulated A", ylabel="counterfactual M",
9       title="Total counterfactual effect of A on M"
10  )
11 end
```

Code 5.23



```
1 let
2   sim2_A = @. ([20, 30] - 26.1) / 1.24;
3   s2_M, s2_D = [], []
4
5   for r ∈ eachrow(m5_3A_df)
6     M = rand(MvNormal((@. r.aM + r.bAM * sim2_A), r.σ_M))
7     D = rand(MvNormal((@. r.a + r.bA * sim2_A + r.bM * M), r.σ))
8     push!(s2_M, M)
9     push!(s2_D, D)
10  end
11
12  s2_M = vcat(s2_M'...)
13  s2_D = vcat(s2_D'...);
14  mean(s2_D[:,2] - s2_D[:,1])
15  # -
16
17  # Code 5.24
18
19  # +
20  M_seq = range(-2, 2; length=30)
21  s_D = []
22
23  for r ∈ eachrow(m5_3A_df)
24    # A is zero, so, we drop it from the μ term
25    D = rand(MvNormal((@. r.a + r.bM * M_seq), r.σ))
26    push!(s_D, D)
27  end
28
29  s_D = vcat(s_D'...);
30
31  μ_D = mean.(eachcol(s_D))
32  PI_D = vcat(PI.(eachcol(s_D))'...)
33
34  plot(
35    M_seq, [μ_D, μ_D];
36    fillrange=PI_D, fillalpha=0.2, color=:black,
37    xlabel="manipulated M", ylabel="counterfactual D",
38    title="Total counterfactual effect of M on D"
39  )
40 end
```

Code 5.25

```
1 A_seq = range(-2, 2; length=30);
```

Code 5.26

1000x30 Matrix{Float64}:

1.1554	-0.0967398	1.7475	-0.609207	...	-0.155994	-1.4304	-2.64872
0.627854	1.03038	1.57602	0.656687		-0.980522	-0.444945	-1.34432
2.51643	0.668524	1.31688	3.21321		-1.37382	-1.49756	-0.481347
1.38541	1.63349	2.08705	1.55058		-0.473135	-0.10908	0.0909892
1.64257	2.29597	0.0414396	1.08773		-1.25094	0.209401	-1.51585
3.60858	2.7533	0.00811689	1.32349	...	-2.16212	-1.80128	-2.15166
-0.173748	2.19753	2.16598	1.82233		-1.2943	-0.463673	-0.411417
:				⋮			
2.01813	0.102639	0.982616	1.00084		-0.113485	-1.75049	-0.737452
0.724954	0.986207	1.17019	1.6036	...	-1.37783	0.619275	0.22252
-1.17693	0.765622	0.706637	1.789		-3.3898	-0.931097	-1.42229
1.58779	1.89716	2.47812	0.868086		-1.89673	-1.57939	-0.945112
-0.465909	3.01401	1.83149	0.806376		-2.61712	-1.68308	-2.02923
1.66261	1.32864	0.0211641	1.70964		0.496661	-0.487398	-1.06269

```
1 let
2     s_M = [
3         rand(MvNormal((@. r.aM + r.bAM * A_seq), r.σ_M))
4         for r ∈ eachrow(m5_3A_df)
5     ]
6     s_M = vcat(s_M'...);
7
8     # Code 5.27
9
10    s_D = [
11        rand(MvNormal((@. r.a + r.bA * A_seq + r.bM * M), r.σ))
12        for (r, M) ∈ zip(eachrow(m5_3A_df), eachrow(s_M))
13    ]
14    s_D = vcat(s_D'...);
15 end
```