



www.zbra.com.br

Stomp 

Filipe Sbragio – filipe.sbragio@zbra.com.br

Márcio Hariki – marcio.hariki@zbra.com.br



Outline

- STOMP
- Why use STOMP?
- Communication
- Headers
- Connection
- Heartbeat
- Frames



STOMP



STOMP



*Mandatory impact image

Why use STOMP?




Stomp 



Communication



Communication



Headers

COMMAND

content-length:50


content-type:text/html;charset=utf-16

receipt:arbitraryString


receipt:y-u-repeat-header?

Body

^@



Connection




Connection



CONNECT(or STOMP)
accept-version:1.0,1.1,2.0
host:hostname.com
login:mylogin
passcode:mypasscode
heart-beat:0,0

Body
^@



CONNECTED
version:1.1
session:s120
server:Apache/1.3.9*(apache
server)
heart-beat:0,0

Body
^@

Connection (StompJS)

Stomp Client

```
let url = "ws://localhost:61614/stomp";  
let client = Stomp.client(url);
```

Connection

```
client.connect(login, passcode, connectCallback, errorCallback);  
  
var headers = {  
  'login': 'mylogin',  
  'passcode': 'mypasscode',  
  // additional header  
  'client-id': 'my-client-id'  
};  
client.connect(headers, connectCallback, errorCallback);
```

Heartbeat

CONNECT

heart-beat:<clientMax>,<clientIdeal>



CONNECTED

heart-beat:<serverMax>,<serverIdeal>

Heartbeat

CONNECT

heart-beat:50,80



CONNECTED

heart-beat:100,150

Client Frames

SEND

destination:/zbra-chat/messages/1

content-length:50

content-type:application/json

irrelevant-header:isIrrelevant

```
{ user: { username: 'zbra054', email: 'zbra054@haha.com' }, text: 'Hello! ' }  
^@
```

Client Frames

SEND

destination:/zbra-chat/messages/1

content-length:50

content-type:application/json

irrelevant-header:isIrrelevant

```
{ user: { username: 'zbra054', email: 'zbra054@haha.com' }, text: 'Hello! ' }  
^@
```

SUBSCRIBE

Id:0

destination:/queue/messages/1

ack:client

^@

Client Frames

SEND

destination:/zbra-chat/messages/1

content-length:50

content-type:application/json

irrelevant-header:isIrrelevant

```
{ user: { username: 'zbra054', email: 'zbra054@haha.com' }, text: 'Hello! ' }  
^@
```

SUBSCRIBE

Id:0

destination:/queue/messages/1

ack:client

^@

UNSUBSCRIBE

id:0

^@

Client Frames

SEND

```
client.send("/queue/test", {priority: 9}, "Hello, STOMP");
```

SUBSCRIBE & UNSUBSCRIBE

```
let callback = function(message) {  
  if (message.body) {  
    alert("got message with body " + message.body)  
  } else {  
    alert("got empty message");  
  }  
};  
  
var subscription = client.subscribe("/queue/test", callback);  
subscription.unsubscribe();
```

Client Frames

ACK

id:12345

transaction:tx1

^@

Client Frames

ACK

id:12345

transaction:tx1

^@

NACK

id:12345

transaction:tx1

^@

Client Frames

ACK

id:12345

transaction:tx1

^@

NACK

id:12345

transaction:tx1

^@

DISCONNECT

receipt:xd

^@

Client Frames

ACK

id:12345

transaction:tx1

^@

NACK

id:12345

transaction:tx1

^@

DISCONNECT

receipt:xd

^@

```
var subscription = client.subscribe("/queue/test",  
  function(message) {  
    message.ack();  
  },  
  {ack: 'client'}  
);
```

Transaction Frames

BEGIN

transaction:tx1

^@

Transaction Frames

BEGIN

transaction:tx1

^@

COMMIT

transaction:tx1

^@

Transaction Frames

BEGIN

transaction:tx1

^@

COMMIT

transaction:tx1

^@

ABORT

transaction:tx1

^@

Transaction Frames

BEGIN

transaction:tx1

^@

COMMIT

transaction:tx1

^@

ABORT

transaction:tx1

^@

```
var subscription = client.subscribe("/queue/test",  
  function(message) {  
    var tx = client.begin();  
    message.ack({ transaction: tx.id, receipt: 'my-receipt' });  
    tx.commit();  
  },  
  {ack: 'client'}  
);
```

Server Frames

MESSAGE

subscription:0

message-id:007

destination:/queue/messages/1

content-type:application/json

```
{ user: { username: 'zbra054', email: 'zbra054@haha.com' }, text: 'Hello! ' }  
^@
```

Server Frames

MESSAGE

subscription:0

message-id:007

destination:/queue/messages/1

content-type:application/json

```
{ user: { username: 'zbra054', email: 'zbra054@haha.com' }, text: 'Hello! ' }  
^@
```

```
@MessageMapping("/join/{roomId}")  
@SendToUser(value = "/queue/room/{roomId}")  
public Room joinRoom(@DestinationVariable String roomId, @Payload User user) {  
    final Optional<Room> room = roomRepository.findById(roomId);  
    if (room.isPresent()) {  
        room.get().getUsers().add(user);  
        return room.get();  
    }  
  
    return null;  
}
```

Server Frames

RECEIPT

receipt-id:xd

^@

Server Frames

RECEIPT

receipt-id:xd

^@

ERROR

receipt-id:xd

content-type:application/json

content-length:171

message:message could not be processed

{ faultReason: 'User zbra054 has been removed, try using zbra54' }

^@

Questions





www.zbra.com.br

Filipe Sbragio - filipe.sbragio@zbra.com.br

Márcio Hariki - marcio.hariki@zbra.com.br

