

EVERROOF®

WEBSEAL

Tape

EVERROOF® Webseal is a pressure sensitive, 30 year cycle, duct joint and general purpose rolled sealant. EVERROOF® Webseal provides an instant aggressive grip to most surfaces including sheet metal, duct board, and flex duct for indoor applications. The Butyl adhesive/sealant is a 100% solids sealant that stays flexible and does not release from the substrate.

APPLICATION

METHOD: Cut desired length, peel off release liner, and apply. (Removal or repositioning may damage 1602 and surface). Overlap at ends. Rub down with heavy pressure to assure complete contact.

PREPARATION: Surface must be clean and dry, oil and dust free.

PAINTING: Use epoxy or water based paint or coating. Use weatherized paint when applied to exterior surfaces.

TEMPERATURE: 35°F to 110° F (1.67°C to 43.33°C)

STORAGE

TEMPERATURE: 35°F to 110° F (1.67°C to 43.33°C)

SHELF LIFE: 24 months

FLAMMABILITY: Non-flammable

SAFETY

Surfaces must be clean and free of moisture and contamination. Do not apply this product in weather exposed area without suitable paint or coating. Do not apply this product where temperatures will exceed 200°F (93.33°C). Keep out of reach of children. Review MSDS for safety information prior to use. DO NOT use where acidic or alkaline chemicals are present (ie., lab fume hood, vents, etc.).

FOR INDUSTRIAL PROFESSIONAL USE ONLY.

TECHNICAL DATA

Appearance	White fabric substrate with gray adhesive/sealant
Backing	Dupont Sontara™ Polyester
Thickness	25 mils
Sealant Material	Modified butyl
Peel Strength	17 lbs/ linear inch
Tensile Strength	790 psi avg.
Elongation	560% avg.
Flexibility	Excellent, no cracking
Bonding Time	Immediate aggressive grip, full bond 24 hours
Time to Test	Immediate
Service Temperature	-20°F to 200°F (-28.89°C to 93.33°C)
Surface Burning, (ASTM E-84):	
Flame Spread	15
Smoke Developed	15
Water Resistance	Excellent. Surface must be dry before application.
Mildew Resistance	Mold and mildew resistant.
VOC	0 g/l
Pressure Classes	SMACNA ½, 1, 2, 3, 4 and 6 inches w.g.

TECHNICAL
DATA SHEET

EVERROOF®
WEBSEAL



THIS PAGE IS INTENTIONALLY LEFT BLANK

Please read all information in the general guidelines, technical data sheets, application guide, and safety data sheets (SDS) before applying material. Published technical data and instructions are subject to change without notice. Contact your local EVERROOF® representative or visit our website for current technical data and instructions. **DISCLAIMER:** All guidelines, recommendations, statements, and technical data contained herein are based on information and tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. It is the user's responsibility to satisfy himself, by his own information and tests, to determine suitability of the product for his own intended use, application and job situation and user assumes all risk and liability resulting from his use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones that may exist. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements, whether verbal or in writing, other than those contained herein shall not be binding upon the manufacturer, unless in writing and signed by a corporate officer of the manufacturer. Technical and application information is provided for the purpose of establishing a general profile of the material and proper application procedures. Test performance results were obtained in a controlled environment and EVERROOF® makes no claim that these tests or any other tests, accurately represent all environments.