



CLOSED CORNER FLASHING SET IN BED OF URETHANE & FASTENED W/SPECIFIED FASTENERS

NOTE: ANY SECUREMENT OF UNITS OR SUPPORTS INTO THE HORIZONTAL PLATFORM SURFACE SHALL BE THROUGH SOLID 1/4" NEOPRENE GASKET TO CREATE A PRESSURE SEAL. APPLY EVERROOF FAST FLASH ON THE UNDERSIDE AND TOP OF GASKET IMMEDIATELY AND FILL BOLT HOLES WITH SEALANT PRIOR TO INSTALLATION BOLTS.

## **PLATFORM DETAIL**



Phone: 702-966-9961 | www.EverRoof.com

The information contained herein is for reference only, and is designed for users having the requisite knowledge, skill, and experience to determine suitability of a product's use and application. Conditions affecting application and use will vary, and users are required to make their own independent determination regarding suitability. No warranties or representations of any kind, whether express or implied, including warranties of merchantability or fitness for a particular purpose are made. EVERROOF assumes no obligation or liability with regard to the descriptions, designs, or information provided herein. All information is designed and intended to be reviewed in conjunction with other detailed specifications, application guidelines, technical bulletins, technical data sheets, and low slope restoration system specifications.