

**EVERROOF ADHESIVE PRIMER****ACRYLIC PRIMER / ADHESIVE****DESCRIPTION**

EVERROOF ADHESIVE PRIMER is a waterborne modified acrylic primer specifically designed to provide maximum adhesion of polyester reinforcing fabric and coatings to various construction surfaces. EVERROOF ADHESIVE PRIMER is resistant to asphaltic bleed through and may be applied to BUR roofing, concrete, plywood and some metallic surfaces. Substrates to receive primer should be clean, dry and free of any foreign material such as grease, oil, water, dirt, etc. EVERROOF ADHESIVE PRIMER is fast-drying and has little or no smell associated with its application.

**APPLICATION**

EVERROOF ADHESIVE PRIMER application rates will vary depending on substrates. EVERROOF ADHESIVE PRIMER can be applied with airless spray equipment, brush, or roller. The primer must be thoroughly mixed prior to application. Cleanup can be accomplished with either water or mineral spirits.

**FEATURES**

Odorless  
Nonflammable  
Nonhazardous  
Minimum overspray  
Optimum Adhesion Characteristics  
(if used as directed)

**PHYSICAL PROPERTIES**

Solids by Weight (Mixed): 50%  
Weight: 8.7 lbs. per gallon  
Viscosity: 300-400 CPS

**TECHNICAL SPECIFICATIONS**

Recommended Thickness: Varies depending on surface.  
Number of Coats: One  
Color: Blue

## **EVERROOF ADHESIVE PRIMER**

### **APPLICATION INFORMATION**

Method:	EVERROOF ADHESIVE PRIMER primer is designed for airless spray equipment, brush, or roller
Minimum Temperature:	38°F
Thinning:	None normally required
Clean-up Solvent:	Water or mineral spirits

NOTE: THE PRIMER SHOULD BE THOROUGHLY MIXED JUST BEFORE APPLICATION, AND APPLIED TO A CLEAN, DRY SURFACE.

### **COMPATIBILITY**

EVERROOF ADHESIVE PRIMER primer is compatible with EVERROOF's foam and most coatings. For information regarding coatings that are not specified in this data sheet, please contact EVERROOF.

### **ORDERING INFORMATION**

Approximate Shipping Weight: 8.7 lbs./gal.

Container Size: 5 gal. pails & 55 gal. drums

Freight Classification: Paint, non-hazardous

The information herein is believed to be reliable, but unknown risks may be present. EVERROOF warrants only that the material shall be of merchantable quality; this warranty is in lieu of all other written or unwritten, expressed or implied warranties, and EVERROOF expressly disclaims any warranty for a particular purpose, or freedom from patent infringement. Accordingly, Buyer assumes all risks whatsoever as to the use of these materials and buyer's exclusive remedy as to any breach of warranty or negligence claim shall be limited to the purchase price of the materials. Failure to strictly adhere to recommended procedure shall relieve EVERROOF of all liability with respect to the materials or the use thereof.

*The information contained herein is for purposes of identifying the product and does not constitute a warranty that the product will conform to that description. Product specifications and performance will vary depending on application methodologies, raw materials and other factors.*

**REVISED: 04/17**