

QUIK FIX

100% Solids, Non-Sag Polyurethane Polyurea Caulking Compound

QuikFix is a two component aromatic, 1:1 ratio, rapid setting, non-sag, 100% solids, polyurethane polyurea caulking compound for bonding application.

FEATURES

- 100% Solids Meets VOC Regulations
- Sandable in 20-30 minutes
- Odorless
- Meets USDA Criteria
- Non-Toxic
- Non-Sag in Vertical Application
- Meets California VOC and SCAQMD Requirements

USES

QuikFix is used as bonding agent for plastics, masonry, wood, polyurethane EPS and other surfaces.

- Automobile Bumper Repair
- EPS Blocks
- Plastic Repair

Note: QuikFix will discolor in exterior applications.

APPLICATION

For best results use a Cartridge Dispensing System, pre-heating as necessary.

This material can be applied at temperatures from 32°F (0°C) to as high as 135°F (57°C).

The product needs to be conditioned at 75-80°F prior to use.

FINISHING

Allow QuikFix to cure for 20-30 minutes before sanding.

CLEAN UP

Cured product may be disposed of without restriction. Mix excess A and B material and allow to cure. Check local, state and federal laws before disposing of material.

STORAGE

QuikFix should be stored at 60-90°F (15-35°C).

WARNING

This product contains Isocyanates and Curatives.

TECHNICAL DATA

Packaging	200 ml cartridges
Color	
Side - A	Black
Side - B	Clear
Shelf Life	12 months (unopened container)
Specific Gravity:	
Side - A	1.18
Side - B	1.01
Gel Time @ 75°F (24°C), ASTM D-2471	90 - 120 seconds
Tack Free Time @ 75°F (24°C)	5 - 7 mins
Sandable Time @ 75°F (24°C)	20 - 30 mins

TECHNICAL
DATA SHEET

QUIK FIX



Please read all information in the general guidelines, product data sheets, guide specifications and safety data sheets (SDS) before applying material. Published technical data and instructions are subject to change without notice. Contact your local EVERROOF representative or visit our website for current technical data and instructions.

LIMITED WARRANTY

EVERROOF warrants its products to be free of manufacturing defects and that they will meet EVERROOF current published physical properties. EVERROOF warrants that its products, when properly installed by a state licensed waterproofing contractor according to EVERROOF guide specifications and product data sheets over a sound, properly prepared substrate, will not allow water migration for a period of 12 months. Seller's sole responsibility shall be to replace that portion of the product which proves to be defective. There are no other warranties by EVERROOF of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. EVERROOF shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. EVERROOF shall not be responsible for use of this product in a manner to infringe on any patent held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and/or physical movement of the substrate or structural defects are also excluded from the limited warranty. EVERROOF reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator.

DISCLAIMER

All guidelines, recommendations, statements, and technical data contained herein are based on information and tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. It is the users responsibility to satisfy himself, by his own information and test, to determine suitability of the product for his own intended use, application and job situation and user assumes all risk and liability resulting from his use of the product. We do not suggest or guarantee that any hazard listed herein are the only ones which may exist. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements, whether in writing or oral, other than those contained herein shall not be binding upon the manufacturer, unless in writing and signed by a corporate officer of the manufacturer. Technical and application information is provided for the purpose of establishing a general profile of the material and proper application procedures. Test performance results were obtained in a controlled environment and EVERROOF makes no claim that these tests or any other tests, accurately represent all environments.