

# EVERROOF® PRIMER M25

## TECHNICAL DATA SHEET

Everroof Primer M25 is a waterborne modified acrylic primer specifically designed as bleed blocking primer over modified bitumen and asphalt BUR roofs prior to the application of a new layer of Acrylic or Silicone top coat.

### RECOMMENDED USES

- Asphalt BUR Surfaces
- Modified Bitumen Surfaces

### PACKAGING

5-gallon pail  
55-gallon drum

### COLOR

Light Grey

### REQUIREMENTS

Primer M25 is a water based acrylic adhesive primer which should be applied only by trained or manufacturer-approved roofing experts familiar with the properties of this material.

### EQUIPMENT

Primer M25 primer is designed for airless or conventional spray equipment. It can also be applied using an airless sprayer, brush, or phenolic resin core roller

### APPLICATION

Material may separate during storage, mechanically mix before using. Primer M25 application rates will vary depending on substrates. When applied to areas that retain water for 48 hours or more, service life may be diminished and adhesion failure can be expected. Primer M25 can be applied with airless spray equipment, brush, or roller.

Cleanup can be accomplished with either water or mineral spirits.

The preceding instructions can be considered guidelines only.

### MIXING

Primer M25 should be thoroughly blended using a mechanical mixer at slow speed or for at least 5 minutes if mixed by hand.

### PERSONAL PROTECTIVE EQUIPMENT

Since Primer M25 is atomized into a very fine particle distribution during spray application, it is essential that maximum effort is made to protect the spray mechanic and others near the workplace from undue exposure. The best form of protection against organic solvents is the use of Type C organic vapor cartridge respirators. To prevent

### TECHNICAL DATA

<b>Coverage Rate*</b>	New Asphalt Membrane (<5 Years ) - 0.75-1 gallon per 100 square feet  Aged Asphalt Membrane (>5 Years) - 0.5 gallon per 100 square feet  Granule Surface (>5 Years) - 0.5 gallon per 100 square feet
<b>Specific Gravity</b>	1.24
<b>Service Temperature</b>	200°F (93°C)
<b>Total Solids by Weight, ASTM D2369</b>	56 ± 2%
<b>Total Solids by Volume, ASTM D2697</b>	39 ± 2%
<b>Viscosity at 75°F (24°C), Part-A &amp; Part-B Combined</b>	300-400 cps
<b>Volatile Organic Compound, ASTM D2369-81</b>	1 g / L
<b>Dry Time</b>	2 hours
<b>Recoat Time</b>	4 hours
<b>Time to Topcoat with Acrylic</b>	4 hours
<b>Time to Topcoat with Silicone</b>	4 hours
<i>*More may be required on granule alligatored or irregular surfaces. Two coats may be needed for complete coverage.</i>	

excessive skin contact with the sprayed product, we recommend use of fabric coveralls and neoprene or other resistant gloves. Wear safety glasses or OSHA-approved protective goggles.

### JOB-SITE PROTECTION

Overspray from Primer M25 can carry considerable distances and attention should be given to the following:

Post warning signs a minimum of 100 feet from the work area.

Cover all intake vents near the work area.

Minimize or exclude all personnel not directly involved with the spray application.

No welding, smoking or open flames.

Have CO2 or other dry chemical fire extinguisher available at the job-site.

Provide adequate ventilation.



## **SHELF LIFE AND STORAGE**

The shelf life of Primer M25 is 12 months from the date of manufacture when stored in original unopened containers at temperatures between 50–75°F (10–24°C). Keep containers closed and store in a dry, cool place away from direct sunlight, heat, sparks, open flame, and moisture.

## **FREIGHT CLASSIFICATION**

Liquid Plastic Material - NOIBN

## **HEALTH AND SAFETY**

Everroof is committed to the health and safety of our customers. Everroof products shall only be installed by certified contractors. Applicators are required to follow all proper handling, safety and installation procedures. Safety Data Sheets (SDS) are available on this material. Any individual who may come in contact with these products should read and understand the SDS.

## **VAPOR INHALATION**

Effects of overexposure to vapor are characterized by nasal and respiratory irritation, dizziness, nausea, headache, fatigue, possible unconsciousness or even asphyxiation. Vapor inhalation problems are characterized by coughing, shortening of breath and tightness in the chest. Anyone exhibiting these types of symptoms should be immediately removed from the workplace and administered oxygen or fresh air. If the condition is prolonged or extreme, SUMMON EMERGENCY TRAINED MEDICAL ATTENTION IMMEDIATELY.

## **SKIN CONTACT**

Skin contact with liquid components can result in a rash or other irritation. Wash the affected skin area with water. Wipe residual liquid from the skin with a clean cloth, then wipe the affected area with 30% solution of rubbing alcohol. Follow the alcohol wipe with repeated washings with soap and water. If a rash or other irritation develops, see a physician.

## **EYE CONTACT**

Eye Contact with liquid or sprayed components can result in corneal burns or abrasions. Upon exposure, eyes should be flushed with water for an extensive period. SUMMON EMERGENCY TRAINED MEDICAL ATTENTION IMMEDIATELY.

## **TECHNICAL SERVICES**

Additional information, such as brochures, technical assistance, and management services are also available from a Everroof Technical Consultant.

---

Please read all information in the general guidelines, technical data sheets, application guide, and safety data sheets (SDS) before applying material. Published technical data and instructions are subject to change without notice. Contact your local EVERROOF® representative or visit our website for current technical data and instructions. DISCLAIMER: All guidelines, recommendations, statements and technical data contained herein are based on information and tests that EVERROOF® believes to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. It is the user's responsibility to satisfy himself, by his own information and tests, to determine suitability of the product for his own intended use, application and/or situation and user assumes all risk and liability resulting from his use of the product(s). EVERROOF® does not suggest or guarantee that any hazards listed herein are the only ones that may exist. EVERROOF® shall not be liable to the user or any third party for any injury, loss, damage, or costs directly or indirectly resulting from use of, or inability to use, the product(s). Recommendations or statements, whether verbal or in writing, other than those contained herein shall not be binding upon EVERROOF®, unless in writing and signed by an authorized corporate officer. Technical and application information is provided for the purpose of establishing a general profile of the material and proper application procedures. Test performance results were obtained in a controlled environment and EVERROOF® makes no claim that these tests or any other tests, accurately represent all environments. Not responsible for typographical errors. REV20240226.EA