

lab 7 submission

source code

Repository

This is the code to be tested.

```
package library.persistence;

import library.models.*;
import org.eclipse.collections.api.block.function.primitive.BooleanFunction;
import org.jetbrains.annotations.NotNull;
import org.mapdb.*;
import org.mapdb.serializer.SerializerArray;
import org.mapdb.serializer.SerializerArrayTuple;

import java.io.Closeable;
import java.util.function.Supplier;

public final class Repository implements Closeable {
    @NotNull
    final DB db;
    @NotNull
    final HTreeMap<User, User.Data> users;
    @NotNull
    final HTreeMap<Book, Book.Data> books;
    @NotNull
    final HTreeMap<User, String[]> userNotifications;
    @NotNull
    final BTreeMap<Object[], BookRequest.Data> userBookRequests; //
    key: (User, BookRequest)
    @NotNull
    final BTreeMap<Object[], Borrow> borrows; // key: (User, Book)
    public final RepositoryUserOps userOps = new
    RepositoryUserOps(this);
    public final RepositoryBookOps bookOps = new
    RepositoryBookOps(this);
    public final RepositoryUserNotificationOps userNotificationOps =
```

```

new RepositoryUserNotificationOps(this);
    public final RepositoryBookRequestOps bookRequestOps = new
RepositoryBookRequestOps(this);
    public final RepositoryBorrowOps borrowOps = new
RepositoryBorrowOps(this);

    public Repository(@NotNull Supplier<DBMaker.Maker> dbMaker) {
        this.db = dbMaker.get().transactionEnable().make();

        final var userS = new User.S();
        final var userDataS = new User.Data.S();
        final var authorS = new Author.S(userS);

        final var bookRequestS = new BookRequest.S();
        final var bookRequestDataS = new BookRequest.Data.S();

        final var bookS = new Book.S(authorS);
        final var bookDataS = new Book.Data.S(bookS);
        final var borrowS = new Borrow.S();

        final var this2 = this;
        this.users = db.hashMap("users", userS,
userDataS).modificationListener(((key, _, newValue, _) → {
            if (newValue == null) {
                final var key2 = new Object[]{key};
                this2.userNotifications.remove(key);
                this2.userBookRequests.prefixSubMap(key2).clear();
                this2.borrows.prefixSubMap(key2).clear();
            }
        })).createOrOpen();
        this.books = db.hashMap("books", bookS,
bookDataS).modificationListener((key, oldValue, newValue, _) → {
            if (oldValue == null) {
                switch (newValue) {
                    case Book.Data(_, _, _, final Book original, _) when
original ≠ null → {
                        switch (this2.books.get(original)) {
                            case null → throw new
IllegalStateException("Original book not found");
                            case Book.Data(_, _, _, final Book
originalOrModified, _) when originalOrModified ≠ null → throw new
IllegalStateException("Original book already linked");
                            case Book.Data data → this2.books.put(original,
data.withOriginalOrModified(key));
                        }
                    }
                }
            }
        }));
    }
}

```

```

        }
    }
    case null, default → {
    }
}
}
if (newValue == null) {
    for (final var userBookBorrowKey : this2.borrows.getKeys())
{
        if (key.equals(userBookBorrowKey[1])) {
            this2.borrows.remove(userBookBorrowKey);
        }
    }
    switch (oldValue) {
        case Book.Data(_, _, _, final Book other, _) when other
≠ null → {
            switch (this2.books.get(other)) {
                case null → throw new IllegalStateException("Other
book not found");
                case Book.Data(_, _, _, final Book
originalOrModified, _) when !key.equals(originalOrModified) →
throw new IllegalStateException("Other book wrongly linked");
                case Book.Data data → this2.books.put(other,
data.withOriginalOrModified(null));
            }
        }
        case null, default → {
        }
    }
}
}).createOrOpen();

this.userNotifications = db.hashMap("userNotifications", userS,
new SerializerArray<(Serializer.STRING)).valueLoader(_ → new
String[0])
    .modificationListener((key, oldValue, newValue, _) → {
        if (oldValue == null && newValue ≠ null) {
            if (!users.containsKey(key)) {
                throw new IllegalStateException("User not found");
            }
        }
    })
    .createOrOpen();
this.userBookRequests = db.treeMap("userBookRequests", new

```

```

SerializerArrayTuple(userS, bookRequestS), bookRequestDataS)
    .modificationListener((key, oldValue, newValue, _) → {
        if (oldValue == null && newValue ≠ null) {
            @SuppressWarnings("SuspiciousMethodCalls") final var
containsUser = users.containsKey(key[0]);
            if (!containsUser) {
                throw new IllegalStateException("User not found");
            }
        }
    })
    .createOrOpen();
    this.borrows = db.treeMap("borrows", new
SerializerArrayTuple(userS, bookS), borrowS)
    .modificationListener((key, oldValue, newValue, _) → {
        if (oldValue == null && newValue ≠ null) {
            @SuppressWarnings("SuspiciousMethodCalls") final var
containsUser = users.containsKey(key[0]);
            if (!containsUser) {
                throw new IllegalStateException("User not found");
            }
            @SuppressWarnings("SuspiciousMethodCalls") final var
containsBook = books.containsKey(key[1]);
            if (!containsBook) {
                throw new IllegalStateException("Book not found");
            }
        }
    }).createOrOpen();
}

public void transact(@NotNull BooleanFunction<@NotNull
TransactData> action) throws TransactionException {
    try {
        var ok = false;
        try {
            ok = action.booleanValueOf(new TransactData(users, books,
userNotifications, userBookRequests, borrows));
        } finally {
            if (!ok) {
                db.rollback();
            }
        }
    }
    if (ok) {
        try {
            db.commit();
        }
    }
}

```

```

        return;
    } catch (Exception exception) {
        db.rollback();
        throw exception;
    }
}
} catch (Exception exception) {
    throw new TransactionException(exception);
}
throw new TransactionException();
}

@Override
public void close() {
    db.close();
}

public record TransactData(@NotNull HTreeMap<User, User.Data>
users,
                           @NotNull HTreeMap<Book, Book.Data>
books,
                           @NotNull HTreeMap<User, String[]>
userNotifications,
                           @NotNull BTreeMap<Object[],
BookRequest.Data> userBookRequests,
                           @NotNull BTreeMap<Object[], Borrow>
borrows
    ) {
}
}

```

RepositoryTest

This is the code to perform the testing.

```

package library.persistence;

import library.models.*;
import library.utils.ByteArray;
import org.jetbrains.annotations.NotNull;
import org.junit.jupiter.api.AfterEach;
import org.junit.jupiter.api.BeforeEach;
import org.junit.jupiter.api.Test;
import org.mapdb.DBMaker;

```

```
import java.time.Duration;
import java.util.Date;

import static org.junit.jupiter.api.Assertions.*;

class RepositoryTest {

    @BeforeEach
    void setUp() {

    }

    @AfterEach
    void tearDown() {
    }

    @Test
    void transact() {
        try (final var repository = new
Repository(DBMaker::memoryDirectDB)) {
            assertDoesNotThrow(() → repository.transact(_ → true));

            assertThrows(TransactionException.class, () →
repository.transact(_ → false));

            assertThrows(TransactionException.class, () →
repository.transact(_ → {
                throw new RuntimeException();
            }));

            assertThrows(Error.class, () → repository.transact(_ → {
                throw new Error();
            }));

            assertDoesNotThrow(() →
repository.transact(RepositoryTest::populateRepository));

            repository.close();
            assertThrows(IllegalAccessError.class, () →
repository.transact(RepositoryTest::populateRepository));
        }
    }
}
```

```

@Test
void close() {
    try (final var repository = new
Repository(DBMaker::memoryDirectDB)) {
        assertDoesNotThrow(() →
repository.transact(RepositoryTest::populateRepository));

        repository.close();
        assertThrows(IllegalAccessError.class, () →
repository.transact(RepositoryTest::populateRepository));
    }
}

public static boolean populateRepository(@NotNull
Repository.TransactData data) {
    final var reader = new User("reader");
    final var author = new User("author");
    final var librarian = new User("librarian");
    data.users().put(reader, new User.Data(User.Role.STUDENT_STAFF,
true, "reader", "reader"));
    data.users().put(author, new User.Data(User.Role.AUTHOR, true,
"author", "author"));
    data.users().put(librarian, new User.Data(User.Role.LIBRARIAN,
true, "librarian", "librarian"));

    final var book = new Book("book", new Author.ByRef(author));
    final var book2 = new Book("book", new
Author.ByName("author"));
    final var oldBook = new Book("book2", new
Author.ByRef(author));
    final var newBook = new Book("book2", new Author.ByRef(author),
true);
    data.books().put(book, new Book.Data("summary", "content",
Book.ApprovalStatus.APPROVED, null, 0));
    data.books().put(book2, new Book.Data("summary", "content",
Book.ApprovalStatus.REJECTED, null, 0));
    data.books().put(oldBook, new Book.Data("summary", "content",
Book.ApprovalStatus.APPROVED, null, 0)); // `originalOrModified`:
newBook
    data.books().put(newBook, new Book.Data("summary", "content",
Book.ApprovalStatus.PENDING, oldBook, 0));

    data.userNotifications().put(reader, new String[]
{"notification", "notification2"});

```

```

        data.userNotifications().put(author, new String[]
{"notification"});
        data.userNotifications().put(librarian, new String[]{});

        data.userBookRequests().put(new Object[]{reader, new
BookRequest("title", "author")}, new BookRequest.Data(new Date()));
        data.userBookRequests().put(new Object[]{author, new
BookRequest("title", "author")}, new BookRequest.Data(new Date()));
        data.userBookRequests().put(new Object[]{librarian, new
BookRequest("title", "author")}, new BookRequest.Data(new Date()));

        data.borrows().put(new Object[]{reader, book}, new Borrow(new
Date(), Duration.ofNanos(42), new ByteArray(new byte[42])));
        data.borrows().put(new Object[]{author, book2}, new Borrow(new
Date(), Duration.ofNanos(42), new ByteArray(new byte[42])));
        data.borrows().put(new Object[]{librarian, oldBook}, new
Borrow(new Date(), Duration.ofNanos(42), new ByteArray(new
byte[42])));

        return true;
    }
}

```

test report and test coverage report

Both test report and test coverage report are shown.

Note that `library.persistence.RepositoryTest` is only intended to test `library.persistence.Repository` only. Please only care about the line coverage of that file and ignore the rest.

hmust-comp-3111h main Repository.java [D:\git\hmust-comp-3111h\src\main\java\library\persistence\Repository.java] RepositoryTest

Project persistence 100% methods, 75% lines
Repository 100% methods, 75% lines
RepositoryBookOps 16% methods, 10% lines
RepositoryBookRequestOps 10% methods, 10% lines
RepositoryBorrowOps 10% methods, 10% lines
RepositoryUserNotificationOps 16% methods, 10% lines
TransactionException 40% methods, 10% lines
utils
Context
FXMls
Main
module-info.java
resources
test
Java
library.persistence
RepositoryBookOpsTest
RepositoryBookRequestOpsTest
RepositoryBorrowOpsTest
RepositoryTest
RepositoryUserNotificationOpsTest
RepositoryUserOpsTest

Coverage RepositoryTest

Element	Class, %	Method, %	Line, %	Branch, %
library.persistence	100%	32%	45%	29%
Repository	100%	100%	75%	46%
RepositoryBookOps	100%	16%	11%	0%
RepositoryBookRequestOps	100%	11%	6%	0%
RepositoryBorrowOps	100%	10%	5%	0%
RepositoryUserNotificationOps	100%	25%	20%	100%
RepositoryUserOps	100%	16%	11%	0%
TransactionException	100%	40%	28%	0%

```
class RepositoryTest {  
    @Test  
    void transact() {  
        try (final var repository = new Repository(DBMaker::memoryDirectDB)) {  
            assertDoesNotThrow(() -> repository.transact(TransactData _ -> true));  
  
            assertThrows(TransactionException.class, () -> repository.transact(TransactData _ -> false));  
  
            assertThrows(TransactionException.class, () -> repository.transact(TransactData _ -> {  
                throw new RuntimeException();  
            }));  
        }  
    }  
}  
  
public final class Repository implements Closeable {  
    public void transact(@NotNull BooleanFunction<@NotNull TransactData> action) throws TransactionException {  
        try {  
            var ok = false;  
            try {  
                ok = action.booleanValueOf(new TransactData(users, books, userNotifications, userBookRequestOps));  
            } finally {  
                if (!ok) {  
                    db.rollback();  
                }  
            }  
        }  
    }  
}
```

RepositoryTest (library.persistence) 356 ms
close() 345 ms
transact() 11 ms

2 tests passed 2 tests total 356 ms

Process finished with exit code 0

WARNING: A restricted method in java.lang.System has been called
WARNING: java.lang.System::load has been called by net.jpountz.util.Native in an unnamed module (file:/C:/Users/polyi/.m2/repository/net/jpountz/lz4/lz4-1.3.0.jar)
WARNING: Use --enable-native-access=ALL-UNNAMED to avoid a warning for callers in this module
WARNING: Restricted methods will be blocked in a future release unless native access is enabled

hmust-comp-3111h src > test > java > library > persistence > RepositoryTest 31.1 CRLF UTF-8