

1022

The polycv class

Martin C Schwarzer
polyluxus@gmail.com

v1.1.dev from 2020/08/24

Abstract

Polycv is a document class to typeset curriculum vitae with \LaTeX . It also provides a template for a cover letter consistent with the layout of the resume.

Contents

1	Introduction	4
1.1	Contributing	4
2	Installation	4
2.1	Prerequisites	5
3	Usage	6
3.1	Class Options	6
3.1.1	Page Layout	7
3.1.2	Colors	7
3.1.3	Progress and Level Bar Options	8
3.1.4	Miscellaneous Options	8
3.1.5	Void Article Options	9
4	Changing Fonts and Text Alignment	9
4.1	Commands to Store and Access Information	9

4.2	Templates	10
4.2.1	General Templates for the CV	10
4.2.2	Special Templates for the CV	12
4.3	The CV Environments	13
4.4	The Cover Letter Environment	14
4.5	Including external PDF as Appendix	15
5	Implementation	16
5.1	Option definitions	16
5.2	Necessary packages	17
5.3	Global settings	18
5.3.1	Colors	19
5.3.2	Extending draft mode	20
5.3.3	Biblatex Mode	20
5.3.4	Lengths	21
5.3.5	Fonts and Styles	23
5.4	Macros and Environments	23
5.4.1	Personal Information	24
5.4.2	Redefinition of Section Headers	26
5.4.3	Header and Footer Boxes	27
5.4.4	Level and Progress Bar	28
5.4.5	Commands for the main Body	32
5.4.6	Side Bar Definitions	34
5.5	Cover Letter Definitions	35
5.6	Appendix	38
6	Building polycv and its Documentation	38

1 Introduction

I previously used the package [koma-moderncvclassic](#) to prepare my CV, and I was actually quite satisfied with the look of it. In a way this class borrows some design elements from it. However, I noticed it was not using a lot of space, which got especially problematic when inserting a picture.

I looked through various templates and classes online ([limecv](#), [simple academic resume](#), [DeedyResume](#), [FancyCV by Adrien Friggeri](#), [the Overleaf CVGallery](#), TeX Stack Exchange [LaTeX template for resume/curriculum vitae](#), ... , there are possibly some I forgot), but couldn't find anything that was exactly to my liking. So I decided to write a class for myself, not just only for my CV, but also for the training in writing such classes (or packages).

The main goal was to structure the information in a way that, if condensed enough, it would fit on one page; but additional pages could be added when the need arose, e.g. a long publication list, or many stations along the way.

Additionally I liked the idea of having a cover letter template, which resembles most of the elements of the CV.

The source code is available at [GitHub](#), where there are also a few example uses of this class. If anything is unclear, needs improvement, is missing please submit an issue there ([GitHub issues](#)). Thank you.

1.1 Contributing


If you find this class useful, you are very welcome to contribute to it. The repository is hosted at [GitHub repository](#). It will consist of one main branch, the release branch, possibly a release candidate branch and a development branch. If you would like to contribute changes, please submit a pull request to the development branch. Once all changes have been pulled in, the commits will be squashed and pulled into the release candidate branch for final testing and adjustment. As such, there will always be only one commit for one release.

2 Installation

This work consists of the files `polycv.dtx` and `polycv.ins` and the derived filebase `polycv.cls`, which should be copied to a location where latex will look for it. How to build the package and documentation from its source files is explained in section 6. The source code is hosted at [GitHub](#), where the derived class and documentation files are also available.

2.1 Prerequisites

In order for this class to function properly, the following packages must be installed:

- The package `etoolbox` provides additional hooks necessary for the setup within the source class.
- The `calc` package allows to derive some lengths from others.
- The `hyperref` package provides clickable cross-references, e.g. to references to the bibliography, or websites.
- Color support comes from `xcolor`.
- Most of the graphical elements within this class are produced with `tikz`, such as the header and footer boxes, and the progress bar.
- To include a signature and profile pictures, `graphicx` is loaded.
- For most of the document the indentation is disabled with the `parskip` package.
- The page layout is produced with the `geometry` package.
- The `fontawesome` is needed for icons, e.g. , in the side bar.
- To include other reference letters as pdfs, `pdfpages` is also loaded.

3 Usage

You can load the class in the same way you would load any other class. The following listing defines a skeleton document containing a elements of the class.


```
\documentclass[{options}]{polycv}
%
% packages,
% define personal information,
% define colours, page layout, etc.
%
\begin{document}
  \begin{polycvfirstpage}
    \begin{polycvsidebar}
      %
      % Contents of the side bar box
      % (personal information image, etc.)
      %
    \end{polycvsidebar}
    %
    % Body of the first page
    %
  \end{polycvfirstpage}
  \begin{polycvpage}
    %
    % Body of additional pages
    %
  \end{polycvpage}
  \begin{polycvletter}%
    [{{Author Address}}]%
    [{{Subject}}]%
    [{{Recipient Address}}]
    \opening{Dear Example,}
    %
    % Letter content
    %
    \closing{Sincerely,}
    \ps{more text}
  \end{polycvletter}
  \pdfappendix{{filename}}
\end{document}
```

3.1 Class Options

This class is build on top of the standard article class. It therefore inherits most options from that class. Some are incompatible with the design of this class and have been disabled. Other options allow for customisation of the used templates. In this section they will be briefly described, along with commands that can be used to set the values in the preamble.

3.1.1 Page Layout

The general page layout will be accomplished by the `geometry` package. Depending on the environment currently in use, a few internal lengths are defined and used. Most of these can only be set via the class options, or within the preamble.

Opt <code>margins</code> Default: <code>1.0 cm</code>	The length of <code>margins</code> is the base length of most surrounding space, it defines and sets the length <code>\polycvmargins</code> . It is used additionally to the header and footer lengths. This setting also controls the space between the side bar and the main body on the first page of the CV environment. The command <code>\setmargins{<length>}</code> is only available in the preamble and can be used to set the margin length after loading the class.
Opt <code>headerheight</code> Default: <code>3.0 cm</code>	The options <code>headerheight</code> and <code>footerheight</code> control the height of the boxes for the header and the footer, respectively. These lengths affect the whole document and can therefore only be set when loading the class or within the preamble. The will be the same for each of the environments used. Instead of choosing the key/value option at load time, the commands <code>\setheaderheight{<length>}</code> and <code>\setfooterheight{<length>}</code> can be issued to manipulate these values.
Opt <code>footerheight</code> Default: <code>0.5 cm</code>	
<code>\setheaderheight</code> <code>\setfooterheight</code>	
Opt <code>sidebarwidth</code> Default: <code>5.0 cm</code>	On the left side of first page of the CV a box is created, the side bar, which may hold personal information, a picture, skills, languages, hobbies, etc.. The width of this box is controlled with the option <code>sidebarwidth</code> . This must be defined before the sidebar is attempted to be set. There is currently no command analogous to the other lengths to set this in the preamble, it must be defined via the options.
 <code>\setsidebarwidth</code>	
Opt <code>iconspace</code> Default: <code>0.8 cm</code>	Closely related is the option <code>iconspace</code> , which defines the width that is reserved for the icon in a line in the side bar environment. It can also be set via <code>\seticonspace{<length>}</code> in the preamble.
<code>\seticonspace</code>	
Opt <code>hintcol</code> Default: <code>2.7 cm</code>	In the main body, each entry will consist of two parts: First, a small column for a keyword, date, bar, which is called hint in this documentation. The width of this column can be adjusted with the option <code>hintcol</code> . Second, a column for the description of this hint. This is just a parbox, and depends on the command used. The width will be automatically calculated from the available space. These two columns are separated by a space. The width of which can be set via the option <code>hintcolsep</code> . Alternatively they can be set in the preamble via <code>\sethintcolwidth{<length>}</code> and via <code>\sethintcolsep{<length>}</code> , respectively.
Opt <code>hintcolsep</code> Default: <code>0.2 cm</code>	
<code>\sethintcolwidth</code> <code>\sethintcolsep</code>	
Opt <code>letterindent</code> Default: <code>1 cm</code>	In the letter environment the indentation of the first line of a paragraph can be adjusted with the <code>letterindent</code> option. This is another length that can (currently) only be controlled with passing the option to the class.

3.1.2 Colors

Opt <code>xcolor</code> Default: <code>dvipsnames</code>	The class loads the <code>xcolor</code> package and passes by default the option <code>dvipsnames</code> to it. This can be changed by using the <code>xcolor</code> option to pass other parameters to this
---	--

package. It is loaded internally before the `tikz` package to avoid option conflicts.

Opt	<code>primary</code>	The main colour of the CV is called <code>primary</code> and can be set via this option. It is used for all parts that will be highlighted, such as the header bar and the section headings. The text color is a composite color from the primary color and the <code>shade</code> color. By default this is defined as black, so the text will appear darker. The amount of primary color mixed in depends on the factor which can be set via the <code>mixing</code> option.
	Default: <code>blue</code>	
Opt	<code>shade</code>	
	Default: <code>black</code>	
Opt	<code>mixing</code>	
	Default: <code>10</code>	
Opt	<code>secondary</code>	The secondary color specifies the background color and is white by default.
	Default: <code>white</code>	
	<code>unused</code>	One last color is defined to highlight items. It can be set via the <code>highlight</code> option. This option currently has little effect as the color itself is not used within the template.
Opt	<code>highlight</code>	
	Default: <code>orange</code>	
	<code>\setcolprimary</code>	To allow for custom colors to be used, all colors can also be set with the <code>\setcol<...>{<color>}</code> commands. Note that the <code>mixing</code> parameter must be set via the options and has no special macro.
	<code>\setcolsecondary</code>	
	<code>\setcolhighlight</code>	
	<code>\setcolshade</code>	



3.1.3 Progress and Level Bar Options

Opt	<code>progbarheight</code>	Skills can be displayed as an CV entry and accompanied with a progress bar or a level (bar) indicator. The width of this bar is by default either determined by the environment in which it is used, or the width of the hint column. The height of the bar can be controlled with the <code>progbarheight</code> option. It can also be set via <code>\setprogbarheight{<length>}</code> . The level bar is divided into boxes or circles. The number of these items can be set via <code>progbarunits</code> and defaults to five. It can also be set via <code>\setprogbarunits{<number>}</code> .
	Default: <code>1.5 ex</code>	
	<code>\setprogbarheight</code>	
Opt	<code>progbarunits</code>	
	Default: <code>5</code>	
	<code>\setprogbarunits</code>	

3.1.4 Miscellaneous Options

Opt	<code>draft, final</code>	The class also extends the <code>draft</code> option of the standard article class. The otherwise invisible boxes, e.g. for the side bar, will be lightly shaded, so that they are visible. The complementary option is <code>final</code> . Note that if the <code>final</code> option is found, the <code>draft</code> option will have no effect and will be ignored.
Opt	<code>biblatex</code>	The <code>biblatex</code> option will inject some code into a bibliography environment, so that the alignment of the hint column will be better. It is turned off by default. If the <code>biblatex</code> package is not loaded (this class will not take care of this), it might lead to problems.
Opt	<code>signcv</code>	In some countries it is customary to sign the CV. The option <code>signcv</code> can be used to enable this behavior. If it is enabled, a box with a signature will be placed in the lower left corner of the first page, below the sidebar contents. The box width is also controlled with the <code>sidebar width</code> option. An image with the signature is necessary (see below).

3.1.5 Void Article Options

Opt	<code>twocolumn</code>	Since every page has a specific layout passing the <code>twocolumn</code> option to the inherited article class will lead to problems. Therefore it has been disabled.
		
Opt	<code>titlepage</code>	For the same reason as above, creating a title page doesn't make sense and will clash with other settings of this class. Therefore the <code>titlepage</code> option has also been disabled.
		

4 Changing Fonts and Text Alignment

<code>\setheaderfont</code> Default: <code>\sffamily\bfseries</code>	By default the font used for the header is made bold and serifs are turned off. In order to change that layout, the command <code>\setheaderfont{}</code> can be used. This command should be used in the preamble.
<code>\setentryragged</code> <code>\setentryjustified</code>	The default layout of an entry in the CV is justified. This can be changed with <code>\setentryragged</code> to flush the contents to the left and leave the right side ragged (<code>\raggedright</code>). For symmetry the command <code>\setentryjustified</code> can be used to unset the above. Both commands will set the internal variable used in the templates at the end of the preamble, so they can only be used there.
<code>\setsigright</code> <code>\setsigleft</code>	The commands <code>\setsigright</code> and <code>\setsigleft</code> determine whether the name below a signature field is right or left aligned. This does not affect where the field itself is placed. These commands can also only be used in the preamble.

4.1 Commands to Store and Access Information

Personal information can be stored in variables so that they become accessible to the defined templates.

<code>\author</code> <code>\insertauthor</code>	The <code>\author{<author name>}</code> command remains unchanged and cannot be used outside of the preamble. The contents of that field is copied to the <code>\insertauthor</code> variable and is accessible throughout the document that way.
<code>\title</code> <code>\inserttitle</code>	Similarly to the above, the <code>\title{<title>}</code> remains unchanged, with the same limitations applied. The contents can be accessed with the <code>\inserttitle</code> command. There is currently no template using this command, but it is recommended to set it to something like <i>Curriculum Vitae</i> for the PDF fields that might use it.
<code>\position</code> <code>\insertposition</code>	The <code>\position{<position>}</code> macro is defined in a similar way to the above commands. The <code>\insertposition</code> macro can be used to access the content. It is used in the header box and can be set to contain, as the name suggest, the title of the current position. A common usage might also be a one line description of one's profession.
<code>\address</code> <code>\insertaddress</code>	The address can either be specified by the direct invocation of <code>\address{<address>}</code>

and is accessible via the `\insertaddress` macro. It is used in the address template (see section 4.2.2), as well as the header of the letter (see section 4.4). Alternatively it the macros `\street{<street>}` and `\location{<location>}` can be used to set the values separately. The `\insertaddress` will then be constructed from these two values. If set, they can be printed with the corresponding `\insertstreet` and `\insertlocation` macros. If the address is set directly the other values remain unchanged. It is therefore also possible to extend the functionality in the following way:

```
\street{123, Example Road}
\location{New Town}
\address{The Old Shack\\ \insertstreet \\ \insertlocation}
```

`\email` The command `\email{<email>}` will wrap the input in a hyperlink, which can be accessed through the `\insertemail` command.

`\phone` Telephone numbers can be stored with `\phone{<number>}` and `\mobile{<number>}` and accessed with the adjacent commands `\insertphone` and `\insertmobile`. Currently the template only provides templates for these two telephone numbers.

`\github` The macro `\github{<username>}` provides a convenient way to display the GitHub username, while also wrapping it into a hyperlink to the associated profile.

`\orcid` Likewise for an ORCID account, the `\orcid{<ID number>}` will wrap the displayed ID into a hyperlink to the respective profile.

`\signaturefile` In order to sign the CV and the cover letter, a file name must be provided with the macro `\signaturefile{<filename>}`. This file name is stored in `\insertsigfilename` and is passed to the command `\includegraphics` in the corresponding templates. For the cover letter it is necessary to set this filename, otherwise it will (currently) lead to an error.

4.2 Templates

The templates that are provided with this class should make typesetting the contents of the resume easier as they provide predefined spacing and markup.

4.2.1 General Templates for the CV

`\section` The `\section{<text>}` and `\subsection{<text>}` commands are redefined to have no numbers. For the former there will be a bar the length of the hint column, while for the latter there is just the same amount of space. Both commands will use the primary color and the predefined header fonts.

`\cvline` The `\cvline[<width>]{<hint>}{<description>}` macro divides an entry line in the CV into two parts: a hint column with the preset width of hint, which can also be set with

the optional argument, and a description box spanning the remaining width of the line. It can be used to set any type of content as a line in the CV.

`\cvitemline` The `\cvitemline[⟨width⟩]{⟨icon⟩}{⟨description⟩}` is similarly constructed as the above command. The general difference is that the hint column is replaced with an icon column. If the optional `⟨width⟩` parameter is not given, it falls back to the definition from the preamble. The line itself is defined consisting of two parboxes, spanning the whole width that is available. This command is primarily intended for the sidebar, but it could be used somewhere else. It is also used for the specialised templates (see section 4.2.2).

`\progressbar` The `\progressbar[⟨width⟩]{⟨level⟩}` typesets a progress bar. The height of this bar is defined via the class options or in the preamble. The width of the bar can be set via the optional parameter `⟨width⟩`, however, in most use cases it will be automatically calculated depending on where it is used. The mandatory argument `⟨level⟩` can be defined as a number between 0 and smaller than 1 and is then used directly as a fraction. Alternatively, if it is a number, it is taken as the numerator for the fraction, where the number of progress bar units is the denominator. If the input is not numeric, or larger than the number of progress bar units, the bar will be filled completely. If the input is smaller than zero, the bar will be completely empty. There are some special templates, which use this command (see section 4.2.2).

For the default setup, the number of units in the level bar is 5, the following two commands will produce the same result:

```
\progressbar{0.6}
\progressbar{3}
```

△ 1 vs. full

On the other hand, (for the default setup) the first command will fill the bar to 20%, but the second and third command will fill it completely.

```
\progressbar{1}      % filled 20% (1/5) for default
\progressbar{6}      % filled 100% for default
\progressbar{full}   % filled 100% (always)
```

`\levelbarsquares` The macros `\levelbarsquares[⟨width⟩]{⟨level⟩}` and `\levelbarcircles[⟨width⟩]{⟨level⟩}` are also progress indicators, which use squares or circles, respectively. The total number of items is set via the class options or in the preamble. The mandatory argument `⟨level⟩` should be an integer within 0 and the set limit. If the `⟨level⟩` has a fractional value smaller than 1, it will be scaled by the limit of items in the bar, and then rounded down. If the level is specified as a fractional number larger than one, only the integer part will be considered. If level exceeds the the upper bound of the predefined range, or is non-numeric, all items will be filled. If the input is smaller than zero, all items will be empty. The width can be given as the optional argument `⟨width⟩` and defaults to the width of the hint column. There are currently no templates that use these commands, but they can be used to redefine existing templates.

For the default setup, the number of units in the level bar is 5, the following two commands will produce the same result:

```
\levelbarsquared{0.8}
\levelbarsquared{4}
```

4.2.2 Special Templates for the CV

`\cventry` The `\cventry` macro is a more specialised template of the `\cvline` macro. It requires six mandatory arguments, which of course can be empty. It is intended to be used in the following form:

```
\cventry[⟨width⟩]{⟨when⟩}{⟨what⟩}{⟨who⟩}{⟨where⟩}{⟨opt.⟩}{⟨descr.⟩}.
```

The entry spans the whole available width, the optional `⟨width⟩` controls the hint column. The first argument `⟨when⟩` contains the hint, which can be a date for example. The second argument `⟨what⟩` will be set in bold font and usually contains the title of the position, or a short job description. This is followed by a comma. The third argument `⟨who⟩` is set in italic font and usually contains the name of the employer, which is again followed by a comma. The fourth argument `⟨where⟩` may contain the location of this job and it is set in normal font style. If the fifth argument `⟨opt.⟩` contains something, it is set in the same style as the preceding element, separated by a comma from it. This could be used to specify a grade in the education section for example. If this argument is empty, the comma is skipped. The line will then be terminated by a full stop. The sixth argument `⟨descr.⟩` can also be empty. If it contains text, it will be set on a new line and can be used as a more detailed description of the entry. The font size is reduced to small for this paragraph.

`\cvskill` The `\cvskill{⟨description⟩}{⟨level⟩}` is a template using `\cvline`, defining a progress bar to `⟨level⟩` and a `⟨description⟩`. If it is used in the main document part, the progress bar will be set into the hint column, and will take half of its width and is flushed to the right. The description is flushed to the left in the main column. If it is used in the side bar, the description will start the line, followed by the progress bar. The progress bar will then use a third of the whole line, and the description the rest excluding separator space.

`\cvlanguage` The `\cvlanguage{⟨language⟩}{⟨level⟩}` is a wrapper to the above command. This was introduced, to allow for the possibility of customisation. For example, it could be redefined to use a different indicator.

```
\renewcommand\cvlanguage[2]{%
\cvline{\levelbarsquares{#2}}{#1}}
```

`\cvlineaddress` The special versions of the `\cvitemline` macro have a preset icon to it. The address (📍), email (✉), phone (☎), and mobile (📱) templates are predefined. These macros are primarily intended for the side bar environment. They may be used in the main part, too, but they could look somewhat odd. Other lines can be added with the generic command.

```
\cvitemline{\faTerminal}{bash, zsh, fish}
```

`\orcidiconfilename` Since there is no \LaTeX package available that includes an Orcid icon, it must be provided with an external file. The command `\orcidiconfilename` will look for a file with the

name `orcidicon.pdf` and include this as a graphic. If such a file is not found, it will use a placeholder icon made of the letters.

`\cvlineorcid` The Orcid and GitHub macros will use their respective icons, similar to the above. The
`\cvlinegithub` contents of the variables defined in the preamble will go into the description column.

4.3 The CV Environments

Env `polycvfirstpage` The class comes with two environments to set the CV contents. The first page is special since it also contains a side bar with additional information. The environment itself sets up the geometry of the page, and the header box including the name and position. It will also set up the footer box to close the page. It should be used to set a single page only.

Env `polycvsidebar` The side bar is part of the first page environment and should be issued inside it. It will produce a box with the specified content on the left side of the page. The main templates of this class will have different definitions inside this environment.

The following code block contains an exemplary usage of the two environments.

```
\begin{polycvfirstpage}
  \begin{polycvsidebar}
    \includegraphics[width=1.0\linewidth]{example-image-1x1}\\[2ex]

    \section{Personal Details}
    \cvitemline{\faStar}{01. 01. 1984,\newline Birthplace, Country}
    \cvlineaddress
    \cvlineemail

    \section{Languages}
    \cvlanguage{English (native)}{1}

    % etc.
  \end{polycvsidebar}%
  \section{Experience}
  \cventry{years}
    {job title}{employer}{place}
    {optional: ...}
    {optional: job description}

  \section{Skills}
  \cvskill{\LaTeX}{0.8}

  % etc.
\end{polycvfirstpage}
```

Env `polycvpage` The generic CV page environment is similar to the firstpage environment, but it doesn't include space for the side bar. The margins are adjusted to fill the whole available width. It is useful to typeset a second (or backside) page of the CV. The header box of this page will be of the same size as for the first page, but remain empty.

The following code block briefly summarises an example usage:

```
\begin{polycvpage}
  \section{Education}
  \cventry{years}
    {degree}{institution}{place}
    {optional: grade/...}
    {optional: comment/ description}

  % etc.
\end{polycvpage}
```

4.4 The Cover Letter Environment

Env `polycvletter` The letter environment takes one optional and two mandatory arguments: The optional argument is the author's address, which, if unspecified, will be constructed from variables set in the preamble. The first mandatory argument is the subject line, while the second is the recipient's address.

```
\begin{polycvletter}
  [⟨Author Address⟩]{⟨Subject Line⟩}{⟨Recipient Address⟩}
  %
  % Letter content
  %
\end{polycvletter}
```

At the end of the environment the signature, a file name provided in the preamble with `\signaturefile{<image file>}`, along with the author name will be set.

`\opening` The letter environment uses indentation specified with the `letterindent` option (see section 3.1.1). This looks odd for the opening and closing statement, therefore a wrapper is provided that turns of the indentation. They each take one argument, like `\opening{⟨statement⟩}`. These commands will be set in place, i.e. you could include text before and after them.

`\ps` Occasionally you would like to include a postscript note. The contents of such a note can be stored with `\ps{⟨note⟩}` and will be produced below the signature of the letter. The font size is also smaller than the one of the text. This command can only be used once; a later occurrence will overwrite a previous one.

`\setpsmark` How the postscript is introduced can be changed with `\setpsmark{⟨psmark⟩}`.
Default: `P. S.`

The following is a minimal working example for a letter created with the `polycv` class.

```
\documentclass[primary=black, 14pt, a4paper]{polycv}
\usepackage{mwe} % for this example
\title{Curriculum Vitae}
\author{Example Author}
\signaturefile{example-image-16x9}

\begin{document}
```

```

\begin{polycvletter}
  [Address line 1\\ Address line 2]
  {Subject line}
  {Company\\ Address line 1\\ Address line 2}
  \opening{Dear Example,}

  \blindtext[1-3]

  \closing{Sincerely,}
  \ps{\blindtext[1]}
\end{polycvletter}
\end{document}

```

4.5 Including external PDF as Appendix

`\pdfappendix`
 Default: `pages={1-}`

It is occasionally necessary to include certificates, letters of recommendation, or other external sources into an application. This class provides a wrapper to the `\includepdf` command from `pdfpages`. The difference to the original command (which still could be used) is that before including the document, the wrapper will unset the page color. This is necessary, even if it is defined as white, due to the way the page color is implemented. You can include pages from a PDF document to use it as appendix with the command `\pdfappendix[<kwargs>]{<filename>}`, where the optional argument accepts arguments like `pages=1-3` or `angle=90`. See the [Documentation of the pdfpages package](#).

5 Implementation

5.1 Option definitions

These simple definitions for key-value pairs as class options are done with `kvoptions` as described in TUGBoat.¹ Using the prefix **polycv@** as an in-between to distinguish values set from class options in the document.

```
1 \RequirePackage{kvoptions}
2 \SetupKeyvalOptions{
3   family=polycv,
4   prefix=polycv@
5 }
```

Define options and preset margins for the page setup via the `geometry` package.

```
6 \DeclareStringOption[1.0cm]{margins}
7 \DeclareStringOption[3.0cm]{headerheight}
8 \DeclareStringOption[0.5cm]{footerheight}
9 \DeclareStringOption[5.0cm]{sidebarwidth}
10 \DeclareStringOption[2.7cm]{hintcol}
11 \DeclareStringOption[0.2cm]{hintcolsep}
12 \DeclareStringOption[1.6cm]{sidebarhint}
13 \DeclareStringOption[0.2cm]{sidebarindent}
14 \DeclareStringOption[0.8cm]{iconspace}
15 \DeclareStringOption[1.5ex]{progbarmheight}
```

The progress bar, which contains of individual items, can be customised to include a certain number of elements. Define the option for this number and set it to five as default.

```
16 \DeclareStringOption[5]{progbarmunits}
```

Define the options for the colors which should be used throughout the document. The `mixing` option is used together with the `shading` color, to modify the primary color.

```
17 \DeclareStringOption[blue]{primary}
18 \DeclareStringOption[white]{secondary}
19 \DeclareStringOption[orange]{highlight}
20 \DeclareStringOption[black]{shade}
21 \DeclareStringOption[10]{mixing}
```

Define an option for a draft mode, analogous to the standard classes. This will be extended, see below.

¹J. Wright, C. Feuersänger, TUGBoat, Vol. 30 (2009), No. 1, p. 110-122.


```

22 \DeclareBoolOption{draft}
23 \DeclareComplementaryOption{final}{draft}

```

Define a biblatex mode, which will adjust some space settings in the bibliography, if desired.

```

24 \DeclareBoolOption{biblatex}

```

Define an option that lets the user pass settings to xcolor, i.e. (the default) dvipsnames.

```

25 \DeclareStringOption[dvipsnames]{xcolor}

```

Define the option whether the CV (front page) is signed or not.

```

26 \DeclareBoolOption{signcv}

```

Define an option to set the indentation in the letter and let it default to the width or one m.

```

27 \DeclareStringOption[1em]{letterindent}

```

Warn about options which will not and cannot be used or passed on, because of potential clashes for this class.

```

28 \DeclareVoidOption{twocolumn}{%
29   \ClassError{polycv}{%
30     Option 'twocolumn' is incompatible because of the special page setup.}}
31 \DeclareVoidOption{titlepage}{%
32   \ClassWarning{polycv}{%
33     Option 'titlepage' is incompatible because of the special page setup.}}

```

Pass all other options to the standard article class.

```

34 \DeclareDefaultOption{%
35   \PassOptionsToClass{\CurrentOptionKey}{article}}

```

Finally, process these options and load the standard class.

```

36 \ProcessKeyvalOptions{polycv}
37 \LoadClass{article}

```

5.2 Necessary packages

Some packages are essential for this class and need to be loaded.

- `kvoptions` is necessary for the use of key-value-options (see above)
- `etoolbox` is necessary for additional hooks like `\AtEndPreamble`.
- `calc` is necessary to do mathematics with lengths
- `xstring` is used to test input strings for numbers
- `hyperref` provides hyperlinks within the CV and letter
- `xcolor` provides convenient color definitions, since `hyperref` is loaded, this option is set by default. Other options can be added with the class options switch. This package must be loaded before `tikz`, otherwise there will be an option clash.
- `tikz` is used for header box, symbols, etc.. (must be loaded after `xcolor`)
- `graphicx` is used for the inclusion of graphics, e.g. signature and profile picture.
- `parskip` turns off indentation and improves spacing
- `geometry` is used for the page layout
- `fontawesome` provides fancy symbols for the sidebar
- `pdfpages` are used to include a pdf in the appendix

```

38 \RequirePackage{etoolbox}
39 \RequirePackage{calc}
40 \RequirePackage{xstring}
41 \RequirePackage{hyperref}
42 \PassOptionsToPackage{\polycv@xcolor,hyperref}{xcolor}
43 \RequirePackage{xcolor}
44 \RequirePackage{tikz}
45 \RequirePackage{graphicx}
46 \RequirePackage[indent=0pt]{parskip}
47 \RequirePackage{geometry}
48 \RequirePackage{fontawesome}
49 \RequirePackage{pdfpages}

```

5.3 Global settings

Issue an informative statement that the CV is signed. (To Do.)

```

50 \AtEndPreamble{%
51   \ifpolycv@signcv%
52     \ClassInfo{polycv}{%
53       Option 'signcv' enabled; CV will be signed.}%
54   \fi
55 }%

```

Set the page style to remove page numbers.

```
56 \pagestyle{empty}
```

5.3.1 Colors

Apart from the switches as options, define some commands that can be used to set the colors for the document.

`\setcolprimary` The primary color used for headers.

```
57 \newcommand*{\setcolprimary}[1]{%
58   \renewcommand*{\polycv@primary}{#1}}
```

`\setcolsecondary` The secondary color is the background color, i.e. the page color.

```
59 \newcommand*{\setcolsecondary}[1]{%
60   {\renewcommand*{\polycv@secondary}{#1}}
```

`\setcolhighlight` If text should be highlighted another color can be set.

```
61 \newcommand*{\setcolhighlight}[1]{%
62   {\renewcommand*{\polycv@highlight}{#1}}
```

`\setcolshade` The color which is used for shading (damping) the primary color.

```
63 \newcommand*{\setcolshade}[1]{%
64   {\renewcommand*{\polycv@shade}{#1}}
```

Disable these changing color commands for body, then define the colors in internal macros along with some mixing. Then set the text color and the color for the page for the entire document.

```
65 \@onlypreamble\setcolprimary
66 \@onlypreamble\setcolsecondary
67 \@onlypreamble\setcolhighlight
68 \@onlypreamble\setcolshade
69 \AtEndPreamble{%
70   \colorlet{polycvpagecolor}{\polycv@secondary}
71   \colorlet{polycvheaderbackground}{\polycv@primary}
72   \colorlet{polycvheadertext}{\polycv@secondary}
73   \colorlet{polycvsectioncolor}{\polycv@primary}
74   \colorlet{polycvtextcolor}{%
75     \polycv@primary!\polycv@mixing!\polycv@shade}
```

```

76 \colorlet{polycvhighlight}{\polycv@highlight}
77 \colorlet{polycvsidebarbackground}{\polycv@secondary}
78 \colorlet{polycvprogbarfilled}{\polycv@primary}
79 \colorlet{polycvprogbarnofill}{%
80   \polycv@primary!10!\polycv@secondary}
81 }
82 \AfterPreamble{%
83   \color{polycvtextcolor}\pagecolor{polycvpagecolor}}

```

5.3.2 Extending draft mode

This section emulates and extends the draft mode. It writes an information message to the log. It then sets the overfull boxes identifier.² Passes the showframe option to the geometry package to make the page borders visible. It also sets the color of the side bar, to make the tikz boxes visible in draft mode.

```

84 \ifpolycv@draft%
85   \ClassInfo{polycv}{Option 'draft' is enabled}
86   \setlength\overfullrule{1em}
87   \PassOptionsToPackage{showframe}{geometry}
88   \AtEndPreamble{%
89     \colorlet{polycvsidebarbackground}{%
90       \polycv@primary!20!\polycv@secondary}%
91   }
92 \fi

```

5.3.3 Biblatex Mode

In this option the biblatex package is set to use the same width as the date column for the numeration.

```

93 \ifpolycv@biblatex%
94   \ClassInfo{polycv}{Option 'biblatex' is enabled}
95   \AtEndPreamble{%
96     \setlength{\biblabelsep}{\polycvhintcolsep}%
97     \DeclareFieldFormat{labelnumberwidth}{%
98       \makebox[\polycvhintcol][r]{[#1]}}%
99   }%
100 \fi

```

²How to test whether report has been called with “draft” option <https://tex.stackexchange.com/a/240128/33413>

5.3.4 Lengths

Define the lengths and use defaults or parameters from the class options for the layout.

```
101 \newlength{\polycvheaderheight}
102 \setlength{\polycvheaderheight}{\polycv@headerheight}
103 \newlength{\polycvfooterheight}
104 \setlength{\polycvfooterheight}{\polycv@footerheight}
105 \newlength{\polycvmargins}
106 \setlength{\polycvmargins}{\polycv@margins}
107 \newlength{\polycvsidebarwidth}
108 \setlength{\polycvsidebarwidth}{\polycv@sidebarwidth}
109 \newlength{\polycvhintcol}
110 \setlength{\polycvhintcol}{\polycv@hintcol}
111 \newlength{\polycvhintcolsep}
112 \setlength{\polycvhintcolsep}{\polycv@hintcolsep}
113 \newlength{\polycvsidebarhint}
114 \setlength{\polycvsidebarhint}{\polycv@sidebarhint}
115 \newlength{\polycvsidebarindent}
116 \setlength{\polycvsidebarindent}{\polycv@sidebarindent}
117 \newlength{\polycviconspace}
118 \setlength{\polycviconspace}{\polycv@iconspace}
119 \newlength{\polycvprogbarheight}
120 \setlength{\polycvprogbarheight}{\polycv@progbarheight}
121 \newlength{\polycvletterindent}
122 \setlength{\polycvletterindent}{\polycv@letterindent}
```

The lengths can also be altered with the following commands.

`\setheaderheight` Define the height for the header box.

```
123 \newcommand*{\setheaderheight}[1]{%
124   \setlength{\polycvheaderheight}{#1}}
```

`\setfooterheight` Define the height for the footer box.

```
125 \newcommand*{\setfooterheight}[1]{%
126   \setlength{\polycvfooterheight}{#1}}
```

`\setmargins` Define the width of the margins.

```
127 \newcommand*{\setmargins}[1]{%
128   \setlength{\polycvmargins}{#1}}
```

`\sethintcolwidth` Define the hint column width (where dates and level, etc. are set).

```

129 \newcommand*{\sethintcolwidth}[1]{%
130   \setlength{\polycvhintcol}{#1}}

```

`\sethintcolsep` Define the space between the hint column and the description column.

```

131 \newcommand*{\sethintcolsep}[1]{%
132   \setlength{\polycvhintcolsep}{#1}}

```

`\seticonspace` Define the space reserved for the items in the sidebar box.

```

133 \newcommand*{\seticonspace}[1]{%
134   \setlength{\polycviconspace}{#1}}

```

`\setprogbarheight` Define the standard height of the progress bar. This will also apply to the levels bar.

```

135 \newcommand*{\setprogbarheight}[1]{%
136   \setlength{\polycvprogbarheight}{#1}}

```

These commands need to be disabled for the body, so that automatically derived lengths will still be useable.

```

137 \@onlypreamble\setheaderheight
138 \@onlypreamble\setfooterheight
139 \@onlypreamble\setmargins
140 \@onlypreamble\sethintcolwidth
141 \@onlypreamble\sethintcolsep
142 \@onlypreamble\seticonspace
143 \@onlypreamble\setprogbarheight

```

Additional lengths, which are derived from the above, will be set at the end of the preamble.

```

144 \newlength{\polycvleftmargin}
145 \newlength{\polycvtopmargin}
146 \newlength{\polycvbottommargin}
147 \AtEndPreamble{%
148   \setlength{\polycvleftmargin}{%
149     \polycvsidebarwidth+2\polycvmargins}
150   \setlength{\polycvtopmargin}{%
151     \polycvheaderheight+\polycvmargins}
152   \setlength{\polycvbottommargin}{%
153     \polycvfooterheight+\polycvmargins}
154 }

```

5.3.5 Fonts and Styles

`\polycv@headerfont` Define the font family for the header and make it bold (by default) and store it in a variable. Provide access to this variable via a set command.
`\setheaderfont`

```
155 \providecommand\polycv@headerfont{}
156 \renewcommand{\polycv@headerfont}{\sffamily\bfseries}
157 \providecommand\setheaderfont{}
158 \renewcommand*{\setheaderfont}[1]{%
159   \renewcommand*{\polycv@headerfont}{#1}}
160 \@onlypreamble\setheaderfont
```

`\polycv@entry@ragged` Provide a variable to store how the output is set, i.e. the standard raggedness. Provide
`\setentryragged` commands to change the raggedness of the output. These need to be set in the preamble,
`\setentryjustified` so they are disabled for the body.

```
161 \providecommand\polycv@entry@ragged{}
162 \newcommand*{\setentryragged}{%
163   \renewcommand{\polycv@entry@ragged}{\raggedright}}
164 \newcommand*{\setentryjustified}{%
165   \renewcommand{\polycv@entry@ragged}{} }
166 \@onlypreamble\setentryragged
167 \@onlypreamble\setentryjustified
```

`\polycv@sig@align` Define the alignment for the signature, which is stored in a variable. Provide commands
`\setsigright` to change it, and disable them for the body.
`\setsigleft`

```
168 \providecommand\polycv@sig@align{right}
169 \newcommand*{\setsigright}{%
170   \renewcommand{\polycv@sig@align}{right}}
171 \newcommand*{\setsigleft}{%
172   \renewcommand{\polycv@sig@align}{left}}
173 \@onlypreamble\setsigright
174 \@onlypreamble\setsigleft
```

5.4 Macros and Environments

Define special commands and environments

`\setprogrbarunits` Control the number of items for the levels bar.

```
175 \newcommand*{\setprogrbarunits}[1]{%
176   \renewcommand*{\polycv@progrbarunits}{#1}}
177 \@onlypreamble\setprogrbarunits
```

5.4.1 Personal Information

This section defines the variables, which will store the personal information. These are used in the template lines of the sidebar.

<code>\insertauthor</code> <code>\inserttitle</code>	<p>The author and title commands already exist, so they only need to be stored.</p> <pre> 178 \providecommand*\insertauthor{} 179 \renewcommand{\insertauthor}{\@author} 180 \providecommand\inserttitle{} 181 \renewcommand{\inserttitle}{\@title} </pre>
<code>\insertposition</code> <code>\position</code>	<p>Store the position, which is used as the sub-heading in the title banner. Disable this command because it is needed before the header is set.</p> <pre> 182 \providecommand*\insertposition{} 183 \providecommand*\position{} 184 \renewcommand{\position}[1]{% 185 \renewcommand{\insertposition}{#1}} 186 \@onlypreamble\position </pre>
<code>\cvitemline</code>	<p>This defines a generic line consisting of two parboxes. This command is primarily needed for the sidebar, but it could be used somewhere else. The left parbox is used as a hint column and contains an icon, the right the value of a variable.</p> <pre> 187 \providecommand\cvitemline[3][\polycviconspace]{% 188 \parbox[t]{#1}{\centering#2}% 189 \parbox[t]{\linewidth-#1}{#3}\par\vspace{0.3\baselineskip}} </pre>
<code>\insertaddress</code> <code>\insertstreet</code> <code>\insertlocation</code>	<p>Variables to store an address.</p> <pre> 190 \providecommand\insertaddress{} 191 \providecommand\insertstreet{} 192 \providecommand\insertlocation{} </pre>
<code>\address</code> <code>\street</code> <code>\location</code>	<p>Commands to set the values used for the address</p> <pre> 193 \providecommand\address{} 194 \providecommand\street{} 195 \providecommand\location{} 196 \renewcommand{\address}[1]{% 197 \renewcommand{\insertaddress}{#1}} 198 \renewcommand{\street}[1]{% 199 \renewcommand{\insertstreet}{#1}} 200 \renewcommand{\location}[1]{% 201 \renewcommand{\insertlocation}{#1}} </pre>

Build the address for street and location.

```
202 \renewcommand{\insertaddress}{\insertstreet\\\insertlocation}
```

`\cvlineaddress` Template to produce the address for the sidebar.

```
203 \providecommand{\cvlineaddress}{%
204   \cvitemline{\faMapMarker}{\insertaddress}}
```

`\insertemail` Store and set email, template for the sidebar.

`\email`

```
\cvlineemail 205 \providecommand*\insertemail{}
206 \providecommand*\email{}
207 \renewcommand{\email}[1]{%
208   \renewcommand{\insertemail}{\href{mailto:#1}{#1}}}
209 \providecommand{\cvlineemail}{%
210   \cvitemline{\faEnvelope}{\insertemail}}
```

`\insertphone` Store and set phone number, template for the sidebar.

`\phone`

```
\cvlinephone 211 \providecommand*\insertphone{}
212 \providecommand*\phone{}
213 \renewcommand{\phone}[1]{\renewcommand{\insertphone}{#1}}
214 \providecommand{\cvlinephone}{%
215   \cvitemline{\faPhone}{\insertphone}}
```

`\insertmobile` Store and set mobile number, template for the sidebar.

`\mobile`

```
\cvlinemobile 216 \providecommand*\insertmobile{}
217 \providecommand*\mobile{}
218 \renewcommand{\mobile}[1]{\renewcommand{\insertmobile}{#1}}
219 \providecommand{\cvlinemobile}{%
220   \cvitemline{\faMobile}{\insertmobile}}
```

`\insertgithub` Store and set username for GitHub, template for the sidebar.

`\github`

```
\cvlinegithub 221 \providecommand*\insertgithub{}
222 \providecommand*\github{}
223 \renewcommand{\github}[1]{\renewcommand{\insertgithub}{%
224   \href{https://github.com/#1}{github.com/#1}}}
225 \providecommand{\cvlinegithub}{%
226   \cvitemline{\faGithub}{\insertgithub}}
```

`\orcidiconfilename` This defines the Orcid icon either from the file `orcidicon.pdf` if it is found by \LaTeX .

I am unaware of a \LaTeX package that defines this symbol.³ If such a file is not found, it will place as small square of bold letters spelling Orcid.

```

227 \providecommand*\orcidiconfilename{}
228 \IfFileExists{orcidicon.pdf}{%
229   \renewcommand{\orcidiconfilename}{%
230     \raisebox{-0.2em}{%
231       \includegraphics[height=1.0em]{orcidicon.pdf}}}%
232 }{%
233   \renewcommand{\orcidiconfilename}{%
234     \raisebox{-0.2em}{%
235       \resizebox{1em}{1em}{\textbf{ORCID}}}}}%
236 }

```

`\insertorcid` Store and set the Orcid number, template for the sidebar.
`\orcid`

```

\cvlineorcid 237 \providecommand*\insertorcid{}
238 \providecommand*\orcid{}
239 \renewcommand{\orcid}[1]{\renewcommand{\insertorcid}{%
240   \href{http://orcid.org/#1}{orcid.org/#1}}}
241 \providecommand{\cvlineorcid}{%
242   \cvitemline{\orcidiconfilename}{\insertorcid}}

```

`\insertsigfilename` Store the filename of an image used to produce the signature.
`\signaturefile`

```

243 \providecommand\insertsigfilename{}
244 \providecommand\signaturefile{}
245 \renewcommand{\signaturefile}[1]{%
246   \renewcommand{\insertsigfilename}{#1}}

```

5.4.2 Redefinition of Section Headers

`\section` The section and subsection commands are redefined to have no numbers. Instead there
`\subsection` will be a bar the length of the hint column, and they will use the primary color.

```

247 \renewcommand{\section}[1]{%
248   \ignorespaces%
249   \parbox[b]{1\linewidth}{%
250     \strut%
251     \color{polycvsectioncolor}%
252     \Large\polycv@headerfont%
253     \rule{\polycvhintcol}{1ex}\hspace{\polycvhintcolsep}%
254     \parbox{1.0\linewidth-\polycvhintcol-\polycvhintcolsep}{%
255       \strut%

```

³For more details see: *Is there a standard way to include ORCID in TeX / PDF?* (<https://tex.stackexchange.com/q/275578/33413>)

```

256      #1%
257    }%
258  }\vspace{0.5\baselineskip}}
259 \renewcommand{\subsection}[1]{%
260   \parbox[b]{1\linewidth}{%
261     \strut%
262     \color{polycvsectioncolor}%
263     \polycv@headerfont%
264     \hspace{\polycvhintcol}\hspace{\polycvhintcolsep}%
265     \parbox{1.0\linewidth-\polycvhintcol-\polycvhintcolsep}{%
266       \strut%
267       #1%
268     }%
269   }\vspace{0.3\baselineskip}}

```

5.4.3 Header and Footer Boxes

`\polycv@header` The header box will be used internally only. It is a simple box produced with tikz, and uses the author and position variables. It is typeset in the primary color of the template.

```

270 \newcommand{\polycv@header}[3][\polycvheaderheight]{%
271   \begin{tikzpicture}[remember picture,overlay]%
272     \node [rectangle, %
273           fill          = polycvheaderbackground, %
274           anchor        = north, %
275           minimum width = \paperwidth, %
276           minimum height = #1%
277           ] (headerbox) at (current page.north){};%
278     \node [anchor = mid] (cv-name) at (headerbox) {%
279       \Huge\polycv@headerfont\color{polycvheadertext}\textbf{%
280         #2
281       }%
282     };%
283     \node [anchor = north] at (cv-name.south) {%
284       \Large\polycv@headerfont\color{polycvheadertext}%
285       #3%
286     };%
287   \end{tikzpicture}%
288   \ignorespaces%
289 }

```

`\polycv@footer` The footer box will be used internally only. It is a simple box produced with tikz, which can be used to display page numbers. If the argument to the macro is empty, nothing will be printed, otherwise dashes are used to surround the command. It is typeset in the primary color of the template.

```

290 \newcommand{\polycv@footer}[2][\polycvfooterheight]{%

```

```

291 \begin{tikzpicture}[remember picture,overlay]%
292   \node [rectangle, %
293         fill          = polycvheaderbackground, %
294         anchor        = south, %
295         minimum width = \paperwidth, %
296         minimum height = #1%
297         ] (footerbox) at (current page.south){};%
298   \node [anchor = center] (pagenumber) at (footerbox) {%
299     \polycv@headerfont\color{polycvheadertext}%
300     \if\relax\detokenize{#2}\relax%
301     \else%
302     - #2 -%
303     \fi%
304   };%
305 \end{tikzpicture}%
306 \ignorespaces%
307 }

```

`\polycv@signature` The signature box will be used internally only. It is a simple box produced with tikz, which wraps around an image defined earlier. It will also print the author name below the image. By default the box has the same background color as the page.

```

308 \newcommand{\polycv@signature}[2][\polycvsidebarwidth]{%
309   \begin{tikzpicture}[remember picture, overlay]%
310     \node [rectangle, %
311           anchor = south west, %
312           text width = #1, %
313           align = \polycv@sig@align, %
314           minimum height = 0.75#1, %
315           yshift = \polycvbottommargin, %
316           xshift = \polycvmargins, %
317           fill = polycvsidebarbackground %
318           ] (cv-signbox) at (current page.south west) {%
319       \includegraphics[width=#1]{#2}\\%
320       \insertauthor%
321     };
322   \end{tikzpicture}%
323   \ignorespaces%
324 }

```

5.4.4 Level and Progress Bar

First a few simple filled and unfilled symbols are defined as tikz pictures.

`\polycv@square@nofill` Square symbols, the height and width are set to the height of the progress bar, which is defined via the options.
`\polycv@square@filled`

```

325 \newcommand{\polycv@square@nofill}[1][\polycvprogbarheight]{%
326   \begin{tikzpicture}[x=#1, y=#1]%
327     \filldraw[polycvprogbarnofill] (0,0) rectangle (1,1);%
328     \draw[polycvtextcolor, thick] (0,0) rectangle (1,1);%
329   \end{tikzpicture}}
330 \newcommand{\polycv@square@filled}[1][\polycvprogbarheight]{%
331   \begin{tikzpicture}[x=#1, y=#1]%
332     \filldraw[polycvprogbarfilled] (0,0) rectangle (1,1);%
333     \draw[polycvtextcolor, thick] (0,0) rectangle (1,1);%
334   \end{tikzpicture}}

```

`\polycv@circle@nofill` Analogous circle symbols.
`\polycv@circle@filled`

```

335 \newcommand{\polycv@circle@nofill}[1][\polycvprogbarheight]{%
336   \begin{tikzpicture}[x=#1, y=#1]%
337     \filldraw[polycvprogbarnofill] (0.5,0.5) circle [radius=0.5];%
338     \draw[polycvtextcolor, thick] (0.5,0.5) circle [radius=0.5];%
339   \end{tikzpicture}}
340 \newcommand{\polycv@circle@filled}[1][\polycvprogbarheight]{%
341   \begin{tikzpicture}[x=#1, y=#1]%
342     \filldraw[polycvprogbarfilled] (0.5,0.5) circle [radius=0.5];%
343     \draw[polycvtextcolor, thick] (0.5,0.5) circle [radius=0.5];%
344   \end{tikzpicture}}

```

`\polycv@repeating` This is a helper function to repeat typesetting a symbol. It will fill the spaces between the symbols.

```

345 \newcommand{\polycv@repeating}[2][5]{%
346   \ifnum#1 > 0%
347     \newcount\rep%
348     \rep0%
349     \loop\ifnum\rep < \number\numexpr#1-1\relax%
350       #2\hfill%
351       \advance\rep by 1%
352     \repeat%
353     #2%
354   \fi%
355 }

```

`\polycv@multiply` These are helper functions to multiply or divide two numbers. First define temporary
`\polycv@divide` lengths to do the calculations with.

```

356 \newlength\polycv@temp@len@a
357 \newlength\polycv@temp@len@b
358 \newlength\polycv@temp@len@res

```

Now use these to do the multiplication. The macro will use the two numbers #1 and #2

to return a token #3 with the result.

```

359 \def\polycv@multiply#1#2#3{%
360   \setlength\polycv@temp@len@a{#1\p@}%
361   \setlength\polycv@temp@len@res{#2\polycv@temp@len@a}%
362   \edef#3{\expandafter\strip@pt\polycv@temp@len@res}\ignorespaces}%

```

Similarly the lengths are used to do division The macro will divide the number #1 by #2 and return a token #3 with the result.

```

363 \def\polycv@divide#1#2#3{%
364   \setlength\polycv@temp@len@a{#1\p@}%
365   \setlength\polycv@temp@len@b{#2\p@}%
366   \setlength\polycv@temp@len@res{%
367     \p@ * \ratio{\polycv@temp@len@a}{\polycv@temp@len@b}}%
368   \edef#3{\expandafter\strip@pt\polycv@temp@len@res}\ignorespaces}%

```

`\polycv@level@bar` The level bar is also a helper function, which wraps around the repeating function. It sets its contents as a parbox with the width of the hint column (#1 by default). It also needs a level to display (#2), which is the number of filled elements (#3). It computes from the options of total units the number of unfilled elements (#4) to typeset.

If the level to display is a decimal number smaller than 1, it will use it as a fraction and determine the number of filled elements automatically (rounding down).

```

369 \newcommand{\polycv@level@bar}[4][\polycvhintcol]{%
370   \newcount\total@units%
371   \total@units\polycv@progbarsunits%
372   \newcount\temp@count%
373   \IfDecimal{#2}{%
374     \ifdim #2\p@ < \z@ %
375       \edef\temp@count{0}%
376     \else%
377       \ifnum\integerpart = 0%
378         \polycv@multiply{#2}{\total@units}{\mult@res}%
379       \IfDecimal{\mult@res}{\temp@count\integerpart}{\temp@count\z@}%
380       \else%
381         \temp@count\integerpart%
382       \fi%
383     \fi%
384   }{\temp@count\total@units}%
385   \newcount\level%
386   \ifnum\temp@count < \total@units \level\temp@count%
387   \else \level\total@units \fi%
388   \newcount\elelevel%
389   \elelevel\numexpr\total@units-\level\relax%
390   \def\symbol@filled{#3}%
391   \def\symbol@nofill{#4}%
392   \parbox{#1}{%

```

```

393 \ifnum\level = 0%
394 \polycv@repeating[\total@units]{\symbol@nofill}%
395 \else
396 \ifnum\level = \total@units%
397 \polycv@repeating[\total@units]{\symbol@filled}%
398 \else
399 \polycv@repeating[\level]{\symbol@filled}%
400 \hfill%
401 \polycv@repeating[\level]{\symbol@nofill}%
402 \fi%
403 \fi%
404 }%
405 }

```

`\levelbarsquares` Wrapper commands as user interfaces to the level bar.
`\levelbarcircles`

```

406 \newcommand{\levelbarsquares}[2][\polycvhintcol]{%
407 \polycv@level@bar[#1]{#2}{%
408 \polycv@square@filled}{\polycv@square@nofill}%
409 }
410 \newcommand{\levelbarcircles}[2][\polycvhintcol]{%
411 \polycv@level@bar[#1]{#2}{%
412 \polycv@circle@filled}{\polycv@circle@nofill}%
413 }

```

`\progressbar` The progress bar is a simple tikz image consisting of three rectangles: one denoting the level using the fill color, one using the empty color, and an empty box encompassing all as a frame. If the level l is $0 \leq l < 1$, it will be used directly, all other values will be converted to l/u , where u is the number of progress bar units. If the input is not a number, or larger than u , the bar is set in full.

```

414 \newcommand{\progressbar}[2][\polycvhintcol]{%
415 \newcount\total@units%
416 \total@units\polycv@progrbarunits%
417 \newcount\temp@count%
418 \IfDecimal{#2}{%
419 \ifdim #2\p@ < \z@ %
420 \edef\level@coord{0}
421 \else%
422 \ifnum\integerpart = 0%
423 \edef\level@coord{#2}%
424 \else%
425 \ifnum\integerpart < \total@units%
426 \temp@count\integerpart%
427 \else%
428 \temp@count\total@units%
429 \fi%
430 \polycv@divide{\temp@count}{\total@units}{\level@coord}%

```

```

431     \fi%
432     \fi%
433   }{\edef\level@coord{1}}%
434   \hfill%
435   \begin{tikzpicture}[x=0.99*#1, y=\polycvproghbarheight]%
436     \filldraw[polycvproghbarnofill]%
437       (0, 0) rectangle (1, 1) ;%
438     \filldraw[polycvproghbarfilled]%
439       (0, 0) rectangle (\level@coord, 1);%
440     \draw[polycvtextcolor, thick]%
441       (0, 0) rectangle (1, 1) ;%
442   \end{tikzpicture}%
443 }%

```

5.4.5 Commands for the main Body

`\cvline` A generic command to typeset a line in the CV. It consists of two parboxes, the left being the hint column, and the right the description. One example usage is: `\cvline[width]{hint}{description}`.

```

444 \providecommand\cvline{}
445 \renewcommand{\cvline}[3][\polycvhintcol]{%
446   \par%
447   \parbox[t]{#1}{\strut\raggedleft #2}%
448   \hspace{\polycvhintcolsep}%
449   \parbox[t]{\linewidth-\polycvhintcolsep-#1}{%
450     \strut\polycv@entry@ragged #3}%
451   \par\vspace{0.2\baselineskip}%
452 }

```

`\cventry` The entry defines a block. It uses the command above, but fills in more details in the description parbox of the template. An example usage is: `\cventry[width]{when}{what}{who}{where}{optional}{optional}`.

```

453 \providecommand\cventry{}
454 \renewcommand{\cventry}[7][\polycvhintcol]{%
455   \cvline[#1]{#2}{%
456     \textbf{#3}, \textit{#4}, #5%
457     \if\relax\detokenize{#6}\relax%
458     \else%
459       , #6%
460     \fi%
461     \if\relax\detokenize{#7}\relax%
462     .%
463     \else%
464     .\newline\small #7%
465     \fi%

```



```

466 }%
467 }

```

`\cvskill` This command uses a progress bar in the hint column.

```

468 \providecommand\cvskill[2]{%
469   \cvline[\polycvhintcol]{%
470     \progressbar[0.5\linewidth]{#2}}{#1}}

```

`\cvlanguage` This is basically a wrapper to the above command.

```

471 \providecommand\cvlanguage[2]{%
472   \cvskill{#1}{#2}}

```

Env `polycvfirstpage` This environment redefines the page layout for the first page, and calls the header and footer templates.

```

473 \newenvironment{polycvfirstpage}{%
474   \newgeometry{%
475     left=\polycvleftmargin,
476     top=\polycvtopmargin,
477     right=\polycvmargins,
478     bottom=\polycvbottommargin,
479     nohead,nofoot}%
480   \polycv@header{\insertauthor}{\insertposition}%
481   \polycv@footer{}%
482 }{%
483   \restoregeometry%
484   \ignorespaces%
485 }

```

Env `polycvpage` This environment defines the page layout for a 'regular' page. It may cause problems, when the content is overflowing, i.e. producing more than one page. Unfortunately, page handling has (still) to be done manually. It also calls the header and footer templates, but they are empty by default.

```

486 \newenvironment{polycvpage}{%
487   \newgeometry{%
488     top=\polycvtopmargin,%
489     left=2\polycvmargins,%
490     right=2\polycvmargins,%
491     bottom=\polycvbottommargin,%
492     nohead,nofoot}%
493   \polycv@header{}{}%
494   \polycv@footer{}%
495 }{%
496   \restoregeometry%

```

```

497 \ignorespaces%
498 }

```

5.4.6 Side Bar Definitions

`\spline` A generic command to typeset a line in the sidebar as a single parbox. It consists of two parboxes, the right being the sidebar hint column, and the left the description. It is basically the reverse layout of the `\cvline` macro. One example usage is: `\spline [width]{hint}{description}`. This macro essentially replaces the original internal macro `\polycv@sidebar@skill`.

```

499 \providecommand\spline{}
500 \renewcommand{\spline}[3][\polycvsidebarhint]{%
501   \parbox{1.0\linewidth}{%
502     \hspace{\polycvsidebarindent}%
503     \parbox[t]{\linewidth-2\polycvsidebarindent-#1}{%
504       \strut\polycv@entry@ragged #2}%
505     \hspace{\polycvsidebarindent}\hfill%
506     \parbox[t]{#1}{\strut\raggedleft #3}%
507     \vspace{0.2\baselineskip}%
508   }%
509 }

```

`\sidebarskill`
`\sidebarlanguage`

```

510 \providecommand\sidebarskill[3][\polycvsidebarhint]{%
511   \spline[#1]{#2}{\progressbar[\linewidth]{#3}}%
512 }
513 \providecommand\sidebarlanguage[3][\polycvsidebarhint]{%
514   \spline[#1]{#2}{\progressbar[\linewidth]{#3}}%
515 }

```

Env `polycvsidebar` This environment provides a box as a tikz picture for the sidebar. It first saves the original definition of the section command, then redefines it for a better fit. It also redefines the skill and language commands for a better fit within the box. At the end, it restores the original definitions. If the option to sign the CV is active, another box will be inserted at the bottom off the page.

```

516 \newenvironment{polycvsidebar}{%
517   \let\section\save@section%
518   \newcommand{\section}[1]{%
519     \parbox[b]{1\linewidth}{%
520       \strut%
521       \color{polycvsectioncolor}\large\polycv@headerfont{##1}%
522     }\par\vspace{0.5\baselineskip}}%
523   \let\cvlanguage\save@polycvlanguage%

```

```

524 \newcommand{\cvlanguage}[2]{%
525     \sidebarlanguage{##1}{##2}}%
526 \let\cvskill\save@polycvskill%
527 \newcommand{\cvskill}[2]{%
528     \sidebarskill{##1}{##2}}%
529 \begin{tikzpicture}[remember picture, overlay]%
530     \node [anchor = north west, %
531           text width = \polycvsidebarwidth, %
532           xshift = \polycvmargins, %
533           yshift = -\polycvheaderheight-\polycvmargins, %
534           fill = polycvsidebarbackground %
535           ] (polycvsidebarbox) at (current page.north west) %
536     \bgroup%
537 }{%
538     \egroup;%
539 \end{tikzpicture}%
540 \let\save@section\section%
541 \let\save@polycvlanguage\cvlanguage%
542 \let\save@polycvlanguage\cvskill%
543 \ifpolycv@signcv%
544     \polycv@signature{\insertsigfilename}%
545 \fi%
546 \ignorespaces%
547 }%

```

5.5 Cover Letter Definitions

In this section the commands for the letter template are set up.

`\polycv@letter@from` The header box is now substituted to include the address. The colour scheme is also adjusted to make the box less bulky. Therefore the usual background colour and the text color will be used.

```

548 \newcommand{\polycv@letter@from}[3][\polycvheaderheight]{%
549     \begin{tikzpicture}[remember picture, overlay]%
550         \node [rectangle, %
551               fill = polycvheadertext, %
552               anchor = north, %
553               minimum width = \paperwidth, %
554               minimum height = #1-1ex%
555               ] (headerbox) at (current page.north){};
556         \node [rectangle, %
557               fill = polycvheaderbackground, %
558               anchor = north, %
559               minimum width = \paperwidth, %
560               minimum height = 1ex%
561               ] (headerline) at (headerbox.south){};

```

```

562 \node [anchor = east, %
563         text width = 5cm, %
564         xshift      = -2\polycvmargins
565       ] (polycv-letter-address) at (headerbox.east) {%
566       \polycv@headerfont\color{polycvheaderbackground}%
567       \parbox[t]{1.0\linewidth}{%
568         \raggedleft%
569         \textbf{\Large #2}\\%
570         \textit{\normalsize #3}%
571       }%
572     };%
573 \end{tikzpicture}%
574 \ignorespaces%
575 }

```

`\polycv@letter@to` This defines the field of the addressee.

```

576 \newcommand{\polycv@letter@to}[1]{%
577   \noindent\parbox[t][4cm][c]{0.4\linewidth}{\raggedright#1}\par%
578   \vspace{1\baselineskip}%
579 }

```

`\polycv@letter@date` This defines and formats the date field.

```

580 \newcommand{\polycv@letter@date}{%
581   \noindent\parbox[t]{1.00\linewidth}{\raggedleft\today}\par%
582 }

```

`\polycv@letter@subject` This defines and formats the subject field.

```

583 \newcommand{\polycv@letter@subject}[1]{%
584   \noindent\parbox[t]{1.00\linewidth}{%
585     \raggedright\textbf{#1}}\par%
586 }

```

`\opening` This defines and formats the opening and closing remarks
`\closing`

```

587 \providecommand\opening{}
588 \renewcommand{\opening}[1]{\noindent{}#1\par}
589 \providecommand\closing{}
590 \renewcommand{\closing}[1]{\noindent{}#1\par}

```

`\polycv@letter@psmark` Define the default postscript mark.

```

591 \newcommand{\polycv@letter@psmark}{P.S.~}

```

`\setpsmark` Command to change the default postscript mark.

```
592 \providecommand\setpsmark{}
593 \renewcommand*{\setpsmark}[1]{%
594   \renewcommand{\polycv@letter@psmark}{#1}}
```

`\polycv@letter@ps`
`\ps` Variable to store the content of the postscript remark and command to set it.

```
595 \providecommand\polycv@letter@ps{}%
596 \providecommand\ps{}
597 \renewcommand{\ps}[1]{%
598   \renewcommand{\polycv@letter@ps}{%
599     \noindent\footnotesize\polycv@letter@psmark#1\par%
600   }%
601 }
```

Env `polycvletter` Here the actual letter environment is defined. Like before, this is intended to be only one page and hence may cause problems for sufficiently long letters. The environment requires two parameters, the recipient address, and the body. First the page setup is changed, then the templates for header, recipient address, subject, and footer are called. The indentation is set to the specified value. At the end, the signature will be inserted, and below that - if present - the postscript remark.

```
602 \newenvironment{polycvletter}[3][\insertaddress]{%
603   \newgeometry{%
604     top=\polycvtopmargin,%
605     left=2\polycvmargins,%
606     right=2\polycvmargins,%
607     bottom=\polycvbottommargin,%
608     nohead,nofoot}%
609   \polycv@letter@from{\insertauthor}{#1}%
610   \polycv@footer{}%
611   \polycv@letter@to{#3}%
612   \polycv@letter@date%
613   \polycv@letter@subject{#2}%
614   \setlength{\parindent}{\polycvletterindent}%
615 }{%
616   \vspace{0.5\baselineskip}%
617   \noindent\includegraphics[width=5cm]{\insertsigfilename}\\%
618   \noindent\insertauthor\par%
619   \if\relax\detokenize{\polycv@letter@ps}\relax%
620   \else%
621     \polycv@letter@ps\par%
622   \fi%
623   \restoregeometry%
624 }
```

5.6 Appendix

`\pdfappendix` The `appendix` command is an interface to include (parts of) a pdf, e.g. for certificates or recommendations. The page colour is first reset to having none, otherwise it would overlay on top of the included pdf. By default all pages will be included, but this can be overwritten to specific range (and other options). The command can be used multiple times.

```
625 \providecommand*\pdfappendix{}
626 \renewcommand*\pdfappendix}[2][pages={1-}]{%
627   \nopagecolor%
628   \includepdf[#1]{#2}}%
```

6 Building polycv and its Documentation

To compile the `polycv` package:

1. `pdflatex polycv.ins`

To compile the `polycv` documentation

1. `pdflatex polycv.dtx`
2. `makeindex -s gglo.ist -o polycv.gls polycv.glo`
3. `makeindex -s gind.ist -o polycv.ind polycv.idx`
4. `pdflatex polycv.dtx` (several times)

Change History

v1.0	the sidebar 33
General: Initial version 1	General: New macro for a line sidebar . 1
v1.1.dev	Options for lengths for indentation and hint column for the sidebar . . 15
\sbline: Added sidebar line 33	polycvsidebar: switched to new language and skill templates 33
\sidebarlanguage: language template for the sidebar 33	
\sidebarskill: skill template for	

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols		\email 9, 205	
\@onlypreamble 65–68, 137–143, 160, 166, 167, 173, 174, 177, 186		environment:	
A		polycvfirstpage 12	
\address 8, 193		polycvletter 13	
\author 8		polycvpage 12	
B		polycvsidebar 12	
biblatex (option) 7		environments:	
C		polycvfirstpage 473	
\closing 13, 587		polycvletter 602	
\cventry 11, 453		polycvpage 486	
\cvitemline		polycvsidebar 516	
.. 10, 187, 204, 210, 215, 220, 226, 242		\expandafter 362, 368	
\cvlanguage 11, 471, 523, 524, 541		F	
\cvline 9, 444, 455, 469		\faEnvelope 210	
\cvlineaddress 11, 203		\faGithub 226	
\cvlineemail 11, 205		\faMapMarker 204	
\cvlinegithub 12, 221		\faMobile 220	
\cvlinemobile 11, 216		\faPhone 215	
\cvlineorcid 12, 237		footerheight (option) 6	
\cvlinephone 11, 211		G	
\cvskill 11, 468, 472, 526, 527, 542		\github 9, 221	
D		H	
draft, final (option) 7		headerheight (option) 6	
E		highlight (option) 7	
\elevel 388, 389, 401		hintcol (option) 6	
		hintcolsep (option) 6	

I	
iconspace (option)	6
\IfDecimal	373, 379, 418
\ifdim	374, 419
\ifpolycv@biblatex	93
\ifpolycv@draft	84
\ifpolycv@signcv	51, 543
\insertaddress 8, 190, 197, 202, 204, 602	
\insertauthor 8, 178, 320, 480, 609, 618	
\insertemail	9, 205
\insertgithub	9, 221
\insertlocation 9, 190, 201, 202	
\insertmobile	9, 216
\insertorcid	9, 237
\insertphone	9, 211
\insertposition	8, 182, 480
\insertsigfilename . 9, 243, 544, 617	
\insertstreet	9, 190, 199, 202
\inserttitle	8, 178
\integerpart 377, 379, 381, 422, 425, 426	
L	
letterindent (option)	6
\level	385–387, 389, 393, 396, 399
\level@coord ..	420, 423, 430, 433, 439
\levelbarcircles	10, 406
\levelbarsquares	10, 406
\location	9, 193
M	
margins (option)	6
mixing (option)	7
\mobile	9, 216
\mult@res	378, 379
O	
\opening	13, 587
option:	
biblatex	7
draft, final	7
footerheight	6
headerheight	6
highlight	7
hintcol	6
hintcolsep	6
iconspace	6
letterindent	6
margins	6
mixing	7
primary	7
progbarheight	7
progbarunits	7
secondary	7
shade	7
sidebarwidth	6
signcv	7
titlepage	8
twocolumn	8
xcolor	6
\orcid	9, 237
\orcidiconfilename ... 11, 227, 242	
P	
\p@	360, 364, 365, 367, 374, 419
\pdfappendix	14, 625
\phone	9, 211
\polycv@circle@filled ... 335, 412	
\polycv@circle@nofill ... 335, 412	
\polycv@divide	356, 430
\polycv@entry@ragged 161, 450, 504	
\polycv@footer ... 290, 481, 494, 610	
\polycv@footerheight	104
\polycv@header	270, 480, 493
\polycv@headerfont	
. 155, 252, 263, 279, 284, 299, 521, 566	
\polycv@headerheight	102
\polycv@highlight	62, 76
\polycv@hintcol	110
\polycv@hintcolsep	112
\polycv@iconspace	118
\polycv@letter@date 580, 612	
\polycv@letter@from 548, 609	
\polycv@letter@ps ... 595, 619, 621	
\polycv@letter@psmark 591, 594, 599	
\polycv@letter@subject .. 583, 613	
\polycv@letter@to	576, 611
\polycv@letterindent	122
\polycv@level@bar ... 369, 407, 411	
\polycv@margins	106
\polycv@mixing	75
\polycv@multiply	356, 378
\polycv@primary	
. 58, 71, 73, 75, 78, 80, 90	
\polycv@progbarheight	120
\polycv@progbarunits 176, 371, 416	
\polycv@repeating	
. 345, 394, 397, 399, 401	
\polycv@secondary	
. 60, 70, 72, 77, 80, 90	
\polycv@shade	64, 75

\polycv@sidebarhint	114	
\polycv@sidebarindent	116	
\polycv@sidebarwidth	108	
\polycv@sig@align	168, 313	
\polycv@signature	308, 544	
\polycv@square@filled ...	325, 408	
\polycv@square@nofill ...	325, 408	
\polycv@temp@len@a		
.....	356, 360, 361, 364, 367	
\polycv@temp@len@b ..	357, 365, 367	
\polycv@temp@len@res		
.....	358, 361, 362, 366, 368	
\polycv@xcolor	42	
\polycvbottommargin		
.....	146, 152, 315, 478, 491, 607	
polycvfirstpage (environment)	12, 473	
\polycvfooterheight		
.....	103, 104, 126, 153, 290	
\polycvheaderheight		
....	101, 102, 124, 151, 270, 533, 548	
\polycvhintcol		
..	98, 109, 110, 130, 253, 254, 264,	
	265, 369, 406, 410, 414, 445, 454, 469	
\polycvhintcolsep	96, 111,	
	112, 132, 253, 254, 264, 265, 448, 449	
\polycviconspace .	117, 118, 134, 187	
\polycvleftmargin ...	144, 148, 475	
polycvletter (environment) ..	13, 602	
\polycvletterindent .	121, 122, 614	
\polycvmargins		
..	105, 106, 128, 149, 151, 153, 316,	
	477, 489, 490, 532, 533, 564, 605, 606	
polycvpage (environment)	12, 486	
\polycvprogbarheight		
..	119, 120, 136, 325, 330, 335, 340, 435	
polycvsidebar (environment) .	12, 516	
\polycvsidebarhint		
.....	113, 114, 500, 510, 513	
\polycvsidebarindent		
.....	115, 116, 502, 503, 505	
\polycvsidebarwidth		
.....	107, 108, 149, 308, 531	
\polycvtopmargin		
.....	145, 150, 476, 488, 604	
\position	8, 182	
primary (option)	7	
progbarheight (option)	7	
progbarunits (option)	7	
\progressbar ...	10, 414, 470, 511, 514	
\ps	13, 595	
		R
\ratio	367	
\rep	347–349, 351	
\RequirePackage	1, 38–41, 43–49	
		S
\save@polycvlanguage	523, 541, 542	
\save@polycvskill	526	
\save@section	517, 540	
\spline	499, 511, 514	
secondary (option)	7	
\section	9, 247, 517, 518, 540	
\setcolhighlight	7, 61, 67	
\setcolprimary	7, 57, 65	
\setcolsecondary	7, 59, 66	
\setcolshade	7, 63, 68	
\setentryjustified	8, 161	
\setentryragged	8, 161	
\setfooterheight	6, 125, 138	
\setheaderfont	8, 155	
\setheaderheight	6, 123, 137	
\sethintcolsep	6, 131, 141	
\sethintcolwidth	6, 129, 140	
\seticonspace	6, 133, 142	
\setmargins	6, 127, 139	
\setprogbarheight	7, 135, 143	
\setprogbarunits	7, 175	
\setpsmark	13, 592	
\setsidebarwidth	6	
\setsigleft	8, 168	
\setsigright	8, 168	
shade (option)	7	
\sidebarlanguage	510, 525	
\sidebarskill	510, 528	
sidebarwidth (option)	6	
\signaturefile	9, 243	
signcv (option)	7	
\street	9, 193	
\strip@pt	362, 368	
\subsection	9, 247	
\symbol@filled	390, 397, 399	
\symbol@nofill	391, 394, 401	
		T
\temp@count	372, 375,	
	379, 381, 384, 386, 417, 426, 428, 430	
\title	8	
titlepage (option)	8	

<code>\total@units</code>	X	
. 370, 371, 378, 384, 386, 387, 389,	<code>xcolor</code> (option)	6
394, 396, 397, 415, 416, 425, 428, 430		
	Z	
<code>twocolumn</code> (option)	8	<code>\z@</code> 374, 379, 419