

Cassandra 1x2m

By PolyMech



1-interlocked-squared



square (extrapolate) image - dont chan...

Key Features

- Produces recycled plastic sheets up to 60mm thick from shredded flake
- Delivers 20 tons of hydraulic pressure for reliable, even compression
- Interlockable plates — combine to press full sheets up to 1150 × 2300 mm
- Hydraulic via pneumatic drive or standard hydraulic cylinder
- Safe, ergonomic mould handling with guided rails
- Sequential heating — staggers plate activation to stay within power supply limits
- Adaptive pressure — fully configurable via the built-in web interface
- Visual and audible feedback at every stage of the cycle
- Advanced web interface for precise pressure, temperature, and event control — [view documentation](#)
- Open hardware — licensed under [CERN OHL v2](#)



**HDPE pellet floor
with a few flakes -
2x1m - 22mm thick**



Polymech Controller



**PolyMech Design -
Research Project**

Compare Cassandra Models

Model

Price (€)

Pressure

Plate size

Max thickness

Power

Voltage

Weight

Cassandra 45cm

2,800

20 T

45 cm (interlockable)

45 mm

3 kW

220 V

140 kg

Cassandra 65cm

4,550

20 T

65 cm (interlockable)

60 mm

6 kW

220/380 V

320 kg

Cassandra 1150

8,500

20 T

1150 mm (up to 1150 × 2300 mm interlocked)

60 mm

22 kW

380 V

710 kg