

Delivering to a Client

Build on your PC, ship one bundle, licence each hospital

October 2026 · For the Polynexus team

THE JOURNEY AT A GLANCE

Part	What happens	Who	Where
1. Build	Make the install bundle	You	Your PC (WSL)
2. Deliver	Send the bundle to the hospital	You	USB drive or link
3. Install	First run of the installer	Hospital IT	Client's server
4. Licence	Issue the licence file	You	Your PC
5. Activate	Second run of the installer	Hospital IT	Client's server
6. Domain	Put it on hms.hospital.com with HTTPS	Hospital IT	Client's server
7. Backups	Send nightly backups off the server	Hospital IT	Client's server
8. Later	Updates and renewals	Both	

Before you start

You never copy code to the client. Everything is built on your PC and only the finished bundle goes to the hospital. The bundle holds the compiled program (no source code) and the installers. The client's server needs only **Docker** — no Python, Node or source code — and can run **Linux** or **Windows**.

One bundle serves every client. What differs per hospital is only its licence file: features, number of users, expiry date, and the machine it's bound to.

Never send: the `Backend` or `Frontend` folders, `venv`, any `.env` file, or your private signing key (`license_signing_key.pem`).

1 Build the bundle

On your PC, with **Docker Desktop** running, open **WSL (Ubuntu)**:

```
# WSL (Ubuntu) on your PC
cd /mnt/e/Aniket/next/Hospital/Hospital/Frontend
git pull
git lfs pull
cd ../Backend
git pull
make bundle VERSION=1.0.1
```

- The bundle contains **both** the backend and the frontend (with nginx), plus the PostgreSQL and Redis images.
- `git lfs pull` downloads the 3D anatomy model (168 MB), which is built into the frontend. Without it the build stops and tells you to run it.
- Use a new, higher version number for every release (1.0.1, 1.0.2, 1.1.0, ...).
- The first build takes 15–30 minutes; later builds are faster.
- Result: `Backend\dist\bundle-1.0.1.tar.gz` (about 430 MB).

2

Deliver the bundle

Send `bundle-1.0.1.tar.gz` to the hospital: USB drive, Google Drive or OneDrive link, or secure file transfer. It's safe to share: it contains no source code and no secrets.

So the hospital can confirm the file arrived complete, send its checksum with it:

```
# WSL (Ubuntu) on your PC
sha256sum dist/bundle-1.0.1.tar.gz
```

The hospital compares it with `Get-FileHash bundle-1.0.1.tar.gz` (Windows) or `sha256sum bundle-1.0.1.tar.gz` (Linux).

3

Install on the client's server

Hospital IT runs this from the folder where they saved the bundle.

Linux server (as root):

```
# Linux server
sudo mkdir -p /opt/hms
sudo tar -xzf bundle-1.0.1.tar.gz -C /opt/hms --strip-components=1
cd /opt/hms
sudo ./install.sh
```

Windows server (PowerShell as administrator; Docker Desktop with Linux containers):

```
# Windows server - PowerShell (administrator)
mkdir -Force C:\hms
tar -xzf bundle-1.0.1.tar.gz -C C:\hms --strip-components=1
cd C:\hms
powershell -ExecutionPolicy Bypass -File .\install.ps1
```

The installer asks for the **hostname or IP** staff will use, generates secrets, loads the program (no internet needed), and then prints a **Deployment ID** and a **Machine fingerprint**. It saves both to `config/REQUEST-LICENCE.txt` , then stops.

The hospital sends you `REQUEST-LICENCE.txt` .

The installer creates `.env` , which holds the keys that decrypt patient data. Tell the hospital to back up `.env` and keep it private.

4

Issue the licence

On **your PC**, in **Command Prompt**:

```
REM Command Prompt on your PC
cd /d E:\Aniket\next\Hospital\Hospital\Backend\tools
set LICENSE_SIGNING_KEY_PATH=C:\Users\User\Desktop\key\license_signing_key.pem
..\venv\Scripts\python.exe -m license_issuer new
```

Question	What to type
Customer / hospital legal name	The hospital's legal name, as in the contract
Deployment ID	Paste from their REQUEST-LICENCE.txt. Never leave it blank.
Start and expiry date	From the contract (YYYY-MM-DD), or Enter for today / one year
Grace period	Enter for 14 days, or as agreed
Maximum active users	From the contract
Features	The numbers of the purchased features, e.g. 1,3,4 , then Enter on the empty line
Bind to one machine?	y , then paste the fingerprint from REQUEST-LICENCE.txt
Output file	e.g. license-city-hospital.lic

Check it before sending:

```
REM Command Prompt on your PC
..\venv\Scripts\python.exe -m license_issuer verify license-city-hospital.lic
```

It must say **Signature OK**, and its Deployment ID and fingerprint must match **REQUEST-LICENCE.txt** . Then **send the .lic file to the hospital**. It is safe to email: it can't be edited and only works on their server.

You can also issue licences from the SaaS console: Tenants & Subscriptions → the hospital → **License**. It produces the same kind of file.

5

Activate

Hospital IT saves the licence as `config/license.lic` in the install folder and runs the installer again.

Linux:

```
# Linux server
sudo cp license-city-hospital.lic /opt/hms/config/license.lic
cd /opt/hms
sudo ./install.sh
```

Windows:

```
# Windows server - PowerShell (administrator)
Copy-Item .\license-city-hospital.lic C:\hms\config\license.lic
cd C:\hms
powershell -ExecutionPolicy Bypass -File .\install.ps1
```

The installer finds the licence, prepares the database, asks for the **administrator email and password**, creates the hospital, and starts everything. It ends by printing the address to open, e.g. `http://hms.cityhospital.local/` (or with `:8080` if port 80 was busy).

The hospital signs in, and checks **Settings** → **License** shows the purchased features, users and expiry.

6

Domain and HTTPS

So staff open `https://hms.hospital.com` instead of an IP address.

1. **DNS:** the hospital's IT points the name at the server. For use inside the hospital (recommended), add it to the internal DNS (Windows Server DNS or the router) with the server's LAN IP. For access from outside, add a public DNS record and forward ports 80 and 443 to the server — a VPN is safer than exposing a hospital system to the internet.
2. **Run the domain script** in the install folder:

```
# Linux server
sudo ./configure-domain.sh
```

```
# Windows server - PowerShell (administrator)
powershell -ExecutionPolicy Bypass -File .\configure-domain.ps1
```

It asks for the domain, then how to do HTTPS:

Choice	When to use it
1. Hospital's own certificate	The hospital has a certificate (e.g. <code>*.hospital.com</code>). Give the PEM certificate and key files; they are checked before use.
2. Let's Encrypt	Free, renews itself automatically. The server must be reachable from the internet on port 80.
3. No certificate	Plain HTTP, internal network only, until a certificate is available.

It updates the settings and restarts. Use ports 80 and 443 for a domain: if the installer moved to 8080 because port 80 was busy, free port 80 first (see RUNBOOK section 8).

7

Backups

Every night at 02:00 the system backs up the whole database and uploaded documents into the `backups` folder, keeps 30 days, and writes the result to `backups/LAST-BACKUP.txt`.

Backups must leave the server, or a disk failure loses them too. Hospital IT sets `BACKUP_DIR` in `.env` to a NAS or external drive and restarts the backup service:

```
# .env in the install folder (one of these)
BACKUP_DIR=/mnt/nas/hms-backups
BACKUP_DIR=D:/hms-backups
```

```
# Linux or Windows server, in the install folder
docker compose up -d backup
docker compose exec backup sh /backup.sh now
```

The second line makes a backup immediately, to confirm it works. Then:

- **Weekly:** open `LAST-BACKUP.txt` and check it says `OK`.
- **Once after installing:** practise a restore (RUNBOOK section 9).
- **Keep a copy of `.env` separately and safely:** backups can't be read without its keys.

8

Updates and renewals

New version of the software:

1. You build a new bundle with a higher version (Part 1) and deliver it (Part 2).
2. Hospital IT unpacks it into a **new, separate folder** and runs the upgrade from there:

```
# Linux server (from the new bundle folder)
sudo ./upgrade.sh /opt/hms
```

```
# Windows server - PowerShell (administrator), from the new bundle folder
powershell -ExecutionPolicy Bypass -File .\upgrade.ps1 -InstallDir C:\hms
```

The upgrade **backs up the database first**, then updates and restarts. The licence, settings and all data are kept.

Licence renewal (yearly, or when they buy more users or features):

```
REM Command Prompt on your PC
..\env\Scripts\python.exe -m license_issuer renew license-city-hospital.lic
```

Send the new file. The hospital admin uploads it in **Settings** → **License** — it applies immediately, no restart.

Full reference: [deploy/RUNBOOK.md](#) (troubleshooting, HTTPS, rollback). **Practice run:** [docs/TRIAL_INSTALL_WINDOWS.pdf](#) .