SfePy - Simple Finite Elements in Python Short Introduction ...

Robert Cimrman¹ Ondřej Čertík²

¹Department of Mechanics & New Technologies Research Centre University of West Bohemia in Plzeň, Czech Republic

²Institute of Physics, Academy of Sciences of the Czech Republic & Charles University in Prague, Czech Republic

EuroSciPy 2008, July 27, Leipzig, Germany



roduction Our choice Complete Example (Simple) Testing Example Problems Conclusion O 0 00000000 00

Outline

- Introduction
 - Notes on Programming Languages
- Our choice
 - Mixing Languages Best of Both Worlds
 - Software Dependencies
- 3 Complete Example (Simple)
 - Introduction
 - Problem Description File
 - Running SfePy
 - Top-level Scripts
- 4 Testing
 - Verification of Numerical Results
- **5** Example Problems
 - Shape Optimization in Incompressible Flow Problems
 - Finite Element Formulation of Schrödinger Equation
- 6 Conclusion

Introduction

- SfePy = simple finite elements in Python
 - general finite element analysis software
 - solving systems of PDEs
- BSD open-source license
- available at
 - http://sfepy.org (developers)
 - mailing lists, issue (bug) tracking
 - we encourage and support everyone who joins!
 - http://sfepy.kme.zcu.cz (project information)
- selected applications:
 - homogenization of porous media (parallel flows in a deformable porous medium)
 - acoustic band gaps (homogenization of a strongly heterogenous elastic structure: phononic materials)
 - shape optimization in incompressible flow problems
 - finite element formulation of Schrödinger equation

Introduction

- SfePy = simple finite elements in Python
 - general finite element analysis software
 - solving systems of PDEs
- BSD open-source license
- available at
 - http://sfepy.org (developers)
 - mailing lists, issue (bug) tracking
 - we encourage and support everyone who joins!
 - http://sfepy.kme.zcu.cz (project information)
- selected applications:
 - homogenization of porous media (parallel flows in a deformable porous medium)
 - acoustic band gaps (homogenization of a strongly heterogenous elastic structure: phononic materials)
 - shape optimization in incompressible flow problems
 - finite element formulation of Schrödinger equation

Notes on Programming Languages Rough Division

compiled (fortran, C, C++, Java, ...)

Pros

Introduction

- speed
- large code base (legacy codes)
- tradition

- (often) complicated build process, recompile after any change
- low-level ⇒ lots of lines to get basic stuff done
- code size ⇒ maintenance problems
- static
- interpreted or scripting (sh, tcl, matlab, perl, ruby, python, . . .

 Introduction
 Our choice
 Complete Example (Simple)
 Testing
 Example Problems
 Conclusion

 ○●
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○
 ○○

Notes on Programming Languages Rough Division

compiled (fortran, C, C++, Java, ...)

Pros

- speed
- large code base (legacy codes)
- tradition

- (often) complicated build process, recompile after any change
- low-level ⇒ lots of lines to get basic stuff done
- ullet code size \Rightarrow maintenance problems
- static!
- interpreted or scripting (sh, tcl, matlab, perl, ruby, python, ...)
- Pros
 - no compiling
 - (very) high-level ⇒ a few of lines to get (complex) stuff done
 - code size ⇒ easy maintenance
 - dynamic!
 - (often) large code base

- many are relatively new
- not known as useful in many scientific communities
- lack of speed

Notes on Programming Languages Rough Division

• compiled (fortran, C, C++, Java, ...)

Pros

Introduction

- speed
- large code base (legacy codes)
- tradition

Cons

- (often) complicated build process, recompile after any change
- low-level ⇒ lots of lines to get basic stuff done
- ullet code size \Rightarrow maintenance problems
- static!
- interpreted or scripting (sh, tcl, matlab, perl, ruby, python, ...)

Pros

- no compiling
- (very) high-level ⇒ a few of lines to get (complex) stuff done
- code size ⇒ easy maintenance
- dvnamic!
- (often) large code base

- many are relatively new
- not known as useful in many scientific communities
- lack of speed

Notes on Programming Languages Rough Division

compiled (fortran, C, C++, Java, ...)

Pros

Introduction

- speed
- large code base (legacy codes)
- tradition

• interpreted or scripting (sh, tcl, matlab, perl, ruby, python, ...)

Pros

- no compiling
- (very) high-level ⇒ a few of lines to get (complex) stuff done
- code size ⇒ easy maintenance
- dynamic!
- (often) large code base

Cons

- (often) complicated build process, recompile after any change
- low-level ⇒ lots of lines to get basic stuff done
- code size ⇒ maintenance problems
- static!

- many are relatively new
- not known as useful in many scientific communities
- lack of speed

Mixing Languages — Best of Both Worlds

- low level code (C or fortran): element matrix evaluations, costly mesh-related functions, . . .
- high level code (Python): logic of the code, particular applications, configuration files, problem description files

www.python.org



SfePy = Python + C (+ fortran)

- notable features:
 - small size (complete sources are just about 1.3 MB, July 2008)
 - fast compilation
 - problem description files in pure Pythor
 - problem description form similar to mathematical description "or paper"

Mixing Languages — Best of Both Worlds

- low level code (C or fortran): element matrix evaluations, costly mesh-related functions, . . .
- high level code (Python): logic of the code, particular applications, configuration files, problem description files

www.python.org

python™

$$SfePy = Python + C (+ fortran)$$

- notable features:
 - small size (complete sources are just about 1.3 MB, July 2008)
 - fast compilation
 - problem description files in pure Python
 - problem description form similar to mathematical description "on paper"

Software Dependencies

- to install and use SfePy, several other packages or libraries are needed:
 - NumPy and SciPy: free (BSD license) collection of numerical computing libraries for Python
 - enables Matlab-like array/matrix manipulations and indexing
 - other: UMFPACK, Pyparsing, Matplotlib, Pytables (+ HDF5), swig
 - visualization of results: ParaView, MayaVi2, or any other VTK-capable viewer
- missing:
 - free (BSD license) 3D mesh generation and refinement tool
 - ...can use netgen, tetgen


Software Dependencies

- to install and use SfePy, several other packages or libraries are needed:
 - NumPy and SciPy: free (BSD license) collection of numerical computing libraries for Python
 - enables Matlab-like array/matrix manipulations and indexing
 - other: UMFPACK, Pyparsing, Matplotlib, Pytables (+ HDF5), swig
 - visualization of results: ParaView, MayaVi2, or any other VTK-capable viewer
- missing:
 - free (BSD license) 3D mesh generation and refinement tool
 - ...can use netgen, tetgen

Introduction

- problem description file is a regular Python module, i.e. all Python syntax and power is accessible
- consists of entities defining:
 - fields of various FE approximations, variables
 - equations in the weak form, quadratures
 - boundary conditions (Dirichlet, periodic, "rigid body")
 - FE mesh file name, options, solvers, . . .
- simple example: the Laplace equation:

$$c\Delta u=0$$
 in $\Omega,\quad u=\bar{u}$ on Γ , weak form: $\int_{\Omega} c \ \nabla u \cdot \nabla v=0, \quad \forall v\in V_0$



Solving Laplace Equation — FE Approximations

• mesh \rightarrow define FE approximation to Ω :

```
filename_mesh = 'simple.mesh'
• fields \rightarrow define space V_h:
```

Solving Laplace Equation — FE Approximations

```
• mesh \rightarrow define FE approximation to \Omega:
                 filename_mesh = 'simple.mesh'
• fields \rightarrow define space V_h:
          field_1 = {
                     'name' : 'temperature',
                     'dim' : (1,1),
                     'domain' : 'Omega',
                     'bases'
                                  : 'Omega' : '3_4_P1'
  '3_4_P1' means P1 approximation, in 3D, on 4-node FEs (tetrahedra)
• variables \rightarrow define u_b. v_b:
```

Solving Laplace Equation — FE Approximations

```
• mesh \rightarrow define FE approximation to \Omega:
                filename_mesh = 'simple.mesh'
• fields \rightarrow define space V_h:
          field_1 = {
                    'name' : 'temperature',
                    'dim' : (1,1),
                    'domain' : 'Omega',
                    'bases' : 'Omega' : '3_4_P1'
  '3_4_P1' means P1 approximation, in 3D, on 4-node FEs (tetrahedra)
• variables \rightarrow define u_h, v_h:
   variables
                'u' : ('unknown field', 'temperature', 0),
                'v' : ('test field', 'temperature', 'u'),
```

Solving Laplace Equation — Boundary Conditions

```
• regions \rightarrow define domain \Omega, regions \Gamma_{\rm left}, \Gamma_{\rm right}, \Gamma = \Gamma_{\rm left} \cup \Gamma_{\rm right}:

 h omitted from now on . . .

    regions
                   'Omega'
                              : ('all', {}),
                   'Gamma_Left' : ('nodes in (x < 0.0001)', {}),
                   'Gamma_Right' : ('nodes in (x > 0.0999)', {}),
• Dirichlet BC \rightarrow define \bar{u} on \Gamma_{left}, \Gamma_{right}:
```

Solving Laplace Equation — Boundary Conditions

```
• regions \rightarrow define domain \Omega, regions \Gamma_{\rm left}, \Gamma_{\rm right}, \Gamma = \Gamma_{\rm left} \cup \Gamma_{\rm right}:

 h omitted from now on . . .

   regions = {
                'Omega' : ('all', {}),
                'Gamma_Left' : ('nodes in (x < 0.0001)', {}),
                'Gamma_Right' : ('nodes in (x > 0.0999)', {}),
• Dirichlet BC \rightarrow define \bar{u} on \Gamma_{left}, \Gamma_{right}:
    ebcs = {
            't_left' : ('Gamma_Left', 'u.0' : 2.0),
            't_right' : ('Gamma_Right', 'u.all' : -2.0),
```

Problem Description File Solving Laplace Equation — Equations

```
• materials \rightarrow define c:
               material_1
                              = {
                              'name'
                                           : 'm',
                              'mode'
                                          : 'here',
                              'region'
                                          : 'Omega',
                              , c,
                                              1.0,
• integrals → define numerical quadrature:
```

equations = {
 'eq' : 'dw_laplace.i1.Omega(m.c, v, u) = 0'
}

nac 10/26

Problem Description File Solving Laplace Equation — Equations

```
• materials \rightarrow define c:
             material_1 = {
                           'name'
                                       : 'm'.
                           'mode' : 'here',
                           'region' : 'Omega',
                           , c ,
                                          1.0,
• integrals → define numerical quadrature:
        integral_1 = {
                      'name'
                                      : 'i1',
                      'kind'
                                  : 'v',
                      'quadrature' : 'gauss_o1_d3',
• equations → define what and where should be solved:
```

Problem Description File Solving Laplace Equation — Equations

Introduction


```
• materials \rightarrow define c:
             material_1 = {
                          'name'
                                     : 'm'.
                          'mode' : 'here',
                          'region' : 'Omega',
                          , ,
                                     : 1.0,
• integrals → define numerical quadrature:
        integral_1 = {
                     'name'
                                : 'i1',
                                : 'v',
                     'kind'
                     'quadrature' : 'gauss_o1_d3',
• equations → define what and where should be solved:
```

Running SfePy

Introduction

```
$ ./simple.py input/poisson.py
sfepy: reading mesh...
sfepv: ...done in 0.02 s
sfepy: setting up domain edges...
sfepv: ...done in 0.02 s
sfepy: setting up domain faces...
sfepv: ...done in 0.02 s
sfepv: creating regions ...
         leaf Gamma_Right region_4
sfepv:
         leaf Omega region_1000
sfepy: leaf Gamma_Left region_03
sfepy: ...done in 0.07 s
sfepy: equation "Temperature":
sfepy: dw_laplace.i1.Omega( coef.val, s, t ) = 0
sfepy: describing geometries...
sfepv: ...done in 0.01 s
sfepy: setting up dof connectivities ...
sfepv: ...done in 0.00 s
sfepy: using solvers:
                 nls: newton
                  Is: Is
sfepy: matrix shape: (300, 300)
sfepy: assembling matrix graph...
sfepy: ...done in 0.01 s
sfepy: matrix structural nonzeros: 3538 (3.93e-02% fill)
sfepy: updating materials ...
sfepy:
           coef
sfepy: ...done in 0.00 s
sfepy: nls: iter: 0, residual: 1.176265e-01 (rel: 1.000000e+00)
                     0.00 [s]
sfepy:
         rezidual:
sfepy:
          solve:
                      0.01 [s]
                      0.00 [s]
sfepy:
           matrix:
sfepy: nls: iter: 1, residual: 9.921082e-17 (rel: 8.434391e-16)
```

- top level of SfePy code is a collection of executable scripts tailored for various applications
- simple.py is dumb script of brute force, attempting to solve any equations it finds by the Newton method
- ... exactly what we need here (solver options were omitted in previous slides)



Top-level Scripts

Main scripts / applications:

- runTests.py ...run all/selected unit tests
- simple.py ... generic problem solver, both for stationary and time-dependent problems
- eigen.py ...application: acoustic band gaps in strongly heterogenous media
- schroedinger.py ...application: Schrödinger equation solver

Auxiliary

- extractor.py ... extract results stored in a HDF5 file, dump results to VTK
- findSurf.py ... extract a mesh surface, mark its components
- gen ... (re-)generate documentation, found in doc/sfepy_manual.pdf, requires additional packages: pexpect, lxml
- genPerMesh.py ...scale and periodically repeat a reference volume mesh

Top-level Scripts

Main scripts / applications:

- runTests.py ...run all/selected unit tests
- simple.py ... generic problem solver, both for stationary and time-dependent problems
- eigen.py ...application: acoustic band gaps in strongly heterogenous media
- schroedinger.py ...application: Schrödinger equation solver

Auxiliary:

- extractor.py ... extract results stored in a HDF5 file, dump results to VTK
- findSurf.py ... extract a mesh surface, mark its components
- gen ... (re-)generate documentation, found in doc/sfepy_manual.pdf, requires additional packages: pexpect, lxml
- genPerMesh.py ...scale and periodically repeat a reference volume mesh

Verification of Numerical Results

- to verify numerical results we use method of manufactured solutions: for example, for Poisson's equation $\operatorname{div}(\operatorname{grad}(u)) = f$:
 - make up a solution, e.g. $u = \sin 3x \cos 4y$
 - ② compute corresponding f, here $f = 25 \sin 3x \cos 4y$, and boundary conditions by substituting u into the equation
 - solve numerically and compare the exact solution of the strong problem with the numerical solution of the weak problem
 - → allows to assess both the discretization and numerical errors
- manual derivation of f tedious $\rightarrow \text{SymPy}$
 - each term class annotated by a corresponding symbolic expression
 - example: anisotropic diffusion term

- f is built by substituting the manufactured solution into the expressions and subsequent evaluation in FE nodes
- work in progress

Verification of Numerical Results

- to verify numerical results we use method of manufactured solutions: for example, for Poisson's equation $\operatorname{div}(\operatorname{grad}(u)) = f$:
 - make up a solution, e.g. $u = \sin 3x \cos 4y$
 - ② compute corresponding f, here $f=25\sin 3x\cos 4y$, and boundary conditions by substituting u into the equation
 - Solve numerically and compare the exact solution of the strong problem with the numerical solution of the weak problem
 - ightarrow allows to assess both the discretization and numerical errors
- manual derivation of f tedious → SymPy
 - each term class annotated by a corresponding symbolic expression
 - example: anisotropic diffusion term

- f is built by substituting the manufactured solution into the expressions and subsequent evaluation in FE nodes
- work in progress


Optimal Flow Problem Problem Setting

Objective Function

$$\Psi(u) \equiv \frac{\nu}{2} \int_{\Omega_c} |\nabla u|^2 \longrightarrow \min$$


- minimize gradients of solution (e.g. losses) in $\Omega_c \subset \Omega$
- by moving design boundary $\Gamma \subset \partial \Omega$
- ullet perturbation of Γ by vector field \mathcal{V}


$$\Omega(t) = \Omega + \{tV(x)\}_{x \in \Omega}$$
 where $V = 0$ in $\bar{\Omega}_c \cup \partial \Omega \setminus \Gamma$



Optimal Flow Problem Example Results

• flow and domain control boxes, left: initial, right: final





- ullet Ω_C between two grey planes
- work in progress . . .

• weak form of Navier-Stokes equations: ? $\mathbf{u} \in \mathbf{V}_0(\Omega)$, $p \in L^2(\Omega)$ such that

$$a_{\Omega}(\mathbf{u}, \mathbf{v}) + c_{\Omega}(\mathbf{u}, \mathbf{u}, \mathbf{v}) - b_{\Omega}(\mathbf{v}, p) = g_{\Gamma_{\text{out}}}(\mathbf{v}) \quad \forall \mathbf{v} \in \mathbf{V}_{0},$$

$$b_{\Omega}(\mathbf{u}, q) = 0 \quad \forall q \in L^{2}(\Omega).$$
(1)

• in SfePy syntax:

Direct Problem

paper ↔ input file

• weak form of Navier-Stokes equations: ? $\mathbf{u} \in \mathbf{V}_0(\Omega)$, $p \in L^2(\Omega)$ such that

$$a_{\Omega}(\mathbf{u}, \mathbf{v}) + c_{\Omega}(\mathbf{u}, \mathbf{u}, \mathbf{v}) - b_{\Omega}(\mathbf{v}, p) = g_{\Gamma_{\text{out}}}(\mathbf{v}) \quad \forall \mathbf{v} \in \mathbf{V}_{0},$$

$$b_{\Omega}(\mathbf{u}, q) = 0 \quad \forall q \in L^{2}(\Omega).$$
 (1)

• in SfePy syntax:

```
equations = {
'balance'
                          11 11 11
                      dw_div_grad.i2.Omega( fluid.viscosity, v, u )
                      + dw_convect.i2.Omega( v, u )
                       - dw_grad.i1.Omega( v, p ) = 0""",
'incompressibility'
                      dw_div.i1.0mega(q, u) = 0""",
```

Adjoint Problem

paper ↔ input file

• KKT conditions $\delta_{\mathbf{u},p}\mathcal{L}=0$ yield adjoint state problem for \mathbf{w}, r :

$$\begin{split} \delta_{\mathbf{u}}\mathcal{L} \circ \mathbf{v} &= 0 = \delta_{u}\Psi(\mathbf{u},p) \circ \mathbf{v} \\ &+ a_{\Omega}\left(\mathbf{v},\,\mathbf{w}\right) + c_{\Omega}\left(\mathbf{v},\,\mathbf{u},\,\mathbf{w}\right) + c_{\Omega}\left(\mathbf{u},\,\mathbf{v},\,\mathbf{w}\right) + b_{\Omega}\left(\mathbf{v},\,r\right) \;, \\ \delta_{p}\mathcal{L} \circ q &= 0 = \delta_{p}\Psi(\mathbf{u},p) \circ q - b_{\Omega}\left(\mathbf{w},\,q\right) \;, \forall \mathbf{v} \in \mathbf{V}_{0}, \; \text{and} \; \forall q \in L^{2}(\Omega). \end{split}$$

• in SfePv syntax:

• KKT conditions $\delta_{\mathbf{u},p}\mathcal{L}=0$ yield adjoint state problem for \mathbf{w}, r :

$$\begin{split} \delta_{\mathbf{u}}\mathcal{L} \circ \mathbf{v} &= 0 = \delta_{u} \Psi(\mathbf{u}, p) \circ \mathbf{v} \\ &+ a_{\Omega} \left(\mathbf{v}, \, \mathbf{w} \right) + c_{\Omega} \left(\mathbf{v}, \, \mathbf{u}, \, \mathbf{w} \right) + c_{\Omega} \left(\mathbf{u}, \, \mathbf{v}, \, \mathbf{w} \right) + b_{\Omega} \left(\mathbf{v}, \, r \right) \;, \\ \delta_{p}\mathcal{L} \circ q &= 0 = \delta_{p} \Psi(\mathbf{u}, p) \circ q - b_{\Omega} \left(\mathbf{w}, \, q \right) \;, \forall \mathbf{v} \in \mathbf{V}_{0}, \; \text{and} \; \forall q \in L^{2}(\Omega). \end{split}$$

in SfePy syntax:

```
equations = {
'balance'
                          11 11 11
                       dw_div_grad.i2.Omega( fluid.viscosity, v, w )
                       + dw_adj_convect1.i2.Omega( v, w, u )
                       + dw_adj_convect2.i2.Omega( v, w, u )
                       + dw_grad.i1.Omega( v, r )
                       = - (\delta_u \Psi(u, p) \circ v)
'incompressibility'
                       dw_div.i1.0mega(q, w) = 0""",
```

One particle Schrödinger equation:

$$\left(-\frac{\hbar^2}{2m}\nabla^2 + V\right)\psi = E\psi.$$

FEM:

$$(K_{ij} + V_{ij}) q_j = EM_{ij}q_j + F_i,$$

$$V_{ij} = \int \phi_i V \phi_j \, dV,$$

$$M_{ij} = \int \phi_i \phi_j \, dV,$$

$$K_{ij} = \frac{\hbar^2}{2m} \int \nabla \phi_i \cdot \nabla \phi_j \, dV,$$

$$F_i = \frac{\hbar^2}{2m} \oint \frac{d\psi}{dn} \phi_i \, dS.$$

Particle in the Box

$$V(x) = \begin{cases} 0, & \text{inside the box} \quad a \times a \times a \\ \infty, & \text{outside} \end{cases}$$

Analytic solution:

$$E_{n_1 n_2 n_3} = \frac{\pi^2}{2a^2} \left(n_1^2 + n_2^2 + n_3^2 \right)$$

where $n_i = 1, 2, 3, \ldots$ are independent quantum numbers. We chose a = 1, i.e.: $E_{111} = 14.804$, $E_{211} = E_{121} = E_{112} = 29.608$. $E_{122} = E_{212} = E_{221} = 44.413$, $E_{311} = E_{131} = E_{113} = 54.282$ $E_{222} = 59.217, E_{123} = E_{perm.} = 69.087.$

Numerical solution (a = 1, 24702 nodes)

Numerical Solution			Julion	$(\alpha - 1, 2 + 102 \text{ Hodes}).$				
	E	1	2-4	5-7	8-10	11	12-	
	theory	14.804	29.608	44.413	54.282	59.217	69.087	
	FEM	14.861	29.833	44.919	55.035	60.123	70.305	
			29.834	44.920	55.042		70.310	
		l	29.836	44.925	55.047			

3D Harmonic Oscillator

$$V(r) = \begin{cases} \frac{1}{2}\omega^2 r^2, & \text{inside the box} \quad a \times a \times a \\ \infty, & \text{outside} \end{cases}$$

Analytic solution in the limit $a \to \infty$:

$$E_{nl} = \left(2n + l + \frac{3}{2}\right)\omega$$


where $n, l = 0, 1, 2, \ldots$ Degeneracy is 2l + 1, so: $E_{00} = \frac{3}{2}$, triple $E_{01}=\frac{5}{2},\,E_{10}=\frac{7}{2},\,$ quintuple $E_{02}=\frac{7}{2}$ triple $E_{11}=\frac{9}{2},\,$ quintuple $E_{12}=\frac{11}{2}$:


Numerical solution (a = 15, $\omega = 1$, 290620 nodes):


E	1	2-4	5-10	11-
theory	1.5	2.5	3.5	4.5
FEM	1.522	2.535	3.554	4.578
		2.536	3.555	4.579
		2.536	3.555	4.579
			3.555	
			3.556	
	İ		3.556	


3D Harmonic Oscillator

Eigenvectors:









Hydrogen Atom

$$V(r) = \begin{cases} -\frac{1}{r}, & \text{inside the box} \quad a \times a \times a \\ \infty, & \text{outside} \end{cases}$$

Analytic solution in the limit $a \to \infty$:

$$E_n = -\frac{1}{2n^2}$$


where
$$n=1,2,3,\ldots$$
 Degeneracy is n^2 , so: $E_1=-\frac{1}{2}=-0.5$, $E_2=-\frac{1}{8}=-0.125$, $E_3=-\frac{1}{18}=-0.055$, $E_4=-\frac{1}{32}=-0.031$.

Numerical solution (a = 15, 160000 nodes):

E	1	2-5	6-14	15-
theory	-0.5	-0.125	-0.055	-0.031
FEM	-0.481	-0.118	-0.006	

Hydrogen Atom

11th eigenvalue (calculated: -0.04398532, exact: -0.056), on the mesh with 976 691 tetrahedrons and 163 666 nodes, for the hydrogen atom (V=-1/r).



What is done

- basic FE element engine:
 - finite-dimensional approximations of continuous fields
 - variables, boundary conditions, FE assembling
 - · equations, terms, regions
 - materials, material caches
- various solvers accessed via abstract interface
- unit tests, automatic documentation generation
- mostly linear problems, but multiphysical

- good documentation

Conclusion

What is done

- basic FE element engine:
 - finite-dimensional approximations of continuous fields
 - variables, boundary conditions, FE assembling
 - equations, terms, regions
 - materials, material caches
- various solvers accessed via abstract interface
- unit tests, automatic documentation generation
- mostly linear problems, but multiphysical

What is not done

- general FE engine, possibly with symbolic evaluation (SymPy)
- good documentation
- fast problem-specific solvers (!)
- adaptive mesh refinement (!)
- parallelization (petsc4py)

What will not be done (?)

- GUI
- real symbolic parsing/evaluation of equations

http://sfepy.org

Conclusion

What is done

- basic FE element engine:
 - finite-dimensional approximations of continuous fields
 - variables, boundary conditions, FE assembling
 - equations, terms, regions
 - materials, material caches
- various solvers accessed via abstract interface
- unit tests, automatic documentation generation
- mostly linear problems, but multiphysical

What is not done

- general FE engine, possibly with symbolic evaluation (SymPy)
- good documentation
- fast problem-specific solvers (!)
- adaptive mesh refinement (!)
- parallelization (petsc4py)

What will not be done (?)

- GUI
- real symbolic parsing/evaluation of equations

http://sfepy.org

Conclusion

What is done

- basic FE element engine:
 - finite-dimensional approximations of continuous fields
 - variables, boundary conditions, FE assembling
 - equations, terms, regions
 - materials, material caches
- various solvers accessed via abstract interface
- unit tests, automatic documentation generation
- mostly linear problems, but multiphysical

What is not done

- general FE engine, possibly with symbolic evaluation (SymPy)
- good documentation
- fast problem-specific solvers (!)
- adaptive mesh refinement (!)
- parallelization (petsc4py)

What will not be done (?)

- GUI
- real symbolic parsing/evaluation of equations

http://sfepy.org


Yes, the final slide!

Acknowledgements

The work on various parts of SfePy has been supported by the following grants and research projects funded by several agencies in the Czech Republic:

- Robert Cimrman:
 - grant project GAČR 101/07/1471, entitled "Finite element modelling of linear, non-linear and multiscale effects in wave propagation in solids and heterogeneous media"
 - research project MŠMT 1M06031
 - research project MŠMT 4977751303
- Ondřej Čertík:
 - research center project LC06040
 - grant project GAČR IAA100100637

This is not a slide!



 ^1Do you like Monty Python's Flying Circus? It helps! (Python FAQ 1.1.17) $^{\circ}$ $^{\circ}$ $^{\circ}$ $^{\circ}$ $^{\circ}$ $^{\circ}$