

Polymorphism-aware phylogenetic models

Workshop, MIC-Phy 2021

Dominik Schrempf

February 16, 2021



Eötvös Loránd
University

Introduction

This workshop is [available on GitHub](#).

Our goal is to understand how we can use polymorphism-aware phylogenetic models (PoMo) to improve inferences from population data.

In the course of this workshop, we will infer a phylogenetic tree from test data using IQ-TREE2.

If you need help, please interrupt me anytime!

Preparation - Command line shell

Basic knowledge of the command line shell of your choice is assumed.

- If you do not know basic commands such as `cd`, `ls`, or `less`, just lean back and listen to the presentation.
- Otherwise, try to follow the steps and complete the workshop yourself.

In case you are lost:

- Have a look at the manual pages, if they exist.

```
1 man less
```

- Read how commands are used.

```
1 less --help
```

Preparation - Download workshop and data

Option 1: If you have git installed, use it.

```
1 git clone https://github.com/pomo-dev/micphy-workshop.git
2 cd micphy-workshop
```

Option 2: Manually download the archive (requires wget, and unzip).

```
1 wget https://github.com/pomo-dev/micphy-workshop/archive/master.zip
2 unzip master.zip
3 cd micphy-workshop-master
```

The advantage of Option 1 is that you can:

- update your working tree if I have to change something during the workshop; use `git pull`;
- reset to the initial state if you mess up; use `git reset --hard HEAD` (be careful, this erases all changes made by you).

Preparation - Install IQ-TREE2

Option 1: Install from the repository of your distribution. For example, use the Arch Linux User Repository.

```
1 yay -S iqtree
2 aura -A iqtree
```

Option 2: Compile yourself (not shown).

Option 3: Use `nix-shell` and the `shell.nix` expression provided in the base directory of the repository (requires `nix`).

```
1 nix-shell
```

Welcome to the MIC-Phy PoMo workshop.

The following version of IQ-TREE2 is available:

IQ-TREE multicore version 2.1.2 COVID-edition for Linux 64-bit built Jan 1 1980

Developed by Bui Quang Minh, James Barbetti, Nguyen Lam Tung,

Olga Chernomor, Heiko Schmidt, Dominik Schrempf, Michael Woodhams.

Preparation - Install IQ-TREE2

Option 4: Download the binary executable from the [IQ-TREE2 homepage](#).

```
1 wget https://github.com/iqtree/iqtree2/releases/download/v2.1.2/iqtree-2.1.2-Linux.tar.gz
```

Make sure that you have permission to execute the file (`chmod +x`), and that the executable is in your `PATH` (or that you provide the path during execution).

```
1 tar -xzf iqtree-2.1.2-Linux.tar.gz
2 chmod +x iqtree-2.1.2-Linux/bin/iqtree2 # Should not be necessary, but who knows.
3 mv iqtree-2.1.2-Linux/bin/iqtree2 ~/bin/ # If ~/bin is in your PATH.
```

Preparation - Test IQ-TREE2 version

Depending on how you installed IQ-TREE2, please check that the version agrees with the one I am using.

```
1 iqtree2 --version
2 # /path/to/iqtree2 --version
3 # ./relative/path/to/iqtree2 --version
```

IQ-TREE multicore version 2.1.2 COVID-edition for Linux 64-bit built Jan 1 1980
Developed by Bui Quang Minh, James Barbetti, Nguyen Lam Tung,
Olga Chernomor, Heiko Schmidt, Dominik Schrempf, Michael Woodhams.

Exercise - IQ-TREE2: Access help

A convenient way to access the help is

```
1 iqtree2 --help | less
```

Here I print the first lines:

```
IQ-TREE multicore version 2.1.2 COVID-edition for Linux 64-bit built Jan  1 1980  
Developed by Bui Quang Minh, James Barbetti, Nguyen Lam Tung,  
Olga Chernomor, Heiko Schmidt, Dominik Schrempf, Michael Woodhams.
```

```
Usage: iqtree [-s ALIGNMENT] [-p PARTITION] [-m MODEL] [-t TREE] ...
```

GENERAL OPTIONS:

-h, --help	Print (more) help usages
-s FILE[,...,FILE]	PHYLIP/FASTA/NEXUS/CLUSTAL/MSF alignment file(s)
-s DIR	Directory of alignment files

Exercise - Run a DNA substitution model

- Run normal model.

Fruit fly data

Data from [PopFly](#)¹. 9 populations with an average number of samples per population of approximately 19, and an estimated heterozygosity of 0.0109:

NTH Netherlands

EG Egypt

FR France

GA Gabon

GU Guinea

EF Ethiopia

KN Kenya

SB South Africa (Barkly East)

SP South Africa (Phalaborwa)

Why is it important to check the heterozygosity?

¹Hervas et al. ([2017](#)).

Exercise - Run PoMo

```
1 iqtree2 -nt 4 -redo -s data/fruit_flies_1000.cf -m HKY+P+N9 -pre fruit_flies_1000.cf.N9
```

- Run PoMo.
- Find best N.
- Compare different DNA substitution models.
- Use gamma rate heterogeneity.
- Probably perform model test?
- Bootstrapping.
- Compare branch lengths for different N values.
- Compare to using normal DNA substitution models.
- Probably provide results for the 10k alignment (different N, different G, with bootstrapping?).

Tips

Numerical underflow: The likelihood derivate is zero or close to zero; this is especially an issue when N is large; try using `-safe` (which is slower). Sometimes, retrying with a different seed also fixes the problem.

Literature





PoMo De Maio et al. (2015).

Reversible PoMo Schrempf et al. (2016) and Schrempf and Hobolth (2017).



Advanced models with PoMo Schrempf et al. (2019).

IQ-TREE2 Minh et al. (2020).

Bibliography I

-  De Maio, Nicola, Dominik Schrempf, and Carolin Kosiol (2015). “PoMo: An Allele Frequency-Based Approach for Species Tree Estimation.” In: *Systematic Biology* 64.6, pp. 1018–1031. DOI: [10.1093/sysbio/syv048](https://doi.org/10.1093/sysbio/syv048).
-  Hervas, Sergi, Esteve Sanz, Sònia Casillas, John E Pool, and Antonio Barbadilla (2017). “Popfly: the Drosophila Population Genomics Browser.” In: *Bioinformatics* 33.17, pp. 2779–2780. DOI: [10.1093/bioinformatics/btx301](https://doi.org/10.1093/bioinformatics/btx301).
-  Minh, Bui Quang, Heiko A Schmidt, Olga Chernomor, Dominik Schrempf, Michael D Woodhams, Arndt von Haeseler, and Robert Lanfear (2020). “IQ-TREE 2: New models and efficient methods for phylogenetic inference in the genomic era.” In: *Molecular Biology and Evolution* 37.5. Ed. by Emma Teeling, pp. 1530–1534. DOI: [10.1093/molbev/msaa015](https://doi.org/10.1093/molbev/msaa015).
-  Schrempf, Dominik, Bui Quang Minh, Nicola De Maio, Arndt von Haeseler, and Carolin Kosiol (2016). “Reversible polymorphism-aware phylogenetic models and their application to tree inference.” In: *Journal of Theoretical Biology* 407, pp. 362–370. DOI: [10.1016/j.jtbi.2016.07.042](https://doi.org/10.1016/j.jtbi.2016.07.042).

Bibliography II

-  Schrempf, Dominik and Asger Hobolth (2017). “An alternative derivation of the stationary distribution of the multivariate neutral Wright–Fisher model for low mutation rates with a view to mutation rate estimation from site frequency data.” In: *Theoretical Population Biology* 114, pp. 88–94. DOI: 10.1016/j.tpb.2016.12.001.
-  Schrempf, Dominik, Bui Quang Minh, Arndt von Haeseler, and Carolin Kosiol (2019). “Polymorphism-Aware Species Trees with Advanced Mutation Models, Bootstrap, and Rate Heterogeneity.” In: *Molecular Biology and Evolution* 36.6. Ed. by Naruya Saitou, pp. 1294–1301. DOI: 10.1093/molbev/msz043.