

Q. 12 points (6 + 6)

The shortest path algorithm using Dijkstra is shown in the pseudo code below. Show that the running time is $O(E \log V)$. Assume Adjacency List to represent the graph. Explain your answer clearly by considering running time for each line and any assumptions used. Assume implementation using a Heap.

```

1 INITIALIZE-SINGLE-SOURCE(G, s)
2 S = {}
3 Q = G.V
4 while Q != {}
5     u = EXTRACT-MIN(Q)
6     S = S ∪ {u}
7     for each vertex v ∈ G.Adj[u]
8         RELAX(u, v, w)
    
```

$\rightarrow O(V)$
 $\rightarrow O(1)$
 $\rightarrow O(\log V)$ - due to heapification.
 $\rightarrow V \cdot \log V$ - Heapification required
 $\rightarrow V \cdot \log V$
 $\rightarrow V(\Delta E \cdot \log V) = E \cdot \log V$ - explain below.


1. Every time we enter line 7, we got small number of nodes (vertices) as neighbor.
2. Hence it is accounts for ΔE .
3. Hence it takes $V \cdot (\Delta E \cdot \log V)$

Since total running time is $O(V \cdot \log V + E \cdot \log V) = O((V + E) \cdot \log V)$

Hence number of edges is higher than number of vertices $O(E \cdot \log V)$

total running time of Dijkstra shortest path algorithm.

Question 4: 11 points (6 + 3 + 2)



(a)

Suppose that A and B, and that $A \leq_p B$. Circle one answer for each statement below.

Answered in 6

Also, briefly justify your answer.

1. If B is NP-Hard then A is NP-Hard

True False

All NP-complete, NP, P questions can be reduced to NP-hard. So not able to exactly reduce A.

2. If A is EXP-COMPLTE then B is EXP-COMPLTE

True False


Answered in 6. Only its solution is EXP-complete means it is EXP-complete.

3. Does $A \leq_p B$ implies $B \leq_p A$ in general?

True False

For example NP problem A can be reduced to NP-complete B. But NP-complete cannot be reduced to A.

(b) In graph theory, a dominating set for a graph $G = (V, E)$ is a subset D of V such that every vertex not in D is adjacent to at least one member of D. An example of a Dominating set is the set of the 3 nodes shown as bold for the graph G shown below.



Show 2 other Dominating sets for the same graph.

(c)



(c) Does Power Set problem belong to NP-Complete problem? Explain your answers.

No Power Set doesn't belong to NP-Complete. Because, it can be solved in Exp time using the Dynamic programming and it can be verified at Exp time.

Question 3: Contd.

b. Consider the following graph. Start at node A. Edges are processed in the following order (B, E), (D, B), (B, D), (A, C), (D, C), (B, C), (E, D). Find all shortest path distances to all nodes using Bellman-Ford algorithm. Show all steps clearly.



Step

1. Bellman-Ford (G, W, S)

2. Initialize Single-Source (G, S)

3. For $u \in V$ do $d[u] \leftarrow \infty$

4. For each edge $(u, v) \in E$ do

5. relax (u, v, w)

6. For each edge $(u, v) \in E$ do

7. if $d[v] > d[u] + w(u, v)$

8. $d[v] \leftarrow d[u] + w(u, v)$

9. else continue

10. Return d

| | A | B | C | D | E |
|---|---|----------|----------|----------|----------|
| 0 | 0 | ∞ | ∞ | ∞ | ∞ |
| 1 | 0 | -1 | ∞ | ∞ | ∞ |
| 2 | 0 | -1 | 4 | ∞ | ∞ |
| 3 | 0 | -1 | 2 | ∞ | ∞ |

Since, number of V is 5, it will iterate 4 times to find accurate.

We get following distances when all edges are processed first time.

Distance of BE, BD, ED and

A, B are processed

Result of A, C.

Result of D, BC and ED

Overall distance of 2 edges

Second iteration

| | A | B | C | D | E |
|---|---|----|---|----------|---|
| 0 | 0 | -1 | 2 | ∞ | 1 |
| 1 | 0 | -1 | 2 | 1 | 1 |
| 2 | 0 | -1 | 2 | -2 | 1 |

Result after second iteration

Third iteration

| | A | B | C | D | E |
|---|---|----|---|----|---|
| 0 | 0 | -1 | 2 | -2 | 1 |

and Fourth iteration is same as below

| | Distance | Prev Vertex |
|---|----------|-------------|
| A | 0 | A |
| B | -1 | A |
| C | 2 | B |
| D | -2 | E |
| E | 1 | B |

So result is. Distance from A to all other nodes

(a)

Suppose that A and B, and that $A \leq_p B$. Circle one answer for each statement below.

A reduced to B.

Also, briefly justify your answer.

1. If B is NP-Hard then A is NP-Hard
Justify -

True False

ALL NP complete, NP, P problems can be reduced to NP hard. So not able to exactly define A.

2. If A is EXP-COMplete then B is EXP-COMplete True False
Justify -



Reduced to B and its solution is EXP-complete means B is

3. Does $A \leq_p B$ implies $B \leq_p A$ in general?
Justify -

True False

For example NP problem A reduced to NP complete B. B cannot be reduced to

(b) In graph theory, a dominating set for a graph $G = (V, E)$ is a subset D of V such that every vertex not in D is adjacent to at least one member of D. An example of a Dominating set is the set of the 3 nodes shown as bold for the graph G shown below:



Show 2 other Dominating sets for the same graph.



Does Power Set problem belong to NP-Complete problem? Explain your answers.

Power Set doesn't belong to NP-Complete. Because, it can be solved in Exp time using the Dynamic programming and it can be solved in polynomial time.

Question 3: 4 points (3 + 1) [Bonus Question]

a. An independent set in a Graph is defined as an independent set of vertices in a graph, no two of which are adjacent. That is, it is a set S of vertices such that for every two vertices in S , there is no edge connecting the two. The size of an independent set is the number of vertices in S . Assume that independent set problem is in NP.


Assume the following 3-CNF which is NP-Complete:

$$(x_1 \vee x_2 \vee \neg x_3) \wedge (x_2 \vee x_3 \vee \neg x_4) \wedge (x_1 \vee \neg x_2 \vee x_4) \text{ where } \neg \text{ means not.}$$

Show that Independent set in a graph corresponding to the 3-CNF is NP-Complete.

What is the size of the Independent set S (i.e. maximum number of nodes in S that are not adjacent)? Explain your answer.

[Hint: Reduce 3-CNF to a graph. For this problem, you may consider a node (e.g. x_2) is connected to ($\neg x_2$) etc.]



We have shown that Solution 1 for 3-CNF is solution of ISet and Solution 2 for Independent Set is solution of 3-CNF as well.

From the graph based on clause above we can see that size of independent set is 3. So, let's prove that there can be solution for 3-CNF $x_1=1, x_3=1$.

$$(2 \vee x_2 \vee \neg x_3) \wedge (x_2 \vee 1 \vee \neg x_4) \wedge (1 \vee \neg x_2 \vee x_4) = 1 \text{ It is true.}$$

Also for x_1 of C_1 , x_2 of C_2 and x_1 of C_3 are member of independent set.

This is clear from the graph above. So, solution for 3-CNF is solution of Independent set as well. Max size of independent set for 3-CNF is 3.

b. Can you use Bellman-Ford shortest path algorithm on undirected graph? Explain your answer. If your answer is yes, will you be able to deal with negative weight?

BF shortest path algorithm can be used on undirected graph because undirected graph is directed graph with 2 ways on each edge.

Generally BF can be used in graph with negative weight but cannot be used on graph with negative cycle. Negative weight on undirected graph means negative cycle. So, all weight has to be positive for undirected graph when we use BF.