



CS 412 Intro. to Data Mining

Chapter 6. Mining Frequent Patterns, Association and Correlations: Basic Concepts and Methods

Jiawei Han, Computer Science, Univ. Illinois at Urbana-Champaign, 2017



Chapter 6: Mining Frequent Patterns, Association and Correlations: Basic Concepts and Methods

- ☐ Basic Concepts 
- ☐ Efficient Pattern Mining Methods
- ☐ Pattern Evaluation
- ☐ Summary

What Is Pattern Discovery?

❑ What are patterns?

- ❑ **Patterns**: A set of items, subsequences, or substructures that occur frequently together (or strongly correlated) in a data set
- ❑ Patterns represent **intrinsic** and **important properties** of datasets

❑ **Pattern discovery**: Uncovering patterns from massive data sets

❑ Motivation examples: *👉 સર્ચ સેચ સર્ચ સર્ચ*

- ❑ What products were often purchased together?
- ❑ What are the subsequent purchases after buying an iPad?
- ❑ What code segments likely contain copy-and-paste bugs?
- ❑ What word sequences likely form phrases in this corpus?

Pattern Discovery: Why Is It Important?

- ❑ Finding **inherent regularities** in a data set
- ❑ **Foundation** for many essential data mining tasks
 - ❑ Association, correlation, and causality analysis
 - ❑ Mining sequential, structural (e.g., sub-graph) patterns
 - ❑ Pattern analysis in spatiotemporal, multimedia, time-series, and stream data
 - ❑ Classification: Discriminative pattern-based analysis
 - ❑ Cluster analysis: Pattern-based subspace clustering
- ❑ Broad applications
 - ❑ Market basket analysis, cross-marketing, catalog design, sale campaign analysis, Web log analysis, biological sequence analysis

Basic Concepts: k-Itemsets and Their Supports

- สิ่งนี้คือสิ่งที่ซื้อด้วยกัน (ชุด)*
- **Itemset**: A set of one or more items
 - **k-itemset**: $X = \{x_1, \dots, x_k\}$
 - Ex. {Beer, Nuts, Diaper} is a 3-itemset *มีสิ่งของ 3 อย่าง*
 - **(absolute) support (count)** of X, $\text{sup}\{X\}$: *บ่อยแค่ไหน*
Frequency or the number of occurrences of an itemset X
 - Ex. $\text{sup}\{\text{Beer}\} = 3$ *มี transaction ที่ beer อยู่ 3*
 - Ex. $\text{sup}\{\text{Diaper}\} = 4$
 - Ex. $\text{sup}\{\text{Beer, Diaper}\} = 3$ *2 item set*
 - Ex. $\text{sup}\{\text{Beer, Eggs}\} = 1$

จำนวนของ transactions ที่ซื้อสิ่งของนี้

Transaction ID

Tid	Items bought
10	Beer, Nuts, Diaper
20	Beer, Coffee, Diaper
30	Beer, Diaper, Eggs
40	Nuts, Eggs, Milk
50	Nuts, Coffee, Diaper, Eggs, Milk

- สัดส่วนที่ซื้อของนี้*
- **(relative) support**, $s\{X\}$: The fraction of transactions that contains X (i.e., the *รู้ transaction ที่ซื้อสิ่งนี้หรือไม่?* **probability** that a transaction contains X)
 - Ex. $s\{\text{Beer}\} = 3/5 = 60\%$ *Tid*
 - Ex. $s\{\text{Diaper}\} = 4/5 = 80\%$
 - Ex. $s\{\text{Beer, Eggs}\} = 1/5 = 20\%$

Basic Concepts: Frequent Itemsets (Patterns)

- An itemset (or a pattern) X is **frequent** if the support of X is no less than a *minsup* threshold σ

- Let $\sigma = 50\%$ (σ : *minsup* threshold)

For the given 5-transaction dataset

- All the frequent 1-itemsets:

- Beer: 3/5 (60%); Nuts: 3/5 (60%)
- Diaper: 4/5 (80%); Eggs: 3/5 (60%)

- All the frequent 2-itemsets:

- {Beer, Diaper}: 3/5 (60%)

- All the frequent 3-itemsets?

- None

Tid	Items bought
10	Beer, Nuts, Diaper
20	Beer, Coffee, Diaper
30	Beer, Diaper, Eggs
40	Nuts, Eggs, Milk
50	Nuts, Coffee, Diaper, Eggs, Milk

- Why do these itemsets (shown on the left) form the complete set of frequent k -itemsets (patterns) for any k ?

- **Observation:** We may need an efficient method to mine a complete set of frequent patterns

Coffee: 2/5 (40%) *is not threshold*

From Frequent Itemsets to Association Rules

- Comparing with itemsets, rules can be more telling

Ex. $Diaper \rightarrow Beer$ *၁၀ Diaper ရှိပါလျှင် ၁၀ beer ရှိပါသည်*

Buying diapers may likely lead to buying beers

အားသာမှုပေးမှု support

- How strong is this rule? (support, confidence)

Measuring association rules: $X \rightarrow Y (s, c)$

Both X and Y are itemsets



Support, s : The probability that a transaction contains $X \cup Y$ *၁၀ ဘီယာနှင့် ၁၀ သီပေါက်*


Ex. $s\{Diaper, Beer\} = 3/5 = 0.6$ (i.e., 60%)

Confidence, c : The *conditional probability* that a transaction containing X also contains Y

Calculation: $c = \text{sup}(X \cup Y) / \text{sup}(X)$

Ex. $c = \text{sup}\{Diaper, Beer\} / \text{sup}\{Diaper\} = 3/4 = 0.75$

Tid	Items bought
10	Beer, Nuts, Diaper
20	Beer, Coffee, Diaper
30	Beer, Diaper, Eggs
40	Nuts, Eggs, Milk
50	Nuts, Coffee, Diaper, Eggs, Milk



Note: $X \cup Y$: the union of two itemsets
 ■ The set contains both X and Y

Mining Frequent Itemsets and Association Rules

- ❑ Association rule mining
 - ❑ Given two thresholds: $minsup$, $minconf$
 - ❑ Find **all** of the rules, $X \rightarrow Y (s, c)$
 - ❑ such that, $s \geq minsup$ and $c \geq minconf$
- ❑ Let $minsup = 50\%$
 - ❑ Freq. 1-itemsets: Beer: 3, Nuts: 3, Diaper: 4, Eggs: 3
 - ❑ Freq. 2-itemsets: {Beer, Diaper}: 3
- ❑ Let $minconf = 50\%$
 - ❑ $Beer \rightarrow Diaper$ (60%, 100%)
 - ❑ $Diaper \rightarrow Beer$ (60%, 75%)

Tid	Items bought
10	Beer, Nuts, Diaper
20	Beer, Coffee, Diaper
30	Beer, Diaper, Eggs
40	Nuts, Eggs, Milk
50	Nuts, Coffee, Diaper, Eggs, Milk

- ❑ Observations:
 - ❑ Mining association rules and mining frequent patterns are very close problems
 - ❑ Scalable methods are needed for mining large datasets

(Q: Are these all rules?)

Challenge: There Are Too Many Frequent Patterns!

- A long pattern contains a combinatorial number of sub-patterns
- How many frequent itemsets does the following TDB₁ contain?

□ TDB₁: T₁: {a₁, ..., a₅₀}; T₂: {a₁, ..., a₁₀₀}

□ Assuming (absolute) *minsup* = 1

□ Let's have a try

1-itemsets: {a₁}: 2, {a₂}: 2, ..., {a₅₀}: 2, {a₅₁}: 1, ..., {a₁₀₀}: 1,

2-itemsets: {a₁, a₂}: 2, ..., {a₁, a₅₀}: 2, {a₁, a₅₁}: 1 ..., ..., {a₉₉, a₁₀₀}: 1,

..., ..., ..., ...

99-itemsets: {a₁, a₂, ..., a₉₉}: 1, ..., {a₂, a₃, ..., a₁₀₀}: 1

100-itemset: {a₁, a₂, ..., a₁₀₀}: 1

- The total number of frequent itemsets:

$$\binom{100}{1} + \binom{100}{2} + \binom{100}{3} + \cdots + \binom{100}{100} = 2^{100} - 1$$

A too huge set for any one to compute or store!



Expressing Patterns in Compressed Form: Closed Patterns

- ❑ How to handle such a challenge?
- ❑ Solution 1: **Closed patterns**: A pattern (itemset) X is **closed** if X is *frequent*, and there exists *no super-pattern* $Y \supset X$, with the same support as X
 - ❑ Let Transaction DB TDB_1 : $T_1: \{a_1, \dots, a_{50}\}$; $T_2: \{a_1, \dots, a_{100}\}$
 - ❑ Suppose $minsup = 1$. How many closed patterns does TDB_1 contain?
 - ❑ Two: $P_1: \{\{a_1, \dots, a_{50}\}: 2\}$; $P_2: \{\{a_1, \dots, a_{100}\}: 1\}$
- ❑ **Closed pattern** is a **lossless compression** of frequent patterns
 - ❑ Reduces the # of patterns but does not lose the support information!
 - ❑ You will still be able to say: $\{\{a_2, \dots, a_{40}\}: 2\}$, $\{\{a_5, a_{51}\}: 1\}$

Expressing Patterns in Compressed Form: Max-Patterns

- ❑ Solution 2: **Max-patterns**: A pattern X is a **max-pattern** if X is frequent and there exists no frequent super-pattern $Y \supset X$
- ❑ Difference from close-patterns?
 - ❑ Do not care the real support of the sub-patterns of a max-pattern
 - ❑ Let Transaction DB TDB_1 : $T_1: \{a_1, \dots, a_{50}\}$; $T_2: \{a_1, \dots, a_{100}\}$
 - ❑ Suppose $minsup = 1$. How many max-patterns does TDB_1 contain?
 - ❑ One: $P: \{\{a_1, \dots, a_{100}\}: 1\}$
- ❑ **Max-pattern** is a **lossy compression**!
 - ❑ We only know $\{a_1, \dots, a_{40}\}$ is frequent
 - ❑ But we do not know the real support of $\{a_1, \dots, a_{40}\}$, ..., any more!
- ❑ Thus in many applications, mining close-patterns is more desirable than mining max-patterns

Apriori Pruning and Scalable Mining Methods

ตัดหาง

- Apriori pruning principle: If there is any itemset which is infrequent, its superset should not even be generated! (Agrawal & Srikant @VLDB'94, Mannila, et al. @ KDD' 94)

ถ้าเกิด itemset ที่
เล็กกว่าไม่บ่อย ก็
ตัด หาง ออก

- Scalable mining Methods: Three major approaches
 - Level-wise, join-based approach: Apriori (Agrawal & Srikant@VLDB'94)
 - Vertical data format approach: Eclat (Zaki, Parthasarathy, Ogihara, Li @KDD'97)
 - Frequent pattern projection and growth: FPgrowth (Han, Pei, Yin @SIGMOD'00)

Apriori: A Candidate Generation & Test Approach

- Outline of Apriori (level-wise, candidate generation and test)
 - Initially, scan DB once to get frequent 1-itemset
 - Repeat
 - Generate length-(k+1) candidate itemsets from length-k frequent itemsets
 - Test the candidates against DB to find frequent (k+1)-itemsets
 - Set $k := k + 1$
 - Until no frequent or candidate set can be generated
 - Return all the frequent itemsets derived

မြန်မာ့ပြည်သူ့သတင်းစာ

↳ Data base

အချက်အလက်များ!

The Apriori Algorithm (Pseudo-Code)

C_k : Candidate itemset of size k

F_k : Frequent itemset of size k

$K := 1$;

$F_k := \{\text{frequent items}\}$; // frequent 1-itemset

While ($F_k \neq \emptyset$) **do** { // when F_k is non-empty

$C_{k+1} := \text{candidates generated from } F_k$; // candidate generation

 Derive F_{k+1} by counting candidates in C_{k+1} with respect to TDB at minsup;

$k := k + 1$

}

return $\cup_k F_k$ // return F_k generated at each level

The Apriori Algorithm—An Example

Database TDB

Tid	Items
10	A, C, D
20	B, C, E
30	A, B, C, E
40	B, E

minsup = 2

C_1

1st scan

Itemset	sup
{A}	2
{B}	3
{C}	3
{D}	1
{E}	3

F_1

တင်စာရင်း

Itemset	sup
{A}	2
{B}	3
{C}	3
{E}	3

ပေးတင်

2 item set

C_2

F_2

Itemset	sup
{A, C}	2
{B, C}	2
{B, E}	3
{C, E}	2

တင်စာရင်း

Itemset	sup
{A, B}	1
{A, C}	2
{A, E}	1
{B, C}	2
{B, E}	3
{C, E}	2

2nd scan

C_2

Itemset
{A, B}
{A, C}
{A, E}
{B, C}
{B, E}
{C, E}

ခု 3 item set

C_3

Itemset
{B, C, E}

3rd scan

F_3

Itemset	sup
{B, C, E}	2

အခုရ! စာရင်း 1 item = 4
2 item = 4
3 item = 1