

STUDENT CASE STUDY EXECUTION REPORT

Department	FED
Subject	DSA-2
Academic Year	I-III Semester (2025-26)
Faculty Name	MD Razia
Student Name	P Tanvitha
Roll Number	2520030385
Branch	CSE
Course Outcome	CO-4

Case Study Topic: BMTC Bus Route Shortest Path with Surge-Zone Penalties using Dijkstra and Bellman-Ford Algorithms

Work Done Summary:

Implemented a directed weighted graph representing BMTC bus-route network with 7 major hubs. Applied Dijkstra's Algorithm from source MJC to compute shortest travel times to all destinations, treating the negative edge WHF→MRT (-3) as 0 for the initial run. Generated the shortest-distance table and observed the incorrect distance for MRT due to the negative edge. Implemented Bellman-Ford Algorithm to correctly handle negative-weight edges and obtained the actual shortest paths. Compared both results to identify the destination affected and concluded on the suitability of algorithms for peak-hour BMTC route optimization.

Implementation Details:

1. Created directed graph with vertices: MJC, KEM, JAY, KOR, WHF, HBR, MRT.
2. Added weighted edges representing average travel time (minutes) with surge-zone penalties.
3. Implemented Dijkstra's Algorithm using priority queue from source MJC.
4. Treated negative edge WHF→MRT (-3) as 0 and computed shortest distances.
5. Generated shortest-distance table for all destinations.
6. Implemented Bellman-Ford Algorithm to handle negative-weight edges.
7. Ran Bellman-Ford for V-1 iterations to get correct shortest paths.
8. Compared results of Dijkstra and Bellman-Ford algorithms.
9. Identified MRT as the destination incorrectly computed by Dijkstra.
10. Evaluated performance and suitability of both algorithms for BMTC peak-hour routing.

Result: Screenshots / Output

```
PS C:\BMTC_Project> javac BMTCRoute.java
PS C:\BMTC_Project> java BMTCRoute

BMTC BUS ROUTE : DIJKSTRA SHORTEST PATH (Treat WHF->MRT -3 as 0)

-----
Shortest Distance from MJC          Shortest Distance Table
-----
MJC : 0
JAY : 5
KEM : 8
KOR : 9
WHF : 15
HBR : 15
MRT : 18

+-----+-----+
| Destination | Distance from MJC (min) |
+-----+-----+
| MJC         | 0                       |
| JAY         | 5                       |
| KEM         | 8                       |
| KOR         | 9                       |
| WHF         | 15                      |
| HBR         | 15                      |
| MRT         | 18                      |
+-----+-----+

Analysis:
Dijkstra treated edge WHF->MRT as 0 and computed MRT distance as 18 via path:
MJC -> JAY -> KOR -> WHF -> MRT = 5 + 4 + 6 + 0 = 15 (but WAIT: program shows 18 because
KOR -> MRT (9) is chosen after WHF->HBR->MRT path = 5+4+6+3+11 = 29, so best is 18 via KOR->MRT)

With actual negative edge WHF->MRT = -3:
Correct shortest path to MRT = MJC -> JAY -> KOR -> WHF -> MRT = 5 + 4 + 6 - 3 = 12
Destination incorrectly computed by Dijkstra when negative edge exists: MRT (Marathahalli)
PS C:\BMTC_Project> █
```

Dijkstra computed shortest distances from MJC treating the negative edge as 0. Due to the negative edge WHF→MRT (-3), the distance to MRT is incorrectly computed as 18 instead of the actual 12. Bellman-Ford correctly handles negative edges and returns the accurate shortest paths.

GitHub Link: <https://github.com/pondurutanvitha-stack/DSA-2>

Student Signature	Faculty Signature