SBI	ใบรับวัตถุดิบ (Incoming Material Acception)	Inspector	Checked	Approved

Receive Date : 02/03/69 **Supplier (ผู้จำหน่าย):** TOYOTA

Grade of Material : S45C **Maker (ผู้ผลิต) :** SHI

No.	Heat No.	Q'ty	Data Inspection						
			Specification	Tool	Tol.	1	2	3	4
1	2416468	25	Ø 46 mm.	Vernier	±0.3	46.20	46.25	46.13	46.19
			L 5,800 mm.	ตลับเมตร	±50	5,830	5,830	5,825	5,820
			Appearance	Visual		ok	ok	ok	ok
				Judgement		O	O	O	O
2			Ø mm.	Vernier	±0.3				
			L mm.	ตลับเมตร	±50				
			Appearance	Visual					
				Judgement					
3			Ø mm.	Vernier	±0.3				
			L mm.	ตลับเมตร	±50				
			Appearance	Visual					
				Judgement					
4			Ø mm.	Vernier	±0.3				
			L mm.	ตลับเมตร	±50				
			Appearance	Visual					
				Judgement					
5			Ø mm.	Vernier	±0.3				
			L mm.	ตลับเมตร	±50				
			Appearance	Visual					
				Judgement					
6			Ø mm.	Vernier	±0.3				
			L mm.	ตลับเมตร	±50				
			Appearance	Visual					
				Judgement					

Reference :

1. ใบรายการตรวจรับเหล็กเส้น (PO or Packing List)
2. ตรวจ Spec ส่วนผสมเหล็ก ตามมาตรฐาน SBI-PC-S01
3. รูปแบบการบรรจุ



ตรวจสอบสภาพการบรรจุ (Package)

หัวข้อการตรวจสอบ	ผลการตรวจสอบ	
1. มัดเหล็กเส้นไม่ขาดจากกัน	☑ OK	☐ NG
2. การจัดเรียงหัว-ท้ายเหล็กเส้นเสมอกัน	☑ OK	☐ NG
3.มีการชี้บ่งที่มัดเหล็กเส้นทุกมัด	☑ OK	☐ NG

石家庄钢铁有限责任公司 T112511005005 Steel grade S45C Heat No. 2416468 Size Φ46 mm MADE IN CHINA

Comment : Appearance

- No Crack
- No Burr
- No Bend
- No Oval

Remark :

SYMBOL FOR JUDGE MENT

O = OK

Δ = SPECIAL ACCEPT

X = NO GOOD

ต้นฉบับ

石钢®

SHIJIAZHUANG IRON & STEEL CO., LTD

NO.24056509

QUALITY CERTIFICATE

SG-MES-PZ-1001

Customer's contract No.	ZTH24C08	Customer	TOYOTA TSUSHO (THAILAND) CO., LTD.	Shape of Product	Round Bar	Standard	JSXY2039-2022	Steel grade	S45C	Certificate No.	2502240211
Heat No.	2416468	Rolling plan No.	B112510405	Delivery condition	Hot rolled	Size(mm)	DIA.46	Weight(MT)	5.753	Bundles	3

Chemical Composition (%)

Item	C	Si	Mn	P	S	Cr	Ni	Cu	O	SP1
Ladle Result	0.44	0.19	0.65	0.012	0.005	0.07	0.05	0.06	0.0006	0.11

Scattered porosity	Center porosity	Ingot shape segregation	Yield strength	Tensile strength	Elongation	Reduction of area	Hardness	dA	d(B+C)	Decarburized layer	Austenite grain size	Inspection	Surface quality & Shape size
Grade	Grade	Grade	ReL MPa	Rm MPa	A %	Z %	HBW	%	%	mm	Grade		
0.5	1	0	423	686	24.0	53	181	0.02	0.02	0.25	8	Qualified	Qualified
0.5	1	0	430	692	23.0	52	180	0.02	0.01	0.22			
							182						

HBIS 河钢集团石钢公司
HBIS GROUP SHISTEEL COMPANY

石家庄钢铁有限责任公司
T112511005005
Steel grade S45C
Heat No. 2416468
Size Φ46 mm
MADE IN CHINA

PASS
02/03/69
ผู้ตรวจสอบ.....
หัวหน้าแผนก.....

Note: SP1-Cr+Ni;

石家庄钢铁有限责任公司
Signature
质量检验专用章
检验合格

Quality department director: Wanglingwen 王玲文

Address: Hebei, Shijiazhuang, China 363 Heping donglu, Code:050031, Tel:(0311) 86913195

MADE IN CHINA