

bI dymaniac language system

© Dmitry Ponyatov <dponyatov@gmail.com>

January 15, 2016

Contents

Intro	8
BE WARNED	9
0.0.1 <i>bI</i> not intended for data crunching itself	9
0.0.2 There is no memory management at all	10
0.0.3 You must have some skills in compiler design and functional programming	10
Installation	10
Compiler structure	12
1 Core system	13
1.1 Files	13
1.1.1 Lexer	14
1.1.2 Parser	15
1.1.3 Headers	16
1.1.4 <i>C++</i> core	17
1.1.5 Build script	18
1.2 Sym: Abstract Symbolic Type	21
1.3 Writers	22
1.4 Global environment	22

1.5	Comments	23
1.5.1	Line comment	23
1.5.2	Block comment	24
1.6	Scalar types	25
1.6.1	str: string	25
1.6.2	int: integer	25
1.6.3	hex: machine hex	25
1.6.4	bin: machine binary	25
1.6.5	num: floating point number	25
1.7	Composites	25
1.7.1	List	25
1.7.2	Pair	25
1.7.3	Vector	26
1.7.4	Tuple	26
1.8	Functionals	26
1.8.1	Operator	26
1.8.2	Function	27
1.8.3	Lambda	27
1.9	Operators	27
1.9.1	= assignment	27
1.9.2	@ apply	27
1.9.3	. index	27
1.9.4	+ add	27
1.9.5	- sub	27
1.9.6	* mul	27
1.9.7	/ div	27
1.9.8	^ pow	27

2	GUI subsystem	28
2.1	Display	29
2.2	Window	29
2.3	Group: widget grouping	29
2.3.1	Tiler window manager	29
2.3.2	Tabber: fullsize with tab/slide	29
2.3.3	Grid: ortho groups	29
2.3.4	FreeForm: movable elements	29
2.3.5	Menu: nested selectors	29
2.3.6	Radio: tiny selectors radiogroup	29
2.3.7	Status: status bar manager	29
2.4	Form controllers	29
2.4.1	Button	29
2.4.2	Check: checkbox	29
2.4.3	Selector: list selector	29
2.4.4	Scroller: process guage	29
2.4.5	Label: text label	29
2.4.6	Entry: text entry with format checker	29
2.4.7	Message: message bar/window	29
2.4.8	Image: pixel view	29
2.4.9	Canvas: vector view	29
2.4.10	Tree: foldable tree view	29
2.4.11	Graph: generic (di)graph interface	29
2.5	Resources	29
2.5.1	Font: register/render	29
2.5.2	Color:	29
2.5.3	Block: 2D vector element	29

2.5.4	Icon: Image register/autoscaler	29
2.6	Std widgets	29
2.6.1	File selector	29
2.6.2	Print	29
2.6.3	Tree view	29
2.7	Controllers	29
2.7.1	One touch interface	29
2.7.2	Multibutton mouse	29
2.7.3	Game controllers	29
2.7.4	MIDI	29
2.8	Text editor	29
2.8.1	Syntax highlight	29
2.8.2	Folding	29
2.9	Schemer: Vector 2D	29
2.9.1	2D Primitives	29
2.9.2	Autoplacing and link tracing	29
2.9.3	Graph view/controller	29
2.10	Grabbers	29
2.10.1	Webcam	29
2.10.2	Scanner/TWAIN	29
2.11	3D	29
2.11.1	OpenGL	29
2.11.2	CAD view	29
2.12	Data visualizer	29
2.12.1	plot: 2D/3D GNUPLOT-like plotting	29
2.12.2	Dynamic data protting	29

3	Data storage	30
3.1	Volume management	31
3.1.1	plug/unplug/status	31
3.2	RDBMS interface	31
3.2.1	Generic interface	31
3.2.2	SQLite	31
3.2.3	MySQL	31
3.2.4	Postgres	31
3.2.5	Cursor	31
3.2.6	Trigger	31
3.2.7	Blob	31
3.3	XML	31
3.4	Object serialization	31
3.5	Binary format coders	31
4	Network	32
5	Math engine	33
5.1	Math types	33
5.1.1	Complex number	33
5.1.2	Matrix	33
5.2	Symbolic algebra	33
5.3	Numeric methods	33
5.4	Signal processing	33
6	CAD/CAM	34
6.1	CAD base	35

6.1.1	Primitives	35
6.1.2	Data interchange	35
6.1.3	Parametric solver	35
6.1.4	Assembly	35
6.1.5	Draft generator	35
6.2	CAM	35
6.2.1	Tool management	35
6.2.2	Technology passes	35
6.2.3	Mill	35
6.2.4	Lathe	35
6.2.5	3D Print layering	35
6.3	EDA	35
6.3.1	Library manager	35
6.3.2	Schematics	35
6.3.3	SPICE	35
6.3.4	PCB	35
6.3.5	Gerber	35
7	Dynamic syntax analysis	36
7.1	Lexer	36
7.2	Parser	36
8	LLVM integration	37
	Bibliography	38
	Dragon Book	38
	SICP	40

Functional programming	41
LLVM	41
9 1/2 books	42



Intro

Any program **must have** scripting ability for **configs** and **user extensions**. *bI* system provides universal script engine for *bI* language dialect and dynamic data types *C++* class tree for internal use in generated program. I was impressed by *SmallTalk* system ideology, *bI* system follows this way to gui-powered interactive system for translators design, symbolic computations and CAD/CAM/EDA environment.

Goals

- metaprogramming, computer language design and translator development
- symbolic and numeric computations
- clustering and cloud computing
- complex engineering systems design
- statical translation to *C++/Java* for multiplatform software development (☒*Windows/Linux/Android*)

Applications


- universal language for configs and parser for computing programs input data presented in text format
- text data and program sources processing

- fast GUI programming for tiny helper programs
- universal template language:
 - files generation based on project templates
 - multiplatform high-level software development
 - config files generation and control in clustering systems

Be Warned

0.0.1 *bI* not intended for data crunching itself

bI not intended for data crunching itself — it's tool for hand-cranked compiling and program transformations. *bI* core supports <num:1.6.5> data type for floating point numbers, but **avoid use of *bI* core for numerical computation**. Right way to use *bI* — construct low-level program which will crunch your data using power of *bI* metaprogramming.



LLVM framework and JIT libraries looks very interesting for **dynamic compilation** — this magic can conjure some speedup of *bI* core¹ itself, and incredible performance of mutable runtime-generated machine code for data crunching.

¹ it's high-level part realized in *bI* language, and *bI/next* generation described via core metamodel

0.0.2 There is no memory management at all

Current version of *bI* core have no any memory management: there is no garbage collector, all created objects will be stay in memory until system crash on memory overflow.

This way was chosen for simplicity. It is sufficient for tiny batch runs and interactive work with "failure and restart from snapshot" hints, but this makes continues or large data crunching impossible.

0.0.3 You must have some skills in compiler design and functional programming

bI system is syntax analyzer and translator framework by design, and user must have some skills in compiler design and functional programming. You must read DragonBook [3], SICP [5] and Harrison/Field [6] before you dig in hedgehog den.

Installation

GitHub: <https://github.com/ponyatov/Y>
dev branch: <https://github.com/ponyatov/Y/tree/dev/>

```
git clone -o gh https://github.com/ponyatov/Y/tree/master/ bI_stable
cd bI_stable
```

bI system provided as source-only, and requires some development tools installed:

- host: `Windows`

git-scm git client <https://git-scm.com/downloads>

MinGW GNU compiler toolchain <http://www.mingw.org/download/installer?>

- **g++** C++ compiler
- **flex** lexer generator
- **bison** parser generator

[*(g)Vim*] text editor <ftp://ftp.vim.org/pub/vim/pc/gvim74.exe>


```
mingw32-make EXE=.exe RES=res.res
```

- host: *Linux*, powered with LLVM dynamic compilation

```
apt install git make g++ flex bison llvm-3.5
```

```
make EXE= RES= LLVER=3.5
```

Compiler structure



Chapter 1

Core system

1.1 Files

ypp.ypp	flex	parser 1.1.2
lpp.lpp	bison	lexer 1.1.1
hpp.hpp	C++	headers 1.1.3
cpp.cpp	C++	core 1.1.4
Makefile	make	build script 1.1.5
rc.rc	windres	win32 resource description
bat.bat	(g)Vim	win32 start helper
filetype.vim	(g)Vim	.bI .blog file type processing
syntax.vim	(g)Vim	syntax coloring
doc/	L ^A T _E X	
doc/Makefile		1.1.5
doc/bl.pdf		manual

1.1.1 Lexer

Lexer uses **flex** generator, produces **lex.yy.c**.

All defines moved to **hpp.hpp**, lexer header includes buffer for string parsing.

lpp.lpp

```
1 %{  
2 #include "hpp.hpp"  
3 string StringLexBuffer;           /* string parsing buffer */  
4 void incLude(Sym*inc) {           /* .inc processing */  
5     if (!(yyin = fopen(inc->val.c_str(),"r"))) yyerror(""); // open  
6     yypush_buffer_state(yy_create_buffer(yyin,YY_BUF_SIZE)); // push to lexer  
7 }  
8 %}
```

Options disables yywrap() function usage and enables line number autocount for error reporting.

lpp.lpp

```
1 %option noyywrap  
2 %option yylineno
```

Rules section described part by part in scalar types **1.6** and operators **??** manual sections.

lpp.lpp

```
1 %%  
2 ...%%  
3 ...
```

Unused chars will be dropped by this rules at end of lexer:

lpp.lpp

```
1 ^\\.inc[ \\t]+[^\\n]+ { yylval.o = new Directive(yytext); /* .inc lude */
2 ^\\. [a-z]+[^\\n]* TOC( Directive , DIR) /* .directive */
3 [ \\t\\r\\n]+ {} /* drop spaces */
4 . {} /* drop undetected chars */
```

Lexer C++ API includes this objects: TOC() macro used in lexer rules, creates

hpp.hpp

```
1 // == lexer interface ==
2 extern int yylex(); // parse next token
3 extern int yylineno; // current source line
4 extern char* yytext; // found token text
5 #define TOC(C,X) { yylval.o = new C(yytext); return X; } // token macro used in lexer
```

1.1.2 Parser

Core parser uses **bison** for **ypp.tab.cpp**, **ypp.tab.hpp**

Parser header looks like lexer header, all defines done in **hpp.hpp**.

ypp.ypp

```
1 %{
2 #include "hpp.hpp"
3 %}
```

hpp.hpp


```

1 // == parser interface ==
2 extern int yyparse();           // run parser
3 extern void yyerror(std::string); // error callback

```

1.1.3 Headers

Header file contents wrapped by include-once preprocessor hint:

hpp.hpp

```

1 #ifndef _H_bl
2 #define _H_bl
3 #endif // _H_bl

```

Some metainfo constants defined, including `-DMODULE=$(CURDIR)` defined in **Makefile**:

hpp.hpp

```

1 #define AUTHOR "(c) Dmitry Ponyatov <dponyatov@gmail.com>, all rights reserved"
2 #define LICENSE "http://www.gnu.org/copyleft/lesser.html"
3 #define GITHUB "https://github.com/ponyatov/Y/tree/dev"
4 #define AUTOGEN "/* ***** DO NOT EDIT: this file was autogenerated by bl ***** */"
5 #define LOGO "logo64x64"
6 #define LISPLOGO "warning64x64"

```

Standard C^{++} includes used in core:

hpp.hpp

```

1 // == std.includes ==
2 #include <iostream>

```

```
3 #include <sstream>
4 #include <cstdlib>
5 #include <vector>
6 #include <map>
7 using namespace std;
```

mingw32.hpp: win32/MinGW

Some OS/platform specifics headers selected into separate files,

mingw32.hpp

```
1 #ifndef _H_MINGW32
2 #define _H_MINGW32
3
4 #include <direct.h>
5 namespace win32 {
6 #include <windows.h>
7 }
8
9 #endif // _H_MINGW32
```

1.1.4 C++ core

C++ code described part by part over this manual in every symbolic type section.

cpp.cpp

```
1 #include "hpp.hpp"
```

Error callback function: it will be called from parser on error. YYERR macro used for doubling error message: to stdout redirected to .blog, and stderr goes to **make** output log¹.

cpp.cpp

```
1 #define YYERR " \n\n"<<yylineno<<" : "<<msg<<" [ "<<yytext<<" ] \n\n"
2 void yyerror(string msg) { cout<<YYERR; cerr<<YYERR; exit(-1); }
```

main() function: call global environment setup and parser:

cpp.cpp

```
1 int main() { env_init(); return yyparse(); } // == main() ==
```

mingw32.cpp: win32/MinGW

OS/platform specifics C^{++} code selected into separate files,

mingw32.cpp

```
1 #include "hpp.hpp"
2
3 Window::Window(Sym*o):Sym(" window", o->val) {}
4
5 void Window::show() { par["show"]=nil; }
```

1.1.5 Build script

Project builds with command [mingw32-]make [vars]. Vars can be:

¹ and IDE report

variable	win32	unix	
EXE	.exe		executable file extension, empty if Linux/UNIX
RES	res.res		resource file name (win32 only)
TAIL	-n17	-n7	number of .blog lines will be printed on make exec build
LLVER		3.5	LLVM version if used

MODULE variable sets name for current module. It was set to *bI*, but can use current dir name as module name.

Makefile

```
1 MODULE = $(notdir $(CURDIR))
2 MODULE = bI
```

exec target build *bI* system core and runs high-level system build from **bl.bl** master source:

Makefile

```
1 .PHONY: exec
2 exec: ./$(MODULE)$(EXE) $(MODULE).bl
3      ./$(MODULE)$(EXE) < $(MODULE).bl > $(MODULE).blog && tail $(TAIL) $(MODULE).blog
```

make clean removes all temporary and produced files, makes all project clean:

Makefile

```
1 .PHONY: clean
2 clean:
3      rm -rf ./$(MODULE)$(EXE) *.log ypp.tab.?pp lex.yy.c $(RES)
```

C\H contains files will be compiled by CXX C++ compiler into interpreter executable:

Makefile

```
1 C = cpp.cpp $(OS).cpp ypp.tab.cpp lex.yy.c
2 H = hpp.hpp $(OS).hpp ypp.tab.hpp
```

C++ compiler run:

Makefile

```
1 OS = $(shell $(CXX) -dumpmachine)
2 CXXFLAGS += -I. -std=gnu++11 -DMODULE=\"$(MODULE)\"
3 ./$(MODULE)$(EXE): $(C) $(H) $(RES) Makefile
4 $(CXX) $(CXXFLAGS) -o $@ $(C) $(RES)
```

bison parser generator run:

Makefile

```
1 ypp.tab.cpp: ypp.ypp
2     bison $<
```

flex lexer generator run:

Makefile

```
1 lex.yy.c: lpp.lpp
2     flex $<
```

win32 resource compiler run:

Makefile

```
1 res.res: rc.rc
2     windres $< -O coff -o $@
```

1.2 Sym: Abstract Symbolic Type

bI language based on operations on **Abstract [Sym]bolic Type**: it's close to classical Abstract Syntax Tree elements, and uses same acronym. For dynamic languages Sym much complicated comparing to *Lisp* cells/lists, and scalar primitive types², but it was selected considering primary *bI* area: computer language processing, where annotated AST trees is basic data type.

class:Sym		abstract symbolic type
	string:tag	type, class tag
	string:val	value
constructors:	Sym(string,string)	<T:V> constructor
	Sym(string)	token constructor
	Sym(Sym)	copy constructor
nest[]ed:	List<Sym>:nest[]	nested elements
	fn:push(Sym)	add nested
par{}ameters:	Dict<string,Sym>:par[]	parameters dict (string-keyed list)
	fn:setpar(Sym)	add/set parameter
dump:	fn:dump(int)->string	recursive dump(+1) tree in text form (with depth padding)
	fn:tagval()->string	dump <T:V> header only
	fn:pad(int)->string	return padding string: n tabs
	fn:eval()->Sym	compute/evaluate object
operators:	op:@(Sym)->Sym	A @ B apply
	op:=(Sym)->Sym	A = B equal
		hpp.hpp

² numbers, strings

Using **virtual base class** `Sym{}` allows to use RTTI and process inherited class instances using pointers to base class, first of all it allows to use storage collections `vector<Sym*>` and `map<string,Sym*>` for any objects³.

1.3 Writers

Writer — function writes argument to *bI* log (.blog):

hpp.hpp

```
1 extern void W(Sym*); // == writers ==
2 extern void W(string);
```

cpp.cpp

```
1 void W(Sym*o) { cout<<o->dump(); } // == writers ==
2 void W(string s) { cout<<s; }
```

1.4 Global environment

hpp.hpp

```
1 extern map<string,Sym*> env; // == global environment ==
2 extern void env_init(); // init env[] on startup
```

³ instances of inherited classes

cpp.cpp

```
1 int main() { env_init(); return yyparse(); } // == main() ==
2     Sym*E = env[val]; if (E) return E; // lookup in glob.env[]
3 Sym* Sym::eq(Sym*o) { env[val]=o; return o; }
4 map<string ,Sym*> env; // == environment ==
5 void env_init() { // init on startup
6     env["nil"]=nil;
7     env["MODULE"] = new Str(MODULE); // module name (CFLAGS -DMODULE)
8     env["AUTHOR"] = new Str(AUTHOR); // author (c)
9     env["LICENSE"] = new Str(LICENSE); // license
10    env["GITHUB"] = new Str(GITHUB); // github home
11    env["AUTOGEN"] = new Str(AUTOGEN); // autogenerated code signature
12    env["LOGO"] = new Str(LOGO); // bl logo (w/o file extension)
13    env["LISPLOGO"] = new Str(LISPLOGO); // Lisp Warning logo
14    env["window"] = new Fn("window",window);
```

1.5 Comments

1.5.1 Line comment

bl.bl

lpp.lpp

```
1 #[^\\|][^\\n]*\\n {} /* line comment */
```


1.5.2 Block comment

Current version have undetected problems with block comments: on multiline block comments lexer hangs until file end, ignoring all source and causing strange syntax errors.

bl.bl

lpp.lpp

```
1                                     /* lexer state: #| block comment|# */
2 %x lexcomment
3 #\|                                {BEGIN(lexcomment);}                                /* block comment*/
4 <lexcomment>\|#                    {BEGIN(INITIAL);}
5 <lexcomment>\n                      {}
6 <lexcomment>.                       {}
```

1.6 Scalar types

1.6.1 str: string

1.6.2 int: integer

1.6.3 hex: machine hex

1.6.4 bin: machine binary

1.6.5 num: floating point number

1.7 Composites

1.7.1 List

hpp.hpp

cpp.cpp

1.7.2 Pair

hpp.hpp

cpp.cpp

1.7.3 Vector

hpp.hpp

cpp.cpp

1.7.4 Tuple

hpp.hpp

cpp.cpp

1.8 Functionals

1.8.1 Operator

All operators described in [1.9](#)

1.8.2 Function

1.8.3 Lambda

1.9 Operators

1.9.1 = assignment

1.9.2 @ apply

1.9.3 . index

1.9.4 + add

1.9.5 - sub

1.9.6 * mul

1.9.7 / div

1.9.8 ^ pow

Chapter 2

GUI subsystem

2.1 Display

2.2 Window

2.3 Group: widget grouping

2.3.1 Tiler window manager

2.3.2 Tabber: fullsize with tab/slide

2.3.3 Grid: ortho groups

2.3.4 FreeForm: movable elements

2.3.5 Menu: nested selectors

Chapter 3

Data storage

3.1 Volume management

3.1.1 plug/unplug/status

3.2 RDBMS interface

3.2.1 Generic interface

3.2.2 SQLite

3.2.3 MySQL

3.2.4 Postgres

3.2.5 Cursor

Chapter 4

Network

Chapter 5

Math engine

5.1 Math types

5.1.1 Complex number

5.1.2 Matrix

5.2 Symbolic algebra

5.3 Numeric methods

5.4 Signal processing

Chapter 6

CAD/CAM

6.1 CAD base

6.1.1 Primitives

6.1.2 Data interchange

STEP

IGES

STL

DXF

6.1.3 Parametric solver

6.1.4 Assembly

Chapter 7

Dynamic syntax analysis

7.1 Lexer

7.2 Parser

Chapter 8


LLVM integration

Bibliography

Dragon Book

- [1] [Dragon Book @ Stanford.edu](#)

Some lection sets on computer language compilers in free e-books




- [2] Green Dragon Book'77

Alfred V. Aho, Jeffrey D. Ullman


Principles of Compiler Design

Addison-Wesley, ISBN 0-201-00022-9, 1977



- [3] classical Red Dragon Book
Alfred V. Aho, Ravi Sethi, Jeffrey D. Ulman

Compilers: Principles, Techniques, and Tools (2nd edition)



- [4] Purple Dragon Book
Alfred V. Aho, Monica S. Lam, Ravi Sethi, Jeffrey D. Ulman


Compilers: Principles, Techniques, and Tools (2nd edition)

Addison-Wesley, 2006

- directed translation
- new data flow analyses
- parallel machines

- JIT compiling
- garbage collection
- new case studies

SICP




[5] SICP

Harold Abelson, Gerald Jay Sussman, Julie Sussman

Structure and Interpretation of Computer Programs second edition

© 1996 by The Massachusetts Institute of Technology

Functional programming



[6]

Peter G. Harrison, Anthony J. Field

Functional Programming

LLVM



[7]

Bruno Cardoso Lopes, Rafael Auler

Getting Started with LLVM Core Libraries

9 1/2 books

- [8] **The Top 9 $\frac{1}{2}$ In a Hackers Bookshelf**
by Jess Johnson in Books & Tools
- [9] Fredrick P. Brooks
The Mythical Man Month: Essays on Software Engineering
Anniversary Edition
- [10] Brian W. Kernighan, Dennis M. Ritchie
The ANSI C Programming Language, Second Edition
Prentice Hall, AT&T, 1988