

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



LAB REPORT
on

MACHINE LEARNING

Submitted by

S R POOJA (1BM19CS135)

in partial fulfillment for the award of the degree of
BACHELOR OF ENGINEERING
in
COMPUTER SCIENCE AND ENGINEERING



B.M.S. COLLEGE OF ENGINEERING

(Autonomous Institution under VTU)

BENGALURU-560019

May-2022 to July-2022

B. M. S. College of Engineering,
Bull Temple Road, Bangalore 560019
(Affiliated To Visvesvaraya Technological University, Belgaum)
Department of Computer Science and Engineering



CERTIFICATE

This is to certify that the Lab work entitled “Machine Learning Lab” carried out by **S R Pooja (1BM19CS135)**, who is a bonafide student of **B. M. S. College of Engineering**. It is in partial fulfillment for the award of **Bachelor of Engineering in Computer Science and Engineering** of the Visvesvaraya Technological University, Belgaum during the year 2022. The Lab report has been approved as it satisfies the academic requirements with respect to **Machine Learning - (20CS6PCMAL)** work prescribed for the said degree.

Dr. Asha G R
Assistant Professor
Department of CSE
BMSCE, Bengaluru

Dr. Jyothi S Nayak
Professor and Head
Department of CSE
BMSCE, Bengaluru

Index Sheet

Sl. No.	Experiment Title	Page No.
1)	Find-S	4-5
2)	Candidate Elimination	6-7
3)	Decision tree based on ID3	8-10
4)	Naive Bayesian Classifier	11-12
5)	Linear Regression	13-14

1. Implement and demonstrate the FIND-S algorithm for finding the most specific hypothesis based on a given set of training data samples.

CODE:

```
import csv

a = []

with open('/kaggle/input/dataset/data.csv','r') as csvfile:

    for row in csv.reader(csvfile):

        a.append(row)

    print(a)

    print("\n The total number of training instances are : ",len(a))

num_attribute = len(a[0])-1

print("\n The initial hypothesis is : ")

hypothesis = ['0']*num_attribute

print(hypothesis)

for i in range(0, len(a)):

    if a[i][num_attribute] == 'yes':

        for j in range(0, num_attribute):

            if hypothesis[j] == '0' or hypothesis[j] == a[i][j]:

                hypothesis[j] = a[i][j]

            else:

                hypothesis[j] = '?'

        print("\n The hypothesis for the training instance { } is :\n" .format(i+1),hypothesis)

print("\n The Maximally specific hypothesis for the training instances is :")

print(hypothesis)
```

OUTPUT:

The total number of training instances are : 5

The initial hypothesis is :

['0', '0', '0', '0', '0', '0']

The hypothesis for the training instance 1 is :

['0', '0', '0', '0', '0', '0']

The hypothesis for the training instance 2 is :

['sunny', 'warm', 'normal', 'strong', 'warm', 'same']

The hypothesis for the training instance 3 is :

['sunny', 'warm', '?', 'strong', 'warm', 'same']

The hypothesis for the training instance 4 is :

['sunny', 'warm', '?', 'strong', 'warm', 'same']

The hypothesis for the training instance 5 is :

['sunny', 'warm', '?', 'strong', '?', '?']

The Maximally specific hypothesis for the training instances is :

['sunny', 'warm', '?', 'strong', '?', '?']

2. For a given set of training data examples stored in a .CSV file, implement and demonstrate the Candidate-Elimination algorithm to output a description of the set of all hypotheses consistent with the training examples.

CODE:

```
import numpy as np
import pandas as pd

data = pd.read_csv('/kaggle/input/dataset/data.csv')
concepts = np.array(data.iloc[:,0:-1])
print(concepts)
target = np.array(data.iloc[:,-1])
print(target)
def learn(concepts, target):
    specific_h = concepts[0].copy()
    print("Initialization of specific_h and general_h")
    print(specific_h)
    general_h = [["?" for i in range(len(specific_h))] for i in range(len(specific_h))]
    print(general_h)

    for i, h in enumerate(concepts):
        print("For Loop Starts")
        if target[i] == "yes":
            print("If instance is Positive ")
            for x in range(len(specific_h)):
                if h[x] != specific_h[x]:
                    specific_h[x] = '?'
                    general_h[x][x] = '?'

        if target[i] == "no":
            print("If instance is Negative ")
            for x in range(len(specific_h)):
                if h[x] != specific_h[x]:
                    general_h[x][x] = specific_h[x]
                else:
                    general_h[x][x] = '?'

    print("Steps of Candidate Elimination Algorithm",i+1)
    print(specific_h)
    print(general_h)
    print("\n")
    print("\n")

    indices = [i for i, val in enumerate(general_h) if val == ['?', '?', '?', '?', '?', '?']]
    for i in indices:
        general_h.remove(['?', '?', '?', '?', '?', '?'])
    return specific_h, general_h

s_final, g_final = learn(concepts, target)

print("Final Specific_h:", s_final, sep="\n")
```

```
print("Final General_h:", g_final, sep="\n")
```

OUTPUT :

```
[[['sunny' 'warm' 'normal' 'strong' 'warm' 'same']
['sunny' 'warm' 'high' 'strong' 'warm' 'same']
['rainy' 'cold' 'high' 'strong' 'warm' 'change']
['sunny' 'warm' 'high' 'strong' 'cool' 'change']]
['yes' 'yes' 'no' 'yes']
Initialization of specific_h and general_h
['sunny' 'warm' 'normal' 'strong' 'warm' 'same']
[[['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]
For Loop Starts
If instance is Positive
Steps of Candidate Elimination Algorithm 1
['sunny' 'warm' 'normal' 'strong' 'warm' 'same']
[[['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

For Loop Starts
If instance is Positive
Steps of Candidate Elimination Algorithm 2
['sunny' 'warm' '?', 'strong' 'warm' 'same']
[[['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

For Loop Starts
If instance is Negative
Steps of Candidate Elimination Algorithm 3
['sunny' 'warm' '?', 'strong' 'warm' 'same']
[['sunny', '?', '?', '?', '?', '?'], ['?', 'warm', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', 'sam
e']]

For Loop Starts
If instance is Positive
Steps of Candidate Elimination Algorithm 4
['sunny' 'warm' '?', 'strong' '?', '?']
[['sunny', '?', '?', '?', '?', '?'], ['?', 'warm', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

Final Specific_h:
['sunny' 'warm' '?', 'strong' '?', '?']
Final General_h:
[['sunny', '?', '?', '?', '?', '?'], ['?', 'warm', '?', '?', '?', '?']]

For Loop Starts
If instance is Positive
Steps of Candidate Elimination Algorithm 2
['sunny' 'warm' '?', 'strong' 'warm' 'same']
[[['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

For Loop Starts
If instance is Negative
Steps of Candidate Elimination Algorithm 3
['sunny' 'warm' '?', 'strong' 'warm' 'same']
[['sunny', '?', '?', '?', '?', '?'], ['?', 'warm', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', 'sam
e']]

For Loop Starts
If instance is Positive
Steps of Candidate Elimination Algorithm 4
['sunny' 'warm' '?', 'strong' '?', '?']
[['sunny', '?', '?', '?', '?', '?'], ['?', 'warm', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

Final Specific_h:
['sunny' 'warm' '?', 'strong' '?', '?']
Final General_h:
[['sunny', '?', '?', '?', '?', '?'], ['?', 'warm', '?', '?', '?', '?']]
```

[+ Code](#)[+ Markdown](#)

3. Write a program to demonstrate the working of the decision tree based ID3 algorithm. Use an appropriate data set for building the decision tree and apply this knowledge to classify a new sample.

CODE:

```
import math
import csv
def load_csv(filename):
    lines=csv.reader(open(filename,"r"));
    dataset = list(lines)
    headers = dataset.pop(0)
    return dataset,headers

class Node:
    def __init__(self,attribute):
        self.attribute=attribute
        self.children=[]
        self.answer=""

def subtables(data,col,delete):
    dic={ }
    coldata=[row[col] for row in data]
    attr=list(set(coldata))

    counts=[0]*len(attr)
    r=len(data)
    c=len(data[0])
    for x in range(len(attr)):
        for y in range(r):
            if data[y][col]==attr[x]:
                counts[x]+=1

    for x in range(len(attr)):
        dic[attr[x]]=[[0 for i in range(c)] for j in range(counts[x])]
        pos=0
        for y in range(r):
            if data[y][col]==attr[x]:
                if delete:
                    del data[y][col]
                    dic[attr[x]][pos]=data[y]
                    pos+=1
    return attr,dic

def entropy(S):
    attr=list(set(S))
    if len(attr)==1:
        return 0

    counts=[0,0]
    for i in range(2):
        counts[i]=sum([1 for x in S if attr[i]==x])/(len(S)*1.0)

    sums=0
    for cnt in counts:
```



```

        sums+=-1*cnt*math.log(cnt,2)
    return sums

def compute_gain(data,col):
    attr,dic = subtables(data,col,delete=False)

    total_size=len(data)
    entropies=[0]*len(attr)
    ratio=[0]*len(attr)

    total_entropy=entropy([row[-1] for row in data])
    for x in range(len(attr)):
        ratio[x]=len(dic[attr[x]])/(total_size*1.0)
        entropies[x]=entropy([row[-1] for row in dic[attr[x]]])
        total_entropy-=ratio[x]*entropies[x]
    return total_entropy

def build_tree(data,features):
    lastcol=[row[-1] for row in data]
    if(len(set(lastcol))==1):
        node=Node("")
        node.answer=lastcol[0]
        return node

    n=len(data[0])-1
    gains=[0]*n
    for col in range(n):
        gains[col]=compute_gain(data,col)
    split=gains.index(max(gains))
    node=Node(features[split])
    fea = features[:split]+features[split+1:]

    attr,dic=subtables(data,split,delete=True)

    for x in range(len(attr)):
        child=build_tree(dic[attr[x]],fea)
        node.children.append((attr[x],child))
    return node

def print_tree(node,level):
    if node.answer!="":
        print(" "*level,node.answer)
        return

    print(" "*level,node.attribute)
    for value,n in node.children:
        print(" "*(level+1),"└",value)
        print_tree(n,level+2)

"""Main program"""
dataset,features=load_csv("/kaggle/input/train/ids_train.csv")
node1=build_tree(dataset,features)

print("The decision tree for the dataset using ID3 algorithm is :\n")
print_tree(node1,0)

```

OUTPUT:

The decision tree for the dataset using ID3 algorithm is :

```
Outlook
├── Rain
│   ├── Wind
│   │   ├── Weak
│   │   │   └── Yes
│   │   └── Strong
│   │       ├── No
│   └── Sunny
│       ├── Humidity
│       │   ├── Normal
│       │   │   └── Yes
│       │   └── High
│       │       ├── No
│   └── Overcast
│       └── Yes
```

4. Write a program to implement the naive Bayesian classifier for a sample training data set stored as a .CSV file. Compute the accuracy of the classifier, considering few test data sets.

CODE:

```
import pandas as pd

from sklearn.model_selection import train_test_split
from sklearn.naive_bayes import GaussianNB
from sklearn import metrics

df = pd.read_csv("/kaggle/input/diabetes/diabetes.csv")
feature_col_names = ['num_preg', 'glucose_conc', 'diastolic_bp', 'thickness', 'insulin', 'bmi', 'diab_pred', 'age']
predicted_class_names = ['diabetes']

X = df[feature_col_names].values
y = df[predicted_class_names].values
print(df.head)
xtrain,xtest,ytrain,ytest=train_test_split(X,y,test_size=0.40)

print ('\n The total number of Training Data :',ytrain.shape)
print ('\n The total number of Test Data :',ytest.shape)

clf = GaussianNB().fit(xtrain,ytrain.ravel())
predicted = clf.predict(xtest)
predictTestData= clf.predict([[6,148,72,35,0,33.6,0.627,50]])

print('\n Confusion matrix')
print(metrics.confusion_matrix(ytest,predicted))
print('\n Accuracy of the classifier is',metrics.accuracy_score(ytest,predicted))
print('\n The value of Precision', metrics.precision_score(ytest,predicted))
print('\n The value of Recall', metrics.recall_score(ytest,predicted))
print("Predicted Value for individual Test Data:", predictTestData)
```

OUTPUT:

```
[145 rows x 9 columns]>
```

```
The total number of Training Data : (87, 1)
```

```
The total number of Test Data : (58, 1)
```

```
Confusion matrix
```

```
[[31  7]  
 [10 10]]
```

```
Accuracy of the classifier is 0.7068965517241379
```

```
The value of Precision 0.5882352941176471
```

```
The value of Recall 0.5
```

```
Predicted Value for individual Test Data: [1]
```

5. Implement the Linear Regression algorithm in order to fit data points. Select appropriate data set for your experiment and draw graphs.

CODE:

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd

# Importing the dataset
dataset = pd.read_csv('/kaggle/input/years-of-experience-and-salary/Years Experience and Salary.csv')
X = dataset.iloc[:, :-1].values #get a copy of dataset exclude last column
y = dataset.iloc[:, 1].values #get array of dataset in column 1st

# Splitting the dataset into the Training set and Test set
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=1/3, random_state=0)

# Fitting Simple Linear Regression to the Training set
from sklearn.linear_model import LinearRegression
regressor = LinearRegression()
regressor.fit(X_train, y_train)

# Predicting the Test set results
y_pred = regressor.predict(X_test)

# Visualizing the Training set results
viz_train = plt
viz_train.scatter(X_train, y_train, color='red')
viz_train.plot(X_train, regressor.predict(X_train), color='blue')
viz_train.title('Salary VS Experience (Training set)')
viz_train.xlabel('Year of Experience')
viz_train.ylabel('Salary')
viz_train.show()

# Visualizing the Test set results
viz_test = plt
viz_test.scatter(X_test, y_test, color='red')
```

```
viz_test.plot(X_train, regressor.predict(X_train), color='blue')  
viz_test.title('Salary VS Experience (Test set)')  
viz_test.xlabel('Year of Experience')  
viz_test.ylabel('Salary')  
viz_test.show()
```

OUTPUT:

