



SIMATS ENGINEERING ASSESSMENT TOOL 3

COURSE CODE: CSA1407

COURSE NAME: Compiler Design

COURSE OUTCOME COVERED

CO2: Construct top-down and bottom up parsers using CFG for parsing conflicts and error recovery for efficient syntax tree generation. (BL3)

Assessment Tool Weightage: 10%

QUESTIONS:

Total Marks:50

Annexure A

SCENARIO BASED TASK

Code of Conduct:

I pooja S (192524211) (Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.

I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the student:

S. pooja

Annexure A

SCENARIO-BASED TASK

QUESTIONS:

- 1.Scenario: Parsing Table Conflict in LL(1) While designing an LL(1) parser, a student constructs a parsing table and finds multiple entries in a single cell for a non-terminal and input symbol combination. This leads to confusion during parsing. Analyze how the syntax analyzer uses FIRST and FOLLOW sets in this process, identify the reason for the conflict, and explain how it affects deterministic parsing. Conclude by suggesting what decision should be taken to modify the grammar so that it becomes suitable for LL(1) parsing.
- 2.Scenario: Incorrect Parse Tree Generation A syntax analyzer generates a parse tree for the expression $id + id - id$, but the evaluation gives incorrect results due to improper grouping of operators. Analyze how the syntax analyzer constructs the parse tree, identify the issue related to associativity, and explain how grammar rules influence the structure of the tree. Finally, discuss what decision should be taken to enforce correct associativity and ensure accurate parsing.
- 3.Scenario: Invalid Expression Handling A syntax analyzer in a compiler receives the token sequence corresponding to the expression $a + * b$ from the lexical analyzer. Although all tokens are valid individually, the parser fails to generate a parse tree and reports an error. In this situation, analyze how the syntax analyzer identifies the error based on grammar rules, determine the key issue in the token arrangement, and explain how parsing techniques such as predictive or shift-reduce parsing handle such cases. Further, discuss what decision should be taken to improve error detection and recovery while maintaining clarity in parsing.
4. Scenario: Ambiguity in Conditional Statements A syntax analyzer is designed using the grammar $S \rightarrow \text{if } E \text{ then } S \mid \text{if } E \text{ then } S \text{ else } S \mid a$. While constructing the parsing table, conflicts arise, and the parser cannot decide which production to apply for certain inputs. In this scenario, explain how the syntax analyzer encounters ambiguity, identify the key issue known as the dangling else problem, and discuss how it impacts parsing. Suggest an appropriate modification or parsing strategy to resolve the ambiguity and ensure correct association of else clauses.
- 5.Scenario: Operator Precedence Conflict A parser is designed for arithmetic expressions using the grammar $E \rightarrow E + E \mid E * E \mid id$. While parsing the input $id + id * id$, the syntax analyzer produces an incorrect parse tree due to ambiguity in operator precedence. Examine how the syntax analyzer processes this input, identify the issue caused by the grammar, and explain how precedence and associativity rules should be applied. Based on this, suggest what changes must be made to the grammar or parsing technique to ensure correct evaluation.

RUBRICS FOR CALCULATION:

Scenario based assessment

Criteria	Weight age (%)	Level 4 (Exemplary)	Level 3 (Proficient)	Level 2 (Developing)	Level 1 (Beginning)
Understanding of Scenario	20%	Demonstrates clear and complete understanding of the scenario and context	Shows good understanding with minor gaps	Partial understanding; misses key aspects	Misinterprets or fails to understand the scenario
Identification of Key Issues	20%	Accurately identifies all relevant issues and factors involved	Identifies most key issues with minor omissions	Identifies limited issues; some irrelevant points	Unable to identify key issues
Application of Concepts	25%	Applies appropriate concepts effectively to address the scenario	Applies concepts with minor errors	Limited or partially correct application	Unable to apply relevant concepts
Decision Making	20%	Makes well-reasoned, logical decisions with strong rationale	Makes reasonable decisions with some justification	Makes weak decisions with limited justification	No clear decisions made or rationale provided
Clarity of Response	15%	Response is clear, structured, and logically presented	Generally clear with minor issues	Somewhat unclear or poorly structured	Disorganized and difficult to understand

Pooja. S

192524211

Scenario: parsing table conflict in LL(1)

In an LL(1) parser, the parsing table is constructed using the FIRST and FOLLOW set of the grammar. The first set terminals determine that can appear at the beginning of strings derived from a production, while the follow set contains terminals that can appear immediately after a non-terminal. During parsing table construction, each production is placed in the table based on these sets.

A conflict occurs when more than one production is entered into the same table cell for a non-terminal and an input symbol. This usually happens because the grammar contains left recursion, common prefixes (left factoring problem), or is ambiguous. As a result, the parser cannot uniquely determine which production should be applied.

Since LL(1) parsing is deterministic, each table entry must contain only one production. Multiple entries make the

Parser non-deterministic and may lead to incorrect parsing or parser failure.

Decision: The grammar should be modified by eliminating left recursion, perform left factoring, and ensuring that the $\text{LR}(0)$ and follow set do not overlap. This converts the grammar into a valid $\text{LR}(1)$ grammar with a conflict-free parsing table.

- 2 Scenario: Incorrect parse tree Generation
- The syntax analyzer constructs a parse tree by applying grammar productions according to the input tokens. For the expression $\text{id} + \text{id} - \text{id}$, the parser determines the order in which operations are evaluated.

If the grammar does not specify operator associativity, the expression may be grouped incorrectly. For example, it may be interpreted as $\text{id} + (\text{id} - \text{id})$ instead of the correct $(\text{id} + \text{id}) - \text{id}$. This results in incorrect evaluation because the operators are not associated properly.

Grammar rules directly influence the structure of the parse tree. A grammar that does not enforce associativity allows multiple valid parse trees for the same expression.

Decision: the grammar should enforce left associativity for addition and subtraction.
For example:

- $E \rightarrow E + T \mid E - T \mid T$
- $T \rightarrow id$

This ensures expressions are evaluated from left to right, producing the correct parse tree and accurate results.

Scenario: Invalid Expression Handling

The lexical analyzer correctly identifies the tokens in the expression $a + * b$ as identifiers and operators. However, the syntax analyzer checks whether these tokens follow the grammar rules.

The error occurs because the grammar expects an operand after the $+$ operator, but another operator ($*$) appears instead. Therefore, the token sequence violates the grammar.

making it impossible to construct a parse tree.

In predictive parsing (LL), the parser detects an error when no valid production exists in the parsing table for the current input symbol. In shift-reduce parsing (LR), the parser detects the error when no valid shift or reduce action is available.

Without proper recovery, the parser stops after reporting the error.

Decision:

The parser should implement error detection and recovery techniques, such as panic-mode recovery, phrase-level recovery, or synchronization using follow sets. These methods allow the parser to continue analyzing the remaining input while providing meaningful error messages.

Scenario: Ambiguity in conditional statements

The grammar

- $S \rightarrow \text{if } E \text{ then } S$
- $S \rightarrow \text{if } E \text{ then } S \text{ else } S$
- $S \rightarrow a$

is ambiguous because the parser cannot

determine which if statement an else belongs to. This is known as the dangling else problem.

When constructing the parsing table, conflicts arise because both productions begin with the same prefix:

if E then S

The parser cannot decide whether to reduce using the first production or continue parsing the second production containing else.

This ambiguity affects deterministic parsing by introducing parsing conflicts and producing multiple possible parse trees.

Decision: The grammar should be rewritten to distinguish matched and unmatched statements for example:

- $S \rightarrow M \mid U$
- $M \rightarrow \text{if } E \text{ then } M \text{ else } M \mid a$
- $U \rightarrow \text{if } E \text{ then } S \mid \text{if } E \text{ then } M \text{ else } U$

Alternatively, parser generators often resolve the ambiguity by associating else with the nearest unmatched if, which is the standard rule used in most programming languages.

Scenario: operator precedence

The grammar

- $E \rightarrow E + E$
- $E \rightarrow E * E$
- $E \rightarrow id$

is ambiguous because it does not define operator precedence or associativity.

For the input $id + id * id$, two different parse trees are possible:

- $(id + id) * id$
- $id + (id * id)$

The correct evaluation requires multiplication to have higher precedence than addition since the grammar does not specify this rule, the parser cannot determine the correct parse tree. Operator precedence and associativity are essential to ensure expressions are evaluated correctly.

Decision: The grammar should be rewritten to enforce precedence, for example:

- $E \rightarrow E + T \mid T$
- $T \rightarrow T * F \mid F$
- $F \rightarrow id$



SAVEETHA

INSTITUTE OF MEDICAL AND TECHNICAL SCIENCES
(Declared as Deemed to be University under Section 3 of UGC Act 1956)



Here :

- Multiplication has higher precedence than addition
- Addition and multiplication are left associative.

Alternatively, parser generators can use precedence and associativity declarations to resolve such conflicts automatically.