

CODETANTRA

HomeLearn Anywhere

202501050057@mitaoe.ac.inSupportLogout

Update ProfileChange PasswordSUBMIT

2.1.1. List operations

Write a Python program that implements a menu-driven interface for managing a list of integers. The program should have the following menu options:
1. Add
2. Remove
3. Display
4. Quit

The program should repeatedly prompt the user to enter a choice from the menu. Depending on the choice selected, the program should perform the following actions:

- Add:** Prompts the user to enter an integer and add it to the integer list. If the input is not a valid integer, display "Invalid input".
- Remove:** Prompts the user to enter an integer to remove from the list. If the integer is found in the list, remove it; otherwise, display "Element not found". If the list is empty, display "List is empty".
- Display:** Displays the current list of integers. If the list is empty, display "List is empty".
- Quit:** Exits the program.

The program should handle invalid menu choices by displaying "Invalid choice". Ensure that the program continues to prompt the user until they choose to quit (option 4).

Sample Test Cases

Test case 1

1. Add
2. Remove
3. Display
4. Quit
Enter choice: 1
Integer: 11
List after adding: [11]
1. Add
2. Remove

listOps.py

1 def main():
2 lst = []
3 while True:
4 print("1. Add")
5 print("2. Remove")
6 print("3. Display")
7 print("4. Quit")
8
9 choice = input("Enter choice: ")
10
11 if choice == "1":
12 try:
13 num = int(input("Integer: "))
14 lst.append(num)
15 print("List after adding:", lst)
16 except ValueError:
17 print("Invalid input")
18
19 elif choice == "2":
20 if not lst:
21 print("List is empty")

Average time: 0.047 sMaximum time: 0.073 s2 out of 2 shown test case(s) passed1 out of 1 hidden test case(s) passed
Test case 1Expected output: 1. Add, 2. Remove, 3. Display, 4. Quit, Enter choice: 1, Integer: 11Actual output: 1. Add, 2. Remove, 3. Display, 4. Quit, Enter choice: 1, Integer: 11

TerminalTest Cases

CODETANTRA

HomeLearn Anywhere

202501050057@mitaoe.ac.inSupportLogout

Update ProfileChange PasswordSUBMIT

2.1.2. Dictionary Operations

Write a Python program to perform insertion, update, deletion, and traversal operations on a dictionary. An initial dictionary containing 10 predefined records is already given in the program.

Operations to be Performed:
1. Insertion – Insert a new key-value pair into the dictionary using user input.
2. Update – Update the value of an existing key using user input.
3. Deletion – Delete a specified key from the dictionary using user input.
4. Traversal – Traverse the final dictionary and display all key-value pairs.

Input and Output Format:
1. Read an integer representing the key to be inserted and a string representing its value. Insert this new key-value pair into the dictionary and display the dictionary after insertion.
2. Read an integer representing the key to be updated and a string representing the new value. Update the value of the specified key (only if it exists) and display the dictionary after the update.
3. Read an integer representing the key to be deleted. Delete the specified key from the dictionary (only if it exists) and display the dictionary after deletion.
4. Finally, traverse the dictionary and display all key-value pairs.

The program should also display the original dictionary before performing any operations. Each output should be printed with appropriate messages.

Note:

- All operations must be performed using dictionary methods.
- Perform deletion only if possible; leave the dictionary unchanged.
- Refer to the visible test cases for better understanding and strictly match with the input/outputs.

Sample Test Cases

DictOper...

1 Initial dictionary with 10 predefined records:
2 student = {
3 1: "Amit",
4 2: "Riya",
5 3: "Kiran",
6 4: "Neha",
7 5: "Arjun",
8 6: "Pooja",
9 7: "Rahul",
10 8: "Sneha",
11 9: "Vikram",
12 10: "Anjali"
13 }
14 print("Original Dictionary:", student)
15 key1 = int(input())
16 value = input()
17 student[key1] = value
18 print("After Insertion:", student)
19 key2 = int(input())
20 value = input()
21 student[key2] = value

Average time: 0.049 sMaximum time: 0.090 s2 out of 2 shown test case(s) passed2 out of 2 hidden test case(s) passed
Test case 1Expected output: Original Dictionary: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}, After Insertion: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}Actual output: Original Dictionary: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}, After Insertion: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}

TerminalTest Cases

CODETANTRA

Home

Learn Anywhere

202501050057@mitaoe.ac.inSupportLogout

2.2.1. Linear search Technique

03:02

🔍

📄

🔗

🔧

Write a program to check whether the given element is present or not in the array of elements using linear search.

Input format:

- The first line of input contains the array of integers which are separated by space
- The last line of input contains the key element to be searched

Output format:

- If the element is found, print the index. If the element found multiple times, print the starting index
- If the element is not found, print **Not found**.

Sample Test Case:

Input:

```
1 2 3 4 3 5 6
3
```

Output:

```
2
```

Sample Test Cases

+

CTP1709...

🔍

📄

🔗

🔧

```
1
2 array = list(map(int, input().split()))
3
4 key = int(input())
5
6 found_index = -1
7 for i in range(len(array)):
8     if array[i] == key:
9         found_index = i
10        break
11
12 # Output the result
13 if found_index != -1:
14     print(found_index)
15 else:
16     print("Not found")
17
```

Average time

0.00s

🔍

Maximum time

0.00s

🔍

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1

🔍

🔍

🔍

Expected output

0 1 2 3 4 5 6

3

Actual output

0 1 2 3 4 5 6

3

Test case 2

🔍

🔍

🔍

Expected output

2

Actual output

2

Terminal

Test cases

PREV

RESET

SUBMIT

NEXT

CODETANTRA

Home

Learn Anywhere

202501050057@mitaoe.ac.inSupportLogout

2.2.2. Captain of the Team

02:20

🔍

📄

🔗

🔧

You are provided with the heights of 11 cricket players (in centimeters). Your task is to identify the tallest player, who will be selected as the captain of the team.

Input Format:

The first line of input will contain 11 integers, each representing the height of a player (in centimeters), each separated by a space.

Output Format

The output should be the height (in centimeters) of the tallest player.

Sample Test Cases

Test case 1

```
174 169 185 156 174 191 195 198 187 172 160
```

191

captainof...

🔍

📄

🔗

🔧

```
1 #Read the heights of the 11 players
2 heights = list(map(int, input().split()))
3
4 #Find the maximum height
5 tallest = max(heights)
6
7 #Output the tallest player's height
8 print(tallest)
9
```

Average time

0.00s

🔍

Maximum time

0.00s

🔍

1 out of 1 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1

🔍

🔍

🔍

Expected output

174 169 185 156 174 191 195 198 187 172 160

191

Actual output

174 169 185 156 174 191 195 198 187 172 160

191

Terminal

Test cases

PREV

RESET

SUBMIT

NEXT