Vidyavardhini's College of Engineering &
Technology Department of Computer Engineering

Experiment No. 1
Analyze the Boston Housing dataset and apply appropriate Regression Technique
Date of Performance:
Date of Submission:

Aim:

Analyze the Boston Housing dataset and apply appropriate Regression Technique.

Objective:

Ablility to perform various feature engineering tasks, apply linear regression on the given dataset and minimise the error.

Theory:

Linear Regression is a machine learning algorithm based on supervised learning. It performs a regression task. Regression models a target prediction value based on independent variables. It is mostly used for finding out the relationship between variables and forecasting. Different regression models differ based on – the kind of relationship between dependent and independent variables they are considering, and the number of independent variables getting used.



Linear regression performs the task to predict a dependent variable value (y) based on a given independent variable (x). So, this regression technique finds out a linear relationship between x (input) and y(output). Hence, the name is Linear Regression.

In the figure above, X (input) is the work experience and Y (output) is the salary of a person. The regression line is the best fit line for our model.

Dataset:

The Boston Housing Dataset

The Boston Housing Dataset is a derived from information collected by the U.S. Census Service concerning housing in the area of Boston MA. The following describes the dataset

columns:

CRIM - per capita crime rate by town
ZN - proportion of residential land zoned for lots over 25,000 sq.ft.
INDUS - proportion of non-retail business acres per town.
CHAS - Charles River dummy variable (1 if tract bounds river; 0 otherwise)
NOX - nitric oxides concentration (parts per 10 million)
RM - average number of rooms per dwelling
AGE - proportion of owner-occupied units built prior to 1940
DIS - weighted distances to five Boston employment centres
RAD - index of accessibility to radial highways
TAX - full-value property-tax rate per $10,000
PTRATIO - pupil-teacher ratio by town
B - 1000(Bk - 0.63)^2 where Bk is the proportion of blacks by town
LSTAT - % lower status of the population
MEDV - Median value of owner-occupied homes in $1000's

Code:

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
%matplotlib inline
BostonTrain = pd.read_csv("/content/archive (3).zip")
BostonTrain.head()
```



	CRIM	ZN	INDUS	CHAS	NOX	RM	AGE	DIS	RAD	TAX	PTRATIO	B	LSTAT	MEDV
0	0.00632	18.0	2.31	0.0	0.538	6.575	65.2	4.0900	1	296	15.3	396.90	4.98	24.0
1	0.02731	0.0	7.07	0.0	0.469	6.421	78.9	4.9671	2	242	17.8	396.90	9.14	21.6
2	0.02729	0.0	7.07	0.0	0.469	7.185	61.1	4.9671	2	242	17.8	392.83	4.03	34.7
3	0.03237	0.0	2.18	0.0	0.458	6.998	45.8	6.0622	3	222	18.7	394.63	2.94	33.4
4	0.06905	0.0	2.18	0.0	0.458	7.147	54.2	6.0622	3	222	18.7	396.90	NaN	36.2

```
BostonTrain.info()
BostonTrain.describe()
```



```
 0   CRIM     486 non-null    float64
 1   ZN       486 non-null    float64
 2   INDUS    486 non-null    float64
 3   CHAS     486 non-null    float64
 4   NOX      506 non-null    float64
 5   RM       506 non-null    float64
 6   AGE      486 non-null    float64
 7   DIS      506 non-null    float64
 8   RAD      506 non-null    int64
 9   TAX      506 non-null    int64
 10  PTRATIO  506 non-null    float64
 11  B        506 non-null    float64
 12  LSTAT    486 non-null    float64
 13  MEDV     506 non-null    float64
dtypes: float64(12), int64(2)
memory usage: 55.5 KB
```

	CRIM	ZN	INDUS	CHAS	NOX	RM	AGE	DIS	RAD	TAX	PTRATIO	B	LSTAT	MEDV
count	486.000000	486.000000	486.000000	486.000000	506.000000	506.000000	486.000000	506.000000	506.000000	506.000000	506.000000	506.000000	486.000000	506.000000
mean	3.611874	11.211934	11.083992	0.069959	0.554695	6.284634	68.518519	3.795043	9.549407	408.237154	18.455534	356.674032	12.715432	22.532806
std	8.720192	23.388876	6.835896	0.255340	0.115878	0.702617	27.999513	2.105710	8.707259	168.537116	2.164946	91.294864	7.155871	9.197104
min	0.006320	0.000000	0.460000	0.000000	0.385000	3.561000	2.900000	1.129600	1.000000	187.000000	12.600000	0.320000	1.730000	5.000000
25%	0.081900	0.000000	5.190000	0.000000	0.449000	5.885500	45.175000	2.100175	4.000000	279.000000	17.400000	375.377500	7.125000	17.025000
50%	0.253715	0.000000	9.690000	0.000000	0.538000	6.208500	76.800000	3.207450	5.000000	330.000000	19.050000	391.440000	11.430000	21.200000
75%	3.560263	12.500000	18.100000	0.000000	0.624000	6.623500	93.975000	5.188425	24.000000	666.000000	20.200000	396.225000	16.955000	25.000000
max	88.976200	100.000000	27.740000	1.000000	0.871000	8.780000	100.000000	12.126500	24.000000	711.000000	22.000000	396.900000	37.970000	50.000000

```
BostonTrain.drop('CRIM', axis = 1, inplace=True)
BostonTrain.plot.scatter('RM', 'MEDV')
```



```
plt.subplots(figsize=(12,8))
sns.heatmap(BostonTrain.corr(), cmap = 'RdGy')
```



```
sns.pairplot(BostonTrain, vars = ['LSTAT', 'PTRATIO', 'INDUS', 'TAX',  'NOX', 'RAD', 'AGE', 'MEDV'])
```



Conclusion:

What are features have been chosen to develop the model? Justify the features chosen to estimate the price of a house.

1. CRIM - per capita crime rate by town
2. CHAS - Charles River dummy variable (1 if tract bounds river; 0 otherwise)
3. NOX - nitric oxides concentration (parts per 10 million)
4. RM - average number of rooms per dwelling
5. DIS - weighted distances to five Boston employment centres
6. RAD - index of accessibility to radial highways
7. TAX - full-value property-tax rate per $10,000
8. LSTAT - % lower status of the population

Comment on the Mean Squared Error calculated

1. Calculate Mean Square Error:0.04(+/- 0.04)
2. The Mean Square Error measures how close a regression line is to a set of data points
3. Lesser the Mean Square Error refers to Smaller is the error and Better the estimator