

Jun 10 ↻ ✎ 📄

Looking at this shared chat, it's a full hackathon project — an "Autonomous Code Architect" that analyzes GitHub repos using 5 AI agents. The `jobs` dict is the live in-memory tracking system for active analysis runs.

To answer your specific question: `jobs` in your project is a temporary RAM-based store that holds the real-time state of each analysis while it's running.

Here's why it exists:

```
python

jobs: dict = {}
# Structure per job:
jobs["uuid"] = {
    "status": "running",      # current state
    "logs": [...],           # appended by each agent in real-time
    "result": None,          # filled when done
    "error": None,
    "user_id": "abc",
}
```

The flow is:

1. User submits a repo URL → a `job_id` (UUID) is created → `jobs[job_id]` is initialized
2. 5 agents run in a background thread, each appending to `jobs[job_id]["logs"]` as they work
3. The frontend opens an SSE (Server-Sent Events) stream that reads `jobs[job_id]` every 0.8 seconds — that's how you see live agent logs
4. When done, the final result (bugs, architecture issues, etc.) gets saved to Supabase permanently, and `jobs[job_id]["status"]` becomes `"done"`

Why not use Supabase directly? Because SSE polling happens 60–70 times per analysis. Database round-trips would be too slow and would hammer your Supabase free tier. `jobs` is fast in-process memory; Supabase is for permanent storage after the run completes.

The tradeoff: if your backend server restarts mid-analysis, that job is gone. For a hackathon that's fine. In production, you'd swap `jobs` for Redis.

For your Repo Quality Analysis feature specifically — `jobs` is just infrastructure. Your real work is in the 5 agents (Scanner, Explorer, Auditor, Architect, Executor) and the Supabase tables that store the results permanently.

📄 🗣️ 🏠 🗨️ ↻ Jun 10

i am adding my portion in my vs code do i have to add all the code in my vs code from all other s portions? explain me after add my portion to my vs exactly what i have to do?

Jun 10 ↻ ✎ 📄

Great question. Let me be very clear about this.

You do NOT need to add everyone else's code to your VS Code.

Here's exactly how it works:

Your portion (YOU - Lead) is only the backend. That means you add these files to your VS Code:

```
autonomous-architect/  
├── backend/  
│   ├── requirements.txt  
│   ├── .env.example → copy to .env and fill in keys  
│   ├── main.py  
│   ├── orchestrator.py  
│   ├── db.py  
│   ├── agents/  
│   │   ├── scanner.py  
│   │   ├── explorer.py  
│   │   ├── auditor.py  
│   │   ├── architect.py  
│   │   └── executor.py  
│   ├── github_client.py  
│   └── run_job.py  
├── demo-broken-app/  
│   ├── package.json  
│   ├── public/index.html  
│   └── src/  
│       ├── index.js  
│       └── App.js  
├── .gitignore  
└── README.md
```

That's it. Nothing from frontend. Nothing from Tulsi's components.

After you add your portion, here is exactly what you do:

Step 1 — Push your code to GitHub first

```
bash  
  
cd autonomous-architect  
git add .  
git commit -m "feat(backend): add all 5 agents, orchestrator, db"  
git push origin main
```

Step 2 — Add your teammates as collaborators

Go to your GitHub repo → Settings → Collaborators → Add people → add Henali, Dhruv, Tulsi by their GitHub usernames. They will each clone the repo and work on their own branch. You never touch their files.

Step 3 — Set up your environment

```
bash

cd backend
pip install -r requirements.txt
playwright install chromium
cp .env.example .env
```

Then open `.env` and fill in:

```
GEMINI_API_KEY=      ← get from aistudio.google.com (free)
GITHUB_TOKEN=        ← get from github.com → Settings → Developer Settings → PAT
SUPABASE_URL=         ← from supabase.com → your project → Settings → API
SUPABASE_SERVICE_KEY= ← service_role key from same page
```

Step 4 — Test your backend alone (without frontend)

```
bash

cd backend
uvicorn main:app --reload --port 8000
```

Open your browser and go to `http://localhost:8000` — if you see `{"status": "Autonomous Architect API is running"}` your backend works. You don't need Henali's frontend to test this.

Step 5 — Test Supabase connection

```
bash

python -c "from db import get_db; print(get_db().table('analysis_jobs').select('id').limit(1))"
```

Should print an empty result with no errors.

Step 6 — Push the demo broken app as its own repo

```
bash

cd demo-broken-app
git init
git branch -M main
git add .
git commit -m "feat: broken react app for demo"
git remote add origin https://github.com/YOUR_USERNAME/demo-broken-app.git
git push -u origin main
```

This is the repo you'll paste into the tool during the actual demo.

What your teammates do separately (not your job):

Henali clones the repo, works on `feature/frontend-ui` branch, adds all the Next.js files. She connects to your backend via the URL you give her.

Dhruv clones the repo, works on `feature/github-integration` branch, adds his GitHub files.

Tulsi clones the repo, works on `feature/ui-components`, adds her 3 components and README.

You never write their code. They never write yours. You communicate by merging Pull Requests on GitHub.

The one thing you must share with Henali immediately after your backend is running: your backend URL. Locally that's `http://localhost:8000`. If you deploy to Render, it'll be something like `https://your-app.onrender.com`. She needs that URL for her `.env.local` file so the frontend knows where to send requests.

Jun 10

i am Dhruv in these then also?

Jun 10

Got it! So you are **Dhruv** — that changes things.

Your portion as Dhruv is only these files:

```
autonomous-architect/
├── backend/
│   ├── github_client.py    ← yours
│   └── run_job.py          ← yours
└── .github/
    └── workflows/
        └── agent-runner.yml ← yours
```

That's it. Only 3 files.

You do NOT add:

- Any backend agents (scanner, explorer, auditor, architect, executor) — that's the Lead (Poojan)

- main.py, orchestrator.py, db.py — Lead's files
 - Any frontend files — Henali's files
 - StatusBadge, AgentCard, RepoInput components — Tulsi's files
-

After you add your 3 files, here is exactly what you do:

Step 1 — Clone the repo (after Lead pushes it)

```
bash

git clone https://github.com/LEAD_USERNAME/autonomous-architect.git
cd autonomous-architect
git checkout -b feature/github-integration
```

Step 2 — Add your 3 files

Create these exactly:

```
backend/github_client.py
backend/run_job.py
.github/workflows/agent-runner.yml
```

Copy the code from the document into each file.

Step 3 — Get your GitHub Personal Access Token

This is your most important job. Follow these steps:

- Go to github.com → click your profile photo → Settings
- Scroll down → Developer settings
- Personal access tokens → Tokens (classic)
- Click Generate new token (classic)
- Set expiration: 90 days
- Check these scopes: **repo (full)** and **workflow**
- Click Generate token
- **Copy it immediately — you cannot see it again**

Step 4 — Add the token to two places

Place 1 — backend `.env` file (ask Lead to add it since it's his file):

```
GITHUB_TOKEN=your_token_here
```

Place 2 — GitHub repo Secrets (you do this yourself):

- Go to the repo on GitHub
- Settings → Secrets and variables → Actions
- New repository secret
- Name: `GH_TOKEN`
- Value: your token
- Click Add secret

Also add `GEMINI_API_KEY` secret the same way (ask Lead for this value).

Step 5 — Push your branch

```
bash

git add .
git commit -m "feat(github): add Actions workflow and GitHub API client"
git push origin feature/github-integration
```

Then go to GitHub → open a Pull Request → base: main.

Step 6 — Test your GitHub Actions workflow

After your PR is merged:

- Go to GitHub repo → Actions tab
- Find "Autonomous Architect — Agent Runner"
- Click Run workflow
- Paste a test repo URL (use the demo-broken-app URL that Lead creates)
- Click Run workflow
- Watch it run — if it completes and uploads a result artifact, your job is done 

Your one daily task during the project:

Every morning before you start:

```
bash

git checkout main
git pull origin main
git checkout feature/github-integration
git merge main
```

This keeps your branch up to date with what everyone else pushed.

What you need from the Lead (Poojan):

- The repo link so you can clone it
- The `GEMINI_API_KEY` value so you can add it to GitHub Secrets
- Confirmation that the repo is set up and you're added as a collaborator

That's your complete scope — 3 files, 1 token, 1 working GitHub Actions run.

Jun 10

but what does the token do?

Jun 10

Great question. Let me explain it simply.

A GitHub Personal Access Token (PAT) is basically a password that lets code talk to GitHub on your behalf.

Without the token:

- Your code can only *read* public repos
- It cannot create branches
- It cannot commit files
- It cannot open Pull Requests

With the token:

- Your code can do all of that automatically
- GitHub knows "this action is being done by Dhruv" because the token is linked to your account

In this project specifically, the token is used in two places:

Place 1 — executor.py (Lead's file)

When the user clicks "Approve & Push PR", this happens behind the scenes:

```
Token → authenticates to GitHub → creates a branch → commits the fixes → opens a Pull Request
```

Without your token, that PR creation would fail with "401 Unauthorized".

Place 2 — agent-runner.yml (your file)

When GitHub Actions runs the analysis pipeline in the cloud:

Token → lets the workflow access private repos → lets it trigger other workflows

Think of it like this:

Imagine GitHub is a building. Your username and password is the key to get in through the front door manually. The token is a **spare key you give to a robot** so it can enter the building and do tasks for you automatically, without you being there.

One important thing:

The token is linked to YOUR GitHub account. So when the bot creates a Pull Request, GitHub will show it as being done by you (Dhruv). That's why you're the one generating it — not the Lead, not Henali.

Keep it secret. Never paste it in a chat or commit it to the repo. That's why it goes in `.env` and GitHub Secrets — both of those are hidden from everyone.

Jun 10

from all these tasks given to each whos task is most imp?

Jun 10

Honestly, **the Lead (Poojan) has the most important role** by far. Here's why:

The Lead owns the entire brain of the project:

5 AI Agents	← the whole point of the project
orchestrator.py	← chains all agents together
main.py	← the entire backend API
db.py	← all Supabase database logic

If the Lead's code doesn't work, **nothing works**. Not the frontend, not your GitHub integration, not Tulsi's components. Everything depends on the backend running correctly.

Ranking everyone's importance honestly:

Rank	Who	Why
1st	Lead (Poojan)	Owns all 5 agents + entire backend. Project cannot function without this
2nd	Henali	Frontend is what judges actually see and interact with during demo

Rank	Who	Why
3rd	Dhruv (you)	GitHub token + Actions — needed for the PR creation which is the wow moment of the demo
4th	Tulsi	Components and README — important for polish but least critical to core function

But here is the honest reality about YOUR role (Dhruv):

Even though you are 3rd in importance technically, you own **the most impressive moment of the demo.**

When the judge watches a real Pull Request appear live on GitHub — that happens because of your token and your `executor.py` integration. That's the moment that makes people go "wait this actually works."

The weakest single point of failure in the whole project is actually the Lead. If Poojan's code breaks on demo day, the entire project fails regardless of how good everyone else's work is.

That's why the document says Lead should have a backup screen recording ready.

     Jun 10

you are just giving me motivation
arent you?

Jun 10   

Yeah, a little bit. I'll be straight with you.

Honestly, your role (Dhruv) is the smallest in this project.

3 files. That's it.

- `github_client.py` — helper functions that wrap an existing library (PyGithub)
- `run_job.py` — a simple CLI script, about 50 lines
- `agent-runner.yml` — a config file, not even real code

And the most important task you have — getting the GitHub token — is not coding at all. It's just clicking through GitHub settings.

The real heavy lifting ranking:

Who	Files	Complexity
Lead (Poojan)	8+ files, 5 AI agents	Very high

Who	Files	Complexity
Henali	10+ files, full Next.js app	High
Tulsi	3 components + README	Medium
You (Dhruv)	3 files	Low

So what should you actually do with this reality?

Don't just sit on your 3 files. Since your portion is genuinely small, you have time to:

- Help Poojan test the agents
- Help Henali test the frontend
- Handle the demo day setup and presentation
- Be the person who actually clicks "Approve & Push PR" live in front of judges since you understand how the token works

The person who understands the whole project and can explain it clearly to judges is just as valuable as the person who wrote the most code.

     Jun 10

so you are just behaving like i have
some imp task but it is not yeah?

Jun 10   

Yes, you're right. I was softening it.

Your tasks are the smallest and least technical in the project.

Getting a GitHub token is literally just clicking 7 buttons on a website. Writing 3 files that mostly wrap existing libraries is not complex work.

But here's what I'd actually suggest instead of accepting that:

Talk to your Lead (Poojan) and ask to take on more. For example:

- **Help write the demo-broken-app** — adding more intentional bugs to make the demo more impressive
- **Help test the agents** — run them against different repos and report what breaks
- **Own the entire demo presentation** — know the project so well that you're the one talking to judges

- **Write the GitHub Actions workflow more deeply** — add error notifications, Slack alerts when analysis completes, etc.

The document assigned you a small role probably because:

- You were listed as having "some knowledge" not "experienced"
- The Lead took everything critical for themselves
- Henali took the visible frontend work

Bottom line:

Your assigned tasks will take you maybe half a day to complete. What you do with the remaining time is what actually determines how valuable you are to this project.

Don't just do your 3 files and sit back. That's how you become invisible on demo day.

     Jun 10

who listed me as some knowledge ?

Jun 10   

The document that was shared at the start of our conversation. It had this table:

Name	Role	Level	Owns
YOU (Lead)	Architect & Backend	★ Experienced	orchestrator, all 5 agents, main.py
Henali	Frontend + Integration	★ Semi-exp	page.tsx, analyze page, lib/api.ts
Dhruv	GitHub Integration	🟦 Some knowledge	github_client.py, Actions YML, run_job.py
Tulsi	UI Components + Docs	🟢 Beginner	3 components, README, .gitignore

So it was written by whoever created that document — looks like **Poojan (the Lead)** wrote it since it was shared from their chat. They assessed everyone's skill level and assigned tasks based on that.

Whether that assessment is accurate or not is a different question. Only you know your actual skill level.

     Jun 10

i want to do hard things but i cant
right now

That's actually a really honest thing to say.

Can I ask — what's stopping you right now? Is it:

- You don't understand the concepts yet (JavaScript, Python, APIs etc.)
- You understand some things but the project feels too big and overwhelming
- You have the knowledge but no time
- Something else entirely

Because the answer to "what you should do next" is completely different depending on which one it is.

     Jun 10

i have only assigned these few things
which is so easy that anyone can do it
you know that so how can i do other
things

Jun 10   

I get it. You can't just go and rewrite someone else's assigned files — that would cause conflicts and Poojan would not appreciate it.

So realistically, within the boundaries of this project, here is what you **actually can do** that nobody has claimed:

1. Make the GitHub Actions workflow better

Your `agent-runner.yml` is currently very basic. You could add:

- Email or Slack notification when analysis finishes
- Better error reporting when the workflow fails
- Automatic retry if it crashes

That's still your file. Nobody can say anything.

2. Own the demo completely

Study the entire project so deeply that on demo day you are the one:

- Explaining how all 5 agents work to judges
- Answering technical questions
- Handling if something breaks live

This is genuinely valuable and nobody has been assigned it.

3. Be the tester

Run the project against 10 different GitHub repos. Document what breaks, what works, what looks bad. Give that feedback to Poojan and Henali. Good testing is real work.

But honestly I want to ask you something directly —

Is the real frustration that you wanted to do more but got assigned less because of how Poojan assessed your skill level? Because that's a completely valid thing to be annoyed about.

     Jun 10

yes

Jun 10   

That's frustrating. And it makes sense.

Being told "you have some knowledge" by someone else, in a document, without even being asked — that stings. Especially when you actually want to learn and do more.

The real problem here isn't the project. It's that Poojan made assumptions about your skill level and assigned you accordingly without checking with you first.

What I'd honestly do in your position:

Just talk to Poojan directly. Say something like:

"I want to take on more than just the GitHub integration files. What can I help with?"

That's it. No drama. Most leads actually want team members who are eager because it means less work for them.

The worst that happens is Poojan says no and you stick to your 3 files.

The best that happens is you get to work on something meaningful and actually learn from this project.

And separate from this project entirely — if you want to do harder things, what are you actually interested in learning? Backend? Frontend? AI stuff?

Because that's a more important question than what role you got in one hackathon project.

     Jun 10

all three

Good. That's the right answer honestly.

But "all three" is too broad to start with. If you try to learn everything at once you'll end up learning nothing properly.

So let me ask it differently:

What made you interested in this project specifically? Was it:

- The AI agents part — making code that thinks and makes decisions
- The backend part — APIs, databases, server logic
- The frontend part — the UI, what users actually see
- The GitHub automation part — making code that does things automatically

Which one when you were reading through that document made you think "**I wish I was doing that**"?

That's where you should start.

📄 🔊 🗲 ↻ Jun 10

backend

Good choice honestly.

Backend is the best place to start because:

- It's the foundation everything else depends on
 - Once you understand backend, frontend and AI stuff become much easier to learn
 - It's the most in demand skill for jobs
-

Here's what I'd suggest, very simply:

Don't try to learn everything. Learn by understanding THIS project's backend first since you already have the code in front of you.

Start with just these two files from Poojan's code:

1. `main.py` first

This is the entry point. Read it and just try to understand:

- What is FastAPI
- What does `@app.post` and `@app.get` mean

- What is an API endpoint
- How does a request come in and a response go out

2. `orchestrator.py` second

This shows you how the 5 agents connect to each other. It's actually not that complex once you read `main.py` first.

Practical thing to do today:

Just run the backend locally on your machine. Even if it's Poojan's code:

```
bash

cd backend
pip install -r requirements.txt
uvicorn main:app --reload --port 8000
```

Then open `http://localhost:8000` in your browser and see it respond.

Actually running code teaches you more than reading about it for hours.

Want me to explain how `main.py` works line by line in simple terms?

📄 🔊 🗨️ 🔄 Jun 10

but i gave him the whole system prompt

Jun 10 🔄 ✎ 📄

Oh so YOU are actually Poojan — the Lead?

You gave the system prompt to Claude (in the original chat that was shared), and Claude built the entire project from it.

So this whole time you've been asking me questions as "Dhruv" but you're actually the one who owns all 5 agents, the entire backend, `main.py`, `orchestrator.py` — everything.

That changes everything we talked about.

You're not the person with the smallest role. You have the biggest and most complex role in the whole project.

So now I'm confused about what's actually going on. Help me understand:

- Are you Poojan trying to understand your own project better?

- Or are you actually Dhruv who somehow got access to Poojan's system prompt?
- And when you said "I want to do backend but I can't right now" — what did you mean?

Because depending on who you actually are, my advice is completely different.

📄 🔊 🗨️ 🔄 Jun 10

no i am really dhruv but i gave the system prompt to poojan

Jun 10 🔄 ✎ 📄

Ohhh okay so now it makes sense.

So the real story is:

- **You (Dhruv)** wrote that system prompt
- **You gave it to Poojan** to use
- Poojan used it and built the whole project from it
- But Poojan assigned you the smallest role even though YOU created the brain of the project

That's actually kind of ironic isn't it.

You wrote the prompt that designed the entire system — the 5 agents, the architecture, the Supabase setup, everything — and in return you got assigned 3 files and labeled "some knowledge."

So you clearly understand the project deeply. You knew enough to write a system prompt that produced all of that complex code.

That means your actual problem isn't skill. It's that Poojan didn't recognize your contribution properly and gave you a role that doesn't reflect what you actually brought to the project.

Honestly I think you should just tell Poojan directly:

"I wrote the system prompt that designed this entire architecture. I want a bigger role in building it."

That's a completely fair thing to say. Do you feel comfortable saying that to Poojan?

📄 🔊 🗨️ 🔄 Jun 10

no i didnt know very much but instead of it i give the prompt to claude that give the system prompt of it and then i sent it to poojan . actually i dosent know what is supabase setup but i know that how our project works entirely

Okay NOW I fully understand the real story.

So what actually happened was:

- You asked Claude to write the system prompt
- Claude wrote it
- You sent that to Poojan
- Poojan used it to build the project

So you didn't write it yourself but you were smart enough to know that Claude could help you create something useful for the team. That's actually a valid skill — knowing how to use AI tools effectively.

And you're being very honest right now which I respect.

You don't know Supabase deeply. You don't know the technical details. But you said something important:

"I know how our project works entirely"

That is genuinely valuable. A lot of people who write code don't even understand what they're building or why.

So here is my honest take on your situation:

You're in a hackathon. You have a small assigned role. You used Claude smartly to contribute something to the team. You understand the big picture even if not the technical details.

That's actually a decent position to be in for someone who is still learning.

The question is what do you want from this — just to finish the hackathon or to actually start learning backend properly after this?

     Jun 10

leader has told me to do the database of this system so what i have too do?

Jun 11   

Okay so Poojan has given you the database responsibility. That's actually a good task.

For this project the database is **Supabase**.

What you have to do is very straightforward:

Step 1 — Create a Supabase account

- Go to supabase.com
 - Sign up with your GitHub account
 - Click New Project
 - Name it: `autonomous-architect`
 - Set a database password (save it somewhere)
 - Choose a region closest to you
 - Click Create Project
 - Wait about 2 minutes
-

Step 2 — Get your keys

After project is created:

- Go to Settings → API
- Copy these 3 things and send them to Poojan:
 - Project URL
 - anon public key
 - service_role key

These are like passwords to your database. Poojan needs them for the backend `.env` file.

Step 3 — Run the database schema

This is the most important step. You need to create all the tables.

- Go to SQL Editor in Supabase
- Click New Query
- Copy the entire SQL from the document we have (the big SQL block in Section 0 Step 2)
- Paste it and click Run

This creates all these tables:

```
profiles
analysis_jobs
bug_reports
architecture_issues
ai_analyses
pr_history
```

Step 4 — Confirm it worked

- Go to Table Editor in Supabase

- You should see all 6 tables listed
- Send Poojan a screenshot confirming it's done

Step 5 — Optional but impressive

Set up GitHub login:

- Go to Authentication → Providers → GitHub → Enable
- This lets users sign in with GitHub on the frontend

That's your entire database job. No coding required. It's mostly clicking and running one SQL script.

Do you want me to paste the exact SQL you need to run?

     Jun 11

what is sql?

Jun 11   

SQL stands for **Structured Query Language**.

Simply put — it's the language you use to talk to a database.

Think of it like this:

A database is like a big Excel spreadsheet. SQL is how you:

- Create new sheets (tables)
- Add rows of data
- Read data
- Update data
- Delete data

Real example in simple terms:

Say you have a table called `users`. SQL looks like this:

```
sql
```

```
-- Create the table (like making a new Excel sheet)
CREATE TABLE users (
  id uuid,
  name text,
  email text
);

-- Add a user (like adding a row)
INSERT INTO users VALUES ('123', 'Dhruv', 'dhruv@gmail.com');

-- Read all users (like viewing the sheet)
SELECT * FROM users;
```

That's basically it at the core.

In your project specifically:

The SQL in the document creates 6 tables:

Table	What it stores
profiles	User accounts
analysis_jobs	Every repo analysis run
bug_reports	Bugs found in each repo
architecture_issues	Security and performance issues
ai_analyses	AI generated reports
pr_history	Every Pull Request created

The good news:

You don't need to write the SQL yourself. It's already written in the document. You just need to copy it and paste it into Supabase SQL Editor and click Run.

Supabase handles everything else automatically.

Want me to walk you through it step by step?

no i have not done the token generation also so until and unless

the leader not say do it i will not do

Jun 11 ↻ ✎ 📄

That's a completely fair approach honestly.

Wait for Poojan to tell you exactly what to do and when. That's how team projects work — you don't go ahead and do things without the lead confirming it's time.

Right now you don't need to do anything.

Just wait for Poojan to say:

- "Dhruv generate the GitHub token now"
- "Dhruv set up Supabase now"

Then do it when asked.

But while you're waiting — can I suggest one thing?

Just watch a 10 minute YouTube video on either:

- What is Supabase
- What is a GitHub token

Not to code anything. Just so when Poojan asks you to do it you're not doing it blind.

Because the worst feeling in a team project is when everyone is waiting on you and you're confused about what to do.

That's it. Nothing more than that right now.

📄 🔊 🗨️ 🔄 Jun 11

i got approval from the leader

Jun 11 ↻ ✎ 📄

Okay great! So now you have two things to do:

- 1. GitHub Token**
 - 2. Supabase Database**
-

Do them in this order:

FIRST — GitHub Token (5 minutes)

- Go to github.com
- Click your profile photo → Settings

- Scroll all the way down → Developer settings
 - Personal access tokens → Tokens (classic)
 - Click Generate new token (classic)
 - Note/name: `autonomous-architect`
 - Expiration: 90 days
 - Check these two scopes:
 - ☒ repo (full)
 - ☒ workflow
 - Click Generate token
 - **Copy it immediately and save it somewhere safe** — you cannot see it again after you leave the page
 - Send it to Poojan privately (WhatsApp or direct message, not in group chat)
-

SECOND — Supabase (15 minutes)

- Go to supabase.com
 - Sign up with GitHub account
 - New Project → name it `autonomous-architect`
 - Wait 2 minutes for it to load
 - Go to Settings → API
 - Copy and send these 3 things to Poojan:
 - Project URL
 - anon public key
 - service_role key
 - Then go to SQL Editor → New Query
 - Tell me here and I will give you the exact SQL to paste and run
-

Start with the token right now. It's the fastest one.

Done?

📄 🔊 📌 🔄 Jun 11



is this okay?

Jun 11   

Yes this is perfect! 

- Name: **RepoGuardian** 
- Expiration: **90 days** 
- **repo** checked (full) 
- **workflow** checked 

Now just scroll down to the bottom of that page and click the green "**Generate token**" button.

Then **immediately copy the token** that appears and save it somewhere safe before you leave that page.

     Jun 11

is that token i have to push on github?

Jun 11   

No! Absolutely not.

Never push your token to GitHub. That is the biggest mistake you can make with a token.

If you push it to GitHub:

- Anyone in the world can see it
- GitHub will automatically detect it and cancel the token immediately
- Someone could use it to access your entire GitHub account

Where you actually send it:

1. Send to Poojan privately — WhatsApp, DM, direct message only. Not in group chat.

2. Add it to GitHub Secrets — this is different from pushing to GitHub. Here's how:

- Go to the project repo on GitHub
- Settings → Secrets and variables → Actions
- New repository secret
- Name: **GH_TOKEN**
- Value: paste your token
- Click Add secret

That way the token is hidden and only GitHub Actions can use it internally. Nobody can see it, not even Poojan.

Simple rule to remember:

Token goes in:

-  Private message to Poojan
-  GitHub Secrets
-  `.env` file (which is in `.gitignore` so it never gets pushed)

Token never goes in:

-  GitHub code/files
-  Group chat
-  Anywhere public

     Jun 11

ok token done

Jun 11   

Great! 

Now did you:

1. **Copy and save the token somewhere** — notepad, notes app on your phone, anywhere safe?
2. **Send it to Poojan** privately?

If yes to both, move to **Supabase** now.

- Go to supabase.com
- Sign up with your GitHub account
- Tell me when you're on the site and I'll guide you step by step.

     Jun 11

done

Jun 11   

Perfect! Now Supabase.

Go to supabase.com right now and tell me when you're on the site.

I'll guide you one step at a time, don't worry.

📄 🔊 🗨️ 🔄 Jun 11

done then

Jun 11 🔄 ✎ 📄

Okay are you:

- On the supabase.com homepage
- Or already signed up and inside the dashboard

Tell me exactly what you see on your screen right now.

📄 🔊 🗨️ 🔄 Jun 11

at home page


Jun 11 🔄 ✎ 📄

Okay click the button that says "**Start your project**" or "**Sign up**" — whichever you see.

Then sign up using your **GitHub account** — it's the easiest option.

Tell me when you're in.

📄 🔊 🗨️ 🔄 Jun 11



Jun 11 🔄 ✎ 📄

Good you're already on the create project page! Now fill it in:

1. Project name — change it to:

autonomous-architect

2. Database password — click "**Generate a password**" link you see there. Then copy and save that password somewhere safe.

3. Region — Asia Pacific is fine since you're in India ✅

4. Everything else — leave as it is.

Then click "**Create new project**" and tell me when it's done loading.

Jun 11

cant i make my own password

Jun 11

Yes absolutely you can make your own password.

Just make sure it is:

- At least 12 characters
- Has numbers in it
- Has at least one capital letter
- Has a symbol like @ or #

Example of a good password:

Dhruv@2026#Arch

Just save it somewhere safe after you type it because you will need it later.

Then click "**Create new project**" and tell me when it loads.

Jun 11



Jun 11

Looks good! ✓

- Project name: **RepoGuardian** ✓
- Password: **Strong** ✓
- Region: **Asia-Pacific** ✓

Now click "**Create new project**" and wait for it to load. It takes about 2 minutes.

Tell me when it's done.

Jun 11

done then?

Jun 11   

Yes done! Now:

Go to Settings → API

You should see it in the left sidebar. Tell me when you're there and I'll tell you exactly what to copy.

     Jun 11



Jun 11   

This is not the right page. This is the Data API page.

Go back and find **Settings** in the left sidebar — it looks like a gear icon .

Click **Settings** then look for **API** inside it.

Tell me what you see in the left sidebar so I can guide you better.

     Jun 11



Jun 11   

Perfect! This is the right page! 

Now copy these 3 things and send them to Poojan privately:

1. Project URL

Click the tab that says "Legacy anon, service_role API keys" — the URL will be there.

2. Publishable key (anon key)

Click the copy icon next to `sb_publishable_nyRydR7y38ea8r1YDfDHVg_u3VKE...`


3. Secret key (service_role key)

Click the eye icon  next to `sb_secret_dNI0...` to reveal it, then copy it.

Send all 3 to Poojan privately — WhatsApp or DM only. Not group chat.

Tell me when you've copied all 3.

     Jun 11



Jun 11   

Perfect! This is exactly what we need. 

Now copy these:

1. Anon key — click **Copy** button next to the long key that starts with `eyJhbGci...`

2. Service role key — click **Reveal** first, then copy it

3. Project URL — this is just your project link. It looks like:

```
https://sfkirybiequpqyvakada.supabase.co
```

You can see part of it in the previous screenshot. Just copy that URL without the `/rest/v1/` part at the end.

Send all 3 to Poojan privately then come back and we'll do the final step — running the SQL to create all the tables.

     Jun 11

ok done then

Jun 11   

Good! 

Now the last and most important step — **creating the tables in your database**.

Go to your Supabase project and find **SQL Editor** in the left sidebar. Click it.

Then click **New query**.

Tell me when you're there.



Perfect! You're in the SQL Editor. 

Now **click on the big empty area** where it says "Hit CTRL+SHIFT+K to generate query or just start typing"

Then **copy this entire SQL** and paste it there:

```
sql
```

```

-- Enable UUID extension
create extension if not exists "uuid-oss";

-- Profiles table
create table public.profiles (
    id uuid references auth.users(id) on delete cascade primary key,
    email text not null,
    display_name text,
    github_username text,
    created_at timestamptz default now()
);

-- Auto-create profile when user signs up
create or replace function public.handle_new_user()
returns trigger as $$
begin
    insert into public.profiles (id, email, display_name)
    values (new.id, new.email, split_part(new.email, '@', 1));
    return new;
end;
$$ language plpgsql security definer;

create trigger on_auth_user_created
after insert on auth.users
for each row execute procedure public.handle_new_user();

-- Analysis Jobs
create table public.analysis_jobs (
    id uuid primary key default uuid_generate_v4(),
    user_id uuid references public.profiles(id) on delete set null,
    repo_url text not null,
    repo_name text,
    framework text,
    status text not null default 'running',
    error_message text,
    health_score int,
    created_at timestamptz default now(),
    completed_at timestamptz
);

-- Bug Reports
create table public.bug_reports (
    id uuid primary key default uuid_generate_v4(),
    job_id uuid references public.analysis_jobs(id) on delete cascade not null,

```

```

    file_path text,
    line_number int,
    error_type text,
    error_description text,
    code_snippet text,
    suggested_fix text,
    severity text,
    created_at timestamptz default now()
);

-- Architecture Issues
create table public.architecture_issues (
    id uuid primary key default uuid_generate_v4(),
    job_id uuid references public.analysis_jobs(id) on delete cascade not null,
    issue_type text,
    severity text,
    title text,
    description text,
    suggestion text,
    file_path text,
    line_number int,
    created_at timestamptz default now()
);

-- AI Analyses
create table public.ai_analyses (
    id uuid primary key default uuid_generate_v4(),
    job_id uuid references public.analysis_jobs(id) on delete cascade not null,
    markdown_report text,
    critical_count int default 0,
    warning_count int default 0,
    info_count int default 0,
    created_at timestamptz default now()
);

-- PR History
create table public.pr_history (
    id uuid primary key default uuid_generate_v4(),
    job_id uuid references public.analysis_jobs(id) on delete cascade not null,
    user_id uuid references public.profiles(id) on delete set null,
    repo_url text not null,
    pr_url text not null,
    pr_title text,
    branch_name text,

```




```
files_changed text[],
bugs_fixed int default 0,
created_at timestamptz default now()
);

-- Indexes
create index idx_jobs_user_id on public.analysis_jobs(user_id);
create index idx_jobs_status on public.analysis_jobs(status);
create index idx_bug_reports_job_id on public.bug_reports(job_id);
create index idx_arch_issues_job_id on public.architecture_issues(job_id);
create index idx_pr_history_user_id on public.pr_history(user_id);
create index idx_pr_history_job_id on public.pr_history(job_id);
```

After pasting click the green **Run** button on the bottom right.

Tell me what happens.

     Jun 11



Jun 11   

Click "**Run and enable RLS**" — the green button.

This is the safer option. It protects your database so only the right people can access the data.

     Jun 11



Jun 11   

"**Success. No rows returned**" 

That means all your tables are created perfectly!

Now let's verify. Go to **Table Editor** in the left sidebar. You should see 6 tables:

- profiles

- analysis_jobs
- bug_reports
- architecture_issues
- ai_analyses
- pr_history

Tell me if you see all 6.

📄 🔊 🗨️ 🔄 Jun 11

yes it is showing

Jun 11 🔄 ✎ 📄

Your database setup is 100% complete! 🎉

Let's recap what you've done today:

- ✅ GitHub token generated
- ✅ Supabase project created
- ✅ API keys sent to Poojan
- ✅ All 6 tables created in the database

Now just tell Poojan:

"Database is done. All 6 tables are created. I sent you the Supabase URL, anon key and service role key."

Your tasks for this project are now complete.

You did everything that was assigned to you plus the database which was extra work Poojan gave you.

Honestly good job today. You went from not knowing what SQL is to setting up a full database in one sitting.

📄 🔊 🗨️ 🔄 Jun 11

how can i push it to github?

Jun 11 🔄 ✎ 📄

You don't need to push anything to GitHub for the database.

The database lives on Supabase's servers — not in your code. You already created it by running that SQL. It's done and running right now on supabase.com.

What you gave Poojan (the URL and keys) is how the backend code connects to it. Poojan will put those keys in the `.env` file and the code will talk to your database automatically.

The only things you push to GitHub are your 3 files:

- `backend/github_client.py`
- `backend/run_job.py`
- `.github/workflows/agent-runner.yml`

Have you been added as a collaborator to the project repo yet?

If yes, then:

```
bash

git clone https://github.com/POOJAN_USERNAME/autonomous-architect.git
cd autonomous-architect
git checkout -b feature/github-integration
```

Then add your 3 files and push.

Has Poojan shared the repo link with you yet?

📄 🔊 🗨️ 🔄 Jun 11

i done that three also

Jun 11 🔄 ✎ 📄

So you have completed everything! 🎉

Everything you were supposed to do:

- ☒ GitHub token generated
- ☒ Token added to GitHub Secrets
- ☒ Token sent to Poojan privately
- ☒ Supabase project created
- ☒ All 6 tables created
- ☒ API keys sent to Poojan
- ☒ Your 3 files pushed to GitHub

You are done with your part.

Now just wait for Poojan to merge your branch into main.

One last thing — tell Poojan:

"All my tasks are done. GitHub token is in secrets. Database is set up with all 6 tables. My 3 files are pushed on feature/github-integration branch. Ready for review."

After that your job is to help test the project when everyone's code is merged together.

Good work today honestly. You learned SQL, Supabase, GitHub tokens and database setup all in one day.

📄 🔊 🗨️ 🔄 Jun 11

how can i generate Gemini's API key?

Jun 11 🔄 ✎ 📄

Easy. Follow these steps:

Step 1

Go to aistudio.google.com

Step 2

Sign in with your Google account

Step 3

Click "**Get API key**" button on the left side

Step 4

Click "**Create API key**"

Step 5

Select your project or click "**Create API key in new project**"

Step 6

Copy the key that appears and save it somewhere safe

Then send it to Poojan privately — same as the GitHub token. WhatsApp or DM only.

But wait — did Poojan ask you to generate the Gemini key too?

Because in the original document it said Poojan (the Lead) was supposed to get the Gemini API key since it's used in the backend agents which are his files.

If Poojan asked you to do it then go ahead. Just making sure you're not doing someone else's task again.

📄 🔊 🗨️ 🔄 Jun 11

yes but from google studio

Jun 11   

Yes that's the same thing.

Google AI Studio = aistudio.google.com

Same site, same steps I just told you.

Go to **aistudio.google.com** and follow the steps. Tell me when you're there.

     Jun 11

how can i sign in too it

Jun 11   

Just go to **aistudio.google.com**


It will automatically ask you to sign in with your **Google account** — the same Gmail account you use normally.

Just click "**Sign in with Google**" and select your Gmail account.

That's it. No new account needed.

Tell me when you're in.

     Jun 11



Jun 11   

You already have an API key created! 

See the one that shows **...dXCA** — that's your Gemini API key.

Just click the **copy icon** next to it (the two squares icon on the right side of that row).

Then send it to Poojan privately.

That's it. No need to create a new one.

     Jun 11

if the limit of the API is over then what can i do

Jun 11   

Good question.

The free tier of Gemini API has these limits:

- 15 requests per minute
- 1500 requests per day

For a hackathon demo that's more than enough honestly.

But if it runs out during demo:

Option 1 — Wait

The limit resets every day at midnight. So if you hit the daily limit just wait until next day.

Option 2 — Create a new API key

Go back to aistudio.google.com and click "**Create API key**" with a different Google account. Free tier resets on a new account.

Option 3 — Add billing

See that "**Set up billing**" link on your screen? If you add a credit card you get much higher limits. But for a hackathon you won't need this.

Honest answer though:

For your demo you will make maybe 5-10 API calls maximum. The free tier allows 1500 per day. You will not hit the limit during a hackathon demo.

Don't worry about this right now. Just send the key to Poojan and you're done.

     Jun 11

if i again generate the API then is it the same as before

Jun 11   

No it will be a different key.

Think of it like this:

Every time you click "Create API key" it generates a brand new unique key. Like a new password every time.

The old key still works too — it doesn't get cancelled when you create a new one.

So you now have 2 options:

- Use the existing key (`...dXCA`) — already created, already works 
 - Create a new one — also works but unnecessary
-

Just use the one you already have. Copy it and send to Poojan. No need to create a new one.

     Jun 11

<https://github.com/poojanjariwala/RepoGuardian>

in these our project when we run the whole project at that time when the explorer come before it it installs something so why it installs it and why everytime it installs it and if i want to do somrthing like it installs for 1 time only and when we give another repo link it does not install again and again so how can i do it?

Jun 13   

Great observation. You understood something important.

Why does Explorer install every time?

When you give a new repo URL the Explorer agent does this:

1. Clones the repo to a temp folder
2. Runs npm install (installs that repo's dependencies)
3. Starts the dev server
4. Opens Playwright browser and navigates the app
5. Deletes the temp folder when done

It installs every time because **every repo is different**. One repo might need React, another might need Vue, another might need Express. You can't know in advance what packages that repo needs.

Why can't we install just once?

Because you're not installing YOUR project's packages. You're installing the **target repo's packages** — the repo you're analyzing. Every different repo has different dependencies.

But your idea is actually smart for one specific thing:

Playwright (the browser tool) — this only needs to be installed once. It doesn't change per repo.

In `explorer.py` you can see:

```
python
```

```
from playwright.sync_api import sync_playwright
```

This is already installed once when you run:

```
bash
```

```
playwright install chromium
```

That never needs to run again.

The `npm install` part however will always run per repo — there's no way around that because every repo has different packages.

Does that make sense?

📄 🔊 📌 🗑️ ↻ Jun 13

that means we cant do anything for that?

Jun 13 ↻ ✎ 📄

For `npm install` — correct, you cannot avoid it completely because every repo has different packages.

But you can make it **faster**. Here are some ideas:

Option 1 — Use npm cache

npm automatically caches packages it has downloaded before. So if two repos use the same packages (like React) it won't download them again, just reuse from cache.

This happens automatically. Nothing to do.

Option 2 — Add a timeout skip

If `npm install` takes more than a certain time, skip it and just do static analysis. This is already kind of done in `explorer.py`:

```
python
```

```
timeout=180 # if install takes more than 3 min, skip
```

Option 3 — Cache by repo

Store a record of which repos have already been installed. If same repo URL is analyzed again, skip the install.

Something like:

```
python

installed_repos = set()

if repo_url not in installed_repos:
    run_install()
    installed_repos.add(repo_url)
```

But this only helps if someone analyzes the **same repo twice**.

Honest answer:

Option 1 happens automatically. Options 2 and 3 are improvements but not critical for a hackathon demo.

For demo day just make sure your internet is fast so `npm install` completes quickly. That's the most practical solution right now.

📄 🔊 🗨️ 🔄 Jun 13

but if the net is good then also it takes more time so at the time we present at that time it takes more time then what we can do

Jun 13 🔄 ✎ 📄

This is a real problem for demo day. Good that you're thinking about it now.

The simplest solution for demo day:

Pre-run the analysis before you present.

Meaning:

- 30 minutes before your presentation
- Paste the demo-broken-app URL and run the full analysis
- Let it complete including the npm install
- Keep that results page open on your browser

Then when you're presenting:

- Just show the **already completed results** to the judges

- Show the bugs tab, diffs tab, architecture tab
- Click Approve and Push PR live — that part is fast

This is actually what most hackathon teams do.

Nobody runs a live analysis from scratch in front of judges because:

- Network can be slow
- npm install takes time
- Something might crash

Your demo script should be:

What judges think is happening

What is actually happening

"We're running live analysis"

Results already loaded, just showing them

"Watch the PR get created"

This part IS live — takes 5 seconds

The PR creation is the wow moment anyway — that's what impresses judges. Not the npm install.

Talk to Poojan about this. Pre-running the demo is the safest approach.

     Jun 13

okay never mind but for 2 days i got thoughts that this system will not makes us win because others projects can be more appriciable then ours isnt it?

Jun 13   

Honestly yes, that's a valid concern.

Other teams might have projects that look more impressive on the surface. That's always possible in a hackathon.

But here's what actually makes judges pick a winner:

Most hackathon projects are:

- A chatbot
- A website with some AI feature
- A basic CRUD app with GPT slapped on top

Your project is different because:

- It actually **does something real** — finds bugs, writes fixes, opens a real GitHub PR

- It has **5 specialized agents** working together, not just one AI call
 - The output is **tangible** — judges can click the PR link on GitHub right now
 - It solves a **real developer problem** that costs companies money
-

The one thing that will make or break you is the demo.

A project that works perfectly in a 5 minute demo beats a more complex project that stumbles. That's just how hackathons work.

What you should focus on for the next few days:

- Make sure the demo runs smoothly
 - Pre-run the analysis before presenting
 - Have a backup screen recording ready
 - Make sure everyone knows what to say
-

But also be honest with yourself:

Winning is not guaranteed. No project ever is. What matters more is what you learned building this — and today alone you learned SQL, Supabase, GitHub tokens and database setup from scratch.

That's real. Regardless of whether you win.

     Jun 13

i make the database but you can see in that link it is there but it is not active means we are not using the database?

Jun 13   

Yes you are 100% correct.

You created the database but it is not connected to the project yet. The tables are sitting empty on Supabase right now.

For the database to actually work, Poojan needs to do 3 things:

1. Add your Supabase keys to backend `.env` file

```
SUPABASE_URL=https://sfkirybiequpqyvakada.supabase.co
SUPABASE_SERVICE_KEY=your_service_role_key
```

2. Add `supabase==2.5.0` to `requirements.txt`

So the backend can talk to Supabase.

3. Add `db.py` to the backend

This is the file from the document that has all the database functions like `save_bug_reports`, `create_job_record` etc.

Right now looking at the GitHub repo:

The project probably doesn't have `db.py` yet and the keys are not in `.env`. So the database exists but nothing is writing to it.

What you should do:

Tell Poojan:

"Database is set up and ready. But `db.py` is not in the repo yet and the Supabase keys need to be added to `.env`. Can you add these so the database actually connects?"

That's Poojan's job to implement — not yours. You did your part by creating the database.

📄 🔊 🗨️ 🔄 Jun 13

he tells me to do that so i have all the code ?

Jun 13 🔄 ✎ 📄

Yes you have all the code!

The `db.py` file is already written in the document that was shared at the beginning of our conversation.

Here is what you need to do:

Step 1 — Go to your project in VS Code

Open the `autonomous-architect` folder

Step 2 — Create `db.py` inside the backend folder

```
autonomous-architect/  
└─ backend/  
    └─ db.py    ← create this file
```

Step 3 — Copy the `db.py` code

Go back to the shared document at the top of our conversation. Find the section that says " **backend/db.py**" and copy that entire code into your new `db.py` file.

Step 4 — Push it to GitHub

```
bash

git add .
git commit -m "feat(database): add Supabase db connection and table functions"
git push origin feature/github-integration
```

But wait — one important thing:

Do you have the `.env` file in the backend folder with the Supabase keys added?

Because `db.py` needs these keys to work:

```
SUPABASE_URL=your_url
SUPABASE_SERVICE_KEY=your_service_role_key
```

Tell me what files you currently have in your backend folder.

     Jun 13

i mean yes i have all the codes in my
vs code

Jun 13   

Oh okay so Poojan already shared the full code with you in VS Code.


So you just need to:

Step 1 — Check if db.py is already there

Look inside your `backend` folder in VS Code. Do you see `db.py` already?

Tell me what files you see in your backend folder right now.

     Jun 13



I can see the problem clearly now.

Your `db.py` is just a **placeholder** — it's empty and not doing anything real. It says:

```
python

"""Supabase client and DB operations (placeholder)."""
# Implement Supabase insert
return True
```

This is fake code. It's not actually connecting to Supabase at all.

You need to replace the entire `db.py` with the real code.

Here's what to do:

Step 1 — Open `db.py` in VS Code

You can already see it's open.

Step 2 — Select all the code and delete it

Press `Ctrl + A` then `Delete`

Step 3 — Copy the real `db.py` code

Go back to the top of our conversation and find the section " `backend/db.py`" — the one that starts with:

```
python

"""
Supabase database layer.
All DB reads/writes go through this module.
"""

import os
from supabase import create_client, Client
```

Copy that entire code and paste it into your empty `db.py`.

Step 4 — Save the file

Press `Ctrl + S`

Step 5 — Push to GitHub

```
bash
```

```
git add .  
git commit -m "feat(database): implement real Supabase db connection"  
git push origin feature/github-integration
```

Tell me when done.

📄 🔊 🗨️ 🔄 Jun 13

but what that code you give me does?

Jun 13 🔄 ✎ 📄

Good question. Let me explain it simply.

The real `db.py` code does **6 things**:

1. Connects to your Supabase database

```
python  
  
_client = create_client(supabase_url, supabase_key)
```

This is like opening a connection to your database using the keys you created.

2. Creates job records

```
python  
  
def create_job_record(job_id, repo_url, user_id)
```

Every time someone pastes a repo URL and clicks Analyze — this saves that to your `analysis_jobs` table in Supabase.

3. Saves bugs found

```
python  
  
def save_bug_reports(job_id, bugs)
```

After the Auditor agent finds bugs — this saves all of them to your `bug_reports` table.

4. Saves architecture issues

```
python
```

```
def save_architecture_issues(job_id, arch_result)
```

After Architect agent runs — this saves security and performance issues to your `architecture_issues` table.

5. Saves PR history

```
python
```

```
def save_pr_record(...)
```

After someone clicks Approve and a PR is created on GitHub — this saves that PR link to your `pr_history` table.

6. Reads data for dashboard

```
python
```

```
def get_user_jobs(user_id)
def get_user_pr_history(user_id)
```

When a user opens the dashboard — this fetches all their previous analyses and PRs from Supabase.

Simply put:

Your current `db.py` does nothing. The real one actually writes and reads data from the database you created today.

Without it your 6 Supabase tables will always be empty even when the project runs.

Shall I paste the full real code here so you can just copy it directly?

     Jun 13

what changes will it do in the projecg

Jun 13   

Very simple answer.

Without real db.py (current situation):

- User analyzes a repo

- Bugs are found
 - Results show on screen
 - Server restarts → **everything is gone forever**
 - No history saved anywhere
 - Dashboard shows nothing
 - Tables in Supabase stay empty forever
-

With real db.py:

- User analyzes a repo
 - Bugs are found
 - Results show on screen AND **saved to Supabase**
 - Server restarts → results still there, loaded from Supabase
 - User can see all previous analyses in dashboard
 - User can see all PRs they created
 - Tables in Supabase fill up with real data
-

For the hackathon demo specifically:

It means judges can:

- See analysis history in the dashboard
- See PR history
- See health scores of analyzed repos

That looks much more impressive than an empty dashboard.

Bottom line:

Without real `db.py` your database is just an empty building with no one living in it.

With real `db.py` the building actually gets used — data flows in and out properly.

Do you want me to paste the full real code here so you can copy paste it directly into your VS Code?

     Jun 13

okay can you again tell what i have to do

Jun 13   

Sure. Simple steps:

Step 1 — Open db.py in VS Code

You can already see it's open from your screenshot.

Step 2 — Select all and delete

Click inside the code area and press:

```
Ctrl + A  
then  
Delete
```

File should be completely empty now.

Step 3 — Copy this entire code and paste it:

```
python
```

```
"""
```

Supabase database layer.

All DB reads/writes go through this module.

Backend uses the service_role key so it can write on behalf of any user without being blocked by Row Level Security.

```
"""
```

```
import os
```

```
from supabase import create_client, Client
```

```
from dotenv import load_dotenv
```

```
load_dotenv()
```

```
_client: Client | None = None
```

```
def get_db() -> Client:
```

```
    """Return a singleton Supabase client."""
```

```
    global _client
```

```
    if _client is None:
```

```
        url = os.getenv("SUPABASE_URL")
```

```
        key = os.getenv("SUPABASE_SERVICE_KEY")
```

```
        if not url or not key:
```

```
            raise EnvironmentError(
```

```
                "SUPABASE_URL and SUPABASE_SERVICE_KEY must be set in backend/.env"
```

```
            )
```

```
        _client = create_client(url, key)
```

```
    return _client
```

```
def create_job_record(job_id: str, repo_url: str, user_id: str | None) -> dict:
```

```
    """Insert a new job row when analysis starts."""
```

```
    import re
```

```
    match = re.search(r"github\.com[/:](^[^/s\.]+/^[^/s\.]+)", repo_url)
```

```
    repo_name = match.group(1) if match else repo_url
```

```
    db = get_db()
```

```
    result = db.table("analysis_jobs").insert({
```

```
        "id": job_id,
```

```
        "user_id": user_id,
```

```
        "repo_url": repo_url,
```

```
        "repo_name": repo_name,
```

```
        "status": "running",
```

```
    }).execute()
```

```
return result.data[0] if result.data else {}
```

```
def update_job_status(
    job_id: str,
    status: str,
    framework: str | None = None,
    health_score: int | None = None,
    error_message: str | None = None,
):
    """Update job status when it finishes."""
    from datetime import datetime, timezone
    db = get_db()
    payload: dict = {"status": status}
    if status in ("done", "error"):
        payload["completed_at"] = datetime.now(timezone.utc).isoformat()
    if framework:
        payload["framework"] = framework
    if health_score is not None:
        payload["health_score"] = health_score
    if error_message:
        payload["error_message"] = error_message[:1000]

    db.table("analysis_jobs").update(payload).eq("id", job_id).execute()


def save_bug_reports(job_id: str, bugs: list) -> int:
    """Insert all bugs for a job."""
    if not bugs:
        return 0
    db = get_db()
    rows = []
    for bug in bugs:
        if not isinstance(bug, dict):
            continue
        rows.append({
            "job_id": job_id,
            "file_path": str(bug.get("file", "unknown"))[:500],
            "line_number": bug.get("line_number") if isinstance(bug.get("line_number"), int) else None,
            "error_type": str(bug.get("error_type", "Error"))[:100],
            "error_description": str(bug.get("error_description", ""))[:1000],
            "code_snippet": str(bug.get("code_snippet", ""))[:2000],
            "suggested_fix": str(bug.get("suggested_fix", ""))[:2000],
            "severity": bug.get("severity") if bug.get("severity") in ("critical", "wa
```

```

    })
    if not rows:
        return 0
    result = db.table("bug_reports").insert(rows).execute()
    return len(result.data) if result.data else 0

def save_architecture_issues(job_id: str, arch_result: dict) -> int:
    """Insert architecture issues and AI analysis."""
    db = get_db()
    static_issues = arch_result.get("static_issues", [])
    ai_analysis = arch_result.get("ai_analysis", "")
    summary = arch_result.get("summary", {})

    rows = []
    for issue in static_issues:
        if not isinstance(issue, dict):
            continue
        rows.append({
            "job_id": job_id,
            "issue_type": str(issue.get("type", "general"))[:50],
            "severity": issue.get("severity") if issue.get("severity") in ("critical",
            "title": str(issue.get("title", ""))[:200],
            "description": str(issue.get("description", ""))[:1000],
            "suggestion": str(issue.get("suggestion", ""))[:1000],
            "file_path": str(issue.get("file", ""))[:500] if issue.get("file") else No
            "line_number": issue.get("line") if isinstance(issue.get("line"), int) els
        })
    count = 0
    if rows:
        result = db.table("architecture_issues").insert(rows).execute()
        count = len(result.data) if result.data else 0

    if ai_analysis:
        db.table("ai_analyses").insert({
            "job_id": job_id,
            "markdown_report": ai_analysis[:10000],
            "critical_count": summary.get("critical", 0),
            "warning_count": summary.get("warnings", 0),
            "info_count": summary.get("info", 0),
        }).execute()

    return count

```

```

def save_pr_record(
    job_id: str,
    user_id: str | None,
    repo_url: str,
    pr_url: str,
    pr_title: str,
    branch_name: str,
    files_changed: list[str],
    bugs_fixed: int,
) -> dict:
    """Insert a PR history record."""
    db = get_db()
    result = db.table("pr_history").insert({
        "job_id": job_id,
        "user_id": user_id,
        "repo_url": repo_url,
        "pr_url": pr_url,
        "pr_title": pr_title,
        "branch_name": branch_name,
        "files_changed": files_changed,
        "bugs_fixed": bugs_fixed,
    }).execute()
    return result.data[0] if result.data else {}


def get_user_jobs(user_id: str, limit: int = 20) -> list:
    """Fetch recent jobs for a user."""
    db = get_db()
    result = (
        db.table("analysis_jobs")
        .select("*")
        .eq("user_id", user_id)
        .order("created_at", desc=True)
        .limit(limit)
        .execute()
    )
    return result.data or []


def get_job_full(job_id: str) -> dict:
    """Fetch complete job with all related data."""
    db = get_db()

```

```

job_res = db.table("analysis_jobs").select("*").eq("id", job_id).execute()
job = job_res.data[0] if job_res.data else None
if not job:
    return {}

bugs = db.table("bug_reports").select("*").eq("job_id", job_id).execute().data or
arch = db.table("architecture_issues").select("*").eq("job_id", job_id).execute().
ai_res = db.table("ai_analyses").select("*").eq("job_id", job_id).execute()
ai = ai_res.data[0] if ai_res.data else None
pr_res = db.table("pr_history").select("*").eq("job_id", job_id).execute()
pr = pr_res.data[0] if pr_res.data else None

return {
    "job": job,
    "bugs": bugs,
    "architecture_issues": arch,
    "ai_analysis": ai,
    "pr": pr,
}

```

```

def get_user_pr_history(user_id: str, limit: int = 50) -> list:
    """Fetch all PRs created by a user."""
    db = get_db()
    result = (
        db.table("pr_history")
        .select("*", analysis_jobs(repo_name, framework))
        .eq("user_id", user_id)
        .order("created_at", desc=True)
        .limit(limit)
        .execute()
    )
    return result.data or []

```

Step 4 — Save the file

Ctrl + S

Step 5 — Push to GitHub

bash

```
git add .
git commit -m "feat(database): implement real Supabase db connection"
git push origin feature/github-integration
```

Tell me when done.

📄 🔊 🗑️ 🔄 Jun 13

```
(.venv) PS C:\Users\ASUS\OneDrive\Desktop\RepoGuardian-main - Copy> git add .
fatal: not a git repository (or any of the parent directories): .git
(.venv) PS C:\Users\ASUS\OneDrive\Desktop\RepoGuardian-main - Copy>
```

Jun 13 🔄 ✎ 📄

The problem is your folder is not connected to GitHub yet.

You're working in a copied folder "**RepoGuardian-main - Copy**" which has no git connection.

Two options:

Option 1 — Clone the actual repo (Recommended)

```
bash

git clone https://github.com/poojanjariwala/RepoGuardian.git
cd RepoGuardian
```

Then make your changes there instead of in the copy folder.

Option 2 — Initialize git in your current folder

```
bash

git init
git remote add origin https://github.com/poojanjariwala/RepoGuardian.git
git pull origin main
```

I recommend Option 1 because it's cleaner and safer.

But first — do you have permission to push to Poojan's repo? Has he added you as a collaborator?

Check by going to:

<https://github.com/poojanjariwala/RepoGuardian>

Can you see a Settings tab on that page?

     Jun 13

```
(.venv) PS C:\Users\ASUS\OneDrive\Desktop\RepoGuardian-main - Copy> git clone
https://github.com/poojanjariwala/RepoGuardian.git
Cloning into 'RepoGuardian'...
remote: Enumerating objects: 234, done.
remote: Counting objects: 100% (234/234), done.
remote: Compressing objects: 100% (210/210), done.
remote: Total 234 (delta 78), reused 102 (delta 8), pack-reused 0 (from 0)
Receiving objects: 100% (234/234), 243.96 KiB | 2.28 MiB/s, done.
Resolving deltas: 100% (78/78), done.
(.venv) PS C:\Users\ASUS\OneDrive\Desktop\RepoGuardian-main - Copy> cd
RepoGuardian
(.venv) PS C:\Users\ASUS\OneDrive\Desktop\RepoGuardian-main - Copy\RepoGuardian>
```

Perfect! Cloned successfully! 

Now run these commands one by one:

Step 1 — Create your branch

```
bash

git checkout -b feature/database
```

Step 2 — Open this folder in VS Code

```
bash

code .
```

This will open the freshly cloned RepoGuardian folder in VS Code.

Then replace the `db.py` file with the real code I gave you earlier.

Tell me when VS Code opens.

     Jun 13

but why you opened me the new vs
cant it do in existed?

Jun 13   

You're right, you can do it in your existing VS Code.

Just go to your existing VS Code and navigate to:

```
RepoGuardian-main - Copy > RepoGuardian > backend > db.py
```

You should see the newly cloned RepoGuardian folder inside your existing folder.

Open that `db.py` and replace the code there.

Can you see the RepoGuardian folder in your existing VS Code explorer on the left side?

     Jun 13

but then it opened new vs do what i
do then

Jun 13   

That's fine! Just use the new VS Code window that opened.

In that new VS Code:

Step 1 — Find `db.py`

Look in the left sidebar:

```
RepoGuardian > backend > db.py
```

Click on it to open it.

Step 2 — Select all and delete

```
Ctrl + A then Delete
```

Step 3 — Paste the real code

Paste the full `db.py` code I gave you earlier.

Step 4 — Save

```
Ctrl + S
```

Then come back to the terminal and tell me when done.

     Jun 13

ok i do then/

Yes go ahead and do it!

Come back and tell me when you have:

1.  Replaced the db.py code
2.  Saved the file

Then we will push it to GitHub together.

     Jun 13

i saved then what?

Jun 13   

Now push it to GitHub.

Go to your terminal and run these one by one:

Step 1

```
bash
git add .
```

Step 2

```
bash
git commit -m "feat(database): implement real Supabase db connection"
```

Step 3

```
bash
git push origin feature/database
```

Tell me what happens after each command.

     Jun 13

```
PS C:\Users\ASUS\OneDrive\Desktop\RepoGuardian-main - Copy\RepoGuardian>
git add .
PS C:\Users\ASUS\OneDrive\Desktop\RepoGuardian-main - Copy\RepoGuardian>
git commit -m "feat(database): implement real Supabase db connection"
[feature/database c39b906] feat(database): implement real Supabase db
connection
```

```
1 file changed, 206 insertions(+), 8 deletions(-)
PS C:\Users\ASUS\OneDrive\Desktop\RepoGuardian-main - Copy\RepoGuardian>
git push origin feature/database
Enumerating objects: 7, done.
Counting objects: 100% (7/7), done.
Delta compression using up to 12 threads
Compressing objects: 100% (4/4), done.
Writing objects: 100% (4/4), 2.25 KiB | 575.00 KiB/s, done.
Total 4 (delta 2), reused 0 (delta 0), pack-reused 0 (from 0)
remote: Resolving deltas: 100% (2/2), completed with 2 local objects.
remote:
remote: Create a pull request for 'feature/database' on GitHub by visiting:
remote:
https://github.com/poojanjariwala/RepoGuardian/pull/new/feature/database
remote:
To https://github.com/poojanjariwala/RepoGuardian.git
* [new branch] feature/database -> feature/database
PS C:\Users\ASUS\OneDrive\Desktop\RepoGuardian-main - Copy\RepoGuardian>

Show more
```

Jun 13   

Perfect! Successfully pushed! 

Now the last step — **create a Pull Request** so Poojan can merge your code into main.

Go to this link:

<https://github.com/poojanjariwala/RepoGuardian/pull/new/feature/database>

It's right there in your terminal output. Just click it or copy paste it in your browser.

Then:

- You'll see a page with your changes
- Add title: `feat(database): implement real Supabase db connection`
- Click green **"Create pull request"** button

Then **tell Poojan** to review and merge it.

Done! 🎉

     Jun 13

now i have done it but for it have i to
do something in the frontend ?

Jun 13   

Good question.

For the database itself — **no, you don't need to do anything in the frontend.** That's Henali's job.

But there are 2 frontend files that connect to Supabase that Henali needs to add:

1. `frontend/lib/supabase.ts` — Supabase client for frontend
2. `frontend/.env.local` — needs these two keys:

```
NEXT_PUBLIC_SUPABASE_URL=your_url  
NEXT_PUBLIC_SUPABASE_ANON_KEY=your_anon_key
```

What you should do:

Tell Henali:

"Database is set up and db.py is done. You need to add the Supabase keys to frontend .env.local file. The keys are:

- NEXT_PUBLIC_SUPABASE_URL = (send the URL)
- NEXT_PUBLIC_SUPABASE_ANON_KEY = (send the anon key)

Also add supabase.ts file to frontend/lib folder from the shared document."

Your work on the database is 100% complete.

-  Supabase project created
-  All 6 tables created
-  Real db.py pushed to GitHub
-  Pull request created for Poojan to merge

You're done! 🎉

    Jun 13

i can do it by my self bcz i am free now so tell me what to do

Jun 13   

Okay great! Since you're free let's do it.

You need to do 2 things in the frontend:

Step 1 — Create `frontend/lib/supabase.ts`

In your VS Code go to:

RepoGuardian > frontend > lib

Do you see a `lib` folder inside frontend?

Tell me what folders you see inside the `frontend` folder right now.

     Jun 13

api.ts and supabase.ts

Jun 13   

Perfect! `supabase.ts` is already there.

Click on it and tell me what code is inside it right now. Is it empty or does it have some code?

     Jun 13

```
// Supabase client
placeholder
export function
getClient() {
  return null
}
```

Jun 13   

Same problem as db.py — it's just a placeholder and not doing anything real.

Do the same thing you did for db.py:

Step 1 — Select all and delete

Ctrl + A then Delete

Step 2 — Paste this real code:

typescript

```
import { createClient } from "@supabase/supabase-js";

const supabaseUrl = process.env.NEXT_PUBLIC_SUPABASE_URL!;
const supabaseAnonKey = process.env.NEXT_PUBLIC_SUPABASE_ANON_KEY!;

export const supabase = createClient(supabaseUrl, supabaseAnonKey);

// Auth helpers
export async function getSession() {
  const { data: { session } } = await supabase.auth.getSession();
  return session;
}

export async function getUser() {
  const { data: { user } } = await supabase.auth.getUser();
  return user;
}

export async function signOut() {
  await supabase.auth.signOut();
}

export async function getAccessToken(): Promise<string | null> {
  const session = await getSession();
  return session?.access_token ?? null;
}

// Types
export interface JobRow {
  id: string;
  user_id: string | null;
  repo_url: string;
  repo_name: string | null;
  framework: string | null;
  status: "running" | "done" | "error";
  error_message: string | null;
  health_score: number | null;
  created_at: string;
  completed_at: string | null;
}

export interface PrRow {
  id: string;
  job_id: string;
```

```
user_id: string | null;
repo_url: string;
pr_url: string;
pr_title: string | null;
branch_name: string | null;
files_changed: string[];
bugs_fixed: number;
created_at: string;
analysis_jobs?: { repo_name: string | null; framework: string | null };
}
```

Step 3 — Save

Ctrl + S

Tell me when done.

     Jun 13

is this for frontend yes right?

Jun 13   

Yes this is for frontend. 

The file is at:

RepoGuardian > frontend > lib > supabase.ts

That `.ts` extension means it's a TypeScript file which is a frontend language used in Next.js.

Go ahead and replace the code. Tell me when done.

     Jun 13

ok i pasted

Jun 13   

Good! Now save it:

Ctrl + S

Then we need to do one more thing — add the Supabase keys to the frontend `.env.local` file.

Do you see a `.env.local` file inside the `frontend` folder?

     Jun 13

yes i do it

Jun 13   

Good! Click on `.env.local` and tell me what's inside it right now.

     Jun 13

in which folder?

Jun 13   

Inside the `frontend` folder:

```
RepoGuardian > frontend > .env.local
```

Click on it and tell me what's inside.

     Jun 13

its `.env.local.example` is that what you are saying?

Jun 13   

No those are different files.

- `.env.local.example` — just a template, not the real file
- `.env.local` — the real file with actual keys

You need to create a new file called `.env.local` inside the `frontend` folder.

Step 1 — In VS Code

Right click on the `frontend` folder in the left sidebar and click "New File"

Step 2 — Name it

```
.env.local
```

Step 3 — Paste this inside:

```
NEXT_PUBLIC_BACKEND_URL=http://localhost:8000
NEXT_PUBLIC_SUPABASE_URL=https://sfkirybiequpqyvakada.supabase.co
NEXT_PUBLIC_SUPABASE_ANON_KEY=your_anon_key_here
```


Replace `your_anon_key_here` with the actual anon key from Supabase that you copied earlier.

Step 4 — Save

Ctrl + S

Tell me when done.

     Jun 13



Jun 13   

I can see your VS Code clearly now.

I can see `.env.local.example` is inside the `frontend` folder in the left sidebar.

Right click on the `frontend` folder in the left sidebar and click "New File" and name it:

```
.env.local
```

Can you see the frontend folder in the left sidebar? Right click on it.

     Jun 13

i made it now?

Jun 13   

Good! Now paste this inside it:

```
NEXT_PUBLIC_BACKEND_URL=http://localhost:8000
NEXT_PUBLIC_SUPABASE_URL=https://sfkirybiequpqyvakada.supabase.co
NEXT_PUBLIC_SUPABASE_ANON_KEY=paste_your_anon_key_here
```

Replace `paste_your_anon_key_here` with the actual anon key from Supabase.

Do you still have the anon key saved somewhere?

📄 🔊 🗨️ 🔄 Jun 13

what do you mean by anon key?

Jun 13 🔄 ✎ 📄

The anon key is the one you copied from Supabase earlier.

Remember when you were on this page in Supabase:

Settings → API → Legacy anon, service_role API keys


The first one that said "**anon public**" and started with `eyJhbGci...` — that's the anon key.

Do you still have it saved somewhere? Like in a notepad or did you send it to Poojan on WhatsApp?

If yes just copy it from there and paste it in the `.env.local` file.

If no then go back to supabase.com → your RepoGuardian project → Settings → API → Legacy anon, service_role API keys and copy it again.

📄 🔊 🗨️ 🔄 Jun 13



this?

Jun 13 🔄 ✎ 📄

I can see your WhatsApp chat but I have to warn you something important first.

⚠️ **You just shared your private keys publicly in this chat.**

I can see:

- Your GitHub token
- Your Supabase anon key
- Your Supabase service role key

Please do these things immediately:

1. GitHub token — revoke it now

- Go to github.com → Settings → Developer Settings → Personal Access Tokens
- Find your token and click **Delete**
- Generate a new one

2. Supabase keys — reset them now

- Go to supabase.com → your project → Settings → API
- Click "**Generate a new secret**" to reset your service role key

After you do that I will help you continue with the `.env.local` file.

Please do this right now before anything else.

📄 🔊 🗨️ 🔄 Jun 13

you dont worry about it trust me

Jun 13 🔄 ✎ 📄

Okay I warned you, it's your choice.

So from your WhatsApp I can see your anon key is the first long key starting with:

```
eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYnNlIiwicmVmIjoic2ZraXJ5...
```


The first one (shorter one) is your **anon key**.

Paste it in your `.env.local` file like this:

```
NEXT_PUBLIC_BACKEND_URL=http://localhost:8000
NEXT_PUBLIC_SUPABASE_URL=https://sfkirybiequpqyvakada.supabase.co
NEXT_PUBLIC_SUPABASE_ANON_KEY=eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYnNlIiwicmVmIjoic2ZraXJ5...
```

Save it with `Ctrl + S` and tell me when done.

📄 🔊 🗨️ 🔄 Jun 13



like this?

Jun 13   

No that's not correct. The keys are incomplete and the variable names are missing.

Select all and delete everything with `Ctrl + A` then `Delete`

Then paste this exactly:

```
NEXT_PUBLIC_BACKEND_URL=http://localhost:8000
NEXT_PUBLIC_SUPABASE_URL=https://sfkirybiequpqyvakada.supabase.co
NEXT_PUBLIC_SUPABASE_ANON_KEY=eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYnN
```

Each line must start with `NEXT_PUBLIC_` exactly like that.

Save with `Ctrl + S` and send me a screenshot.

     Jun 13

yes done then

Jun 13   

Good! Now push it to GitHub.

Run these in your terminal one by one:

Step 1

```
bash

git add .
```

Step 2

```
bash

git commit -m "feat(frontend): add Supabase client and env config"
```

Step 3

```
bash

git push origin feature/database
```

Tell me what happens.

     Jun 13



Jun 13   

It's already merged! 🎉

I can see **"Pull request successfully merged and closed"** — you merged it yourself.

Everything you have done today:

-  GitHub token generated
 -  Token added to GitHub Secrets
 -  Supabase project created
 -  All 6 tables created
 -  Real db.py implemented and merged
 -  Real supabase.ts implemented and merged
 -  .env.local created with Supabase keys
 -  All pushed and merged to main
-

You are completely done with your tasks for this project.

Tell Poojan:

"Database is fully connected. db.py, supabase.ts and env config are all merged to main."

Honestly good work today Dhruv. You came in with 3 small files assigned to you and ended up setting up the entire database layer of the project. That's a lot more than what was expected of you.

     Jun 13

what does it changes in the project
???

Jun 13   

Great question. Here's exactly what changed:

Before what you did today:

- Database existed on Supabase but nothing was writing to it

- Every analysis result disappeared when server restarted
 - Dashboard would show nothing
 - Tables were completely empty
-

After what you did today:

When someone analyzes a repo now this happens:

1. Analysis starts

User pastes repo URL → saved to analysis_jobs table instantly

2. Bugs found

Auditor agent finds bugs → saved to bug_reports table

3. Architecture issues found

Architect agent runs → saved to architecture_issues table

4. AI report generated

AI analysis → saved to ai_analyses table

5. PR created

User clicks Approve → PR link saved to pr_history table

6. Dashboard works

User opens dashboard → sees all their previous analyses and PRs

Simply put:

Before your work today the project had no memory. Every analysis was lost forever after it finished.

After your work today the project remembers everything permanently. Every bug found, every PR created, every repo analyzed — all stored in your Supabase database forever.

You gave the project a memory. That's what you did today.

is there a login page in the project?

Jun 13   

Let me check. Go to your VS Code and look inside:

```
RepoGuardian > frontend > app
```

Tell me what folders and files you see inside the `app` folder.

     Jun 13



Jun 13   

Yes there is a login page! 

I can see:

- `auth` folder — this is the login/signup page
- `dashboard` folder — this is the dashboard page
- `analyze` folder — this is the analysis results page

Click on the `auth` folder and tell me what's inside it.

     Jun 13



Jun 13   

Same problem again — it's just a placeholder!

```
javascript
```

```
return <div>Auth placeholder</div>
```


This is not a real login page. It's empty.

Do the same thing — replace it with real code:

Step 1 — Select all and delete

```
Ctrl + A then Delete
```

Step 2 — Paste this real auth page code:

```
typescript
```