Linux command line

Command	Meaning / purpose
`pwd`	Displays the current working directory.
`ls`	Lists files and directories.
`ls -l`	Lists files with details, including permissions and sizes.
`ls -a`	Shows hidden files and directories too.
`cd folder`	Changes the current directory to `folder`.
`cd ..`	Moves to the parent directory.
`cd ~`	Changes to the user's home directory.
`clear`	Clears the terminal screen.
`mkdir folder`	Creates a directory.
`mkdir -p a/b`	Creates nested directories, including missing parent directories.
`touch file.txt`	Creates an empty file if it doesn't exist.
`cat file.txt`	Displays file contents.

`echo "text"`	Prints text to the terminal.
`>`	Redirects output to a file, replacing its existing contents.
`>>`	Appends output to a file.
`cp source dest`	Copies a file.
`mv source dest`	Moves or renames a file.
`rm -i file`	Requests confirmation before deleting a file.
`head -n 5 file`	Displays the first five lines.
`tail -n 5 file`	Displays the last five lines.
`wc -l file`	Counts the lines in a file.
`grep "ERROR" file`	Displays lines containing `ERROR`.
`grep -c "ERROR" file`	Counts matching lines.
`find . -name "*.log"`	Searches the current directory tree for `.log` files.
`sort file`	Sorts lines in a file.

`command1 | command2`	Sends the first command's output to the second command.
`chmod +x script.sh`	Adds executable permission to a script.
`whoami`	Displays the current username.
`echo "$VAR"`	Displays the value of a shell variable.
`export VAR=value`	Exports a variable to programs launched from the shell.
`ps`	Displays available process information.
`./script.sh`	Runs an executable script in the current directory.

Important concepts

- Terminal: An interface where you type commands.
- Shell: A program that interprets commands, such as Bash.
- Directory: Another word for a folder.
- Path: The location of a file or directory.
- Process: A running program.
- Permission: Controls whether a user can read, write or execute a file.
- Shell script: A file containing commands that run together.
- Pipe: Connects the output of one command to another.
- Redirection: Sends command output to a file instead of, or in addition to, the terminal.