



(https://colab.research.google.com/github/poojashah19/Applied-AI-Course/blob/main/Assignment%202/pandas_basics_practice.ipynb)

Consider the following Python dictionary data and Python list labels:

```
data = {'birds': ['Cranes', 'Cranes', 'plovers', 'spoonbills', 'spoonbills', 'Cranes', 'plovers', 'Cranes', 'spoonbills', 'spoonbills'],
```

```
'age': [3.5, 4, 1.5, np.nan, 6, 3, 5.5, np.nan, 8, 4],
```

```
'visits': [2, 4, 3, 4, 3, 4, 2, 2, 3, 2],
```

```
'priority': ['yes', 'yes', 'no', 'yes', 'no', 'no', 'no', 'yes', 'no', 'no']}]
```

```
labels = ['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h', 'i', 'j']
```

1. Create a DataFrame birds from this dictionary data which has the index labels.

```
In [3]: ## I have referenced few topics on geekforgeeks for syntax
import pandas as pd
import numpy as np
data = {'birds': ['Cranes', 'Cranes', 'plovers', 'spoonbills', 'spoonbills', 'Cranes', 'plovers', 'Cranes', 'spoonbills', 'spoonbills'],
'age': [3.5, 4, 1.5, np.nan, 6, 3, 5.5, np.nan, 8, 4],
'visits': [2, 4, 3, 4, 3, 4, 2, 2, 3, 2],
'priority': ['yes', 'yes', 'no', 'yes', 'no', 'no', 'no', 'yes', 'no', 'no']}
labels = ['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h', 'i', 'j']
```

```
In [4]: df = pd.DataFrame(data, index = labels)
df
```

Out[4]:

	birds	age	visits	priority
a	Cranes	3.5	2	yes
b	Cranes	4.0	4	yes
c	plovers	1.5	3	no
d	spoonbills	NaN	4	yes
e	spoonbills	6.0	3	no
f	Cranes	3.0	4	no
g	plovers	5.5	2	no
h	Cranes	NaN	2	yes
i	spoonbills	8.0	3	no
j	spoonbills	4.0	2	no

2. Display a summary of the basic information about birds DataFrame and its data.

```
In [5]: df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
Index: 10 entries, a to j
Data columns (total 4 columns):
#   Column      Non-Null Count  Dtype
---  -
0   birds       10 non-null    object
1   age         8 non-null     float64
2   visits      10 non-null    int64
3   priority    10 non-null    object
dtypes: float64(1), int64(1), object(2)
memory usage: 400.0+ bytes
```

3. Print the first 2 rows of the birds dataframe

```
In [6]: df[:2]
```

Out[6]:

	birds	age	visits	priority
a	Cranes	3.5	2	yes
b	Cranes	4.0	4	yes

4. Print all the rows with only 'birds' and 'age' columns from the dataframe

```
In [7]: df[['birds', 'age']]
```

```
Out[7]:
```

	birds	age
a	Cranes	3.5
b	Cranes	4.0
c	plovers	1.5
d	spoonbills	NaN
e	spoonbills	6.0
f	Cranes	3.0
g	plovers	5.5
h	Cranes	NaN
i	spoonbills	8.0
j	spoonbills	4.0

5. select [2, 3, 7] rows and in columns ['birds', 'age', 'visits']

```
In [11]: dataf = pd.DataFrame.from_dict(data)
dataf.loc[[2,3,7], ['birds', 'age', 'visits']]
```

```
Out[11]:
```

	birds	age	visits
2	plovers	1.5	3
3	spoonbills	NaN	4
7	Cranes	NaN	2

6. select the rows where the number of visits is less than 4

In [12]: `df.loc[df.visits < 4]`

Out[12]:

	birds	age	visits	priority
a	Cranes	3.5	2	yes
c	plovers	1.5	3	no
e	spoonbills	6.0	3	no
g	plovers	5.5	2	no
h	Cranes	NaN	2	yes
i	spoonbills	8.0	3	no
j	spoonbills	4.0	2	no

7. select the rows with columns ['birds', 'visits'] where the age is missing i.e NaN

In [13]: `df.loc[df.age.isna(), ['birds', 'visits']]`

Out[13]:

	birds	visits
d	spoonbills	4
h	Cranes	2

8. Select the rows where the birds is a Cranes and the age is less than 4

In [14]: `df[(df['birds']=='Cranes') & (df['age'] < 4)]`

Out[14]:

	birds	age	visits	priority
a	Cranes	3.5	2	yes
f	Cranes	3.0	4	no

9. Select the rows the age is between 2 and 4(inclusive)

```
In [15]: df[(df['age']>=2) & (df['age'] <= 4)]
```

```
Out[15]:
```

	birds	age	visits	priority
a	Cranes	3.5	2	yes
b	Cranes	4.0	4	yes
f	Cranes	3.0	4	no
j	spoonbills	4.0	2	no

10. Find the total number of visits of the bird Cranes

```
In [16]: df.loc[df['birds']=='Cranes', ['visits']].sum(axis=0)
```

```
Out[16]: visits    12
dtype: int64
```

11. Calculate the mean age for each different birds in dataframe.

```
In [17]: df.loc[:,['birds','age']].groupby('birds').mean()
```

```
Out[17]:
```

	age
birds	
Cranes	3.5
plovers	3.5
spoonbills	6.0

12. Append a new row 'k' to dataframe with your choice of values for each column. Then delete that row to return the original DataFrame.

```
In [29]: df.loc['k'] = ['plovers', 4.0, 5, 'yes']  
df
```

Out[29]:

	birds	age	visits	priority
a	Cranes	3.5	2	yes
b	Cranes	4.0	4	yes
c	plovers	1.5	3	no
d	spoonbills	NaN	4	yes
e	spoonbills	6.0	3	no
f	Cranes	3.0	4	no
g	plovers	5.5	2	no
h	Cranes	NaN	2	yes
i	spoonbills	8.0	3	no
j	spoonbills	4.0	2	no
k	plovers	4.0	5	yes

```
In [30]: df=df.drop('k')  
df
```

Out[30]:

	birds	age	visits	priority
a	Cranes	3.5	2	yes
b	Cranes	4.0	4	yes
c	plovers	1.5	3	no
d	spoonbills	NaN	4	yes
e	spoonbills	6.0	3	no
f	Cranes	3.0	4	no
g	plovers	5.5	2	no
h	Cranes	NaN	2	yes
i	spoonbills	8.0	3	no
j	spoonbills	4.0	2	no

13. Find the number of each type of birds in dataframe (Counts)

```
In [31]: df.loc[:,['birds']].groupby('birds').size()
```

```
Out[31]: birds
Cranes      4
plovers     2
spoonbills  4
dtype: int64
```

14. Sort dataframe (birds) first by the values in the 'age' in descending order, then by the value in the 'visits' column in ascending order.

```
In [33]: ## referred https://stackoverflow.com/questions/17141558/how-to-sort-a-dataframe-in-python-pandas-by-two-or-more-columns Link
df.sort_values(by=['age','visits'], ascending=[False, True])
```

```
Out[33]:
```

	birds	age	visits	priority
i	spoonbills	8.0	3	no
e	spoonbills	6.0	3	no
g	plovers	5.5	2	no
j	spoonbills	4.0	2	no
b	Cranes	4.0	4	yes
a	Cranes	3.5	2	yes
f	Cranes	3.0	4	no
c	plovers	1.5	3	no
h	Cranes	NaN	2	yes
d	spoonbills	NaN	4	yes

15. Replace the priority column values with 'yes' should be 1 and 'no' should be 0

```
In [34]: df.replace({ 'priority' : { 'yes' : 1, 'no' : 0 }})
```

```
Out[34]:
```

	birds	age	visits	priority
a	Cranes	3.5	2	1
b	Cranes	4.0	4	1
c	plovers	1.5	3	0
d	spoonbills	NaN	4	1
e	spoonbills	6.0	3	0
f	Cranes	3.0	4	0
g	plovers	5.5	2	0
h	Cranes	NaN	2	1
i	spoonbills	8.0	3	0
j	spoonbills	4.0	2	0

16. In the 'birds' column, change the 'Cranes' entries to 'trumpeters'.

```
In [35]: df.replace({ 'birds' : { 'Cranes' : 'trumpeters'}})
```

```
Out[35]:
```

	birds	age	visits	priority
a	trumpeters	3.5	2	yes
b	trumpeters	4.0	4	yes
c	plovers	1.5	3	no
d	spoonbills	NaN	4	yes
e	spoonbills	6.0	3	no
f	trumpeters	3.0	4	no
g	plovers	5.5	2	no
h	trumpeters	NaN	2	yes
i	spoonbills	8.0	3	no
j	spoonbills	4.0	2	no