Gates Pass, Code Fails: A Measurement-Validity Study of LLM-as-Judge Test Adequacy for Requirement-to-Test Generation

Poojitha J, Arushi Tandon, Brahma Reddy Korraprolu, Y. Raghu Reddy
Software Engineering Research Center
International Institute of Information Technology, Hyderabad
Hyderabad, India

***Abstract*—Large language models are increasingly used to turn natural-language software requirements directly into test cases, and evaluating the result with text-similarity metrics such as BLEU, ROUGE, or CodeBLEU is now widely recognized as inadequate: a syntactically similar test can still exercise the wrong behaviour, miss the requirement entirely, or assert a value the requirement never specified. Those metrics work by comparing the generated test's wording to a reference test's wording. The emerging alternative drops that comparison entirely and instead hands the generated test to a second LLM and asks it to read and judge whether the test is actually correct. This paper asks a blunt question: how much should that judge be trusted? We built what we believe is a reasonably rigorous instance of this approach, a three-gate pipeline covering representational suitability, syntactic validity, and LLM-judged semantic adequacy with an explicit groundedness check, with closed-loop repair, and used it to benchmark 10 open-weight LLMs generating tests from three real software requirement specifications (496 test suites, 4,058 test cases, across 29 project×model pairs). The benchmark itself surfaces useful, non-obvious comparative findings: model parameter count does not predict test adequacy (Spearman $\rho = -0.015$), code-specialized models do not outperform general-purpose ones (Mann-Whitney $p = 0.1407$), and which test-case representation a model is asked to use matters more than which model is used. But when we check the judge's own outputs against ground truth, the picture changes: the LLM-based code audit agrees with real test execution only 18% of the time, only 1 to 2 of 148 to 315 generated tests for one case study actually pass when executed, and 49% of all suites assert at least one specific value that is not grounded in the source requirement despite otherwise passing the adequacy gate. We argue that gate-passing, as currently operationalized by LLM-judge pipelines including our own, is a measurably weak proxy for correctness, and that any such pipeline needs an explicit, reported execution-grounded validity check rather than being trusted at face value.**

***Index Terms*—test case generation, large language models, requirements-based testing, LLM-as-judge, evaluation metrics, software testing**

I. Introduction

Software requirements specifications (SRS) describe what a system must do in natural language; test cases verify that it does. Turning the first into the second has always been labour-intensive, and large language models (LLMs) are now routinely proposed to automate it, generating unit tests, behavioural scenarios, or formal test obligations directly from a requirement's text. The question this raises is not whether LLMs can produce *something* that looks like a test case; they reliably can. The question is whether what they produce is the *right* test case for that requirement, and whether we can tell.

Text-similarity metrics such as BLEU, ROUGE, and CodeBLEU answer a different question than the one that matters: they measure how closely generated text resembles a reference, not whether the generated test exercises the correct behaviour, uses an appropriate representation for the kind of requirement it came from, or asserts values the requirement actually specifies. A test case can score well on n-gram overlap while testing nothing the requirement cares about, and score poorly while being a perfectly adequate test phrased differently from the reference. This is well understood in the LLM-for-testing literature [3]. The natural response has been to stop comparing generated-text wording to reference-text wording, and instead hand the generated test to a second LLM that reads it and judges whether it is actually correct.

That response trades one hard-to-trust proxy for another. An LLM judge can be wrong in ways that are harder to detect than a low BLEU score: it can be confidently, fluently wrong. This paper's contribution is not another judge, but a direct measurement of how much a reasonably careful judge-based pipeline should be trusted, obtained by building such a pipeline, running it at benchmark scale, and then checking its verdicts against the one thing that is not a proxy: whether the generated tests actually execute against, and agree with, the real implementation.

Contributions.

1) A three-gate evaluation framework, comprising Representational Suitability (RSS), Syntactic Form Validity (SFV), and Functional Semantic Adequacy with Groundedness (FSA+M_g), with closed-loop repair, grounded in a 30-representation taxonomy of test-case forms (Sections III to IV).
2) A benchmark of 10 open-weight LLMs generating tests from three real SRS case studies: 496 test suites, 4,058 test cases, 29 project×model pairs, each suite also compared against the real implementation (Sections V to VI).
3) A quantified measurement-validity gap between what the gates report and what execution against real code shows: three independent checks (audit agreement, execution pass rate, and representation-choice agreement with an

independent heuristic) all land far below what the gate-pass rates alone would suggest (Section VII).

4) A recommendation, supported by that gap, that groundedness be reported and thresholded as its own first-class check rather than folded into a single blended adequacy score.

II. Motivation: Why Not Just Score Similarity?

To establish that the problem this paper studies is not a straw man, we conducted a systematic review of the literature on LLMs applied to software testing. Starting from 1,200 preprint sources (63 discarded for having zero citations) merged with published-venue results, we categorized 1,392 papers into four relevance tiers: 127 core, 501 relevant, 484 tangential, and 280 excluded (709 were preprints, 683 published). Of these, 1,315 were independently screened for inclusion by two of the authors, with a third author arbitrating disagreements. Inter-rater agreement was moderate (unweighted Cohen's $\kappa = 0.5253$, 84.79% observed agreement, $p < 0.0001$, 95% CI $[0.4702, 0.5805]$) and substantial once near-misses ("maybe" judgments) are weighted as partial agreement (linear-weighted $\kappa = 0.6187$, quadratic-weighted $\kappa = 0.6790$). The final screened portfolio retained 183 papers (13.9%).

We read this moderate-to-substantial agreement, reached only after a third arbitrator, as itself a symptom: even two researchers applying the same inclusion criteria to the same corpus disagree on which LLM-testing papers are relevant roughly one time in six. The underlying literature is similarly inconsistent about what "evaluating an LLM-generated test" should even mean: surface similarity, compilation, line coverage, and human judgment are all in active use, frequently within the same subfield, rarely cross-validated against one another. This motivates treating evaluation methodology itself, rather than any particular generation technique, as the object of study.

III. A Taxonomy of Test-Case Representations

A requirement's natural test representation depends on what kind of behaviour it describes: a state-dependent requirement is naturally tested with a finite state machine or a transition table; a concurrency requirement with an interaction diagram or a temporal-logic obligation; a pure business rule with a decision table. Treating "generate a test" as representation-agnostic discards this structure. To ground Gate 1 (Section IV) in something more principled than intuition, we conducted a second, separate systematic review targeted specifically at the test-case representation literature: 412 candidate papers (185 IEEE Xplore, 112 ACM Digital Library, 115 Google Scholar) were deduplicated to 328, reduced to 95 after title/abstract screening, and reduced to 30 after full-text review, each of the 30 retained papers anchoring one distinct test-case representation.

Each representation was classified along eight dimensions (abstraction level, V-model phase, underlying mechanism, representation language, formality, testing paradigm, representation object, and usage context) and the 30 representations group into six broad paradigms, summarized in Table I. A single running example, Requirement C of the case-study SRS (§9.2.1, "The support structure for communicating commands must be reliable, with a uniform ACK/NAK protocol adopted across all systems. Timeouts must be supported at approximately 500 msec."), was instantiated across all 30 representations as a worked catalog, so that what "the same requirement, a different representation" actually looks like in practice is concrete rather than asserted.

TABLE I
The six representation paradigms (30 representations total)

Paradigm	Representative forms
Scenario/Behavioral	Gherkin (BDD), use cases, user stories
Stateful/Transitions	finite state machines, statecharts
Concurrency/Interaction	sequence diagrams, GUI event graphs
Logical/Combinatorial	decision tables, test requirement matrices
Programmatic/Code-level	xUnit test cases, UML Testing Profile
Formal/Symbolic/Contract	temporal logic (LTL), transition systems

A. Worked Example

Table II shows Requirement C instantiated in three representations spanning three different paradigms, to make the taxonomy's central claim concrete: each representation foregrounds a different aspect of the same requirement. The Gherkin scenario (Scenario/Behavioral) foregrounds the observable sequence of events; the finite-state-machine table (Stateful/Transitions) foregrounds the states the subsystem can be in and which inputs move it between them; the decision table (Logical/Combinatorial) foregrounds the combinations of conditions (command sent, response type, elapsed time) that determine each outcome. A model that is only ever asked to produce xUnit-style assertions, regardless of which of these aspects the requirement is actually about, is being asked to flatten this distinction, which is precisely what Gate 1 is designed to catch.

IV. The Three-Gate Framework

Every generated suite passes through three gates in sequence, each with a fixed, pre-registered threshold; thresholds below are exactly what the pipeline implementation enforces, not an idealized or aspirational version of the design. Table III summarizes the three gates before the formulas and thresholds are given in full.

Gate 1: Representational Suitability (RSS). Before any test is generated, the model must choose, or be offered, a representation for the requirement at hand. RSS scores that choice heuristically:

$$\mathrm{RSS} = 0.40\,M_1 + 0.30\,M_2 + 0.15\,M_3 + 0.15\,M_4, \qquad (1)$$

TABLE II
REQUIREMENT C (SRS §9.2.1) IN THREE REPRESENTATIONS

Gherkin	`Scenario: 500ms Watchdog Timeout`
	`Given the subsystem is IDLE`
	`When the workstation sends SELF_TEST`
	`And no response arrives within 500ms`
	`Then status becomes TIMEOUT_ERROR`

FSM table	`(Idle, send_command) ->`
	`(AwaitingResponse, StartTimer)`
	`(AwaitingResponse, recv_ACK) -> (Idle,`
	`StopTimer)`
	`(AwaitingResponse, timer_expired) ->`
	`(TimeoutState, LogTimeout)`

Decision table	`CommandSent=Y, Response=NAK,`
	`Elapsed<500ms=Y → LogProtocolError`
	`CommandSent=Y, Response=none,`
	`Elapsed<500ms=N → RaiseTimeoutException`

TABLE III
THE THREE GATES AT A GLANCE

Gate	Threshold	What it checks
Gate 1: RSS	≥ 0.60	Is the chosen test-case representation actually suited to this requirement's kind of behaviour?
Gate 2: SFV	≥ 0.60	Is the generated suite syntactically well formed, both as canonical JSON and in its chosen notation?
Gate 3: FSA + M_g	≥ 0.50	Does the suite cover the right clauses, including negative and boundary cases, with precise oracles and values grounded in the requirement text?

where M_1 is concern alignment (does the representation match the kind of property the requirement describes), M_2 is abstraction-level alignment, M_3 penalizes unnecessary representational complexity (Occam's razor), and M_4 scores whether the representation is one an LLM can plausibly generate correctly. An extended ten-metric form adds six further metrics, M_5 to M_{10} (Table IV), reweighted under six system-profile-specific weight sets (standard, safety-critical, rapid-prototyping, data-pipeline, distributed-concurrent, interaction-heavy) for domain-specific weighting. Each requirement's system profile is inferred automatically from its text; in the benchmark, 248 of 496 suites were scored under the standard profile and the remaining 248 split across the other five, so the extended metrics are not a dormant option but an active part of roughly half the reported results. **Threshold: RSS** ≥ 0.60, with up to three re-picks before the pipeline falls back to a default representation.

Gate 2: Syntactic Form Validity (SFV). Once a suite is generated, SFV checks two things separately and blends them evenly:

$$\mathrm{SFV} = 0.5\, S_{\text{schema}} + 0.5\, S_{\text{repr}}. \tag{2}$$

S_{schema} is the fraction of canonical test cases that validate against the pipeline's JSON schema, meaning every required field is present, case ids are unique, and every `req_id` the case cites traces to a requirement actually present in the unit. S_{repr} is a family-specific syntax check of the representation

TABLE IV
THE SIX METRICS ADDED UNDER THE EXTENDED RSS FORM (M_5-M_{10})

Metric	What it scores
M_5 Oracle Executability	Can a test runner execute the suite's assertions automatically, without adapter code or a human in the loop.
M_6 Traceability Density	How directly each generated test maps back to one specific requirement clause.
M_7 Cognitive Auditability	Whether a human reviewer can read a test and spot a hallucinated value at a glance.
M_8 Change Fragility	Whether a small requirement edit needs only a localized change to the suite, rather than breaking the whole model.
M_9 Mutation Support	Whether the representation supports automated fault injection, so the suite's ability to catch real bugs can itself be tested.
M_{10} Standards and Compliance Fit	Whether the representation is an officially recognized formal model for the applicable safety-certification standard (e.g. ISO 26262, DO-178C); capped at 0.65 outside safety-critical systems.

artifact itself, routed by the suite's *actual* representation group rather than one generic parser applied to everything. Gherkin suites are parsed with the official Gherkin grammar (0.0 on a parse error, 0.4 if it parses but declares no `Scenario`, 0.8-1.0 depending on step density); Programmatic/Code-level suites are checked with Python's `ast` parser plus the presence of test functions and assertions; Stateful/Transitions suites are scored on five structural signals (declared states, an initial state, at least two transitions, events/guards, and balanced brackets); Scenario/Behavioral suites that are not Gherkin, such as use cases and user stories, are scored on four signals (a named actor, a main flow, at least one alternative or exception flow, and numbered steps); Concurrency/Interaction, Logical/Combinatorial, and Formal/Symbolic/Contract suites each get an analogous family-specific structural check (arrow and participant markers for sequence diagrams, consistent column counts and separator rows for decision tables, relational operators and matrix-like rows for symbolic notations). A suite passes Gate 2 only if $S_{\text{schema}} = 1.0$ *and* S_{repr} separately clears a per-group threshold (Table V); a perfect schema score cannot compensate for a failing representation score, or vice versa. **Threshold: SFV** ≥ 0.60 by default, tightened to ≥ 0.70 for Stateful/Transitions and Formal/Symbolic/Contract suites, and to 1.00 for Programmatic/Code-level suites, since a syntax error there means the suite does not run at all.

Gate 3: Functional Semantic Adequacy with Groundedness (FSA+M_g). Suites that clear Gates 1 and 2 are reviewed by a frontier-model judge along four adequacy dimensions plus groundedness:

$$\mathrm{FSA} = w_c C_{\text{clause}} + w_n C_{\text{neg}} + w_o A_{\text{oracle}} + w_b C_{\text{bound}} + w_g M_g, \tag{3}$$

with standard-profile weights $w_c = 0.30$ (clause coverage), $w_n = 0.20$ (negative-path coverage), $w_o = 0.15$ (oracle as-

TABLE V
GATE 2 REPRESENTATION-SCORE THRESHOLD BY PARADIGM GROUP

Paradigm group (Table I)	S_{repr} **threshold**
Scenario/Behavioral	≥ 0.60
Stateful/Transitions	≥ 0.70
Concurrency/Interaction	≥ 0.60
Logical/Combinatorial	≥ 0.60
Programmatic/Code-level	≥ 1.00
Formal/Symbolic/Contract	≥ 0.70

sertiveness), $w_b = 0.20$ (boundary-case coverage), $w_g = 0.15$ (groundedness), and six system profiles analogous to Gate 1. Groundedness itself is

$$M_g = 1 - \frac{H}{A}, \tag{4}$$

the fraction of asserted concrete values (A) that are *not* traceable to the source requirement text (H = hallucinated). **Threshold: FSA** ≥ 0.50**.** Suites that fail Gate 3 are fed back for up to three closed-loop repair attempts before being recorded as a final failure. The full pipeline is shown in Fig. 1.

We note, as a methodological point, that two earlier design documents produced during this project specify different thresholds for Gates 2 and 3 (SFV ≥ 0.80, FSA ≥ 0.75) and a simpler four-term FSA without groundedness. The numbers above are not those design-document values; they are what the pipeline implementation actually enforced when producing every result in this paper, confirmed directly against the configuration module. We flag the discrepancy explicitly because a methods section that quietly followed the more demanding, unimplemented thresholds would misrepresent the very results it reports, an error of exactly the kind this paper is arguing the field should stop making silently.

A. Prompt Design

Every prompt used in the pipeline is a plain text template with explicit placeholders, stored and versioned separately from the pipeline code, so that what a model was actually asked is always directly inspectable rather than reconstructed from code. Table VI gives the abbreviated form of the three prompts most central to this paper's argument: the representation choice prompt (Gate 1), the generation prompt (Stage S3), and the judge prompt (Gate 3). Full prompt text is included in the project repository.

The judge prompt (`fsa_judge.txt`) is the one most relevant to Section VII: it instructs the judge to decide, value by value, whether a concrete number, name, or state asserted in the suite is actually entailed by the requirement text, which is exactly the groundedness check later found to disagree so often with what execution against real code shows.

V. EXPERIMENTAL SETUP

A. Model Selection

Candidate models were narrowed from an initial pool of 65 through a four-stage funnel: licensing/recency screening (65→31→29), hardware feasibility by VRAM and context length (29→22), capability and benchmark screening (22→16), and a final state-of-the-art (SOTA)/diversity pass (16→14), yielding 12 open-weight models plus two closed-source controls (GPT-4o, Claude 3.5 Sonnet) intended as reference points.

Of the 12 open-weight models, **10 completed the full benchmark**: Llama-3.1-8B, Qwen2.5-Coder-7B, Qwen2.5-Coder-32B, Qwen3-30B-A3B, Gemma-3-27B, CodeGemma-7B, DeepSeek-Coder-V2-Lite, Granite-4.1-8B, Phi-3.5-mini, and Phi-3.5-MoE. Phi-4-14B failed Gate 1 on every attempted unit (server errors mid-generation) and is excluded from the comparative results; Llama-3.3-70B and the two closed-source controls were not executed, for compute and cost reasons. We also note that Gemma-3-27B and DeepSeek-Coder-V2-Lite completed only a small fraction of the full unit set (7 and 6 suites respectively, against 58 to 61 for the other eight models); their aggregate statistics below should be read with correspondingly lower confidence.

B. Case Studies

Three SRS/implementation pairs were used, each with its generated tests later compared against its real codebase (Section VI):

- **doorstop**: the requirements-management tool Doorstop, with its own Python implementation. 13 requirements extracted; time-budgeting restricted generation to 2 units, each run against 2 representations (4 suites per model).
- **ventilator**: an open-source ventilator control system with its own SRS and software implementation. 151 requirements extracted; 21 units generated, one representation per unit.
- **virtual_clinic**: a clinic-management web application (Django-based) with a PDF SRS. 251 requirements extracted; 36 units generated, one representation per unit.

Across the three case studies and 10 executed models this yields **496 test suites and 4,058 test cases** (40 doorstop, 170 ventilator, 286 virtual_clinic suites). The same extraction, judge, and executor model (`gpt-oss-20b`, a different model family from every subject under test) was used for every generator, to avoid a model favouring its own family's outputs. Test generation used only the SRS text; the real implementation was opened only at the execution/audit stage (Stage S6), after every suite had been fingerprinted, to prevent code leakage into generation.

VI. RESULTS I: MODEL AND REPRESENTATION COMPARISON

Fig. 2 shows mean FSA per model pooled across all three case studies. We emphasize a reading hazard visible in this figure: mean FSA is computed only over suites that *reached* the judge (i.e., passed Gate 2), so a model with a very low Gate-2 pass rate can still show a high mean FSA on the small number of suites it did get judged on. Phi-3.5-mini, for instance, shows the single highest pooled mean FSA (0.74) in Fig. 2 despite passing Gate 2 on only 9% of its 58 attempted suites and Gate




Fig. 1. The requirement-to-test pipeline: extraction, the three gates in sequence with their exact formulas and thresholds as implemented, closed-loop repair on Gate-3 failure, then execution/audit against the real implementation.

TABLE VI
ABBREVIATED PROMPT TEMPLATES FOR THE STAGES CENTRAL TO THIS PAPER (PLACEHOLDERS SHOWN AS {{FIELD}})

Prompt	Used at	Abbreviated template
select_reps.txt	Gate 1 (representation choice)	"Choose the test-case representations best suited to the requirements below. REQUIREMENTS: {{REQS}} DEPENDENCIES: {{DEPS}} AVAILABLE REPRESENTATIONS: {{CATALOG}} Pick the {{K}} most suitable, judged by concern alignment, abstraction level, simplicity, and LLM feasibility. Respond with ONLY a JSON object: {"selected": [{"representation": ..., "covers": [...], "reason": ...}]}"
generate.txt	Stage S3 (test generation)	"Write a complete test suite for the requirements below in the representation {{REP}}. REQUIREMENTS: {{REQS}} DEPENDENCIES (context only): {{DEPS}} SUFFICIENCY CRITERIA: {{CHECKLIST}} The suite will be scored on: syntactic validity; clause coverage; negative and boundary paths; oracle assertiveness; groundedness (every concrete value must come from the requirement text, never invented). Output exactly two fenced blocks: the artifact in {{REP}} notation, and the same cases as canonical JSON."
fsa_judge.txt	Gate 3 (semantic adequacy judge)	"You are an independent test-quality evaluator. You did NOT write the suite below. Score it strictly against the SRS requirements, and check every concrete value for hallucination. REQUIREMENTS (ground truth): {{REQS}} ARTIFACT: {{ARTIFACT}} CANONICAL CASES: {{TESTCASES}} Score clause_coverage, negative_coverage, oracle_assertiveness, boundary_coverage in [0,1]; for every concrete element asserted, decide "grounded": true/false by entailment against the SRS text. Respond with ONLY a JSON object: {"clause_coverage": ..., ..., "concrete_elements": [{"value": ..., "grounded": ...}], "weaknesses": [...]}"

3 on only 2%; a leaderboard built from FSA alone would rank it first on the strength of essentially one or two judged suites. On the richer, equal-sample doorstop comparison (Table VII, where every model attempted the same four suites), Llama-3.1-8B is the clearest overall performer (FSA 0.73, both-gates 100%) and CodeGemma-7B the weakest among models that passed Gate 1 at all (FSA 0.47, both-gates 25%).

Two comparisons that a practitioner might expect to predict quality do not: model size (Spearman $\rho(\text{parameters}, \text{FSA}) = -0.015$, $n = 311$) and code specialization (FSA 0.58 for code-specialized models vs. 0.64 for general-purpose, Mann-Whitney $p = 0.1407$). Mixture-of-experts models score slightly below dense models of comparable scale (FSA 0.59 vs. 0.62).

Representation choice shows a larger, more consistent effect than model identity. Fig. 3 breaks FSA and both-gates pass rate down by the six paradigms of Section III: Logical/Combinatorial representations (decision tables, etc.) both score highest on mean FSA (0.70) and pass both gates most often (55%), while Stateful/Transitions representations (FSMs,




Fig. 2. Mean FSA per model, pooled across all three case studies, with the number of judged suites each mean is computed over. Sample sizes vary sharply by model (6 to 61 judged suites); see text for why this figure alone should not be read as a leaderboard.

TABLE VII
MEAN ADEQUACY BY MODEL, DOORSTOP CASE STUDY (SAME UNITS FOR EVERY MODEL; $n = 4$ SUITES/MODEL). G2 AND G3 ARE THE GATE 2 (SFV) AND GATE 3 (FSA) PASS RATES; "BOTH" IS THE SHARE OF SUITES PASSING BOTH GATES.

Model	G2 pass	G3 pass	both	FSA
Llama-3.1-8B	100%	100%	100%	0.73
Qwen2.5-Coder-32B	75%	75%	75%	0.67
Gemma-3-27B	100%	100%	100%	0.66
DeepSeek-Coder-V2-Lite	75%	25%	25%	0.63
Granite-4.1-8B	75%	50%	50%	0.57
Qwen2.5-Coder-7B	50%	50%	50%	0.55
Qwen3-30B-A3B	25%	25%	25%	0.53
Phi-3.5-MoE	25%	25%	25%	0.53
CodeGemma-7B	75%	25%	25%	0.47
Phi-3.5-mini	0%	0%	0%	n/a

statecharts) are both lowest on FSA (0.62) and both-gates pass rate (23%). At the level of individual representations, the 30 available forms are used very unevenly: five representations (Gherkin, xUnit, Use-Cases, Decision Tables, FSMs) account for the overwhelming majority of all choices models made, with 18 of the 30 catalog representations used at all. Strikingly, a model's own Gate-1 choice agrees with the independent RSS heuristic's top-3 recommendation only 20% of the time on average; the two notions of "suitable representation" mostly disagree, a point we return to in Section VII.

Table VIII breaks this down to the level of individual representations with at least 15 suites generated in that form. GUI Event Graphs post the highest both-gates pass rate (64%, $n = 28$) despite a mid-pack FSA; Decision Tables and Gherkin, the two most heavily-used representations, sit in the middle; UML Testing Profile and Use-Cases & User Stories,

TABLE VIII
GATE OUTCOMES BY REPRESENTATION ($n \geq 15$ SUITES; n = SUITES GENERATED IN THAT REPRESENTATION; "BOTH-PASS" = SHARE PASSING BOTH GATE 2 AND GATE 3)

Representation	n	SFV	both-pass	FSA
GUI Event Graphs	28	0.96	64%	0.74
Decision Tables	44	0.77	55%	0.70
Gherkin (BDD DSL)	207	0.82	54%	0.67
Sequence Diagrams	18	0.85	44%	0.67
Finite State Machines	40	0.71	28%	0.66
Use-Cases & User Stories	39	0.86	28%	0.62
xUnit Test Cases	79	0.61	29%	0.68
UML Testing Profile (UTP)	15	0.92	27%	0.58

despite very high syntactic validity (SFV 0.92 and 0.86), both-gates pass at only 27% to 28%, since most of their failures occur at the semantic Gate 3 rather than the syntactic Gate 2, a reminder that a well-formed suite is not automatically an adequate one.

Closed-loop repair is effective where it is invoked: 207 of the 496 suites were repaired after an initial Gate-3 failure, with a mean FSA gain of $+0.131$ on those suites.

VII. RESULTS II: VALIDITY CHECKS

Section VI reports what the three-gate pipeline says about itself. This section checks those statements against evidence the pipeline did not produce: real test execution, a code-grounded audit, and an independent heuristic. All three checks were built into this study specifically because we did not want to publish a benchmark leaderboard without first asking how much the leaderboard's underlying scores can be trusted.

Execution agreement. On doorstop, the one case study where generated tests were actually executed against the real




Fig. 3. Mean FSA and both-gates pass rate by representation paradigm, pooled across all models and case studies.

implementation rather than only audited, the picture is stark: across the ten executed models, a combined **148 generated tests for the eight best-represented models (and up to 315 when extended to the full 10-model doorstop run) produced only 1 to 2 passing executions in total**. Four of ten models produced zero passing tests out of 10 to 49 attempts each; the best case, Qwen2.5-Coder-7B, passed 1 of 25. Gate-passing and real test-execution success are, on this evidence, close to unrelated for this case study: a suite that clears Gates 1 through 3 is not meaningfully more likely to run successfully against the real system than one that does not. The one weak positive signal is a moderate correlation between FSA and execution pass rate across the models for which both are available ($\rho = 0.433$, $n = 15$), present but on a small sample, and far from strong enough to license treating a high FSA score as evidence a suite will execute correctly.

Audit agreement. Because full execution was only feasible for doorstop (ventilator and virtual_clinic lack an automatable test harness in this study), the other two case studies instead rely on an LLM-judge *code audit*: the same judge model is shown retrieved code excerpts and asked, for each test case, to return one of four verdicts describing whether the code's behaviour matches the test's expectation: `satisfied`, the code does what the test expects; `violated`, the code implements the feature but disagrees with the expectation; `not_implemented`, the feature is absent; or `unclear`, the retrieved excerpt is insufficient to tell. (On doorstop, actually running a test and seeing it fail triggers a separate, three-way triage of *why* it failed, by the same judge model: `code_mismatch`, the implementation disagrees with the requirement; `test_bug`, the generated test itself is wrong; or `spec_ambiguous`, the requirement does not clearly settle the question.) On the subset of doorstop suites where both execution and audit results are available ($n = 11$), **the audit agrees with real execution only 18% of the time**. This is the single most important caveat on every audit-based result reported for ventilator and virtual_clinic elsewhere in this paper and in the underlying analysis report: audit mode should be read as a weak, frequently-wrong proxy for ground truth, not a substitute for execution. Separately, across all three case studies, the audit flagged 190 individual test cases as contradicting the real implementation, combining an audit `violated` verdict with, on the executed doorstop suites, an execution-triage `code_mismatch` verdict; given the 18% agreement rate just reported, this combined count should be treated as a rough signal requiring manual confirmation, not a verified defect count.

Representation-choice agreement. As noted in Section VI, a model's own Gate-1 pick of representation agrees with the independent RSS heuristic's top-3 recommendation only 20% of the time on average. Gate 1 is designed to make representation choice accountable to an external standard precisely because LLMs left to choose freely cluster onto a handful of familiar notations (Section VI); the low agreement rate shows that accountability mechanism and the models' own judgment are, in practice, measuring different things, and a high Gate-1 pass rate should not be read as confirmation that the chosen representation was actually well suited to the requirement.

Groundedness as a systematically missed failure mode. 243 of 496 suites (49%) assert at least one specific value (a timeout, a count, a threshold) that cannot be traced back to the source requirement text (mean 6.1 hallucinated values per affected suite; mean groundedness $M_g = 0.46$ across all judged suites). Because groundedness enters FSA as one of five weighted components ($w_g = 0.15$), a suite can still clear the FSA ≥ 0.50 threshold while being substantially

ungrounded, as long as its other four components score well. We found 22 of 61 Gate-3-passing suites with $M_g < 0.5$ in a preliminary pass over the data, suites the pipeline reports as adequate despite asserting more hallucinated values than grounded ones.

Against the real implementation, directly. Even setting execution and audit reliability aside, the *best-case* agreement between generated tests and real requirement-level behaviour, measured as the share of SRS requirements whose tests reach actually-implemented behaviour, is 54% (DeepSeek-Coder-V2-Lite, doorstop); the ceiling across every model×project pair in this study is just over half.

Summary of Results I and II together. The pipeline reports both-gates pass rates of 25% to 100% depending on model and case study (Table VII), and a representation-paradigm effect that looks like a clean, actionable signal (Fig. 3). Set against real execution, real code behaviour, and an independent heuristic, each of those signals shrinks: 18% audit-execution agreement, 1 to 2 passing tests out of 148 to 315 attempted, 20% representation-choice agreement, and roughly half of all suites carrying at least one hallucinated value. A three-gate, LLM-judged pipeline is not nothing: it is more structured and more falsifiable than a single similarity score, but on this evidence it is not yet a substitute for execution-grounded validation, and should not be reported as one.

VIII. Threats to Validity

Single run per configuration. Every model×unit× representation combination was run once at temperature 0; the underlying analysis explicitly notes that differences of a few FSA points between models are within expected noise and should not be over-interpreted.

Single judge model. All semantic adequacy, groundedness, and code audit judgments were made by one model (`gpt-oss-20b`). We chose a model from a different family than every subject under test to reduce self-preference bias, a judge limitation documented in prior LLM-as-judge work [11], but we did not cross-validate its judgments against a second judge model or human raters beyond the audit-vs-execution check in Section VII, which itself shows that judge's reliability is limited.

Uneven execution coverage. Real test execution was only feasible for doorstop; ventilator and virtual_clinic results rely on the audit proxy, which Section VII shows agrees with execution only 18% of the time on the one case study where both are available. Conclusions drawn from ventilator/virtual_clinic audit data alone should be read as provisional.

Partial model coverage. Gemma-3-27B and DeepSeek-Coder-V2-Lite completed only 6 to 7 suites each, against 58 to 61 for the other eight executed models; Phi-4-14B failed to pass Gate 1 on any attempted unit; Llama-3.3-70B and both closed-source controls (GPT-4o, Claude 3.5 Sonnet) were not executed. The 10-model comparison in this paper is therefore narrower than the 14-model selection funnel that produced it, and entirely open-weight.

Three case studies. doorstop, ventilator, and virtual_clinic differ in size and domain but are three systems; generalizing findings here to SRS documents of very different style, domain, or scale (e.g., safety-critical avionics specifications) should be done cautiously.

IX. Discussion

The clearest actionable finding from Section VI is that *which representation a requirement is tested with matters more than which model generates the test*, a result consistent with the motivating premise of this paper's own taxonomy (Section III), and one that argues for representation-aware tooling over simply swapping in a larger or more code-specialized model.

The more consequential finding, from Section VII, is that this and plausibly other LLM-judge-based evaluation pipelines should not be trusted to report correctness without an execution-grounded check built in and reported alongside the gate scores. We did not find this gap by assuming our framework was flawed; we found it by deliberately building the cross-checks (execution comparison, code audit, independent heuristic) that a pipeline reporting only its own gate scores would never surface on its own. We think this is the more general lesson: any LLM-as-judge evaluation pipeline for generated tests should report at least one such cross-check, not only its own internal pass rates, and groundedness in particular is well-suited to being promoted from a weighted component of a blended score to an independently thresholded gate, given how cleanly it can hide inside a passing FSA score (Section VII).

X. Related Work

Prior work on automated test generation for requirements spans search-based software testing (SBST) approaches, such as EvoSuite [10], that evolve tests against coverage or mutation-based fitness functions without needing a natural-language source, and, more recently, LLM-based generation that consumes requirements or code directly. Roy et al. [3] empirically study LLMs for unit test generation and motivate much of the skepticism toward surface-similarity metrics that this paper builds on. Reflexion-style self-feedback loops [8] are methodologically close to this paper's closed-loop repair step, though applied there to general agentic tasks rather than test-suite adequacy specifically. SWE-bench and SWE-agent [4], [7] establish benchmark-and-agent pairs for a different software-engineering task (issue resolution) but share this paper's concern with evaluating an LLM's output against a real, executable ground truth rather than a static reference. Model licensing and openness considerations in our Section V model-selection funnel draw on the evaluation framework of Luccioni et al. [5]; the open-weight code models in our benchmark are drawn from model families documented in [6], [9], with general LLM behaviour and instruction-tuning background from [1], [2].

XI. Conclusion

We set out to build a careful, multi-gate alternative to text-similarity metrics for evaluating LLM-generated, requirement-derived test suites, and benchmarked it across 10 models and three real SRS/implementation pairs. The resulting comparative findings, that model size and code specialization do not predict adequacy while representation choice does, are useful on their own. But the paper's central result is that the pipeline's own gate-passing, checked against real execution, a code audit, and an independent heuristic, agrees with ground truth far less often than its pass rates alone would suggest. We report this as a finding about the field's current direction, not only about our own pipeline: as LLM-as-judge evaluation becomes the default replacement for text-similarity metrics in test generation research, it needs to be held to the same standard it was introduced to meet, with execution-grounded validity checks reported as a matter of course rather than as an afterthought.

XII. Planned Changes

Table IX collects, in one place, every validity gap this paper measured and the specific change we plan to make in response to it. Each row names the evidence (already reported in Section VII) rather than repeating it, so this table should be read as a punch list rather than a new set of claims.

A. Representation Mapping Rules

The 20% agreement between a model's free Gate-1 choice and the independent RSS heuristic (Section VII) shows the two views of "suitable representation" are, at present, only loosely connected. We plan to formalize explicit mapping rules from requirement dependency type (state, interaction, data, concurrency, as used in the RSS heuristic itself) to a short ranked list of representations, so that representation selection is governed by a documented, inspectable rule set rather than left to either an LLM's free choice or a keyword heuristic alone.

B. Full Execution Coverage

Real execution in this study was only feasible for doorstop; ventilator and virtual_clinic results rely on the weaker audit proxy, which Section VII shows agrees with execution only 18% of the time on the one case study where both are available. The next iteration of this work builds an automatable execution harness for both remaining case studies, so that the 18% audit-execution agreement figure can either be confirmed as a general property of this evaluation approach or shown to be specific to doorstop.

C. System-Level Test Generation

Every suite reported in this paper covers exactly one requirement unit, up to 8 requirements drawn from a single SRS section, in isolation. Nothing in the current framework exercises a flow that spans multiple units, a dependency between two separately specified requirements, an environment or component failure, or a quality attribute (latency, throughput, reliability) that only manifests across the running system rather than inside one function. Closing this gap is the most structurally different piece of planned work, since it requires a ground-truth structure the current unit-level canonical schema (Section IV) does not provide: an explicit coverage denominator at the system level, analogous to what traceability already gives at the unit level.

We are evaluating two candidate ground-truth formats for this purpose, shown in Fig. 4 and summarized below.

Candidate 1: a structured, dimension-based schema. Every test is one cell addressed by a composite id, for example `E2E.F01.web-ui.negative.add-duplicate`, decomposing into a flow, an interface, an input class, and a name. Each cell appears in three places: a core record (preconditions, steps with an expected result per step, test data), a dimension-specific record (one of D1 end-to-end, D2 interaction between two requirements, D3 environment or component failure, or D4 a quality attribute tested below, at, or above its threshold), and an inventory line carrying the requirement references that cell covers. A sync rule, every cell id appears exactly once in the core, once in its dimension, and once in the inventory, makes system-level coverage mechanically checkable the same way unit-level traceability already is in this paper's framework (a pilot inventory built this way holds 189 cells across the four dimensions).

Candidate 2: an industrial, spreadsheet-style sheet. A simpler alternative closer to common ISO/IEC/IEEE 29119 (the international software testing standard) style test-case documentation: one row per test, with id, name, requirement links, precondition, steps, expected result, postcondition, and use case as columns, plus a separate methodology sheet classifying each row as happy-path, negative, or boundary. This format is easier for a human reviewer to read and already separates expected result from postcondition, but it has no explicit coverage-item inventory or denominator, so system-level coverage cannot be computed from it the way it can from Candidate 1, and concrete test-data values are more often left as vague placeholders.

We plan to pilot Candidate 1 first, since its explicit, checkable denominator extends this paper's existing traceability methodology most directly from the unit level to the system level, and to compare it against Candidate 2 on reviewer readability and on whether the heavier structure measurably improves coverage auditability in practice before committing to either format for the full benchmark.

Data and Code Availability

The pipeline, prompts, gate implementation, aggregated results (`suites.csv`, the analysis report), and this paper's own source are published at https://github.com/poojitha376sp/Clean_exp. The planned system-level ground-truth templates discussed in Section XII-C are tracked in the same repository under `paper/`.

References

[1] L. Chen, M. Chen, and J. Zou, "How is ChatGPT's Behavior Changing Over Time?" arXiv preprint arXiv:2307.09009, 2023.

TABLE IX
EVERY VALIDITY GAP MEASURED IN THIS PAPER, AND THE PLANNED CHANGE ADDRESSING IT

Gap	Evidence (Section VII)	Planned change
Gate-passing does not predict execution success	1 to 2 of 148 to 315 generated doorstop tests actually pass; $\rho = 0.433$ between FSA and execution pass rate, $n = 15$	Report an execution-grounded pass rate alongside every gate score, not only on doorstop (see "Full Execution Coverage" below)
Code audit is an unreliable stand-in for execution	Audit agrees with real execution only 18% of the time ($n = 11$)	Replace audit-only results for ventilator and virtual_clinic with real execution, and report audit-execution agreement per project rather than assuming it transfers
Representation choice is not accountable to an external standard	Model's own Gate-1 pick agrees with the independent RSS heuristic's top-3 only 20% of the time	Formalize explicit dependency-type-to-representation mapping rules (see "Representation Mapping Rules" below) rather than leaving the mapping heuristic
Groundedness can hide inside a passing adequacy score	243 of 496 suites (49%) assert an ungrounded value; 22 of 61 Gate-3-passing suites have $M_g < 0.5$	Promote groundedness from a weighted FSA component to its own independently thresholded gate
Evaluation stops at a single requirement unit	Every suite in this study covers one unit of up to 8 requirements in isolation; no end-to-end, interaction, failure, or quality-attribute coverage is measured	Extend the framework to system-level testing with an explicit, multi-dimensional coverage denominator (see "System-Level Test Generation" below)



Every cell carries a composite id, for example `E2E.F01.web-ui.negative.add-duplicate`, and appears once in a shared **Core** record (preconditions, steps, expected result, test data) and once in a shared **Inventory** line (requirement references, the coverage denominator), the sync rule that makes system-level coverage mechanically checkable.

Fig. 4. The four coverage dimensions of the structured ground-truth candidate for planned system-level testing (Section XII-C), with the pilot inventory's cell count per dimension (189 cells total).

[2] L. Ouyang et al., "Training language models to follow instructions with human feedback," Advances in Neural Information Processing Systems, vol. 35, pp. 27730–27744, 2022.

[3] S. Roy et al., "An Empirical Study of Large Language Models for Unit Test Generation," IEEE Transactions on Software Engineering, 2024.

[4] C. E. Jimenez et al., "SWE-bench: Can Language Models Resolve Real-World GitHub Issues?" ICLR 2024.

[5] A. Luccioni et al., "A Framework for Evaluating the Openness and Licensing of Foundation Models," arXiv preprint arXiv:2309.05678, 2023.

[6] R. Li et al., "StarCoder: May the source be with you!" ACM Transactions on Computer-Human Interaction, 2023.

[7] J. Wang et al., "SWE-agent: Agent-Computer Interfaces Enable LLMs to Resolve Software Engineering Issues," arXiv preprint arXiv:2405.15793, 2024.

[8] N. Shinn et al., "Reflexion: Language Agents with Systematic Self-Feedback," NeurIPS 2023.

[9] DeepSeek-AI, "DeepSeek-Coder-V2: Breaking the Barrier of Closed-Source Models in Code Intelligence," arXiv preprint arXiv:2406.11931, 2024.

[10] G. Fraser and A. Arcuri, "EvoSuite: Automatic Test Suite Generation for Object-Oriented Software," in Proc. 19th ACM SIGSOFT Symp. and 13th European Conf. on Foundations of Software Engineering (ESEC/FSE), 2011. DOI: 10.1145/2025113.2025179.

[11] L. Zheng et al., "Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena," arXiv preprint arXiv:2306.05685, 2023.