Program-2

Write a C program to simulate multi-level queue scheduling algorithm considering the following scenario. All the processes in the system are divided into two categories –system processes and user processes. System processes are to be given higher priority than user processes. Use FCFS scheduling for the processes in each queue.

Code:

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#define MAX 100
typedef struct {
  int pid;
  int arrival_time;
  int burst_time;
  int completion_time;
  int turnaround_time;
  int waiting_time;
  char type[10]; // "system" or "user"
} Process;
void sort_by_arrival(Process p[], int n) {
  Process temp;
  for (int i = 0; i < n - 1; i++) {
     for (int j = 0; j < n - i - 1; j++) {
       if (p[j].arrival\_time > p[j + 1].arrival\_time) {
          temp = p[i];
          p[j] = p[j+1];
          p[j + 1] = temp;
       }
void calculate_times(Process p[], int n) {
  int current_time = 0;
  for (int i = 0; i < n; i++) {
     if (current_time < p[i].arrival_time)</pre>
```

```
current_time = p[i].arrival_time;
    p[i].completion_time = current_time + p[i].burst_time;
    p[i].turnaround_time = p[i].completion_time - p[i].arrival_time;
    p[i].waiting_time = p[i].turnaround_time - p[i].burst_time;
    current_time = p[i].completion_time;
  }
}
void print_processes(Process p[], int n, const char *queue_name) {
  printf("\n%s Queue:\n", queue_name);
  printf("PID\tAT\tBT\tCT\tTAT\tWT\n");
  for (int i = 0; i < n; i++) {
     printf("P%d\t%d\t%d\t%d\t%d\t%d\n",
         p[i].pid,
         p[i].arrival time,
         p[i].burst_time,
         p[i].completion_time,
         p[i].turnaround_time,
         p[i].waiting_time);
  }
int main() {
  int n;
  Process system queue[MAX], user queue[MAX];
  int sys_count = 0, user_count = 0;
  printf("Enter total number of processes: ");
  scanf("%d", &n);
  for (int i = 0; i < n; i++) {
    Process temp;
    temp.pid = i + 1;
     printf("\nEnter details for Process %d:\n", temp.pid);
    printf("Arrival Time: ");
     scanf("%d", &temp.arrival_time);
     printf("Burst Time: ");
     scanf("%d", &temp.burst_time);
    printf("Type (system/user): ");
    scanf("%s", temp.type);
    if (strcmp(temp.type, "system") == 0) {
       system_queue[sys_count++] = temp;
     } else if (strcmp(temp.type, "user") == 0) {
```

```
user_queue[user_count++] = temp;
  } else {
     printf("Invalid type! Skipping process.\n");
}
// Sort both queues by arrival time
sort_by_arrival(system_queue, sys_count);
sort_by_arrival(user_queue, user_count);
// Calculate times for each queue
calculate_times(system_queue, sys_count);
// Calculate starting time for user queue
int last_completion_time = 0;
if (sys count > 0)
  last_completion_time = system_queue[sys_count - 1].completion_time;
// Adjust user arrival time to account for idle time if any
for (int i = 0; i < user\_count; i++) {
  if (user_queue[i].arrival_time < last_completion_time)
     user_queue[i].arrival_time = last_completion_time;
}
// Sort again in case arrival times changed
sort_by_arrival(user_queue, user_count);
// Calculate times for user queue
calculate_times(user_queue, user_count);
// Print results
print_processes(system_queue, sys_count, "System");
print_processes(user_queue, user_count, "User");
return 0;
```

Output:

```
Enter total number of processes: 4
Enter details for Process 1:
Arrival Time: 0
Burst Time: 4
Type (system/user): system
Enter details for Process 2:
Arrival Time: 1
Burst Time: 3
Type (system/user): user
Enter details for Process 3:
Arrival Time: 2
Burst Time: 2
Type (system/user): system
Enter details for Process 4:
Arrival Time: 3
Burst Time: 1
Type (system/user): user
System Queue:
PÍD
        ÀΤ
                 ВТ
                         \mathsf{CT}
                                 TAT
                                          WT
Ρ1
        0
                4
                         4
                                          0
                                 4
Р3
        2
                                 4
                                          2
                 2
                         6
User Queue:
PID
        \mathsf{AT}
                 вт
                         \mathsf{CT}
                                 TAT
                                          WT
P2
        6
                 3
                         9
                                  3
                                          0
Р4
                 1
                         10
                                 4
                                          3
        6
Process returned 0 (0x0)
                            execution time : 99.468 s
Press any key to continue.
```