

PS5841

Data Science in Finance & Insurance

Many Trees

Yubo Wang

Autumn 2021

Many Trees: Bagging

- Bagging: Bootstrap Aggregation
 - Generate N different bootstrapped (sample with replacement) training sets from a single data set
 - Fit a tree to each training set
 - Combine the trees to form a single predictive model

$$\hat{f}_{bag}(\mathbf{x}) = \frac{1}{N} \sum_{n=1}^N \hat{f}^n(\mathbf{x})$$

Many Trees: Random Forest

- Random Forest: Bagging with a twist that decorrelates trees
 - Each split use one optimal predictor out of a random subset (of size m) of the full set of predictors (of size p)
 - Typically, $m \approx \sqrt{p}$


Many Trees: Boosting (1)

- Boosting: Sequentially grown trees
 - Each tree is grown using information from previously grown trees
 - Each tree is fit on a modified version of the original data set
 - Learns slowly: slowly improves prediction in areas where it does not perform well (residuals).

Many Trees: Boosting (2)

$$\hat{f}(x)^{(0)} = 0; \quad r_i^{(0)} = y_i \quad \forall i$$

$\hat{f}^{(b)}$ is fit to the
training data
 $(\mathbf{X}, \mathbf{r}^{(b-1)})$



$$\begin{aligned}\hat{f}(x)^{(1)} &= \hat{f}(x)^{(0)} + \lambda \hat{f}^{(1)}(x) = \lambda \hat{f}^{(1)}(x) \\ r_i^{(1)} &= y_i - \hat{f}(x_i)^{(1)} = r_i^{(0)} - \lambda \hat{f}^{(1)}(x_i)\end{aligned}$$

$$\begin{aligned}\hat{f}(x)^{(2)} &= \hat{f}(x)^{(1)} + \lambda \hat{f}^{(2)}(x) \\ &= \lambda \hat{f}^{(1)}(x) + \lambda \hat{f}^{(2)}(x) = \sum_{b=1}^2 \lambda \hat{f}^{(b)}(x)\end{aligned}$$


$$\begin{aligned}r_i^{(2)} &= y_i - \hat{f}(x_i)^{(2)} = y_i - \lambda \hat{f}^{(1)}(x_i) - \lambda \hat{f}^{(2)}(x_i) \\ &= r_i^{(0)} - \lambda \hat{f}^{(1)}(x_i) - \lambda \hat{f}^{(2)}(x_i) = r_i^{(1)} - \lambda \hat{f}^{(2)}(x_i)\end{aligned}$$

Many Trees: Boosting (3)

⋮

$$\hat{f}(x) = \hat{f}^{(N)}(x) = \sum_{n=1}^N \lambda \hat{f}^{(n)}(x)$$

Decision Boundary random forest



That was

