- MODULE Contracts -

EXTENDS Integers,

TLC,

Sequences

CONSTANTS

CSV,

The csv value to use in contracts

Height

The height up to which we run the spec

Channel contracts only ever have two parties

$$Party \triangleq \{ \text{"alice"}, \text{"bob"} \}$$

For the first revocation we only need two keys per party

 $NumKey \triangleq 2$

Set of all keys

 $Key \stackrel{\Delta}{=} \forall p \in Party, k \in 0 ... NumKey - 1 : \langle p, k \rangle$

Value to capture missing CSV in output

 $NoCSV \triangleq CHOOSE \ c : c \notin 0 ... \ CSV$

Multisig outputs without CSV encumberance

 $MultiSigOutput \stackrel{\Delta}{=} \forall a, b \in Party \times Party : \langle a, b, NoCSV \rangle$

Multisig outputs with CSV encumberance

 $MultiSigWithCSVOutput \stackrel{\triangle}{=} \forall a, b \in Party \times Party : \langle a, b, CSV \rangle$

P2PKH outputs, without encumbrance

 $P2PKH \triangleq Key$

 $AllOutput \triangleq MultiSigOutput \cup MultiSigWithCSVOutput \cup P2PKH$

 $NoOutput \stackrel{\triangle}{=} CHOOSE \ o : o \notin AllOutput$

Set of all signatures for all commit txs. The signature in real world is related to the commit transaction, however, leave out this complication of how the signature is generated. If there is a signature by a key on a tx, it is assumed it is correctly signed as per bitcoin's requirements

$$Sig \stackrel{\triangle}{=} \forall p \in Party, k \in 0 ... NumKey - 1 : \langle p, k \rangle$$

Value to capture unsigned transactions

 $NoSig \stackrel{\triangle}{=} CHOOSE \ s : s \notin Sig$

Define the commitment tx type. We don't have HTLCs yet. We also don't filter outputs to the party here. We leave that for actions, or we'll add the filter when needed.

 $CommitmentTx \triangleq [$

 $party \mapsto Party$,

```
outputs \mapsto Seq(AllOutput), \\ local\_sig \mapsto Sig \cup NoSig, \\ remote\_sig \mapsto Sig \cup NoSig
]
VARIABLES \\ commitment\_txs \qquad \text{The set of all commiment transactions for both parties}
vars \triangleq \langle commitment\_txs \rangle
Init \triangleq \\ \land commitment\_txs = \forall \ p \in Party : [p \rightarrow \langle \rangle]
TypeInvariant \triangleq \\ \land commitment\_txs \in CommitmentTx
```