

---

MODULE *BitcoinTransactionsSpec*

---

This *Spec* is used to run a model against the *BitcoinTransactions* module.

By moving the model and the runner here, we allow other modules like *LNContracts* to freely use *BitcoinTransactions* to add models, *Init* conditions etc.

EXTENDS *BitcoinTransactions*

$vars \triangleq \langle chain\_height, transactions, mempool, published \rangle$

$Init \triangleq$

- $\wedge transactions = [id \in TXID \mapsto [inputs \mapsto \langle \rangle, outputs \mapsto \langle \rangle]]$
- $\wedge chain\_height = 0$
- $\wedge mempool = \{\}$
- $\wedge published = \{\}$

$TypeOK \triangleq$

- $\wedge transactions \in [TXID \rightarrow [inputs : Seq(Input), outputs : Seq(Output)]]$
- $\wedge mempool \in SUBSET TXID$
- $\wedge published \in SUBSET TXID$

---

$Next \triangleq$

- $\vee \exists k \in KEY, id \in TXID, a \in AMOUNT :$
- $\vee AddP2WKHCoinbaseToMempool(id, k, a)$
- $\vee \exists keys \in KEY \times KEY, id \in TXID, amount \in AMOUNT :$
- $\vee AddMultisigCoinbaseToMempool(id, keys, amount)$
- $\vee \exists id \in TXID, a \in AMOUNT, k \in KEY, input\_type \in OutputTypes, output\_type \in OutputTypes :$
- $AddSpendTxToMempool(id, k, a, input\_type, output\_type)$
- $\vee ConfirmCoinbaseMempoolTx$

$Spec \triangleq$

- $\wedge Init$
- $\wedge \Box [Next]_{\langle vars \rangle}$

---