ME 599/699 Robot Modeling & Control
Fall 2021

Drive Trains

Hasan A. Poonawala

Department of Mechanical Engineering
University of Kentucky

Email: hasan.poonawala@uky.edu
Web: https://www.engr.uky.edu/~hap

Permanent Magnet DC motors

We consider permanent magnet DC motors. Other kinds include *AC* motors and brushless *DC* motors.

A model for the motor torque is $\tau = K_m i_a$, if the flux in the motor is constant. The current is generated by a voltage source, and has dynamics

$$L \frac{d}{dt} i_a + R i_a = V - V_b, \tag{1}$$

where L is the motor inductance, R is the winding resistance, V_b is the back EMF and is proportional to ω_m, the motor speed.

PMDC Model

The dynamics governing θ_m are

$$\begin{aligned} J_m\ddot{\theta}_m + B_m\dot{\theta}_m &= \tau_m - \tau_l/r && (2)\\ &= K_m i_a - \tau_l/r && (3) \end{aligned}$$

We can rewrite (1) and (5) as

$$\begin{aligned} (Ls+R)I_a(s) &= V(s) - K_b\; s\Theta_m(s), && (4)\\ (J_m s^2 + B_m s)\Theta_m(s) &= K_m I_a(s) - \tau_l(s)/r && (5) \end{aligned}$$

We combine these equations to obtain

$$s\left((Ls+R)(J_m s + B_m) + K_b K_m\right)\Theta_m(s) = K_m V(s) - \frac{(Ls+R)}{r}\tau_l(s). \qquad (6)$$

Fast Electrical Dynamics

The electrical time constant L/R is much smaller than the mechanical time constant J_m/B_m. So, we can divide by R and set L/R to zero, obtaining.

$$s\left((J_m s + B_m) + \frac{K_b K_m}{R}\right)\Theta_m(s) = \frac{K_m}{R}V(s) - \frac{1}{r}\tau_l(s).$$

Setting $u \leftarrow K_m V/R$, and $B \leftarrow B_m + K_b K_m/R$, we obtain the motor equation as

$$J\ddot{\theta}_m + B\dot{\theta}_m = u(t) - \frac{1}{r}\tau_l. \tag{7}$$

Combined Link-Actuator Model

Let's combine the motor m with the link l

$$J_m\ddot{\theta}_m + B\dot{\theta}_m = u(t) - \frac{1}{r}\tau_l \tag{8}$$

$$J_l\ddot{\theta}_l + B_l\dot{\theta}_l = \tau_l \tag{9}$$

Due to the gears, $\dot{\theta}_m = r\dot{\theta}_l$. We eliminate θ_l to obtain

$$\left(J_m r^2 + J_l\right)\ddot{\theta}_l + \left(Br + B_l\right)\dot{\theta}_l = ru \tag{10}$$

The main takeaway is that when r is large, then the link inertia becomes negligible compared to the motor's inertia.