ME 599/699 Robot Modeling & Control Fall 2021

Rotations

Hasan A. Poonawala

Department of Mechanical Engineering University of Kentucky

Email: hasan.poonawala@uky.edu Web: https://www.engr.uky.edu/~hap

A linear transformation from one vector space B to another vector space A may be represented by a matrix T_R^A

- ▶ A linear transformation from one vector space B to another vector space A may be represented by a matrix T^A_B
- ▶ If the basis of space B is $\mathcal{B} = \{e_B^1, e_B^2, \dots, e_B^n\}$, then

$$T_B^A = \begin{bmatrix} \left(e_B^1\right)^A & \left(e_B^2\right)^A & \cdots & \left(e_B^n\right)^A \end{bmatrix}.$$

- ▶ A linear transformation from one vector space B to another vector space A may be represented by a matrix T^A_B
- ▶ If the basis of space B is $\mathcal{B} = \{e_B^1, e_B^2, \dots, e_B^n\}$, then

$$T_B^A = \left[\left(e_B^1 \right)^A \quad \left(e_B^2 \right)^A \quad \cdots \quad \left(e_B^n \right)^A \right].$$

▶ If $(T_B^A)^T$ $T_B^A = I$, then in frame A

- ▶ A linear transformation from one vector space B to another vector space A may be represented by a matrix T^A_B
- ▶ If the basis of space B is $\mathcal{B} = \{e_B^1, e_B^2, \dots, e_B^n\}$, then

$$T_B^A = \left[\left(e_B^1 \right)^A \quad \left(e_B^2 \right)^A \quad \cdots \quad \left(e_B^n \right)^A \right].$$

- ▶ If $(T_B^A)^T$ $T_B^A = I$, then in frame A
 - ightharpoonup Basis ${\cal B}$ is mutually orthogonal

- ▶ A linear transformation from one vector space B to another vector space A may be represented by a matrix T^A_B
- ▶ If the basis of space B is $\mathcal{B} = \{e_B^1, e_B^2, \dots, e_B^n\}$, then

$$T_B^A = \left[\left(e_B^1 \right)^A \quad \left(e_B^2 \right)^A \quad \cdots \quad \left(e_B^n \right)^A \right].$$

- ▶ If $(T_R^A)^T$ $T_R^A = I$, then in frame A
 - ightharpoonup Basis \mathcal{B} is mutually orthogonal
 - ightharpoonup Basis vector in \mathcal{B} are unit norm

- ▶ A linear transformation from one vector space B to another vector space A may be represented by a matrix T^A_B
- ▶ If the basis of space B is $B = \{e_B^1, e_B^2, \dots, e_B^n\}$, then

$$T_B^A = \left[\left(e_B^1 \right)^A \quad \left(e_B^2 \right)^A \quad \cdots \quad \left(e_B^n \right)^A \right].$$

- ▶ If $(T_R^A)^T$ $T_R^A = I$, then in frame A
 - ightharpoonup Basis \mathcal{B} is mutually orthogonal
 - ▶ Basis vector in B are unit norm
- ▶ If det $T_B^A = 1$, then the ordering of the basis of B satisfies some order defined by basis of B

Since the transformation T_B^A is linear, 0 of frame B maps to 0 of frame A.

- Since the transformation T_B^A is linear, 0 of frame B maps to 0 of frame A.
- ▶ Therefore, T_B^A represents a transformation between two cartesian coordinate frames with the same origin

- Since the transformation T_B^A is linear, 0 of frame B maps to 0 of frame A.
- ▶ Therefore, T_B^A represents a transformation between two cartesian coordinate frames with the same origin
- ▶ Since $(T_B^A)^T$ $T_B^A = I$, the magnitude of vectors doesn't change, only the direction

- Since the transformation T_B^A is linear, 0 of frame B maps to 0 of frame A.
- ▶ Therefore, T_B^A represents a transformation between two cartesian coordinate frames with the same origin
- ► Since $(T_B^A)^T T_B^A = I$, the magnitude of vectors doesn't change, only the direction
- ► Therefore, these transformations are rotations, and they form the special orthogonal group SO(3) (in 3D).

Definition (Special Orthogonal group in 3D)

The Special Orthogonal Group SO(3) is the set of matrices $R \in \mathbb{R}^{3 \times 3}$ such that

$$R^T R = Id$$
, and $\det R = 1$

SO(3) is known as the orientation group and the rotation group.

Exercise: Show that SO(3) forms a group under matrix multiplication.

Constructing Rotations/Orientations

► An orientation relative to frame *A* corresponds to an orthonormal set of vectors

Constructing Rotations/Orientations

- ► An orientation relative to frame *A* corresponds to an orthonormal set of vectors
- ▶ If these vectors have coordinates v_1^A , v_2^A , and v_3^A , then $R = \begin{bmatrix} v_1^A & v_2^A & v_3^A \end{bmatrix}$.

Constructing Rotations/Orientations


- ► An orientation relative to frame *A* corresponds to an orthonormal set of vectors
- ▶ If these vectors have coordinates v_1^A , v_2^A , and v_3^A , then $R = \begin{bmatrix} v_1^A & v_2^A & v_3^A \end{bmatrix}$.

$$e_{B}^{1} = \frac{1}{\sqrt{2}} e_{A}^{1} - \frac{1}{\sqrt{2}} e_{A}^{2}$$

$$e_{B}^{2} = \frac{1}{\sqrt{2}} e_{A}^{1} + \frac{1}{\sqrt{2}} e_{A}^{2}$$

$$e_{B}^{3} = 1 \cdot e_{A}^{3}$$

$$\implies R = T_{B}^{A} = \begin{bmatrix} \frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} & 0\\ -\frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} & 0\\ 0 & 0 & 1 \end{bmatrix}$$



Constructing Coordinate Frames

- ► Given any three non-collinear 3D vectors, we may define a rotation matrix by Gram-Schmidt orthonormalization.
- ► Therefore, four non-coplanar points *a*, *b*, *c*, *d* on a rigid body are enough to define a cartesian frame fixed to the body
 - One point becomes the origin
 - ► The remaining three points define a vector relative to the origin point
 - orthonormalize vectors to get vectors defining cartesian frame and its orientation
 - origin + rotation matrix = coordinate of body (frame)

► Rigid bodies correspond to cartesian frames

- ▶ Rigid bodies correspond to cartesian frames
- ► Cartesian frames have a position and orientation

- ► Rigid bodies correspond to cartesian frames
- Cartesian frames have a position and orientation
- Orientations are also a G-Torsor

- Rigid bodies correspond to cartesian frames
- Cartesian frames have a position and orientation
- Orientations are also a G-Torsor
- ► Rotations help us get from one orientation to another (similar to translation vectors for Euclidean points).

- Rigid bodies correspond to cartesian frames
- Cartesian frames have a position and orientation
- Orientations are also a G-Torsor
- Rotations help us get from one orientation to another (similar to translation vectors for Euclidean points).
- ► A rotation relative to a reference defines a new frame; the rotation matrix becomes the 'orientation' coordinate of that frame.

- Rigid bodies correspond to cartesian frames
- Cartesian frames have a position and orientation
- Orientations are also a G-Torsor
- Rotations help us get from one orientation to another (similar to translation vectors for Euclidean points).
- ▶ A rotation relative to a reference defines a new frame; the rotation matrix becomes the 'orientation' coordinate of that frame.
- ▶ We've called this matrix T_B^A , R_B^A , R, T

- Rigid bodies correspond to cartesian frames
- Cartesian frames have a position and orientation
- Orientations are also a G-Torsor
- Rotations help us get from one orientation to another (similar to translation vectors for Euclidean points).
- ▶ A rotation relative to a reference defines a new frame; the rotation matrix becomes the 'orientation' coordinate of that frame.
- We've called this matrix T_B^A , R_B^A , R, T
- ▶ The G-Torsor nature is why SO(3) is called both the rotation group and the orientation group.

- Rigid bodies correspond to cartesian frames
- Cartesian frames have a position and orientation
- Orientations are also a G-Torsor
- Rotations help us get from one orientation to another (similar to translation vectors for Euclidean points).
- ▶ A rotation relative to a reference defines a new frame; the rotation matrix becomes the 'orientation' coordinate of that frame.
- We've called this matrix T_B^A , R_B^A , R, T
- ▶ The G-Torsor nature is why SO(3) is called both the rotation group and the orientation group.
- ► Assigning coordinates to an orientation is the same as defining the rotation that generates that frame relative to a reference.

Consider three frames rotated about each one of the world frame axes by an angle θ .

Consider three frames rotated about each one of the world frame axes by an angle θ . Each rotation is given by


$$R_{\mathsf{x},\theta} = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos(\theta) & -\sin(\theta) \\ 0 & \sin(\theta) & \cos(\theta) \end{bmatrix}$$



Consider three frames rotated about each one of the world frame axes by an angle θ . Each rotation is given by

$$R_{\mathsf{x},\theta} = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos(\theta) & -\sin(\theta) \\ 0 & \sin(\theta) & \cos(\theta) \end{bmatrix}$$

$$R_{y,\theta} = \begin{bmatrix} \cos(\theta) & 0 & \sin(\theta) \\ 0 & 1 & 0 \\ -\sin(\theta) & 0 & \cos(\theta) \end{bmatrix}$$




Consider three frames rotated about each one of the world frame axes by an angle θ . Each rotation is given by

$$R_{\mathsf{x},\theta} = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos(\theta) & -\sin(\theta) \\ 0 & \sin(\theta) & \cos(\theta) \end{bmatrix}$$


$$R_{y,\theta} = \begin{bmatrix} \cos(\theta) & 0 & \sin(\theta) \\ 0 & 1 & 0 \\ -\sin(\theta) & 0 & \cos(\theta) \end{bmatrix}$$


$$R_{z,\theta} = \begin{bmatrix} \cos(\theta) & -\sin(\theta) & 0 \\ \sin(\theta) & \cos(\theta) & 0 \\ 0 & 0 & 1 \end{bmatrix}$$




General Rotations

- We can construct a general rotation using a sequence of basic rotations. (Compare to Euclidean space)
- So, orientation coordinates can be derived by sequences of basic rotations (combined through multiplications).
- For Euclidean vector spaces, the order of a sequence of (vector space) operations didn't matter: v + w = w + v.
- ▶ For rotations, they do. In general, $R_1R_2 \neq R_2R_1$.
- ► One interpretation of the two orders of multiplication is extrinsic vs. intrinsic rotations (next slide)







- A first rigid motion corresponding to rotation R_1 relative to a frame A produces frame B
- A second rigid motion rotation R₂ can be applied relative to either A or B.
- ▶ When applied relative to B, the second rotation is an intrinsic rotation. $R = R_1 R_2$.
- ▶ When applied relative to A, the second rotation is an extrinsic rotation. $R = R_2R_1$.

Euler Angles

- ▶ Euler angles use three basic rotations to define any orientation
- Many possible conventions based on
 - Choice of axes of three basic rotations
 - Sequence of extrinsic vs intrinsic rotations
- See notes and texts for more details

Axis-Angle Formula

Alternatively, we may represent a rotation as a single angle of rotation θ and an axis $\mathbf{k} = \begin{bmatrix} k_1 & k_2 & k_3 \end{bmatrix}^T$, leading to a formula for R:

$$R = I + (\sin \theta)K + (1 - \cos \theta)K^2 \tag{1}$$

where

$$K = \begin{bmatrix} 0 & -k_3 & k_2 \\ k_3 & 0 & -k_1 \\ -k_2 & k_1 & 0 \end{bmatrix},$$

and k has unit norm.

The notes provide another formula where we represent the vector \mathbf{k} using two angles α and β that define basic rotations to produce R .

Change-of-Basis For Orientations

Suppose we define an orientation B relative to a orientation A through a rotation R_B^A .

Suppose we define an orientation B relative to a orientation A through a rotation R_B^A .

Now, someone decides to change the identity element to be orientation C, with coordinate R_C^A (in frame A).

Suppose we define an orientation B relative to a orientation A through a rotation R_B^A .

Now, someone decides to change the identity element to be orientation C, with coordinate R_C^A (in frame A).

Which rotation R_B^C below correctly defines the new orientation of B relative to orientation C?

- $1. \ R_B^C = R_B^A R_A^C$
- $2. R_B^C = R_B^A R_C^A$
- $3. R_B^C = R_A^C R_B^A$
- 4. $R_B^C = R_C^A R_B^A$

Suppose we define an orientation B relative to a orientation A through a rotation R_B^A .

Now, someone decides to change the identity element to be orientation C, with coordinate R_C^A (in frame A).

Which rotation R_B^C below correctly defines the new orientation of B relative to orientation C?

- 1. $R_B^C = R_B^A R_A^C$
- $2. R_B^C = R_B^A R_C^A$
- $3. R_B^C = R_A^C R_B^A$
- $4. R_B^C = R_C^A R_B^A$

How would you pick the right transformation? Why did we not consider R_A^B ?

- For example, imagine you, a driver, and a passenger in a car. Your orientation frames are aligned: Forward: x, upwards: z.
- ▶ When the car stops, the passenger opens the door spins to their right $(R_C^A = R_{z,-90^\circ})$
- You lean back in your driver's seat $(R_R^A = R_{\nu,-20^{\circ}})$
- ▶ What is your orientation according to the passenger?
 - 1. $R_{B}^{C} = R_{B}^{A}R_{A}^{C}$ 2. $R_{B}^{C} = R_{B}^{A}R_{C}^{A}$ 3. $R_{B}^{C} = R_{A}^{C}R_{B}^{A}$ 4. $R_{B}^{C} = R_{C}^{C}R_{B}^{A}$

Rotation matrix R_B^A gives the coordinates of the basis vectors of frames B in A.

Rotation matrix R_B^A gives the coordinates of the basis vectors of frames B in A.

We want to change the frame of these coordinates to frame C.

Rotation matrix R_B^A gives the coordinates of the basis vectors of frames B in A.

We want to change the frame of these coordinates to frame C.

To change the coordinates of vectors from A to C, we must pre-multiply by $\left(R_C^A\right)^{-1}=R_A^C$. So,

$$R_B^C = R_A^C R_B^A$$

.

Alternatively, The rigid motion in A corresponding to moving to frame B is R_B^A ; the rigid motion in frame C corresponding to moving to frame A is R_A^C .

The combined rigid motion in C is achieved by first moving by R_B^A in \mathbf{C} , then moving the result by R_A^C . Therefore,

$$R_B^C = R_A^C R_B^A$$

.

Alternatively, The rigid motion in A corresponding to moving to frame B is R_B^A ; the rigid motion in frame C corresponding to moving to frame A is R_A^C .

The combined rigid motion in C is achieved by first moving by R_B^A in \mathbf{C} , then moving the result by R_A^C . Therefore,

$$R_B^C = R_A^C R_B^A$$

.

► We have looked at transforming points (or orientations) between frames, either as

- We have looked at transforming points (or orientations) between frames, either as
 - ► a rigid motion (coordinates stay in the same frame)

- We have looked at transforming points (or orientations) between frames, either as
 - ▶ a rigid motion (coordinates stay in the same frame)
 - ▶ a change of basis (coordinates are in a new frame)

- We have looked at transforming points (or orientations) between frames, either as
 - a rigid motion (coordinates stay in the same frame)
 - ▶ a change of basis (coordinates are in a new frame)
- Only two frames are involved

- We have looked at transforming points (or orientations) between frames, either as
 - a rigid motion (coordinates stay in the same frame)
 - a change of basis (coordinates are in a new frame)
- Only two frames are involved
- We now look at transforming transformations between frames.

- We have looked at transforming points (or orientations) between frames, either as
 - a rigid motion (coordinates stay in the same frame)
 - a change of basis (coordinates are in a new frame)
- Only two frames are involved
- We now look at transforming transformations between frames.

- We have looked at transforming points (or orientations) between frames, either as
 - a rigid motion (coordinates stay in the same frame)
 - a change of basis (coordinates are in a new frame)
- Only two frames are involved
- We now look at transforming transformations between frames.

Instead of orientation R_B^A in frame A, what if we define **rotation** R^A in frame A.

How do we represent this rotation in frame C?

Change-of-Basis For Rotations

- ▶ The rotation R^A is relative to frame A.
- ightharpoonup Any generic orientation P has coordinates R_P^A in frame A
- ▶ Rotating this orientation results in a new orientation $R^A R_P^A$ in frame A:

$$R_P^A \mapsto R^A R_P^A$$

- ▶ But, note that $R_P^A = R_C^A R_P^C$
- ► Therefore :

$$R_C^A R_P^C \mapsto R^A R_C^A R_P^C$$
, or

$$R_P^C \mapsto \left(R_C^A\right)^{-1} R^A R_C^A R_P^C$$
, or

 \triangleright Therefore, a rotation R^A in frame A becomes a rotation

$$R^C = \left(R_C^A\right)^{-1} R^A R_C^A$$

in frame C.

Summary

- Rotations of bodies (equivalently, cartesian frames) correspond to a specific linear transformation
- ► The matrix representing any rotation belongs to SO(3), a group under matrix multiplication
- ► A rotation defines an orientation (part of the coordinates of a frame), given a reference orientation.
- We may use basic rotations defined about axes to construct any orientation
- ► Changing reference frames requires changing orientations, and also rotations, appropriately