RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Friday, 31 July 2026, 12:30 PM
State	Finished
Completed on	Friday, 31 July 2026, 12:35 PM
Time taken	5 mins 29 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

```
Convert the following algorithm into a program and find its time complexity using the counter method.
void function (int n)
{
    int i= 1;
```

```
    int s =1;
```

```
    while(s <= n)
    {
         i++;
         s += i;
     }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
void function(int n){
    int i=1;
    int s=1;
    int counter=2;
    while(s<=n){
        counter++;
        i++;
        counter++;
        s+=i;
        counter++;

    }
    counter++;
    printf("%d",counter);
}
int main(){
    int n;
    scanf("%d",&n);
    function(n);
    return 0;
}
```


Scanned with OKEN Scanner

	Input	Expected	Got	
✔	9	12	12	✔
✔	4	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Friday, 31 July 2026, 12:15 PM
State	Finished
Completed on	Friday, 31 July 2026, 12:55 PM
Time taken	40 mins 7 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
void func(int n)
{
    int counter=0;
    if(n==1)
    {
         counter++;
     // printf("*");
    }
    else
    {    counter++;
     for(int i=1; i<=n; i++)
     {
         counter++;
       for(int j=1; j<=n; j++)
       {
           counter++;
          //printf("*");
          //printf("*");
           counter++;
           counter++;
          break;

       }
       counter++;
     }
     counter++;
  }
```


Scanned with OKEN Scanner

```
29      printf("%d",counter);
30  }
31  int main() {
32      int n;
33      scanf("%d",&n);
34     func(n);
35      return 0;
36  }
37
38
```

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Friday, 31 July 2026, 12:45 PM
State	Finished
Completed on	Friday, 31 July 2026, 1:06 PM
Time taken	21 mins 34 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
   for (i = 1; i <= num;++i)
   {
    if (num % i== 0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include<stdio.h>
 void Factor(int num)
 {
     int counter=0;
    for (int i = 1; i <= num;++i)
    {
        counter++;
     if (num % i== 0)
        {
            counter++;
          //printf("%d ", i);

        }
        counter++;
     }
     counter++;
     printf("%d",counter);
  }
 int main() {
     int num;
     scanf("%d",&num);
     Factor(num);
     return 0;
 }
```

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔

Scanned with OKEN Scanner

	Input	Expected	Got	
✔	4	12	12	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Friday, 31 July 2026, 1:07 PM
State	Finished
Completed on	Friday, 31 July 2026, 1:14 PM
Time taken	6 mins 56 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time

complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include<stdio.h>
void function(int n)
{
    int c= 0;
    c++;
    for(int i=n/2; i<n; i++) {
        c++;
        for(int j=1; j<n; j = 2 * j) {
            c++;
            for(int k=1; k<n; k = k * 2) {
                c++;
                c++;



            }
            c++;
        }
        c++;
    }
    c++;
    printf("%d",c);
}
int main() {
    int n;
    scanf("%d",&n);
    function(n);
    return 0;
}
```

	Input	Expected	Got	
✔	4	30	30	✔

Scanned with OKEN Scanner

	Input	Expected	Got	
✔	10	212	212	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Sunday, 30 August 2026, 10:15 PM
State	Finished
Completed on	Sunday, 30 August 2026, 10:24 PM
Time taken	9 mins 12 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int v, count = 0;
    int denominations[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};

    scanf("%d", &v);

    for (int i = 0; i < 9; i++) {
        count += v / denominations[i];
        v %= denominations[i];
    }

    printf("%d", count);

    return 0;
}
```

	Input	Expected	Got	
✔	49	5	5	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Scanned with OKEN Scanner

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Sunday, 30 August 2026, 10:18 PM
State	Finished
Completed on	Sunday, 30 August 2026, 10:24 PM
Time taken	6 mins 48 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor g[i], which is the minimum size of a cookie that the child will be content with; and each cookie j has a size s[j]. If s[j] >= g[i], we can assign the cookie j to the child i, and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

3

1 2 3

2

1 1

Output:

1

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

1 <= g.length <= 3 * 10^4

0 <= s.length <= 3 * 10^4

1 <= g[i], s[j] <= 2^31 - 1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int compare(const void *a, const void *b)
{
    return (*(int *)a - *(int *)b);
}

int main()
{
    int n, m, i;


    scanf("%d", &n);

    int g[n];


    for (i = 0; i < n; i++)
    {
        scanf("%d", &g[i]);
    }


    scanf("%d", &m);

    int s[m];


    for (i = 0; i < m; i++)
    {
        scanf("%d", &s[i]);
    }


    qsort(g, n, sizeof(int), compare);
```


Scanned with OKEN Scanner

```
37      qsort(s, m, sizeof(int), compare);
38
39      int child = 0;
40      int cookie = 0;
41      int count = 0;
42
43
44      while (child < n && cookie < m)
45      {
46          if (s[cookie] >= g[child])
47          {
48              count++;
49              child++;
50              cookie++;
51          }
52          else
```

	Input	Expected	Got	
✔	2 1 2 3 1 2 3	2	2	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Sunday, 30 August 2026, 10:21 PM
State	Finished
Completed on	Sunday, 30 August 2026, 10:21 PM
Time taken	34 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a distance to burn out his calories.

If he has eaten i burgers with c calories each, then he has to run at least $3^i * c$ kilometers to burn out the calories. For example, if he ate 3

burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are $(3^0 * 1) + (3^1 * 3) + (3^2 * 2) = 1 + 9 + 18 = 28$.

But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum distance

he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm.Apply greedy approach to solve the problem.

Input Format

First Line contains the number of burgers

Second line contains calories of each burger which is n space-separate integers

Output Format

Print: Minimum number of kilometers needed to run to burn out the calories

Sample Input

```
3
5 10 7
```

Sample Output

```
76
```

For example:

Test	Input	Result
Test Case 1	3 1 3 2	18

Answer: (penalty regime: 0 %)

```
#include<stdio.h>

#include<math.h>

#include<stdlib.h>

int cmp(const void *a, const void *b) { return (*(int*)b -*(int*)a);

}

int main(){

int n,cnt=0;

scanf("%d", &n);

int d[n];

for(int i=0;i<n;i++){

scanf("%d", &d[i]);
```


Scanned with OKEN Scanner

```
22
23  }
24
25  qsort(d,n,sizeof(int),cmp); for(int i=0;i<n;i++){
26
27  cnt += pow(n,i) * d[i];
28
29  }
30
31  printf("%d",cnt);
32
33  return 0;
34
35  }
```

	Test	Input	Expected	Got	
✔	Test Case 1	3 1 3 2	18	18	✔
✔	Test Case 2	4 7 4 9 6	389	389	✔
✔	Test Case 3	3 5 10 7	76	76	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Sunday, 30 August 2026, 10:19 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 11:57 AM
Time taken	30 days 13 hours
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int compare(const void *a, const void *b)
{
    return (*(int *)a - *(int *)b);
}

int main()
{
    int n, i;
    long long sum = 0;

    scanf("%d", &n);

    int arr[n];

    for (i = 0; i < n; i++)
    {
        scanf("%d", &arr[i]);
    }


    qsort(arr, n, sizeof(int), compare);


    for (i = 0; i < n; i++)
    {
        sum += (long long)arr[i] * i;
    }

    printf("%lld", sum);

    return 0;
}
```


Scanned with OKEN Scanner

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔
✔	10 2 2 2 4 4 3 3 5 5 5	191	191	✔
✔	2 45 3	45	45	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Sunday, 30 August 2026, 10:20 PM
State	Finished
Completed on	Sunday, 30 August 2026, 10:22 PM
Time taken	2 mins 21 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int compareAsc(const void *a, const void *b)
{
    return (*(int *)a - *(int *)b);
}

int compareDesc(const void *a, const void *b)
{
    return (*(int *)b - *(int *)a);
}

int main()
{
    int n, i;
    long long sum = 0;

    scanf("%d", &n);

    int array_One[n];
    int array_Two[n];


    for (i = 0; i < n; i++)
    {
        scanf("%d", &array_One[i]);
    }


    for (i = 0; i < n; i++)
    {
        scanf("%d", &array_Two[i]);
    }


    qsort(array_One, n, sizeof(int), compareAsc);


    qsort(array_Two, n, sizeof(int), compareDesc);


    for (i = 0; i < n; i++)
    {
        sum += (long long)array_One[i] * array_Two[i];
    }

    printf("%lld", sum);
```


Scanned with OKEN Scanner

```
49
50      return 0;
51  }
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Sunday, 30 August 2026, 10:26 PM
State	Finished
Completed on	Sunday, 30 August 2026, 10:27 PM
Time taken	19 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement

Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

Input Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int firstZero(int arr[], int low, int high)
{
    if (high >= low)
    {
        int mid = low + (high - low) / 2;

        if ((mid == 0 || arr[mid - 1] == 1) && arr[mid] == 0)
            return mid;

        if (arr[mid] == 1)
            return firstZero(arr, mid + 1, high);
        else
            return firstZero(arr, low, mid - 1);
    }

    return -1;
}

int countZeroes(int arr[], int n)
{
    int first = firstZero(arr, 0, n - 1);

    if (first == -1)
        return 0;

    return n - first;
}

int main()
{
    int n;
    scanf("%d", &n);

    int arr[n];

    for (int i = 0; i < n; i++)
    {
        scanf("%d", &arr[i]);
    }

    printf("%d", countZeroes(arr, n));

    return 0;
}
```


Scanned with OKEN Scanner

	Input	Expected	Got	
✔	5 1 1 1 0 0	2	2	✔
✔	10 1 1 1 1 1 1 1 1 1 1	0	0	✔
✔	8 0 0 0 0 0 0 0 0	8	8	✔
✔	17 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 0 0	2	2	✔

Passed all tests! ✔

Correct

Scanned with OKEN Scanner

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Sunday, 30 August 2026, 10:27 PM
State	Finished
Completed on	Sunday, 30 August 2026, 10:27 PM
Time taken	23 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- $1 <= n <= 5 * 10^4$
- $-2^{31} <= nums[i] <= 2^{31} - 1$

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int countOccurrences(int nums[], int low, int high, int target)
{
    int count = 0;

    for (int i = low; i <= high; i++)
    {
        if (nums[i] == target)
        {
            count++;
        }
    }

    return count;
}

int majorityElement(int nums[], int low, int high)
{
    if (low == high)
    {
        return nums[low];
    }

    int mid = low + (high - low) / 2;

    int leftMajority = majorityElement(nums, low, mid);
    int rightMajority = majorityElement(nums, mid + 1, high);

    if (leftMajority == rightMajority)
    {
        return leftMajority;
    }

    int leftCount = countOccurrences(nums, low, high, leftMajority);
```


Scanned with OKEN Scanner

```
36      int rightCount = countOccurrences(nums, low, high, rightMajority);
37
38      if (leftCount > rightCount)
39      {
40          return leftMajority;
41      }
42      else
43      {
44          return rightMajority;
45      }
46  }
47
48  int main()
49  {
50      int n;
51      scanf("%d", &n);
52
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Sunday, 30 August 2026, 10:28 PM
State	Finished
Completed on	Sunday, 30 August 2026, 10:29 PM
Time taken	17 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement:

Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x.

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

Output Format

First Line Contains Integer – Floor value for x

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int findFloor(int arr[], int low, int high, int x)
{

    if (low > high)
        return -1;


    int mid = low + (high - low) / 2;


    if (arr[mid] == x)
        return arr[mid];


    if (arr[mid] > x)
        return findFloor(arr, low, mid - 1, x);

    int floorValue = findFloor(arr, mid + 1, high, x);


    if (floorValue != -1)
        return floorValue;

    return arr[mid];

}

int main()
{

    int n;
    scanf("%d",&n);
    int arr[n] ;
    for(int i=0;i<n;i++){
        scanf("%d",&arr[i]);
    }
    int x;
scanf("%d",&x);
    int result = findFloor(arr, 0, n - 1, x);

    if (result == -1)
        printf("Floor does not exist\n");
    else
        printf("%d",result);

    return 0;
}
```


Scanned with OKEN Scanner

	Input	Expected	Got	
✔	6 1 2 8 10 12 19 5	2	2	✔
✔	5 10 22 85 108 129 100	85	85	✔
✔	7 3 5 7 9 11 13 15 10	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Sunday, 30 August 2026, 10:29 PM
State	Finished
Completed on	Sunday, 30 August 2026, 10:30 PM
Time taken	18 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement:

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as "No".

Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

Output Format

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value "x")

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>


int findPair(int arr[], int left, int right, int x)
{

    if (left >= right)
        return 0;

    int sum = arr[left] + arr[right];


    if (sum == x)
    {
        printf("%d\n%d",arr[left], arr[right]);
        return 1;
    }


    if (sum > x)
        return findPair(arr, left, right - 1, x);


    return findPair(arr, left + 1, right, x);

}

int main()
{
    int n;
    scanf("%d",&n);
    int arr[n] ;
    for(int i=0;i<n;i++){
        scanf("%d",&arr[i]);
    }
    int x;
scanf("%d",&x);
    if (!findPair(arr, 0, n - 1, x))
        printf("No\n");

    return 0;
}
```


Scanned with OKEN Scanner

	Input	Expected	Got	
✔	4 2 4 8 10 14	4 10	4 10	✔
✔	5 2 4 6 8 10 100	No	No	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Sunday, 30 August 2026, 10:35 PM
State	Finished
Completed on	Sunday, 30 August 2026, 10:35 PM
Time taken	33 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Write a Program to Implement the Quick Sort Algorithm

Input Format:
The first line contains the no of elements in the list-n
The next n lines contain the elements.

Output:
Sorted list of elements

For example:

Input	Result
5 67 34 12 98 78	12 34 67 78 98

Answer:

```c
#include <stdio.h>


void swap(int *a, int *b)
{
    int temp = *a;
    *a = *b;
    *b = temp;
}

int partition(int arr[], int low, int high)
{
    int pivot = arr[high];
    int i = low - 1;

    for (int j = low; j < high; j++)
    {
        if (arr[j] <= pivot)
        {
            i++;
            swap(&arr[i], &arr[j]);
        }
    }

    swap(&arr[i + 1], &arr[high]);

    return i + 1;
}


void quickSort(int arr[], int low, int high)
{
    if (low < high)
    {

        int pi = partition(arr, low, high);


        quickSort(arr, low, pi - 1);

        quickSort(arr, pi + 1, high);
    }
}

void printArray(int arr[], int n)
{
    for (int i = 0; i < n; i++)
        printf("%d ", arr[i]);

    printf("\n");

}
```


Scanned with OKEN Scanner

	Input	Expected	Got	
✔	5 67 34 12 98 78	12 34 67 78 98	12 34 67 78 98	✔
✔	10 1 56 78 90 32 56 11 10 90 114	1 10 11 32 56 56 78 90 90 114	1 10 11 32 56 56 78 90 90 114	✔
✔	12 9 8 7 6 5 4 3 2 1 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Monday, 5 October 2026, 12:05 PM
State	Finished
Completed on	Monday, 5 October 2026, 12:07 PM
Time taken	2 mins 29 secs
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 10.00 out of 10.00

Playing with Numbers:

Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive integer 'n' and two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 and 3.Write any efficient algorithm to find the possible ways.

Example 1:

Input: *6*

Output:*6*

Explanation: *There are 6 ways to 6 represent number with 1 and 3*

1+1+1+1+1+1

3+3

1+1+1+3

1+1+3+1

1+3+1+1

3+1+1+1

Input Format

First Line contains the number n

Output Format

Print: The number of possible ways 'n' can be represented using 1 and 3

Sample Input

6

Sample Output

6

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

long long countWays(int n) {
    if (n < 0) return 0;

    // Allocate DP array for numbers up to n
    long long *dp = (long long *)malloc((n + 1) * sizeof(long long));
    if (dp == NULL) return 0;

    dp[0] = 1; // 1 way to form sum 0

    for (int i = 1; i <= n; i++) {
        long long ways = 0;
        if (i - 1 >= 0) ways += dp[i - 1];
        if (i - 3 >= 0) ways += dp[i - 3];
        dp[i] = ways;
    }

    long long result = dp[n];
    free(dp);
    return result;
}

int main() {
    int n;
```


Scanned with OKEN Scanner

```
    int n;
    if (scanf("%d", &n) == 1) {
        printf("%lld\n", countWays(n));
    }
    return 0;
}
```

	Input	Expected	Got	
✔	6	6	6	✔
✔	25	8641	8641	✔
✔	100	24382819596721629	24382819596721629	✔

Passed all tests! ✔

Correct

Marks for this submission: 10.00/10.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Monday, 5 October 2026, 12:08 PM
State	Finished
Completed on	Monday, 5 October 2026, 12:08 PM
Time taken	24 secs
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 10.00 out of 10.00

Playing with Chessboard:

Ram is given with an n*n chessboard with each cell with a monetary value. Ram stands at the (0,0), that the position of the top left white rook. He is been given a task to reach the bottom right black rook position (n-1, n-1) constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:

Input

3

1 2 4

2 3 4

8 7 1

Output:

19

Explanation:

Totally there will be 6 paths among that the optimal is

Optimal path value:1+2+8+7+1=19

Input Format

First Line contains the integer n

The next n lines contain the n*n chessboard values

Output Format

Print Maximum monetary value of the path

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Helper function to return the maximum of two numbers
int max(int a, int b) {
    return (a > b) ? a : b;
}

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    int grid[n][n];
    int dp[n][n];

    // Read input grid
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            scanf("%d", &grid[i][j]);
        }
    }

    // Initialize the starting point
    dp[0][0] = grid[0][0];

    // Initialize first row (can only be reached from left)
    for (int j = 1; j < n; j++) {
        dp[0][j] = dp[0][j - 1] + grid[0][j];
    }
```


Scanned with OKEN Scanner

```
30
31      // Initialize first column (can only be reached from top)
32      for (int i = 1; i < n; i++) {
33          dp[i][0] = dp[i - 1][0] + grid[i][0];
34      }
35
36      // Fill the DP table
37      for (int i = 1; i < n; i++) {
38          for (int j = 1; j < n; j++) {
39              dp[i][j] = grid[i][j] + max(dp[i - 1][j], dp[i][j - 1]);
40          }
41      }
42
43      // Output maximum monetary path value to destination (n-1, n-1)
44      printf("%d\n", dp[n - 1][n - 1]);
45
46      return 0;
47  }
```

	Input	Expected	Got	
✔	3 1 2 4 2 3 4 8 7 1	19	19	✔
✔	3 1 3 1 1 5 1 4 2 1	12	12	✔
✔	4 1 1 3 4 1 5 7 8 2 3 4 6 1 6 9 0	28	28	✔

Passed all tests! ✔

Correct

Marks for this submission: 10.00/10.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Monday, 5 October 2026, 12:08 PM
State	Finished
Completed on	Monday, 5 October 2026, 12:09 PM
Time taken	28 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

s1	a	g	**g**	**t**	**a**	**b**
s2	**g**	x	**t**	**x**	**a**	**y**	**b**

The length is 4

Solveing it using Dynamic Programming

For example:

Input	Result
aab azb	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <string.h>

// Helper function to return maximum of two integers
int max(int a, int b) {
    return (a > b) ? a : b;
}

int main() {
    char s1[1005], s2[1005];

    // Read the two input strings
    if (scanf("%s %s", s1, s2) != 2) return 0;

    int n = strlen(s1);
    int m = strlen(s2);

    int dp[n + 1][m + 1];

    // Fill DP table
    for (int i = 0; i <= n; i++) {
        for (int j = 0; j <= m; j++) {
            if (i == 0 || j == 0) {
                dp[i][j] = 0;
            } else if (s1[i - 1] == s2[j - 1]) {
                dp[i][j] = 1 + dp[i - 1][j - 1];
            } else {
                dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
            }
        }
    }

    // Output length of LCS
    printf("%d\n", dp[n][m]);

    return 0;
```


Scanned with OKEN Scanner

```
36          return 0;
37      }
```

	Input	Expected	Got	
✔	aab azb	2	2	✔
✔	ABCD ABCD	4	4	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Monday, 5 October 2026, 12:09 PM
State	Finished
Completed on	Monday, 5 October 2026, 12:10 PM
Time taken	30 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Problem statement:

Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:9

Sequence:[-1,3,4,5,2,2,2,2,3]

the subsequence is [-1,2,2,2,2,3]

Output:6

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n <= 0) return 0;

    int arr[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    int dp[n];
    int max_len = 1;

    // Every element is a non-decreasing subsequence of length 1 initially
    for (int i = 0; i < n; i++) {
        dp[i] = 1;
    }

    // Dynamic Programming to find the maximum length
    for (int i = 1; i < n; i++) {
        for (int j = 0; j < i; j++) {
            // Non-decreasing condition: arr[i] >= arr[j]
            if (arr[i] >= arr[j] && dp[i] < dp[j] + 1) {
                dp[i] = dp[j] + 1;
            }
        }
        if (dp[i] > max_len) {
            max_len = dp[i];
        }
    }

    printf("%d\n", max_len);

    return 0;
}
```

	Input	Expected	Got	
✔	9 -1 3 4 5 2 2 2 2 3	6	6	✔
✔	7 1 2 2 4 5 7 6	6	6	✔

Scanned with OKEN Scanner

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Monday, 5 October 2026, 12:11 PM
State	Finished
Completed on	Monday, 5 October 2026, 12:12 PM
Time taken	1 min 10 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n <= 0) return 0;

    int arr[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    int duplicate = -1;

    // O(n^2) Brute Force Approach with O(1) Space Complexity
    for (int i = 0; i < n; i++) {
        for (int j = i + 1; j < n; j++) {
            if (arr[i] == arr[j]) {
                duplicate = arr[i];
                break;
            }
        }
        if (duplicate != -1) break;
    }

    if (duplicate != -1) {
        printf("%d\n", duplicate);
    }

    return 0;
}
```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔

Scanned with OKEN Scanner

	Input	Expected	Got	
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Monday, 5 October 2026, 12:12 PM
State	Finished
Completed on	Monday, 5 October 2026, 12:16 PM
Time taken	4 mins 5 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int findDuplicate(int arr[], int n) {
    // Floyd's Cycle Finding Algorithm (Tortoise and Hare)
    int slow = arr[0];
    int fast = arr[0];

    // Phase 1: Detect cycle
    do {
        slow = arr[slow];
        fast = arr[arr[fast]];
    } while (slow != fast);

    // Phase 2: Find entrance to the cycle
    slow = arr[0];
    while (slow != fast) {
        slow = arr[slow];
        fast = arr[fast];
    }

    return slow;
}

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n <= 0) return 0;

    int arr[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    printf("%d\n", findDuplicate(arr, n));

    return 0;
}
```


Scanned with OKEN Scanner

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Monday, 5 October 2026, 12:16 PM
State	Finished
Completed on	Monday, 5 October 2026, 12:17 PM
Time taken	41 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

void findIntersection(int arr1[], int n1, int arr2[], int n2) {
    int first = 1; // Flag to handle spacing

    // O(m * n) Brute force approach
    for (int i = 0; i < n1; i++) {
        for (int j = 0; j < n2; j++) {
            if (arr1[i] == arr2[j]) {
                if (!first) {
                    printf(" ");
                }
                printf("%d", arr1[i]);
                first = 0;
```


Scanned with OKEN Scanner

```
                    break; // Break inner loop to prevent duplicates if any
                }
            }
        }
        printf("\n");
}

int main() {
    int t;
    if (scanf("%d", &t) != 1) return 0;

    while (t--) {
        int n1, n2;

        // Read N1 and elements of first array
        if (scanf("%d", &n1) != 1) return 0;
        int arr1[n1];
        for (int i = 0; i < n1; i++) {
            scanf("%d", &arr1[i]);
        }

        // Read N2 and elements of second array
        if (scanf("%d", &n2) != 1) return 0;
        int arr2[n2];
        for (int j = 0; j < n2; j++) {
            scanf("%d", &arr2[j]);
        }

        findIntersection(arr1, n1, arr2, n2);
    }

    return 0;
}
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Monday, 5 October 2026, 12:18 PM
State	Finished
Completed on	Monday, 5 October 2026, 12:19 PM
Time taken	1 min 28 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

void findIntersection(int arr1[], int n1, int arr2[], int n2) {
    int i = 0, j = 0;
    int first = 1;

    // Two-pointer approach since both arrays are sorted
    while (i < n1 && j < n2) {
        if (arr1[i] < arr2[j]) {
            i++;
        } else if (arr2[j] < arr1[i]) {
            j++;
        } else {
            // Elements match
            if (!first) {
                printf(" ");
            }
            printf("%d", arr1[i]);
            first = 0;
```


Scanned with OKEN Scanner

```
            i++;
            j++;
        }
    }
    printf("\n");
}

int main() {
    int t;
    if (scanf("%d", &t) != 1) return 0;

    while (t--) {
        int n1, n2;

        // Read N1 and elements of first array
        if (scanf("%d", &n1) != 1) return 0;
        int arr1[n1];
        for (int i = 0; i < n1; i++) {
            scanf("%d", &arr1[i]);
        }

        // Read N2 and elements of second array
        if (scanf("%d", &n2) != 1) return 0;
        int arr2[n2];
        for (int j = 0; j < n2; j++) {
            scanf("%d", &arr2[j]);
        }

        findIntersection(arr1, n1, arr2, n2);
    }

    return 0;
}
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Monday, 5 October 2026, 12:20 PM
State	Finished
Completed on	Monday, 5 October 2026, 12:20 PM
Time taken	33 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int findPairWithDifference(int arr[], int n, int k) {
    // O(n^2) Brute Force Approach
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (i != j && (arr[j] - arr[i] == k)) {
                return 1;
            }
        }
    }
    return 0;
}

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n <= 0) return 0;

    int arr[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    int k;
    scanf("%d", &k);

    printf("%d\n", findPairWithDifference(arr, n, k));

    return 0;
}
```


Scanned with OKEN Scanner

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✔
✔	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

B Poornasree 251001182-2025-IT

B2

Started on	Monday, 5 October 2026, 12:20 PM
State	Finished
Completed on	Monday, 5 October 2026, 12:21 PM
Time taken	31 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int findPairWithDifference(int arr[], int n, int k) {
    int i = 0, j = 1;

    // Two-pointer approach on a sorted array
    while (i < n && j < n) {
        int diff = arr[j] - arr[i];

        if (i != j && diff == k) {
            return 1;
        } else if (diff < k) {
            j++;
        } else {
            i++;
        }
    }

    return 0;
}

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n <= 0) return 0;

    int arr[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    int k;
    scanf("%d", &k);
```


Scanned with OKEN Scanner

```
33
34      printf("%d\n", findPairWithDifference(arr, n, k));
35
36      return 0;
37  }
```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✔
✔	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner