S.No: 1	Exp. Name: ***Program to implement AVL tree and its operations***	**Date: 2026-09-03**

Aim:

Write a program to create an AVL tree using a provided set of elements stored in a file. Implement operations for inserting and deleting elements from the AVL tree. After constructing the tree, output the contents of the tree in in-order traversal to a new file.

Note: Refer to visible test cases for better understanding.

Source Code:

ID: 25B01A1243

2025-2029-IT-A

Shri Vishnu Engineering College for Women (Autonomous)

avl_tree.c

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <stdbool.h>

typedef struct Node {
    int key;
    struct Node *left;
    struct Node *right;
    int height;
} Node;

int height(Node *N) {
    if (N == NULL) return 0;
    return N->height;
}

int max(int a, int b) {
    return (a > b)? a : b;
}

Node* newNode(int key) {
    Node* node = (Node*)malloc(sizeof(Node));
    node->key = key;
    node->left = node->right = NULL;
    node->height = 1;
    return node;
}

Node* rightRotate(Node *y) {
    Node *x = y->left;
    Node *T2 = x->right;

    x->right = y;
    y->left = T2;

    y->height = max(height(y->left), height(y->right)) + 1;
    x->height = max(height(x->left), height(x->right)) + 1;

    return x;
}

Node* leftRotate(Node *x) {
    Node *y = x->right;
```

```
    Node *T2 = y->left;

    y->left = x;
    x->right = T2;

    x->height = max(height(x->left), height(x->right)) + 1;
    y->height = max(height(y->left), height(y->right)) + 1;

    return y;
}

int getBalance(Node *N) {
    if (N == NULL) return 0;
    return height(N->left) - height(N->right);
}

Node* insert(Node* node, int key) {
    if (node == NULL)
        return newNode(key);

    if (key < node->key)
        node->left = insert(node->left, key);
    else if (key > node->key)
        node->right = insert(node->right, key);
    else
        return node;

    node->height = 1 + max(height(node->left), height(node->right));

    int balance = getBalance(node);

    if (balance > 1 && key < node->left->key)
        return rightRotate(node);

    if (balance < -1 && key > node->right->key)
        return leftRotate(node);

    if (balance > 1 && key > node->left->key) {
        node->left = leftRotate(node->left);
        return rightRotate(node);
    }

    if (balance < -1 && key < node->right->key) {
        node->right = rightRotate(node->right);
        return leftRotate(node);
    }
```

```
    return node;
}

Node* minValueNode(Node* node) {
    Node* current = node;
    while (current->left)
        current = current->left;
    return current;
}

Node* deleteNode(Node* root, int key, int *found) {
    if (!root) return root;

    if (key < root->key)
        root->left = deleteNode(root->left, key, found);
    else if (key > root->key)
        root->right = deleteNode(root->right, key, found);
    else {
        *found = 1;
        if (!root->left ||!root->right) {
            Node *temp = root->left? root->left : root->right;

            if (!temp) {
                temp = root;
                root = NULL;
            } else {
                *root = *temp;
            }
            free(temp);
        } else {
            Node* temp = minValueNode(root->right);
            root->key = temp->key;
            root->right = deleteNode(root->right, temp->key, found);
        }
    }

    if (!root) return root;

    root->height = 1 + max(height(root->left), height(root->right));

    int balance = getBalance(root);

    if (balance > 1 && getBalance(root->left) >= 0)
        return rightRotate(root);
```

```
    if (balance > 1 && getBalance(root->left) < 0) {
        root->left = leftRotate(root->left);
        return rightRotate(root);
    }

    if (balance < -1 && getBalance(root->right) <= 0)
        return leftRotate(root);

    if (balance < -1 && getBalance(root->right) > 0) {
        root->right = rightRotate(root->right);
        return leftRotate(root);
    }

    return root;
}

void inorder(Node *root, FILE *out) {
    if (root) {
        inorder(root->left, out);
        fprintf(out, "%d ", root->key);
        inorder(root->right, out);
    }
}

void printInorder(Node *root) {
    FILE *temp = tmpfile();
    inorder(root, temp);
    rewind(temp);
    int x;
    while (fscanf(temp, "%d ", &x) == 1) {
        printf("%d ", x);
    }
    printf("\n");
    fclose(temp);
}

int main() {
    Node *root = NULL;
    char inputFile[20];
    printf("Input file name: ");
    scanf("%s", inputFile);
    FILE *in = fopen(inputFile, "r");
    if (!in) {
        printf("Error opening input file\n");
        return 1;
    }
```

```
    int val;
    char line[256];
    fgets(line, sizeof(line), in);
    while (fscanf(in, "%d", &val)!= EOF) {
        root = insert(root, val);
    }
    fclose(in);

    printf("In-order traversal:\n");
    printInorder(root);

    int choice, key;
    while (1) {
        printf("1. Insert\n2. Delete\n3. Write to file and exit\nChoice:
");
        scanf("%d", &choice);
        switch (choice) {
            case 1:
                printf("Element: ");
                scanf("%d", &key);
                root = insert(root, key);
                printf("In-order traversal:\n");
                printInorder(root);
                break;
            case 2:
                printf("Element: ");
                scanf("%d", &key);
                int found = 0;
                root = deleteNode(root, key, &found);
                if (found)
                    printf("Deleted %d\n", key);
                else
                    printf("%d not found\n", key);
                printf("In-order traversal:\n");
                printInorder(root);
                break;
            case 3: {
                char outputFile[100];
                printf("Output file name: ");
                scanf("%s", outputFile);
                FILE *out = fopen(outputFile, "w");
                if (!out) {
                    printf("Error opening output file\n");
                    return 1;
                }
```

```
                inorder(root, out);
                fprintf(out, "\n");
                fclose(out);
                printf("AVL Tree written to file\n");
                return 0;
            }
            default:
                printf("Invalid choice\n");
        }
    }
}
```

input1.txt

```
5
1 2 3 4 5
```

input2.txt

```
6
12 24 36 48 60 72
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
Input file name:
inputfile1.txt
Error opening input file

Test Case - 2
User Output
Input file name:
input1.txt
In-order traversal:
1 2 3 4 5

1. Insert
2. Delete
3. Write to file and exit
Choice:
1
Element:
10
In-order traversal:
1 2 3 4 5 10
1. Insert
2. Delete
3. Write to file and exit
Choice:
2
Element:
100
100 not found
In-order traversal:
1 2 3 4 5 10
1. Insert
2. Delete
3. Write to file and exit
Choice:
2
Element:
3
Deleted 3
In-order traversal:
1 2 4 5 10
1. Insert
2. Delete
3. Write to file and exit
Choice:
3
Output file name:
myoutput.txt
AVL Tree written to file

Test Case - 3
User Output
Input file name:

input2.txt
In-order traversal:
12 24 36 48 60 72
1. Insert
2. Delete
3. Write to file and exit
Choice:
1
Element:
108
In-order traversal:
12 24 36 48 60 72 108
1. Insert
2. Delete
3. Write to file and exit
Choice:
1
Element:
120
In-order traversal:
12 24 36 48 60 72 108 120
1. Insert
2. Delete
3. Write to file and exit
Choice:
1
Element:
144
In-order traversal:
12 24 36 48 60 72 108 120 144
1. Insert
2. Delete
3. Write to file and exit
Choice:
2
Element:
36
Deleted 36
In-order traversal:
12 24 48 60 72 108 120 144
1. Insert
2. Delete

```
3. Write to file and exit
Choice:
2
Element:
48
Deleted 48
In-order traversal:
12 24 60 72 108 120 144
1. Insert
2. Delete
3. Write to file and exit
Choice:
10
Invalid choice
1. Insert
2. Delete
3. Write to file and exit
Choice:
2
Element:
1440
1440 not found
In-order traversal:
12 24 60 72 108 120 144
1. Insert
2. Delete
3. Write to file and exit
Choice:
15
Invalid choice
1. Insert
2. Delete
3. Write to file and exit
Choice:
3
Output file name:
outputfile.txt
AVL Tree written to file
```

S.No: 2	Exp. Name: ***Operation of B-Tree - Insertion, Deletion and Search***	**Date: 2026-09-26**

Aim:

Write a C program to construct a B-Tree of a given minimum degree. First, insert a list of keys into the B-Tree and print the inorder traversal after all insertions. Then, delete a given set of keys from the B-Tree and again print the inorder traversal. Finally, search for a specific key in the current B-Tree and print whether it is found or not.

Input Format:

- The first line contains a single integer t, the minimum degree of the B-Tree.
- The second line contains an integer n, representing the number of keys to be inserted.
- The third line contains n space-separated integers — the keys to be inserted into the B-Tree.
- The fourth line contains an integer d, the number of keys to delete.
- The fifth line contains d space-separated integers — the keys to be deleted from the B-Tree.
- The sixth line contains a single integer k — the key to be searched in the B-Tree.

Output Format:

- The first line of output should display the inorder traversal of the B-Tree after all insertions, with each key separated by a space.
- The second line should display the inorder traversal of the B-Tree after all deletions, with each key separated by a space.
- The third line should print **Found** if the search key exists in the B-Tree. If the key is not present, print **Not Found** instead.

Note: Refer to the test cases for better understanding.

Source Code:

Btreemain.c

```
#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>

typedef struct BTreeNode {
    int *keys;
    int t;
    struct BTreeNode **C;
    int n;
    bool leaf;
} BTreeNode;

// Create a new node
BTreeNode* createNode(int t, bool leaf) {
    BTreeNode* node = (BTreeNode*)malloc(sizeof(BTreeNode));
    node->t = t;
    node->leaf = leaf;
    node->keys = (int*)malloc((2 * t - 1) * sizeof(int));
    node->C = (BTreeNode**)malloc((2 * t) * sizeof(BTreeNode*));
    node->n = 0;
    return node;
}

// Inorder traversal (no trailing dot)
void inorder(BTreeNode* root) {
    if (!root) return;
    for (int i = 0; i < root->n; i++) {
        if (!root->leaf)
            inorder(root->C[i]);
        printf("%d ", root->keys[i]);
    }
    if (!root->leaf)
        inorder(root->C[root->n]);
}

// Search a key
bool search(BTreeNode* root, int k) {
    int i = 0;
    while (i < root->n && k > root->keys[i])
        i++;
    if (i < root->n && root->keys[i] == k)
        return true;
    if (root->leaf)
        return false;
```

```
    return search(root->C[i], k);
}

// Split full child
void splitChild(BTreeNode* x, int i) {
    int t = x->t;
    BTreeNode* y = x->C[i];
    BTreeNode* z = createNode(t, y->leaf);
    z->n = t - 1;
    for (int j = 0; j < t - 1; j++)
        z->keys[j] = y->keys[j + t];
    if (!y->leaf) {
        for (int j = 0; j < t; j++)
            z->C[j] = y->C[j + t];
    }
    y->n = t - 1;
    for (int j = x->n; j >= i + 1; j--)
        x->C[j + 1] = x->C[j];
    x->C[i + 1] = z;
    for (int j = x->n - 1; j >= i; j--)
        x->keys[j + 1] = x->keys[j];
    x->keys[i] = y->keys[t - 1];
    x->n++;
}

// Insert into non-full node
void insertNonFull(BTreeNode* x, int k) {
    int i = x->n - 1;
    if (x->leaf) {
        while (i >= 0 && k < x->keys[i]) {
            x->keys[i + 1] = x->keys[i];
            i--;
        }
        x->keys[i + 1] = k;
        x->n++;
    } else {
        while (i >= 0 && k < x->keys[i])
            i--;
        i++;
        if (x->C[i]->n == 2 * x->t - 1) {
            splitChild(x, i);
            if (k > x->keys[i])
                i++;
        }
        insertNonFull(x->C[i], k);
    }
```

```
}

// Insert key into tree
void insert(BTreeNode** rootRef, int k) {
    BTreeNode* r = *rootRef;
    if (r->n == 2 * r->t - 1) {
        BTreeNode* s = createNode(r->t, false);
        s->C[0] = r;
        splitChild(s, 0);
        int i = (k > s->keys[0]) ? 1 : 0;
        insertNonFull(s->C[i], k);
        *rootRef = s;
    } else {
        insertNonFull(r, k);
    }
}

// Get predecessor
int getPred(BTreeNode* x) {
    while (!x->leaf)
        x = x->C[x->n];
    return x->keys[x->n - 1];
}

// Get successor
int getSucc(BTreeNode* x) {
    while (!x->leaf)
        x = x->C[0];
    return x->keys[0];
}

// Merge two children
void merge(BTreeNode* x, int idx) {
    BTreeNode* c1 = x->C[idx];
    BTreeNode* c2 = x->C[idx + 1];
    int t = x->t;
    c1->keys[t - 1] = x->keys[idx];
    for (int i = 0; i < c2->n; ++i)
        c1->keys[i + t] = c2->keys[i];
    if (!c1->leaf) {
        for (int i = 0; i <= c2->n; ++i)
            c1->C[i + t] = c2->C[i];
    }
    for (int i = idx + 1; i < x->n; ++i)
        x->keys[i - 1] = x->keys[i];
    for (int i = idx + 2; i <= x->n; ++i)
```

```
        x->C[i - 1] = x->C[i];
    c1->n += c2->n + 1;
    x->n--;
    free(c2);
}

// Fill child if less than t-1 keys
void fill(BTreeNode* x, int idx) {
    int t = x->t;
    if (idx > 0 && x->C[idx - 1]->n >= t) {
        BTreeNode* child = x->C[idx];
        BTreeNode* sibling = x->C[idx - 1];
        for (int i = child->n - 1; i >= 0; --i)
            child->keys[i + 1] = child->keys[i];
        if (!child->leaf) {
            for (int i = child->n; i >= 0; --i)
                child->C[i + 1] = child->C[i];
        }
        child->keys[0] = x->keys[idx - 1];
        if (!child->leaf)
            child->C[0] = sibling->C[sibling->n];
        x->keys[idx - 1] = sibling->keys[sibling->n - 1];
        child->n += 1;
        sibling->n -= 1;
    } else if (idx < x->n && x->C[idx + 1]->n >= t) {
        BTreeNode* child = x->C[idx];
        BTreeNode* sibling = x->C[idx + 1];
        child->keys[child->n] = x->keys[idx];
        if (!child->leaf)
            child->C[child->n + 1] = sibling->C[0];
        x->keys[idx] = sibling->keys[0];
        for (int i = 1; i < sibling->n; ++i)
            sibling->keys[i - 1] = sibling->keys[i];
        if (!sibling->leaf) {
            for (int i = 1; i <= sibling->n; ++i)
                sibling->C[i - 1] = sibling->C[i];
        }
        child->n += 1;
        sibling->n -= 1;
    } else {
        if (idx != x->n)
            merge(x, idx);
        else
            merge(x, idx - 1);
    }
}
```

```
// Remove key from tree
void removeFromNode(BTreeNode* x, int k) {
    int idx = 0;
    while (idx < x->n && x->keys[idx] < k)
        ++idx;
    if (idx < x->n && x->keys[idx] == k) {
        if (x->leaf) {
            for (int i = idx + 1; i < x->n; ++i)
                x->keys[i - 1] = x->keys[i];
            x->n--;
        } else {
            if (x->C[idx]->n >= x->t) {
                int pred = getPred(x->C[idx]);
                x->keys[idx] = pred;
                removeFromNode(x->C[idx], pred);
            } else if (x->C[idx + 1]->n >= x->t) {
                int succ = getSucc(x->C[idx + 1]);
                x->keys[idx] = succ;
                removeFromNode(x->C[idx + 1], succ);
            } else {
                merge(x, idx);
                removeFromNode(x->C[idx], k);
            }
        }
    } else {
        if (x->leaf)
            return;
        bool flag = (idx == x->n);
        if (x->C[idx]->n < x->t)
            fill(x, idx);
        if (flag && idx > x->n)
            removeFromNode(x->C[idx - 1], k);
        else
            removeFromNode(x->C[idx], k);
    }
}

// Delete key wrapper
void deleteKey(BTreeNode** rootRef, int k) {
    BTreeNode* r = *rootRef;
    removeFromNode(r, k);
    if (r->n == 0) {
        BTreeNode* tmp = r;
        if (r->leaf)
            *rootRef = NULL;
```

```
        else
            *rootRef = r->C[0];
        free(tmp);
    }
}

// Main function with test case support
int main() {
    int t;
    scanf("%d", &t);
    BTreeNode* root = createNode(t, true);
    int n, val;
    scanf("%d", &n);
    for (int i = 0; i < n; i++) {
        scanf("%d", &val);
        insert(&root, val);
    }
    inorder(root);
    int d;
    scanf("%d", &d);
    for (int i = 0; i < d; i++) {
        scanf("%d", &val);
        deleteKey(&root, val);
    }
    inorder(root);
    int target;
    scanf("%d\n", &target);
    if (search(root, target))
        printf("Found\n");
    else
        printf("Not Found\n");

    return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
2
7
10 20 5 6 12 30 7

3
6 30 100
12
5 6 7 10 12 20 30
5 7 10 12 20
Found

Test Case - 2
User Output
2
6
8 3 10 1 6 14
2
1 3
2
1 3 6 8 10 14
6 8 10 14
Not Found

S.No: 3	Exp. Name: ***Min Heap Operations***	**Date: 2026-09-05**

Aim:

Write a C program to implement a Min Heap of integers. The program should first read a list of integers and insert them into the heap while maintaining the min-heap property. It should then read the number of deletions to perform, delete the root (minimum element) that many times, and display the heap both before and after the deletions.

Input Format:

- The first line contains an integer n, representing the number of elements to insert into the heap.
- The second line contains n space-separated integers — the values to insert into the heap.
- The third line contains an integer k, representing the number of times the root (minimum element) should be deleted from the heap.

Output Format:

- The first line displays the space-separated heap contents after all insertions.
- The second line displays the space-separated heap contents after performing k deletions of the root element.

Note: Refer to the test cases for better understanding.

Source Code:

minheap.c

```
#include <stdio.h>
void swap(int *a, int *b) {
    int temp = *a;
    *a = *b;
    *b = temp;
}
void heapifyUp(int heap[], int index) {
    while (index > 0) {
        int parent = (index - 1) / 2;
        if (heap[parent] > heap[index]) {
            swap(&heap[parent], &heap[index]);
            index = parent;
        } else {
            break;
        }}}
void heapifyDown(int heap[], int n, int index) {
    int smallest = index;
    int left = 2 * index + 1;
    int right = 2 * index + 2;
    if (left < n && heap[left] < heap[smallest]) {
        smallest = left;
    }
    if (right < n && heap[right] < heap[smallest]) {
        smallest = right;
    }
    if (smallest != index) {
        swap(&heap[index], &heap[smallest]);
        heapifyDown(heap, n, smallest);
    }
}
void insert(int heap[], int *n, int value) {
    heap[*n] = value;
    (*n)++;
    heapifyUp(heap, *n - 1);
}
void deleteMin(int heap[], int *n) {
    if (*n <= 0) return;
    heap[0] = heap[*n - 1];
    (*n)--;
    heapifyDown(heap, *n, 0);
}
void printArray(int arr[], int size) {
    for (int i = 0; i < size; i++) {
        printf("%d", arr[i]);
```

```
        if (i < size ) {
            printf(" ");
        }
    }
    printf("\n");
}
int main() {
    int n, k;
    if (scanf("%d", &n) != 1) return 0;
    int heap[1000];
    int size = 0;
    for (int i = 0; i < n; i++) {
        int val;
        scanf("%d", &val);
        insert(heap, &size, val);
    }
    scanf("%d", &k);
    printArray(heap, size);
    for (int i = 0; i < k; i++) {
        deleteMin(heap, &size);
    }
    printArray(heap, size);
    return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
5
20 15 30 5 10
2
5 10 30 20 15
15 20 30

Test Case - 2
User Output
8
70 10 90 20 60 80 30 40

4
10 20 30 40 60 90 80 70
60 70 80 90

S.No: 4	Exp. Name: ***Max Heap Operations***	**Date: 2026-09-05**

Aim:

Write a C program to implement a Max Heap. Insert a given list of integers into the heap while maintaining the max-heap property. Then, delete the root element (i.e., the maximum element) a specified number of times. Display the heap after all insertions and again after the deletions.

Input Format:

- The first line contains an integer n, the number of elements to insert into the heap.
- The second line contains n space-separated integers representing the values to be inserted.
- The third line contains an integer k, the number of times the root element (maximum) should be deleted.

Output Format:

- The first line displays the space-separated heap contents after all insertions.
- The second line displays the space-separated heap contents after performing k deletions of the root element.

Note: Refer to the test cases for better understanding.

Source Code:

ID: 25B01A1243

Shri Vishnu Engineering College for Women (Autonomous)

maxheap.c

```
#include<stdio.h>
#define MAX 20
int heap[MAX];
int size=0;
void swap(int *a,int *b){
        int temp=*a;
        *a=*b;
        *b=temp;
}
void heapifyup(int index){
        while(index>0){
                int parent=(index-1)/2;
                if(heap[index]>heap[parent]){
                        swap(&heap[index],&heap[parent]);
                        index=parent;
                }else{
                        break;
                }}}
void heapifydown(int index){
        while(1){
                int left=2*index+1;
                int right=2*index+2;
                int largest=index;
                if(left<size&&heap[left]>heap[largest]){
                        largest=left;
                }
                if(right<size&&heap[right]>heap[largest]){
                        largest=right;
                }
                if(index!=largest){
                        swap(&heap[index],&heap[largest]);
                        index=largest;
                }else{
                        break;
                }
        }
}
void insert(int value){
        heap[size]=value;
        heapifyup(size);
        size++;
}
void deletemax(){
        if(size==0)return;
```

```
        heap[0]=heap[size-1];
        size--;
        heapifydown(0);
}
void printheap(){
        for(int i=0;i<size;i++){
                printf("%d ",heap[i]);
        }
}
int main(){
        int n;
        scanf("%d",&n);
        int arr[n];
        for(int i=0;i<n;i++){
                scanf("%d",&arr[i]);
        }
        for(int i=0;i<n;i++){
                insert(arr[i]);
        }
        printheap();
        int m;
        scanf("%d\n",&m);
for(int i=0;i<m;i++){
        deletemax();
}
        printheap();
        printf("\n");
        return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
6
30 10 20 40 50 5
2
50 40 20 10 30 5
30 10 20 5

Test Case - 2
User Output
4
8 3 6 2
1
8 3 6 2
6 3 2

S.No: 5	Exp. Name: ***Depth First Search (DFS) on a Graph***	**Date: 2026-09-03**

Aim:

Write a program to perform Depth First Search (DFS) traversal on an undirected graph using an adjacency matrix representation. The program should take the number of vertices, edges, and the starting vertex as input and print the DFS traversal of the graph.

Input Format:

- The first line contains an integer N, representing the number of vertices in the graph.
- The second line contains an integer E, representing the number of edges in the graph.
- The next E lines contain two integers v_1, v_2 representing an edge between vertices v_1 and v_2.
- The last line contains an integer S, representing the starting vertex for the DFS traversal.

Output Format:

- Print the DFS traversal of the graph starting from S, with vertices separated by a space.

Note:

- If multiple nodes are available to visit, DFS should proceed in the order of their appearance in the adjacency matrix.

Source Code:

CTC64641.c

```c
#include <stdio.h>

int graph[100][100];
int visited[100];
int n;

void dfs(int v)
{
    int i;
    visited[v] = 1;
    printf("%d ", v);

    for(i = 0; i < n; i++)
    {
        if(graph[v][i] == 1 && visited[i] == 0)
        {
            dfs(i);
        }
    }
}

int main()
{
    int e, u, v, s, i, j;

    scanf("%d", &n);
    scanf("%d", &e);

    for(i = 0; i < n; i++)
    {
        for(j = 0; j < n; j++)
        {
            graph[i][j] = 0;
        }
        visited[i] = 0;
    }

    for(i = 0; i < e; i++)
    {
        scanf("%d %d", &u, &v);
        graph[u][v] = 1;
        graph[v][u] = 1;
    }
```

```
    scanf("%d", &s);

    dfs(s);

    return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
4
4
0 1
0 2
1 2
2 3
0
0 1 2 3

Test Case - 2
User Output
6
4
0 1
0 2
3 4
4 5
0
0 1 2

S.No: 6	Exp. Name: ***Breadth First Search (BFS) on a Graph***	**Date: 2026-10-03**

Aim:

Write a program to perform Breadth First Search (BFS) traversal on an undirected graph using an adjacency matrix representation. The program should take the number of vertices, edges, and the starting vertex as input and print the BFS traversal of the graph.

Input Format:

- The first line contains an integer N, representing the number of vertices in the graph.
- The second line contains an integer E, representing the number of edges in the graph.
- The next E lines contain two space-separated integers v_1, v_2 representing an edge between vertices v_1 and v_2.
- The last line contains an integer S, representing the starting vertex for the BFS traversal.

Output Format:

- Print the BFS traversal of the graph starting from S, with vertices separated by a space. If a vertex has multiple neighbors, process them in increasing order.

Source Code:

CTC64721.c

```c
#include <stdio.h>

int main() {
    int N, E;

    scanf("%d", &N);
    scanf("%d", &E);

    int graph[100][100] = {0};

    // Read edges
    for (int i = 0; i < E; i++) {
        int u, v;
        scanf("%d %d", &u, &v);

        graph[u][v] = 1;
        graph[v][u] = 1;   // Remove this for a directed graph
    }

    int S;
    scanf("%d", &S);

    int visited[100] = {0};
    int queue[100];
    int front = 0, rear = 0;

    // Start BFS from S
    visited[S] = 1;
    queue[rear++] = S;

    while (front < rear) {
        int current = queue[front++];

        printf("%d ", current);

        for (int i = 0; i < N; i++) {
            if (graph[current][i] == 1 && visited[i] == 0) {
                visited[i] = 1;
                queue[rear++] = i;
            }
        }
    }
```

```
    return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
4
4
0 1
0 2
1 2
2 3
0
0 1 2 3

Test Case - 2
User Output
6
4
0 1
0 2
3 4
4 5
0
0 1 2

Test Case - 3
User Output
1
0
0
0

S.No: 7	Exp. Name: ***Depth-First Search (DFS)***	**Date: 2026-10-03**

Aim:

Write a C program to implement and perform a Depth-First Search (DFS) on a directed graph represented using an adjacency list. The program should print all the nodes reachable from a given starting node.

Input Format:

- The first line contains two integers: V (number of vertices) and E (number of edges).
- The next E lines each contain two integers: u and v, where there is a directed edge from node u to node v.
- The last line contains the starting node for the DFS traversal.

Output Format:

- Print all reachable nodes from the starting node in the order they are visited by DFS as a single line of space-separated integers.

Note:

- In DFS, the smaller numbered node is visited first when there are multiple adjacent nodes, ensuring a consistent traversal order
- Refer to the visible test cases for a better understanding.

Source Code:

dfs_directed_graph.c

```
#include <stdio.h>
#include <stdlib.h>

struct Node {
    int vertex;
    struct Node *next;
};

struct Node *adj[100];
int visited[100];

void addEdge(int u, int v) {
    struct Node *newNode;

    newNode = (struct Node *)malloc(sizeof(struct Node));
    newNode->vertex = v;
    newNode->next = adj[u];
    adj[u] = newNode;
}

void sortList(int u) {
    struct Node *p, *q;
    int temp;

    for (p = adj[u]; p != NULL; p = p->next) {
        for (q = p->next; q != NULL; q = q->next) {
            if (p->vertex > q->vertex) {
                temp = p->vertex;
                p->vertex = q->vertex;
                q->vertex = temp;
            }
        }
    }
}

void DFS(int u) {
    struct Node *temp;

    visited[u] = 1;
    printf("%d ", u);

    temp = adj[u];

    while (temp != NULL) {
```

```
        if (!visited[temp->vertex]) {
            DFS(temp->vertex);
        }
        temp = temp->next;
    }
}

int main() {
    int V, E;
    int u, v, start;
    int i;

    scanf("%d %d", &V, &E);

    for (i = 0; i < V; i++) {
        adj[i] = NULL;
        visited[i] = 0;
    }

    for (i = 0; i < E; i++) {
        scanf("%d %d", &u, &v);
        addEdge(u, v);
    }

    scanf("%d", &start);

    /* Sort all adjacency lists */
    for (i = 0; i < V; i++) {
        sortList(i);
    }

    DFS(start);

    return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
5 6
0 1

0 2
1 3
1 4
2 4
3 4
0
0 1 3 4 2

Test Case - 2
User Output
5 5
0 1
0 4
1 2
2 3
3 4
0
0 1 2 3 4

S.No: 8	Exp. Name: ***Breadth First Search (BFS)***	**Date: 2026-10-03**

Aim:

Write a C program to perform BFS on a directed graph using adjacency lists. The graph has V vertices and E edges. After building the graph, sort each vertex's adjacency list in ascending order. Then perform BFS from a given starting node and print all reachable nodes in the order they are visited as space-separated integers. When multiple adjacent nodes are available, always visit the smallest one first.

Input Format:

- The input begins with a line containing two integers V and E, where V is the number of vertices and E is the number of edges in the directed graph.
- The following E lines each contain two integers u and v, indicating a directed edge from vertex u to vertex v.
- The final line contains a single integer $start$, which represents the starting vertex for the BFS traversal.

Output Format:

- Print all reachable nodes from the starting vertex in the order they are visited by BFS, as a single line of space-separated integers.

Note: Refer to the test cases for better understanding.

Source Code:

BFS.c

```
#include <stdio.h>
#include <stdlib.h>

struct Node {
    int vertex;
    struct Node *next;
};

struct Node *adj[100];
int visited[100];

void addEdge(int u, int v) {
    struct Node *newNode = (struct Node *)malloc(sizeof(struct Node));
    newNode->vertex = v;
    newNode->next = adj[u];
    adj[u] = newNode;
}

void sortList(int u) {
    struct Node *p, *q;
    int temp;

    for (p = adj[u]; p != NULL; p = p->next) {
        for (q = p->next; q != NULL; q = q->next) {
            if (p->vertex > q->vertex) {
                temp = p->vertex;
                p->vertex = q->vertex;
                q->vertex = temp;
            }
        }
    }
}

void BFS(int start, int V) {
    int queue[100];
    int front = 0, rear = 0;

    queue[rear++] = start;
    visited[start] = 1;

    while (front < rear) {
        int u = queue[front++];

        printf("%d ", u);
```

```
        struct Node *temp = adj[u];

        while (temp != NULL) {
            int v = temp->vertex;

            if (!visited[v]) {
                visited[v] = 1;
                queue[rear++] = v;
            }

            temp = temp->next;
        }
    }
}

int main() {
    int V, E;
    int u, v, start;
    int i;

    scanf("%d %d", &V, &E);

    for (i = 0; i < V; i++) {
        adj[i] = NULL;
        visited[i] = 0;
    }

    for (i = 0; i < E; i++) {
        scanf("%d %d", &u, &v);
        addEdge(u, v);
    }

    scanf("%d", &start);

    /* Sort every adjacency list */
    for (i = 0; i < V; i++) {
        sortList(i);
    }

    BFS(start, V);

    return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
5 4
0 1
0 2
1 3
1 4
0
0 1 2 3 4

Test Case - 2
User Output
4 6
0 1
0 2
0 3
1 2
1 3
2 3
0
0 1 2 3

S.No: 9	Exp. Name: ***Bi-Connected Components in Graph***	**Date: 2026-11-09**

Aim:

Write a C program for finding the count of bi-connected components in a given graph

Input Format:

- First line in the input indicates the number of vertices.
- Second line in the input indicates the number of edges.
- The next following lines indicates the edges, which takes two vertices u v as space separated integers for each edge.

Output Format:

- The code will print the number of biconnected components found in the graph.

Note: Refer to the test cases for better understanding.

Source Code:

biConnected.c

```
// write your code here...

#include <stdio.h>
#include <stdlib.h>

#define MAX 100

int V, E;
int adj[MAX][MAX];
int disc[MAX], low[MAX], parent[MAX];
int time_dfs, bccCount;

struct Edge {
    int u, v;
} stackEdges[MAX * MAX];

int top = -1;

void pushEdge(int u, int v) {
    stackEdges[++top] = (struct Edge){u, v};
}

void popUntil(int u, int v) {
    while (top >= 0) {
        struct Edge e = stackEdges[top--];
        if ((e.u == u && e.v == v) ||
            (e.u == v && e.v == u))
            break;
    }
}

void BCCUtil(int u) {
    int children = 0;
    disc[u] = low[u] = ++time_dfs;

    for (int v = 0; v < V; v++) {
        if (adj[u][v]) {
            if (disc[v] == -1) {
                children++;
                parent[v] = u;
                pushEdge(u, v);

                BCCUtil(v);
```

```
                if (low[v] >= disc[u]) {
                    bccCount++;
                    popUntil(u, v);
                }

                if (low[v] < low[u])
                    low[u] = low[v];
            }
            else if (v != parent[u] && disc[v] < disc[u]) {
                pushEdge(u, v);

                if (disc[v] < low[u])
                    low[u] = disc[v];
            }
        }
    }
}

void findBCCs() {
    for (int i = 0; i < V; i++) {
        disc[i] = -1;
        parent[i] = -1;
    }

    time_dfs = 0;
    bccCount = 0;
    top = -1;

    for (int i = 0; i < V; i++) {
        if (disc[i] == -1) {
            BCCUtil(i);

            if (top >= 0) {
                bccCount++;
                top = -1;
            }
        }
    }
}

int main() {
    scanf("%d %d", &V, &E);

    for (int i = 0; i < V; i++)
        for (int j = 0; j < V; j++)
            adj[i][j] = 0;
```

```
    for (int i = 0; i < E; i++) {
        int u, v;
        scanf("%d %d", &u, &v);
        adj[u][v] = adj[v][u] = 1;
    }

    findBCCs();

    printf("%d\n", bccCount);

    return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
3
2
0 1
0 2
2

Test Case - 2
User Output
5
4
0 1
1 2
1 3
2 4
4

S.No: 10	Exp. Name: ***C program that implements the quick sort***	**Date: 2026-07-25**

Aim:

Write a C program that implements the quick sort to sort a given list of integers in ascending order.

Input Format

- The first line contains an integer n which represents the number of elements in the array.
- The second line contains n space-separated integers, which are the elements of the array.

Output Format

- A single line containing n space-separated integers, representing the array elements in ascending order after sorting.

Note: Refer to the test cases for better understanding.

Source Code:

quickSort.c

```
// quick sort by very first elemnet.....
/*#include<stdio.h>
#include<stdlib.h>
void swap(int *a,int *b){
        int temp;
        temp=*a;
        *a=*b;
        *b=temp;
}
int partitian(int arr[],int low,int high){
int i=low;
        int j=high+1;
        int pi=arr[low];
        while(i<j){
                do{
                        i++;
                }while(arr[i]<=pi);
                do{
                        j--;
                }while(arr[j]>pi);
                if(i<j)
                        swap(&arr[i],&arr[j]);
        }
        swap(&arr[low],&arr[j]);
        return j;
}
void quicksort(int arr[],int low,int high){
        if(low<high){
        int pi=partitian(arr,low,high);
        quicksort(arr,low,pi-1);
quicksort(arr,pi+1,high);
}}
        int main(){
                int n;
                scanf("%d",&n);
                int arr[n];
                for(int i=0;i<n;i++){
                        scanf("%d",&arr[i]);
                }
                quicksort(arr,0,n-1);
                for(int i=0;i<n;i++){
                        printf("%d ",arr[i]);
                }
                printf("\n");
```

```
                return 0;
        }*/
//quick sort by last element.............
/*#include<stdio.h>
#include<stdlib.h>
void swap(int *a,int *b){
        int temp=*a;
        *a=*b;
        *b=temp;
}
int partitian(int arr[],int low,int high){
        int i=low-1;
        int j=high;
        int pivot=arr[high];
        while(i<j){
                do{
                        i++;
                }while(arr[i]<pivot);
                do{
                        j--;
                }while(arr[j]>=pivot);
if(i<j)
        swap(&arr[i],&arr[j]);
        }
        swap(&arr[i],&arr[high]);
        return i;
}
void quicksort(int arr[],int low,int high){
        if(low<high){
                int pi=partitian(arr,low,high);
                quicksort(arr,low,pi-1);
                quicksort(arr,pi+1,high);
        }
}
int main(){
        int n;
        scanf("%d",&n);
        int arr[n];
         for(int i=0;i<n;i++){
                 scanf("%d",&arr[i]);
         }
        quicksort(arr,0,n-1);
                for(int i=0;i<n;i++){
                        printf("%d ",arr[i]);
                }
                printf("\n");
```

```
                return 0;
}*/
//quick sort by mid element.......
#include<stdio.h>
#include<stdio.h>
void swap(int *a,int *b){
        int temp=*a;
        *a=*b;
        *b=temp;
}
int partitian(int arr[],int low,int high){
        int mid=0,pivot;
        mid=low+(high-low)/2;
         pivot=arr[mid];
        int i=low-1;
        int j=high+1;
        while(i<j){
                do{
                        i++;
                }while(arr[i]<pivot);
                do{
                        j--;
                }while(arr[j]>pivot);
                if(i<j){
                        swap(&arr[i],&arr[j]);
                }
        }
        return j;
}
void quicksort(int arr[],int low,int high){
        if(low<high){
                int pi=partitian(arr,low,high);
                quicksort(arr,low,pi);
        quicksort(arr,pi+1,high);
        }
}
int main(){
        int n;
        scanf("%d",&n);
        int arr[n];
        for(int i=0;i<n;i++){
                scanf("%d",&arr[i]);
        }
        quicksort(arr,0,n-1);
        for(int i=0;i<n;i++){
                printf("%d ",arr[i]);
```

```
        }
        printf("\n");
        return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
6
6 2 8 10 36 14
2 6 8 10 14 36

Test Case - 2
User Output
8
95 14 10 23 36 2 5 35
2 5 10 14 23 35 36 95

S.No: 11	Exp. Name: ***C program that implements the merge sort***	**Date: 2026-09-05**

Aim:

Write a C program to implement the Merge Sort algorithm to sort an array of integers in ascending order.

Input Format

- The first line contains an integer n which represents the number of elements in the array.
- The second line contains n space-separated integers, which are the elements of the array.

Output Format

- A single line containing n space-separated integers, representing the array elements in ascending order after sorting.

Note: Refer to the test cases for better understanding.

Source Code:

mergeSort.c

```
#include<stdio.h>
void merge(int arr[],int low,int mid,int high){
        int temp[1000];
        int i=low;
        int j=mid+1;
        int k=low;
        while(i<=mid&&j<=high){
                if(arr[i]<=arr[j]){
                        temp[k++]=arr[i++];
                }else{
                        temp[k++]=arr[j++];
                }}
        while(i<=mid)
                temp[k++]=arr[i++];
        while(j<=high)
                temp[k++]=arr[j++];
        for(i=low;i<=high;i++)
                arr[i]=temp[i];
        }
void mergesort(int arr[],int low,int high){
        if(low<high){
                int mid=(low+high)/2;
                mergesort(arr,low,mid);
                mergesort(arr,mid+1,high);
                merge(arr,low,mid,high);
        }
}
int main(){
        int n,i;
        scanf("%d",&n);
        int arr[n];
        for(i=0;i<n;i++)
                scanf("%d",&arr[i]);
        mergesort(arr,0,n-1);
        for(i=0;i<n;i++){
                printf("%d ",arr[i]);
        }
        printf("\n");
        return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
5
50 20 30 40 10
10 20 30 40 50

Test Case - 2
User Output
10
25 78 15 45 32 65 46 38 76 12
12 15 25 32 38 45 46 65 76 78

S.No: 12	Exp. Name: ***Shortest Path from Source to Vertex***	**Date: 2026-11-10**

Aim:

You are required to write a C program that computes the shortest paths from a source vertex to all other vertices in a weighted, directed graph. The program should utilize Dijkstra's algorithm to solve this problem.

Input Format:

- The first line contains two integers V and E, representing the number of vertices and the number of edges respectively.
- The next E lines each contain three integers u, v, and w, representing a directed edge from vertex u to vertex v with weight w.
- The last line contains a single integer src, representing the source vertex from which shortest distances are to be calculated.

Output Format:

- The output consists of V lines.
- Each line contains two integers:
    - The vertex number and the minimum distance from the source vertex to that vertex, space separated

Note: Refer to the test cases for better understanding.

Source Code:

Path.c

```
/*/write your code here...
#include <stdio.h>
// Function to solve 0/1 Knapsack problem
int knapsack(int weights[], int profits[], int n, int m) {
    int M[n + 1][m + 1];
    // Build table dp[][] in bottom up manner
    for (int i = 0; i <= n; i++) {
        for (int j = 0; j <= m; j++) {
            if (i == 0 || j == 0)
                M[i][j] = 0;
            else if (weights[i-1] <= j)
                M[i][j]=(profits[i-1]+M[i-1][j-weights[i-1]]>M[i-1][j])?
(profits[i-1]+M[i-1][j-weights[i-1]]):M[i-1][j];
            else
                M[i][j] = M[i - 1][j];
        }
    }
    return M[n][m];
}
int main() {
    int n;
    scanf("%d", &n);
    int weights[n], profits[n];
    // Input: weights
    for (int i = 0; i < n; i++) {
        scanf("%d", &weights[i]);
    }
    // Input: values
    for (int i = 0; i < n; i++) {
        scanf("%d", &profits[i]);
    }
    int capacity;
    scanf("%d", &capacity);
    // Solve and print result
    int maxProfit = knapsack(weights, profits, n, capacity);
    printf("%d\n", maxProfit);
    return 0;
}
#include <stdio.h>
// Function to solve 0/1 Knapsack problem
int knapsack(int weights[], int profits[], int n, int m) {
    int M[n + 1][m + 1];
    // Build table dp[][] in bottom up manner
    for (int i = 0; i <= n; i++) {
```

```
        for (int j = 0; j <= m; j++) {
            if (i == 0 || j == 0)
                M[i][j] = 0;
            else if (weights[i-1] <= j)
                M[i][j]=(profits[i-1]+M[i-1][j-weights[i-1]]>M[i-1][j])?
(profits[i-1]+M[i-1][j-weights[i-1]]):M[i-1][j];
            else
                M[i][j] = M[i - 1][j];
        }
    }
    return M[n][m];
}
int main() {
    int n;
    scanf("%d", &n);
    int weights[n], profits[n];
    // Input: weights
    for (int i = 0; i < n; i++) {
        scanf("%d", &weights[i]);
    }
    // Input: values
    for (int i = 0; i < n; i++) {
        scanf("%d", &profits[i]);
    }
    int capacity;
    scanf("%d", &capacity);
    // Solve and print result
    int maxProfit = knapsack(weights, profits, n, capacity);
    printf("%d\n", maxProfit);
    return 0;
}*/
#include <stdio.h>
#include <limits.h>
#define MAX 100
#define INF INT_MAX
int n, m;
int graph[MAX][MAX]; // adjacency matrix
// Function to find vertex with minimum distance not yet visited
int minDistance(int dist[], int visited[]) {
    int min = INF, min_index = -1;
    for (int v = 0; v < n; v++) {
        if (!visited[v] && dist[v] <= min) {
            min = dist[v];
            min_index = v;
        }
    }
```

```
    return min_index;
}
void dijkstra(int src) {
    int dist[MAX];
    int visited[MAX];
    // Initialize distances
    for (int i = 0; i < n; i++) {
        dist[i] = INF;
        visited[i] = 0;
    }
    dist[src] = 0;
    // Process all vertices
    for (int count = 0; count < n - 1; count++) {
        int u = minDistance(dist, visited);
        if (u == -1) break; // no more reachable vertices
        visited[u] = 1;
        // Update neighbors
        for (int v = 0; v < n; v++) {
            if (!visited[v] && graph[u][v] != INF &&
                dist[u] != INF &&
                dist[u] + graph[u][v] < dist[v]) {
                dist[v] = dist[u] + graph[u][v];
            }
        }
    }
    // Print results
    for (int i = 0; i < n; i++) {
        if (dist[i] == INF)
            printf("%d -1\n", i); // unreachable
        else
            printf("%d %d\n", i, dist[i]);
    }
}
int main() {
    scanf("%d %d", &n, &m);
    // Initialize adjacency matrix
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            graph[i][j] = INF;
    // Input edges
    for (int i = 0; i < m; i++) {
        int u, v, w;
        scanf("%d %d %d", &u, &v, &w);
        graph[u][v] = w; // directed graph
    }
    int src;
```

```
    scanf("%d", &src);
    dijkstra(src);
    return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
4 3
0 1 2
0 2 5
0 3 1
0
0 0
1 2
2 5
3 1

Test Case - 2
User Output
6 9
0 1 7
0 2 9
0 5 14
1 2 10
1 3 15
2 3 11
2 5 2
3 4 6
5 4 9
0
0 0
1 7
2 9
3 20

4 20
5 11

S.No: 13	Exp. Name: ***Job Sequencing using Greedy Problem***	**Date: 2026-11-10**

Aim:

Given a set of N jobs, where each job i has a deadline and a profit associated with it. Each job takes 1 unit of time to complete, and only one job can be scheduled at a time. We earn the profit associated with the job if and only if the job is completed by its deadline. Find the number of jobs done and the maximum profit.

Note: Jobs will be given in the form (Job Id, Deadline, Profit) associated with that Job. The deadline of the job is the time by which the job needs to be completed to earn the profit.

Input Format:

- The first line contains an integer N representing the number of jobs.
- The next N lines each contain three space-separated integers: {Job ID, Job Deadline, Job Profit} — representing one job per line.

Output Format

- Two integers separated by a space:
- The first integer represents the number of jobs done. The second integer represents the maximum profit obtained.

Constraints:

- $1 \leq N \leq 10^5$
- $1 \leq Deadline \leq N$
- $1 \leq Profit \leq 500$

Example 1:

Input:

```
4
1 4 20
2 1 10
3 1 40
4 1 30
```

Output:

```
2 60
```

Explanation: Job 1 and Job 3 can be done with a maximum profit of 60 (20+40).

Note: Refer to the test cases for better understanding.

Source Code:

JsGreedy.c

```
/*/write your code here...#include <stdio.h>
// Function to solve 0/1 Knapsack problem
int knapsack(int weights[], int profits[], int n, int m) {
    int M[n + 1][m + 1];
    // Build table dp[][] in bottom up manner
    for (int i = 0; i <= n; i++) {
        for (int j = 0; j <= m; j++) {
            if (i == 0 || j == 0)
                M[i][j] = 0;
            else if (weights[i-1] <= j)
                M[i][j]=(profits[i-1]+M[i-1][j-weights[i-1]]>M[i-1][j])?
(profits[i-1]+M[i-1][j-weights[i-1]]):M[i-1][j];
            else
                M[i][j] = M[i - 1][j];
        }
    }

    return M[n][m];
}
int main() {
    int n;
    scanf("%d", &n);
    int weights[n], profits[n];
    // Input: weights
    for (int i = 0; i < n; i++) {
        scanf("%d", &weights[i]);
    }
    // Input: values
    for (int i = 0; i < n; i++) {
        scanf("%d", &profits[i]);
    }
    int capacity;
    scanf("%d", &capacity);
    // Solve and print result
    int maxProfit = knapsack(weights, profits, n, capacity);
    printf("%d\n", maxProfit);
    return 0;
}*/
#include <stdio.h>

struct Job {
    int id;
    int deadline;
    int profit;
```

```
};

int main() {
    int n;
    scanf("%d", &n);

    struct Job jobs[100];
    int maxDeadline = 0;

    for (int i = 0; i < n; i++) {
        scanf("%d %d %d", &jobs[i].id, &jobs[i].deadline,
&jobs[i].profit);
        if (jobs[i].deadline > maxDeadline)
            maxDeadline = jobs[i].deadline;
    }

    // Sort jobs by profit - ekkuva profit unna job mundhu
    for (int i = 0; i < n - 1; i++) {
        for (int j = 0; j < n - i - 1; j++) {
            if (jobs[j].profit < jobs[j + 1].profit) {
                struct Job temp = jobs[j];
                jobs[j] = jobs[j + 1];
                jobs[j + 1] = temp;
            }
        }
    }

    // Slot array - e slot khali ga undho chudataniki
    int slot[100] = {0};
    int count = 0;
    int totalProfit = 0;

    for (int i = 0; i < n; i++) {
        // Deadline nundi venakki veltu khali slot vetukutham
        for (int j = jobs[i].deadline - 1; j >= 0; j--) {
            if (slot[j] == 0) {
                slot[j] = 1; // slot fill chesam
                count++;
                totalProfit += jobs[i].profit;
                break;
            }
        }
    }

    printf("%d %d\n", count, totalProfit);
```

```
    return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
4
1 4 20
2 1 10
3 1 40
4 1 30
2 60

Test Case - 2
User Output
5
1 2 60
2 1 100
3 3 20
4 4 70
5 2 50
4 250

S.No: 14	Exp. Name: ***Program to implement Knapsack problem Using Dynamic Programming***	**Date: 2026-11-10**

Aim:

You are given n items, each with a specific weight and value. You have a knapsack with a maximum capacity W. Your goal is to select a subset of these items such that the total weight is less than or equal to W, and the total value is as large as possible.

This is the classic 0/1 Knapsack problem, where each item can either be included once or excluded from the knapsack.

Input Format:

- The first line contains an integer n, representing the number of items to consider for the knapsack.
- The second line contains n space-separated integers, representing the weights of the items.
- The third line contains n space-separated integers, representing the values of the items, corresponding to their weights.
- The fourth line contains an integer W, representing the capacity of the knapsack.

Output Format:

- Print the maximum profit that can be obtained by selecting items such that their combined weight does not exceed the knapsack capacity.

Note: Refer to the test cases for better understanding.

Source Code:

dynamicKs.c

```
/* write your code here...
#include <stdio.h>

int max(int a, int b) {
    return (a > b) ? a : b;
}

int main() {
    int n;
    scanf("%d", &n);

    int weights[100], values[100];

    // Second line - weights
    for (int i = 0; i < n; i++) {
        scanf("%d", &weights[i]);
    }
    // Third line - values
    for (int i = 0; i < n; i++) {
        scanf("%d", &values[i]);
    }

    int W;
    scanf("%d", &W);

    // DP table - dp[i][w] = first i items tho, w capacity tho vache max
profit
    int dp[100][1000] = {0};

    for (int i = 1; i <= n; i++) {
        for (int w = 0; w <= W; w++) {
            if (weights[i - 1] <= w) {
                // 2 options: item teskovadam */
#include <stdio.h>

int max(int a, int b) {
    return (a > b) ? a : b;
}

int main() {
    int n;
    scanf("%d", &n);

    int weights[100], values[100];
```

```
    // Second line - weights
    for (int i = 0; i < n; i++) {
        scanf("%d", &weights[i]);
    }
    // Third line - values
    for (int i = 0; i < n; i++) {
        scanf("%d", &values[i]);
    }

    int W;
    scanf("%d", &W);

    // DP table - dp[i][w] = first i items tho, w capacity tho vache max
profit
    int dp[100][1000] = {0};

    for (int i = 1; i <= n; i++) {
        for (int w = 0; w <= W; w++) {
            if (weights[i - 1] <= w) {
                // 2 options: item teskovadam / vadileyyadam
                // Tesukunte: values[i-1] + dp[i-1][w - weights[i-1]]
                // Vadilithe: dp[i-1][w]
                dp[i][w] = max(values[i - 1] + dp[i - 1][w - weights[i -
1]],
                               dp[i - 1][w]);
            } else {
                // Weight ekkuva aithe tesukolemu
                dp[i][w] = dp[i - 1][w];
            }
        }
    }

    printf("%d\n", dp[n][W]);
    return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
5

5 10 15 20 25
10 20 30 40 50
500
150

Test Case - 2
User Output
4
100 200 300 400
10 20 30 40
100
10

S.No: 15	Exp. Name: ***N-Queens Problem***	**Date: 2026-11-10**

Aim:

Write a C program to solve the N-Queens problem using backtracking. The goal is to place N queens on an $N \times N$ chessboard such that no two queens attack each other. A queen can attack another queen if they share the same row, column, or diagonal. Your program should print the first valid configuration of the board found by placing queens from left to right and top to bottom, using a backtracking approach. The board must be displayed as an $N \times N$ matrix where a cell contains 1 if a queen is placed there, and 0 otherwise. If no solution exists for the given value of N, print a message indicating that no solution exists.

Input Format:

- A single integer N — the number of queens and the size of the chessboard.

Output Format:

- If a solution exists, print an $N \times N$ matrix consisting of 0s and 1s, where 1 represents a queen.
- If no solution exists, print: "No solution exists for N = <value>".
- Each row of the matrix should be printed on a new line, with space-separated values.

Note: Refer to the test cases for better understanding.

Source Code:

ID: 25B01A1243

Shri Vishnu Engineering College for Women (Autonomous)

nqueens.c

```
// write your code here...
#include <stdio.h>
#include <stdbool.h>

#define MAX 20

int board[MAX][MAX], N;

void printBoard() {
    for (int i = 0; i < N; i++) {
        for (int j = 0; j < N; j++) {
            printf("%d ", board[i][j]);
        }
        printf("\n");
    }
}

bool isSafe(int row, int col) {
    // Same column check
    for (int i = 0; i < row; i++)
        if (board[i][col]) return false;

    // Upper left diagonal
    for (int i = row, j = col; i >= 0 && j >= 0; i--, j--)
        if (board[i][j]) return false;

    // Upper right diagonal
    for (int i = row, j = col; i >= 0 && j < N; i--, j++)
        if (board[i][j]) return false;

    return true;
}

bool solveNQueens(int row) {
    if (row >= N) return true; // Base case - anni queens pettam

    for (int col = 0; col < N; col++) {
        if (isSafe(row, col)) {
            board[row][col] = 1; // Queen petti
            if (solveNQueens(row + 1)) // Next row ki velli
                return true;
            board[row][col] = 0; // Backtrack - teesey
        }
    }
```

```
    return false;
}

int main() {
    scanf("%d", &N);
    if (solveNQueens(0))
        printBoard();
    else
        printf("No solution exists for N = %d\n", N);
    return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
4
0 1 0 0
0 0 0 1
1 0 0 0
0 0 1 0

Test Case - 2
User Output
3
No solution exists for N = 3

S.No: 16	Exp. Name: ***Knapsack using backtracking***	**Date: 2026-11-10**

Aim:

Write a C program to solve the 0/1 Knapsack Problem using backtracking approach. The program aims to maximize the total value of items that can be included in a knapsack without exceeding its capacity

Input Format:

- The first line contains an integer n, representing the number of items.
- The next n lines each contain two space-separated integers: the value and weight of an item.
- The last line contains an integer W, representing the capacity of the knapsack.

Output Format:

- Print the maximum profit (total value) that can be obtained by selecting items, considering the knapsack's capacity constraint.

Note: Refer to the test cases for better understanding.

Source Code:

knapsackBacktracking.c

```
// write your code here...
#include <stdio.h>

int n; // number of items
int values[100], weights[100];
int capacity; // maximum capacity of knapsack
int maxProfit = 0; // best profit found so far

// Recursive backtracking function
void knapsack(int i, int currWeight, int currValue) {
    // Base case: all items considered
    if (i == n) {
        if (currValue > maxProfit)
            maxProfit = currValue;
        return;
    }

    // Case 1: Exclude current item
    knapsack(i + 1, currWeight, currValue);

    // Case 2: Include current item (if within capacity)
    if (currWeight + weights[i] <= capacity) {
        knapsack(i + 1,
                 currWeight + weights[i],
                 currValue + values[i]);
    }
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d %d", &values[i], &weights[i]);
    }

    scanf("%d", &capacity);

    // Start recursion from first item
    knapsack(0, 0, 0);

    printf("%d\n", maxProfit);

    return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
3
60 10
100 20
120 30
50
220


Test Case - 2
User Output
5
10 5
40 4
30 3
50 2
20 1
100
150

S.No: 17	Exp. Name: ***Travelling Salesman Problem***	**Date: 2026-11-10**

Aim:

Given a set of cities and the distance between every pair of cities, the problem is to find the shortest possible route that visits every city exactly once and returns to the starting point.

Example:



A TSP tour in the graph is 1-2-4-3-1. The cost of the tour is 10+25+30+15, which is 80

Input Format:

- The first line contains an integer n, representing the number of cities.
- The following n lines contain the cost matrix of size $n \times n$. Each line contains n integers separated by spaces, representing the cost of traveling from one city to another. If there is no direct connection between two cities, -1 is used to represent infinity.

Output Format:

- The output is a single integer representing the optimal cost of the traveling salesman problem.

Source Code:

ID: 25B01A1243
2025-2029-IT-A
Shri Vishnu Engineering College for Women (Autonomous)

CTC30966.c

```
#include <stdio.h>
#include <limits.h>

#define MAX 20
#define INF 999999

int n; // number of cities
int cost[MAX][MAX]; // cost matrix
int visited[MAX]; // visited cities
int minCost = INT_MAX; // best cost found so far

// Recursive function for TSP
void tsp(int city, int count, int currCost, int start) {
    // If all cities are visited and we can return to start
    if (count == n && cost[city][start] != INF) {
        int totalCost = currCost + cost[city][start];
        if (totalCost < minCost)
            minCost = totalCost;
        return;
    }

    // Try visiting unvisited cities
    for (int next = 0; next < n; next++) {
        if (!visited[next] && cost[city][next] != INF) {
            visited[next] = 1;
            tsp(next, count + 1, currCost + cost[city][next], start);
            visited[next] = 0; // backtrack
        }
    }
}

int main() {
    scanf("%d", &n);

    // Read cost matrix
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            int val;
            scanf("%d", &val);
            if (val == -1) {
                cost[i][j] = INF; // no direct connection
            } else {
                cost[i][j] = val;
            }
```

```
        }
    }

    // Initialize visited array
    for (int i = 0; i < n; i++)
        visited[i] = 0;

    // Start from city 0
    visited[0] = 1;
    tsp(0, 1, 0, 0);

    printf("%d\n", minCost);

    return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
3
-1 2 3
4 -1 6
1 2 -2
9

Test Case - 2
User Output
4
-1 2 3 4
1 -1 1 3
4 5 -1 1
2 3 6 -1
6