

C Programming Assignment

1). Write a C program to find sum of proper division of a number using recursion.

```
#include<stdio.h>

int sumdiv(int num, int x);

int main()
{
    int num;
    printf("Enter a number:");
    scanf("%d",&num);
    printf("-----\n");
    printf("Sum of divisors=%d\n",sumdiv(num,num/2));
    printf("-----\n");
    return 0;
}

sumdiv(int num, int x)
{
    if(x==1)
    {
        printf("%d \n",x);
        return 1;
    }
    if(num%x==0)
    {
        printf("%d + ",x);
        return x + sumdiv(num,x-1);
    }
    else
        return sumdiv(num,x-1); }
```

2). Write a C program to display a number in words using recursion.

```
#include <stdio.h>

void printWords(int n);

int main()
{
    int n ;

    printf("Enter any number:");

    scanf("%d",&n);

    printWords(n);

    return 0;
}

void printWords(int n)
{
    int m;

    if(n==0)
        return;

    printWords(n/10);

    m=n%10;

    switch(m)
    {
        case 0: printf("Zero");
                break;

        case 1: printf("One");
                break;

        case 2: printf("Two");
                break;

        case 3: printf("Three");
                break;
```

```
        case 4: printf("Four");
                break;
        case 5: printf("Five");
                break;
        case 6: printf("Six");
                break;
        case 7: printf("Seven");
                break;
        case 8: printf("Eight");
                break;
        case 9: printf("Nine");
                break;
    }
}
```

3). Write a C program to perform multiplication by Russian Peasant method.

```
#include<stdio.h>

int RussianPeasant(int a, int b);

int main()
{
    int a,b;
    printf("Enter 1st number:\n");
    scanf("%d",&a);
    printf("Enter 2nd number:\n");
    scanf("%d",&b);
    printf("Product of two numbers is: ");
    printf("%d\n",RussianPeasant(a,b));
    return 0;
}
```

```

int RussianPeasant(int a, int b)
{
    if(a==0)
        return 0;
    if(a%2!=0)
        return b+RussianPeasant(a/2,b*2);
    return RussianPeasant(a/2,b*2);
}

```

4). Write a C program to calculate log to the base 2 and base n using recursion.

```

#include<stdio.h>

int logbase2(int num);
int logbasen(int num,int base);
int main()
{
    int num,base;
    printf("Enter a number for Base-2 logarithm:\n");
    scanf("%d",&num);
    printf("Value of log base2 of %d=%d\n",num,logbase2(num));
    printf("\nEnter any number:\n");
    scanf("%d",&num);
    printf("Enter base to %d:",num);
    scanf("%d",&base);
    printf("Value of log base %d of %d=%d\n",base,num,logbasen(num,base));
    return 0;
}

int logbase2(int num)
{
    if(num==1)

```

```

        return 0;
    return 1 + logbase2(num/2);
}
int logbasen(int num,int base)
{
    if(num<base)
        return 0;
    return 1 + logbasen(num/base,base);
}

```

5). Write a C program to calculate binomial coefficient using recursion.

```

#include<stdio.h>

int binomialCoef(int n,int m);

int main()
{
    int n,m;
    printf("Enter n and m:\n");
    scanf("%d%d",&n,&m);
    printf("Binomial coefficient\n",binomialCoef(n,m));
    printf("%d\n",binomialCoef(n,m));
    return 0;
}

int binomialCoef(int n,int m)
{
    if(m==0 | m==n)
        return 1;
    return binomialCoef(n-1,m-1)+binomialCoef(n-1,m);
}

```

6). Write a C program to implement Ackermann Function using Recursion.

```
#include <stdio.h>

int ackermann(int m,int n)
{
    if (m == 0){
        return n+1;
    }
    else if((m > 0) && (n == 0)){
        return ackermann(m-1, 1);
    }
    else if((m > 0) && (n > 0)){
        return ackermann(m-1, ackermann(m, n-1));
    }
}

int main()
{
    int x;
    x= ackermann(1, 2);
    printf("%d", x);
    return 0;
}
```

7). Write a C program to find frequency of vowels in string using recursion.

```
#include<stdio.h>
#include<string.h>
int count_vowels(char *str);
int main()
{
    char str[100];
```

```

    printf("Enter a string:");
    gets(str);
    printf("Number of vowels in the string is %d\n",count_vowels(str));
    return 0;
}
int count_vowels(char *str)
{
    if(*str == '\0')
        return 0;
    switch(*str)
    {
        case 'A': case 'a':
            case 'E': case 'e':
            case 'I': case 'i':
            case 'O': case 'o':
            case 'U': case 'u':
                return 1 + count_vowels(str+1);
            default:
                return count_vowels(str+1);
    }
}

```

8). Write a C program to replace a character in a string by another character.

```

#include <string.h>
#include<stdio.h>
void replacechar(char *s,char c1,char c2)
{
    int i=0;
    for(i=0;s[i];i++)

```

```

        {
            if(s[i]==c1)
            {
                s[i]=c2;
            }
        }
    }
}

int main()
{
    char str[100],c1,c2;
    printf("Enter the string :\n ");
    gets(str);
    printf("Enter a character to replace: \n");
    c1=getchar();
    getchar();
    printf("Enter character to replace with %c :\n ",c1);
    c2=getchar();
    printf("Before replacing:%s\n",str);
    replacechar(str,c1,c2);
    printf("After replacing:%s\n",str);
    return 0;
}

```

9). Write a C program to print pyramid of numbers using recursion.

```

#include<stdio.h>

void first(int n);
void second(int n);
void third(int n);
int main( )

```



```

{
    int n;

    printf("Enter how many lines u want to print ? ");
    scanf("%d",&n);

    printf("----- First Pattern -----\\n");
    first(n);

    printf("----- Second Pattern ----- \\n");
    func2(n);

    printf("----- Third Pattern ----- \\n");
    func3(n);

    return 0;
}

void first(int n)
{
    int i;

    if(n==0)
        return;

    else
    {
        first(n-1);

        for(i=1; i<= n; i++)
            printf("%d ",i);

        printf("\\n");
    }
}

void second(int n)
{
    int i;

    if(n==0)

```

```

        return;
    else
    {
        for(i=1; i<=n; i++)
            printf("%d ",i);
        printf("\n");
        second(n-1);
    }
}

void third(int n)
{
    int i;
    if(n==0)
        return;
    else
    {
        for(i=n; i>=1; i--)
            printf("%d ",i);
        printf("\n");
        third(n-1);
    }
}

```

10). Write a C program to convert numbers to string using recursion.

```

#include<stdio.h>

void numtostr(long int n, char str[]);

int main()
{
    long int num;

```

```

printf("Enter any number to convert to String:\n");
scanf("%ld",&num);
char str[30];
numtostr(num, str);
printf("\nAfter Converting Number to String:");
puts(str);
printf("\nEnter another number to convert to String:");
scanf("%ld",&num);
numtostr(num, str);
printf("\nAfter Converting 2nd Number to String:");
puts(str);
}
void numtostr(long int n, char s[])
{
    static int i=0;
    if(n==0)
    {
        i=0;
        return;
    }
    numtostr(n/10, s);
    s[i++] = n%10 + '0';
    s[i]='\0';
}

```

11). Write a C program to convert string of numbers to integer using recursion.

```

#include <stdio.h>

#include <string.h>

int num = 0;

```

```

int strtonum(char *string1) {
int i = 0;
if (string1[i] != '\0') {
    if (string1[i]<'0' || string1[i]>'9') {
        printf("Not Possible\n");

    }
    else {
        num *= 10;
        num += string1[i] - '0';
        strtonum(&string1[i+1]);
    }
}
return num;
}

int main(int argc, const char *argv[]) {
    printf("After string to integer : %i\n", (strtonum("99256")));
    return 0;
}

```

12). Write a C program to find all permutations of string by Recursion and Iteration.

```

#include<stdio.h>

#include<string.h>

void strpermute1(char str[], char* currentptr);
void strpermute2(char str[], int startIndex, int lastIndex);
void Swap(char *a, char *b);

int main()
{
    char str[20];

```

```

    printf("Enter any String:");
    scanf("%s",str);
    printf("Using Iteration:\n");
    strpermute1(str,str);
    printf("\n\n");
    printf("Using Recursion:\n");
    strpermute2(str,0,strlen(str)-1);
    printf("\n");
    return 0;
}

void strpermute1(char str[], char* currentptr)
{
    char *ptr;
    if(*(currentptr + 1) == '\0')
        printf("%s\t", str);
    else
        for(ptr=currentptr; *ptr!='\0'; ptr++)
        {
            Swap(ptr,currentptr);
            strpermute1(str, currentptr+1);
            Swap(ptr,currentptr);
        }
}

void strpermute2(char str[], int startIndex, int lastIndex)
{
    int i;
    if(startIndex==lastIndex)
    {
        for(i=0;i<=lastIndex;i++)

```

```
        printf("%c",str[i]);
    printf("\t");
}
else
for(i=startIndex;i<=lastIndex;i++)
{
    Swap(&str[startIndex], &str[i]);
    strpermute2(str,startIndex+1,lastIndex);
    Swap(&str[startIndex], &str[i]);
}
}
void Swap(char *a, char *b)
{
    char temp = *a; *a=*b; *b=temp;
}
```
