


MODULE 02 · 24 MIN

Prompting Like a Tech Lead

Claude Code Bootcamp · Day 1 · Block 2 of 10



Promise

In 24 minutes you will:

- 1 Write a Tech-Lead-grade prompt using the **GCOE pattern** (Goal, Constraints, Output, Examples).
- 2 Ship a working **CLI Task Manager** — add, list, complete, delete — to disk.
- 3 Iterate the prompt by deleting one constraint and observing the diff.

Why this matters

- A vague prompt produces vague code. The bottleneck for AI-paired coding is **prompt quality**, not model quality.
- A Tech Lead does not say "*build a CLI*". They write a one-page spec. We are going to write that spec in 90 seconds and let Claude implement it.
- Every later module reuses GCOE. Get this right and the day gets faster.

Concepts

- **GCOE:** Goal · Constraints · Output format · Examples. Skip any one and quality drops.
- **Goal:** what the user can do at the end. Verb-led, single sentence.
- **Constraints:** language, dependencies, file layout, error handling, what must *not* be done.
- **Output format:** file paths, exit codes, JSON schema if applicable.
- **Examples:** one happy path + one edge case = enough.

ANATOMY OF A TECH-LEAD PROMPT

ROLE	You are a senior backend engineer.
GOAL	Add a /tasks endpoint that returns JSON.
CONSTRAINTS	Python 3.11. No new deps. ≤ 60 lines.
FORMAT	Return only the file contents in one fence.
CHECK	List the 3 invariants you will preserve.

FIVE SLOTS — EVERY PROMPT FILLS THEM.

Live demo flow

1. Instructor pastes a deliberately vague prompt: *"Make a CLI to manage tasks."*
2. Class observes Claude's reasonable but generic output.
3. Instructor rewrites in GCOE form. Re-runs.
4. Class observes the lift: real CLI, real persistence, real tests scaffolded.
5. Instructor **deletes one constraint** mid-demo (e.g., "no third-party deps") and re-runs to show the regression.

Mini project

CLI Task Manager.

- `task add "<text>"` → appends a task with id, status, timestamp.
- `task list [--status open|done]` → tabular output to stdout.
- `task done <id>` → flips status.
- `task delete <id>` → removes the row.
- Persisted to `tasks.json` in the working directory.

► Step-by-step lab

- STEP 1 Pick your track: **Python** (`argparse` , `stdlib` only) or **Node.js + TypeScript** (`commander` + `tsx`).
- STEP 2 Create `module-02/` in your working directory.
- STEP 3 Open Claude Code, paste the GCOE prompt below (verbatim, then edit the *Goal* line if you want a twist).
- STEP 4 Save the generated files into `module-02/` .
- STEP 5 Manually run all four commands; verify `tasks.json` updates.
- STEP 6 Iterate: delete the "*no third-party deps*" line in your prompt, re-generate, diff. Note the change in `module-02/iteration-notes.md` .

Suggested Claude Code prompts

GOAL

Build a single-binary CLI Task Manager so a developer can manage TODOs from the terminal.

CONSTRAINTS

- Language: Python 3.11 (stdlib only) – OR – TypeScript on Node.js 20 with `commander` + `tsx`.
- Persistence: a single JSON file `tasks.json` in CWD.
- No background processes. No network calls.
- Exit code 0 on success, 1 on user error, 2 on internal error.
- All user-facing strings in English.

OUTPUT FORMAT

- One source file (Python) or `src/index.ts` + `package.json` (Node).
- A short README explaining install + the four commands.

EXAMPLES

- `task add "Write the spec"` → "Added task #1: Write the spec"
- `task list` → tabular: id, status, created_at, text
- `task done 1` → "Marked #1 as done"
- `task delete 99` → exit 1, "No task with id 99"

✓ Deliverable checklist

- ☐ [] `module-02/` contains source + README.
- ☐ [] All four commands work end-to-end with `tasks.json`.
- ☐ [] `module-02/iteration-notes.md` documents one prompt edit and the resulting code diff.
- ☐ [] Reference solution **not** consulted before completing the lab.

✓ Definition of done

- ✓ Four commands all return correct exit codes · ✓ `tasks.json` round-trips state across runs · ✓ Iteration note explains *why* the deleted constraint mattered.

► Review checkpoint

In pairs (60 s each):

STEP 1 Run each other's `task add` and `task list`.

STEP 2 Identify one missing edge case (empty title? duplicate id? corrupt JSON?).

STEP 3 Decide whether you would add it as a new constraint or accept the gap.

Common mistakes

- Asking Claude for "a CLI" with no constraints — output looks fine, fails review.
- Allowing third-party deps you didn't intend to install. The constraint exists for a reason.
- Skipping examples. The model uses examples to disambiguate; without them it guesses.
- Forgetting exit codes. Production CLIs are graded on exit codes, not stdout.

Instructor notes

- 6 / 4 / 12 / 2 split: concept · demo · lab · checkpoint.
- The "delete one constraint and re-run" moment is the highlight. Don't skip it.
- For mixed-language rooms: write the GCOE prompt in language-agnostic terms, only specify language in CONSTRAINTS.
- If short on time, drop the iteration notes (still ship the CLI).

Transition to next module



The prompt worked because it carried context: language, layout, exit codes. We now persist that context to a file so Claude remembers it across every prompt for the rest of the day.

Next: Module 3 — Project Context with `CLAUDE.md`.