

Exercise (Instructions): Basic Git Commands

Objectives and Outcomes

In this exercise you will get familiar with some basic Git commands. At the end of this exercise you will be able to:

- Set up a folder as a Git repository
- Perform basic Git operations on your Git repository

Basic Git Commands

- At a convenient location on your computer, create a folder named **git-test**.
- Open this git-test folder in your favorite editor.
- Add a file named *index.html* to this folder, and add the following HTML code to this file:

```
1 <!DOCTYPE html>
2 <html>
3   <head></head>
4
5   <body>
6     <h1>This is a Header</h1>
7   </body>
8 </html>
```

Initializing the folder as a Git repository

- Go to the git-test folder in your cmd window/terminal and type the following at the prompt to initialize the folder as a Git repository:

```
1 git init
```

Checking your Git repository status

- Type the following at the prompt to check your Git repository's status:

```
1 git status
```

Adding files to the staging area

- To add files to the staging area of your Git repository, type:

```
1 git add .
```

Committing to the Git repository

- To commit the current staging area to your Git repository, type:

```
1 git commit -m "first commit"
```

Checking the log of Git commits

- To check the log of the commits to your Git repository, type

```
1 git log --oneline
```

- Now, modify the *index.html* file as follows:

```
1 <!DOCTYPE html>
2 <html>
3   <head></head>
4
5   <body>
6     <h1>This is a Header</h1>
7     <p>This is a paragraph</p>
8   </body>
9 </html>
```

- Add a sub-folder named **templates** to your **git-test** folder, and then add a file named *temp.html* to the templates folder. Then set the contents of this file to be the same as the *index.html* file above.
- Then check the status and add all the files to the staging area.
- Then do the second commit to your repository
- Now, modify the *index.html* file as follows:

```
1 <!DOCTYPE html>
2 <html>
3   <head></head>
4
5   <body>
6     <h1>This is a Header</h1>
7     <p>This is a paragraph</p>
8     <p>This is a second paragraph</p>
9   </body>
10 </html>
```

- Now add the modified *index.html* file to the staging area and then do a third commit.

Checking out a file from an earlier commit

- To check out the index.html from the second commit, find the number of the second commit using the git log, and then type the following at the prompt:

```
1 git checkout <second commit's number> index.html
```

Resetting the Git repository

- To discard the effect of the previous operation and restore index.html to its state at the end of the third commit, type:

```
1 git reset HEAD index.html
```

- Then type the following at the prompt:

```
1 git checkout -- index.html
```

- You can also use *git reset* to reset the staging area to the last commit without disturbing the working directory.

Conclusions

At the end of this exercise you should have learnt some basic Git commands. Experiment with these commands until you fully understand how to use Git.

Mark as completed

